

---

**Aeronavtika - Jeklo FE-PM2701 (X2NiCoMo18-8-5) - Taljeno z vakuumsko indukcijo in vakuumsko obločno pretaljeno - Žarjeno v topilu in utrjeno - Izkovki - a ali  $D \leq 150$  mm -  $1750 \text{ MPa} \leq R_m \leq 2000 \text{ MPa}$**

Aerospace series - Steel FE-PM2701 (X2NiCoMo18-8-5) - Vacuum induction melted and vacuum arc remelted - Solution treated and precipitation treated - Forgings - a or  $D \leq 150$  mm -  $1750 \text{ MPa} \leq R_m \leq 2000 \text{ MPa}$

Luft- und Raumfahrt - Stahl FE-PM2701 (X2NiCoMo18-8-5) - Vakuuminduktionserschmolzen und mit selbstverzehrender Elektrode im Vakuum umgeschmolzen - Lösungsgeglüht und ausgelagert - Schmiedestücke - a oder  $D \leq 150$  mm -  $1750 \text{ MPa} \leq R_m \leq 2000 \text{ MPa}$  [SIST EN 3529:2010](https://standards.iteh.ai/catalog/standards/sist/125a6a29-e7b7-470f-a55c-566e3b162425/sist-en-3529-2010)

<https://standards.iteh.ai/catalog/standards/sist/125a6a29-e7b7-470f-a55c-566e3b162425/sist-en-3529-2010>

Série aérospatiale - Acier FE-PM2701 (X2NiCoMo18-8-5) - Élaboré sous vide et refondu par arc sous vide - Mis en solution et vieilli - Pièces forgées et pièces matricées - a ou  $D \leq 150$  mm -  $1750 \text{ MPa} \leq R_m \leq 2000 \text{ MPa}$

**Ta slovenski standard je istoveten z: EN 3529:2010**

---

**ICS:**

49.025.10      Jekla

Steels

**SIST EN 3529:2010**

**en,de**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 3529:2010

<https://standards.iteh.ai/catalog/standards/sist/125a6a29-e7b7-470f-a55c-566e3b162425/sist-en-3529-2010>

EUROPEAN STANDARD  
NORME EUROPÉENNE  
EUROPÄISCHE NORM

**EN 3529**

March 2010

ICS 49.025.10

English Version

**Aerospace series - Steel FE-PM2701 (X2NiCoMo18-8-5) -  
Vacuum induction melted and vacuum arc remelted - Solution  
treated and precipitation treated - Forgings - a or D ≤ 150 mm -  
1 750 MPa ≤ Rm ≤ 2 000 MPa**

Série aérospatiale - Acier FE-PM2701 (X2NiCoMo18-8-5) -  
Élaboré sous vide et refondu par arc sous vide - Mis en  
solution et vieilli - Pièces forgées et pièces matricées - a ou  
D ≤ 150 mm - 1 750 MPa ≤ Rm ≤ 2 000 MPa

Luft- und Raumfahrt - Stahl FE-PM2701 (X2NiCoMo18-8-5)  
- Vakuuminduktionerschmolzen und mit  
selbstverzehrender Elektrode im Vakuum umgeschmolzen  
- Lösungsgeglüht und ausgelagert - Schmiedestücke - a  
oder D ≤ 150 mm - 1 750 MPa ≤ Rm ≤ 2 000 MPa

This European Standard was approved by CEN on 28 November 2009.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

<https://standards.iteh.ai/catalog/standards/sist/125a6a29-e7b7-470f-a55c-f6c01167125a/en-3529-2010>

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**Management Centre: Avenue Marnix 17, B-1000 Brussels**

**Contents**

Page

|                                          |          |
|------------------------------------------|----------|
| <b>Foreword.....</b>                     | <b>3</b> |
| <b>Introduction .....</b>                | <b>4</b> |
| <b>1      Scope .....</b>                | <b>5</b> |
| <b>2      Normative references .....</b> | <b>5</b> |

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 3529:2010

<https://standards.iteh.ai/catalog/standards/sist/125a6a29-e7b7-470f-a55c-566e3b162425/sist-en-3529-2010>

## Foreword

This document (EN 3529:2010) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2010, and conflicting national standards shall be withdrawn at the latest by September 2010.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

**ITEH STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 3529:2010

<https://standards.iteh.ai/catalog/standards/sist/125a6a29-e7b7-470f-a55c-566e3b162425/sist-en-3529-2010>

## Introduction

This standard is part of the series of EN metallic material standards for aerospace applications. The general organization of this series is described in EN 4258.

This standard has been prepared in accordance with EN 4500-5.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 3529:2010

<https://standards.iteh.ai/catalog/standards/sist/125a6a29-e7b7-470f-a55c-566e3b162425/sist-en-3529-2010>

## 1 Scope

This standard specifies the requirements relating to:

Steel FE-PM2701 (X2NiCoMo18-8-5)  
Vacuum induction melted and vacuum arc remelted  
Solution treated and precipitation treated  
Forgings  
 $a$  or  $D \leq 150$  mm  
 $1\,750\text{ MPa} \leq R_m \leq 2\,000\text{ MPa}$

for aerospace applications.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 3530, Aerospace series — Steel FE-PA95 — Softened — Reference heat treatment: solution treated and precipitation treated — Forging stock —  $D_a \leq 200$  mm <sup>1)</sup>

EN 4258, Aerospace series — Metallic materials — General organization of standardization — Links between types of EN standards and their use

EN 4500-5, Aerospace series — Metallic materials — Rules for drafting and presentation of material standards — Part 5: Specific rules for steels <sup>1)</sup>

EN 4700-006, Aerospace series — Steel and heat resisting alloys — Wrought product — Technical specification — Part 006: Pre-production and production forgings <sup>1)</sup>

---

<sup>1)</sup> Published as ASD Prestandard at the date of publication of this standard.

## EN 3529:2010 (E)

|     |                         |         |                                                 |      |      |       |       |     |      |      |     |      |      |
|-----|-------------------------|---------|-------------------------------------------------|------|------|-------|-------|-----|------|------|-----|------|------|
| 1   | Material designation    |         | Steel FE-PM2701 (X2NiCoMo18-8-5)                |      |      |       |       |     |      |      |     |      |      |
| 2   | Chemical composition %  | Element | C                                               | Si   | Mn   | P     | S     | Mo  | Ni   | Al   | Co  | Ti   | Fe   |
|     |                         | min.    | —                                               | —    | —    | —     | —     | 4,6 | 17,0 | 0,05 | 7,0 | 0,30 | Base |
|     |                         | max.    | 0,03                                            | 0,10 | 0,10 | 0,010 | 0,010 | 5,2 | 19,0 | 0,15 | 8,5 | 0,60 |      |
| 3   | Method of melting       |         | Vacuum induction melted and vacuum arc remelted |      |      |       |       |     |      |      |     |      |      |
| 4.1 | Form                    |         | Forgings                                        |      |      |       |       |     |      |      |     |      |      |
| 4.2 | Method of production    |         | Forged from forging stock                       |      |      |       |       |     |      |      |     |      |      |
| 4.3 | Limit dimension(s)      | mm      | $a$ or $D \leq 150$                             |      |      |       |       |     |      |      |     |      |      |
| 5   | Technical specification |         | EN 4700-006                                     |      |      |       |       |     |      |      |     |      |      |

|     |                         |  |                                                                                                        |  |  |  |  |                                                                                                                                                |  |  |  |  |  |
|-----|-------------------------|--|--------------------------------------------------------------------------------------------------------|--|--|--|--|------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|--|
| 6.1 | Delivery condition      |  | Solution treated                                                                                       |  |  |  |  | Solution treated and precipitation treated                                                                                                     |  |  |  |  |  |
|     | Heat treatment          |  | $790\text{ °C} \leq \theta \leq 840\text{ °C} / \text{AC}$                                             |  |  |  |  | $790\text{ °C} \leq \theta \leq 840\text{ °C} / \text{AC}$<br>$+ 465\text{ °C} \leq \theta \leq 495\text{ °C} / t \geq 3\text{ h} / \text{AC}$ |  |  |  |  |  |
| 6.2 | Delivery condition code |  | W                                                                                                      |  |  |  |  | U                                                                                                                                              |  |  |  |  |  |
| 7   | Use condition           |  | Solution treated and precipitation treated                                                             |  |  |  |  | Delivery condition                                                                                                                             |  |  |  |  |  |
|     | Heat treatment          |  | Delivery condition<br>$+ 465\text{ °C} \leq \theta \leq 495\text{ °C} / t \geq 3\text{ h} / \text{AC}$ |  |  |  |  | —                                                                                                                                              |  |  |  |  |  |

## iTeh STANDARD PREVIEW

### Characteristics

(standards.iteh.ai)

|     |                                    |                   |                     |                  |                     |                                |
|-----|------------------------------------|-------------------|---------------------|------------------|---------------------|--------------------------------|
| 8.1 | Test sample(s)                     |                   |                     | See EN 4700-006. |                     |                                |
| 8.2 | Test piece(s)                      |                   |                     | See EN 4700-006. |                     |                                |
| 8.3 | Heat treatment                     |                   |                     | Solution treated |                     | Use condition                  |
| 9   | Dimensions concerned               | mm                | $a$ or $D \leq 150$ |                  | $a$ or $D \leq 150$ | $75 < a$ or $D \leq 150$       |
| 10  | Thickness of cladding on each face | %                 | —                   |                  | —                   | —                              |
| 11  | Direction of test piece            |                   | —                   |                  | L                   | T                              |
| 12  | Temperature                        | $\theta$          | °C                  | —                |                     | Ambient                        |
| 13  | Proof stress                       | R <sub>p0,2</sub> | MPa                 | —                |                     | ≥ 1 650                        |
| 14  | T Strength                         | R <sub>m</sub>    | MPa                 | —                |                     | 1 750 ≤ R <sub>m</sub> ≤ 2 000 |
| 15  | Elongation                         | A                 | %                   | —                |                     | ≥ 6                            |
| 16  | Reduction of area                  | Z                 | %                   | —                |                     | ≥ 40                           |
| 17  | Hardness                           |                   |                     | HB ≤ 352         |                     | 510 ≤ HV ≤ 600                 |
| 18  | Shear strength                     | R <sub>c</sub>    | MPa                 | —                |                     | —                              |
| 19  | Bending                            | k                 | —                   | —                |                     | —                              |
| 20  | Impact strength                    | kV                | J                   | —                |                     | ≥ 15;<br>Notch direction T     |
| 21  | Temperature                        | $\theta$          | °C                  | —                |                     |                                |
| 22  | Time                               |                   | h                   | —                |                     |                                |
| 23  | Stress                             | σ <sub>a</sub>    | MPa                 | —                |                     |                                |
| 24  | Elongation                         | a                 | %                   | —                |                     |                                |
| 25  | Rupture stress                     | σ <sub>R</sub>    | MPa                 | —                |                     |                                |
| 26  | Elongation at rupture              | A                 | %                   | —                |                     |                                |
| 27  | Notes (see line 98)                |                   |                     | —                |                     |                                |



|    |                                             |   |                                                                                                         |                                              |
|----|---------------------------------------------|---|---------------------------------------------------------------------------------------------------------|----------------------------------------------|
| 34 | Grain size                                  | – | See EN 4700-006.                                                                                        |                                              |
|    |                                             | 7 | Dimension<br>mm                                                                                         | Grain size number                            |
|    |                                             |   | $a \text{ or } D \leq 75$                                                                               | $G \geq 6$ ; occasional $G \geq 4$ permitted |
|    |                                             |   | $75 < a \text{ or } D \leq 150$                                                                         | $G \geq 4$ ; occasional $G \geq 2$ permitted |
| 44 | External defects                            | – | See EN 4700-006.                                                                                        |                                              |
|    |                                             | 7 | Visual                                                                                                  |                                              |
| 51 | Macrostructure                              | – | See EN 4700-006.                                                                                        |                                              |
|    |                                             | 2 | Grain flow on first article                                                                             |                                              |
| 61 | Internal defects                            | 1 | EN 4700-006                                                                                             |                                              |
|    |                                             | 6 | $a \text{ or } D \leq 100$ mm may be tested either on the product or at an earlier stage of manufacture |                                              |
|    |                                             | 7 | Class 5                                                                                                 |                                              |
| 82 | Batch uniformity<br>(Material verification) | – | See EN 4700-006.                                                                                        |                                              |
|    |                                             |   |                                                                                                         |                                              |
| 95 | Marking inspection                          | – | See EN 4700-006.                                                                                        |                                              |
| 96 | Dimensional inspection                      | – | See EN 4700-006.                                                                                        |                                              |
| 98 | Notes                                       | – | –                                                                                                       |                                              |
| 99 | Typical use                                 | – | –                                                                                                       |                                              |