

ISO/IEC 29341-8-10

Edition 1.0 2008-11

INTERNATIONAL STANDARD

Information technology – UPnP Device Architecture –

Part 8-10: Internet Gateway Device Control Protocol – Local Area Network Host Configuration Management Service

ISO/IEC 29341-8-10:2008 https://standards.iteh.ai/catalog/standards/sist/9f8c6bc9-87dc-4a0b-84ca-

baf47811f2a7/iso-iec-29341-8-10-2008





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2008 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Email: inmail@iec.ch Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: <u>www.iec.ch/searchpub</u>
- The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.
- IEC Just Published: www.iec.gh/online_news/justpub Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.
- Electropedia: www.electropedia.org
 (standards.iteh.ai)

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

ISO/IEC 29341-8-10:2008

Customer Service Centre: www.index.ch/webstoret/dustserv.dards/sist/9f8c6bc9-87dc-4a0b-84ca-

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: <u>csc@iec.ch</u> Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00



ISO/IEC 29341-8-10

Edition 1.0 2008-11

INTERNATIONAL STANDARD

Information technology – UPnA Device Architecture V IE W
Part 8-10: Internet Gateway Device Control Protocol – Local Area Network Host
Configuration Management Service

ISO/IEC 29341-8-10:2008 https://standards.iteh.ai/catalog/standards/sist/9f8c6bc9-87dc-4a0b-84ca-baf47811f2a7/iso-iec-29341-8-10-2008

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE



CONTENTS

FOI	FOREWORD4							
OR	ORIGINAL UPNP DOCUMENTS (informative)6							
1.	1. Overview and Scope8							
2.		vice Modeling Definitions						
2	.1.	ServiceType						
	2	State Variables						
_	.2. 2.2.							
	2.2.							
	2.2.							
	2.2.	4. DNSServers	9					
	2.2.	5. DomainName	.10					
	2.2.	6. MinAddress	.10					
	2.2.							
	2.2.							
	2.2.							
	2.2.	10. Relationships Between State Variables	.10					
2	.3.	Eventing and Moderation	.11					
	2.3.	1. Event Model	.11					
2	.4.	ActionsiTeh STANDARD PREVIEW						
	2.4.	1. SetDHCPServerConfigurable	.12					
	2.4.		.13					
	2.4.	3. SetDHCPRelay	.13					
	2.4.							
	2.4.							
	2.4.0	6. GetSubnetMask	.15					
	2.4.	6. GetSubnetMaskbaf47811f2a7/iso-iec-29341-8-10-2008	.15					
	2.4.							
	2.4.	9. GetIPRoutersList	.16					
	2.4.	10. SetDomainName	.17					
	2.4.	11. GetDomainName	.17					
	2.4.	12. SetAddressRange	.18					
	2.4.							
	2.4.							
	2.4.		.19					
	2.4.	16. GetReservedAddresses	.20					
	2.4.							
	2.4.							
	2.4.							
	2.4.							
	2.4.	·						
	2.4.							
2.5. Theory of Operation								
3.	XMI	_ Service Description	.23					
4	Toc	•	27					

LIST OF TABLES

Table 1: State Variables	9
Table 2: Event Moderation	11
Table 3: Actions	12
Table 4: Arguments for SetDHCPServerConfigurable	12
Table 5: Arguments for GetDHCPServerConfigurable	13
Table 6: Arguments for SetDHCPRelay	13
Table 7: Arguments for GetDHCPRelay	14
Table 8: Arguments for SetSubnetMask	14
Table 9: Arguments for GetSubnetMask	15
Table 10: Arguments for SetIPRouter	15
Table 11: Arguments for DeleteIPRouter	16
Table 12: Arguments for GetIPRoutersList	16
Table 13: Arguments for SetDomainName	17
Table 14: Arguments for GetDomainName	17
Table 15: Arguments for SetAddressRange D.A.R.D. P.R.E.V.I.E.W.	18
Table 16: Arguments for GetAddressRange and S.itch.ai	18
Table 17: Arguments for SetReservedAddress	19
Table 18: Arguments for DeleteReservedAddress—https://standards.iteh.ai/catalog/standards/sist/9f8c6bc9-87dc-4a0b-84ca-	19
Table 19: Arguments for GetResegwedAddresses.29341.8.10.2008	20
Table 20: Arguments for SetDNSServer	20
Table 21: Arguments for DeleteDNSServer	21
Table 22: Arguments for GetDNSServers	21
Table 23: Common Error Codes	22

INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

Part 8-10: Internet Gateway Device Control Protocol – Local Area Network Host Configuration Management Service

FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC
 Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. A while all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter ds. iich avcatalog/standards/sist/918c6bc9-87dc-4a0b-84ca-baf47811f2a7/iso-iec-29341-8-10-2008
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

IEC and ISO draw attention to the fact that it is claimed that compliance with this document may involve the use of patents as indicated below.

ISO and IEC take no position concerning the evidence, validity and scope of the putative patent rights. The holders of the putative patent rights have assured IEC and ISO that they are willing to negotiate free licences or licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of the putative patent rights are registered with IEC and ISO.

Intel Corporation has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Intel Corporation Standards Licensing Department 5200 NE Elam Young Parkway MS: JFS-98 USA – Hillsboro, Oregon 97124

Microsoft Corporation has informed IEC and ISO that it has patent applications or granted patents as listed below:

6101499 / US; 6687755 / US; 6910068 / US; 7130895 / US; 6725281 / US; 7089307 / US; 7069312 / US; 10/783 524 /US

Information may be obtained from:

Microsoft Corporation One Microsoft Way USA – Redmond WA 98052

Philips International B.V. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Philips International B.V. – IP&S High Tech campus, building 44 3A21 NL – 5656 Eindhoven

NXP B.V. (NL) has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

NXP B.V. (NL) High Tech campus 60 NL – 5656 AG Eindhoven

Matsushita Electric Industrial Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Matsushita Electric Industrial Co. Ltd.
1-3-7 Shiromi, Chuoh-ku STANDARD PREVIEW
JP – Osaka 540-6139 Ch. STANDARD PREVIEW

Hewlett Packard Company has informed EC and ISO that it has patent applications or granted patents as listed below:

5 956 487 / US; 6 170 007 / US; 6 139/1177 LUS; 16/529:936V US; 6 470 339 / US; 6 571 388 / US; 6 205 https://standards.iteh.ai/catalog/standards/sist/9f8c6bc9-87dc-4a0b-84ca-

Information may be obtained from:

baf47811f2a7/iso-iec-29341-8-10-2008

Hewlett Packard Company 1501 Page Mill Road USA – Palo Alto, CA 94304

Samsung Electronics Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Digital Media Business, Samsung Electronics Co. Ltd. 416 Maetan-3 Dong, Yeongtang-Gu, KR – Suwon City 443-742

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 29341-8-10 was prepared by UPnP Implementers Corporation and adopted, under the PAS procedure, by joint technical committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Universal plug and play (UPnP) architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

ORIGINAL UPNP DOCUMENTS (informative)

Reference may be made in this document to original UPnP documents. These references are retained in order to maintain consistency between the specifications as published by ISO/IEC and by UPnP Implementers Corporation. The following table indicates the original UPnP document titles and the corresponding part of ISO/IEC 29341:

UPnP Document Title	ISO/IEC 29341 Part
UPnP Device Architecture 1.0	ISO/IEC 29341-1
UPnP Basic:1 Device	ISO/IEC 29341-2
UPnP AV Architecture:1	ISO/IEC 29341-3-1
UPnP MediaRenderer:1 Device	ISO/IEC 29341-3-2
UPnP MediaServer:1 Device	ISO/IEC 29341-3-3
UPnP AVTransport:1 Service	ISO/IEC 29341-3-10
UPnP ConnectionManager:1 Service	ISO/IEC 29341-3-11
UPnP ContentDirectory:1 Service	ISO/IEC 29341-3-12
UPnP RenderingControl:1 Service	ISO/IEC 29341-3-13
UPnP MediaRenderer:2 Device	ISO/IEC 29341-4-2
UPnP MediaServer:2 Device	ISO/IEC 29341-4-3
UPnP AV Datastructure Template:1	ISO/IEC 29341-4-4
UPnP AVTransport:2 Service	ISO/IEC 29341-4-10
UPnP ConnectionManager:2 Service	ISO/IEC 29341-4-11
UPnP ContentDirectory:2 Service	ISO/IEC 29341-4-12
UPnP RenderingControl:2 Service	ISO/IEC 29341-4-13
UPnP ScheduledRecording:1	ISO/IEC 29341-4-14
UPnP DigitalSecurityCamera:1 Device	ISO/IEC 29341-5-1
UPnP DigitalSecurityCameraMotionImage:1 Service	ISO/IEC 29341-5-10
UPnP DigitalSecurityCameraSettings:1 Service	ISO/IEC 29341-5-11
UPnP DigitalSecurityCameraStillImage:1 Service	ISO/IEC 29341-5-12
UPnP HVAC_System 1 Device Cards.iteh.	ISO/IEC 29341-6-1
UPnP HVAC_ZoneThermostat:1 Device	ISO/IEC 29341-6-2
UPnP ControlValve:1 Service	ISO/IEC 29341-6-10
UPnP HVAC_FanOperatingMode: 1 Service 8-10:2008	ISO/IEC 29341-6-11
UPnP FanSpeed:1 Service UPnP HouseStatus;1 Service	JSO/IEC 29341-6-12
UPnP HouseStatus:1 Service	ISO/IEC 29341-6-13
UPnP HVAC_SetpointSchedule:17 Service 29341-8-10-2	
UPnP TemperatureSensor:1 Service	ISO/IEC 29341-6-15
UPnP TemperatureSetpoint:1 Service	ISO/IEC 29341-6-16
UPnP HVAC_UserOperatingMode:1 Service	ISO/IEC 29341-6-17
UPnP BinaryLight:1 Device	ISO/IEC 29341-7-1
UPnP DimmableLight:1 Device UPnP Dimming:1 Service	ISO/IEC 29341-7-2 ISO/IEC 29341-7-10
UPnP SwitchPower:1 Service	ISO/IEC 29341-7-10
UPnP InternetGatewayDevice:1 Device	ISO/IEC 29341-8-1
UPnP LANDevice:1 Device	ISO/IEC 29341-8-2
UPnP WANDevice:1 Device	ISO/IEC 29341-8-3
UPnP WANConnectionDevice:1 Device	ISO/IEC 29341-8-4
UPnP WLANAccessPointDevice:1 Device	ISO/IEC 29341-8-5
UPnP LANHostConfigManagement:1 Service	ISO/IEC 29341-8-10
UPnP Layer3Forwarding:1 Service	ISO/IEC 29341-8-11
UPnP LinkAuthentication:1 Service	ISO/IEC 29341-8-12
UPnP RadiusClient:1 Service	ISO/IEC 29341-8-13
UPnP WANCableLinkConfig:1 Service	ISO/IEC 29341-8-14
UPnP WANCommonInterfaceConfig:1 Service	ISO/IEC 29341-8-15
UPnP WANDSLLinkConfig:1 Service	ISO/IEC 29341-8-16
UPnP WANEthernetLinkConfig:1 Service	ISO/IEC 29341-8-17
UPnP WANIPConnection:1 Service	ISO/IEC 29341-8-18
UPnP WANPOTSLinkConfig:1 Service	ISO/IEC 29341-8-19
UPnP WANPPPConnection:1 Service	ISO/IEC 29341-8-20
UPnP WLANConfiguration:1 Service	ISO/IEC 29341-8-21
UPnP Printer:1 Device	ISO/IEC 29341-9-1
UPnP Scanner:1.0 Device	ISO/IEC 29341-9-2
UPnP ExternalActivity:1 Service	ISO/IEC 29341-9-10
UPnP Feeder:1.0 Service	ISO/IEC 29341-9-11
UPnP PrintBasic:1 Service	ISO/IEC 29341-9-12
UPnP Scan:1 Service	ISO/IEC 29341-9-13
UPnP QoS Architecture:1.0	ISO/IEC 29341-10-1
UPnP QosDevice:1 Service	ISO/IEC 29341-10-10
UPnP QosManager:1 Service	ISO/IEC 29341-10-11 ISO/IEC 29341-10-12
UPnP QosPolicyHolder:1 Service UPnP QoS Architecture:2	ISO/IEC 29341-10-12 ISO/IEC 29341-11-1
UPnP QOS v2 Schema Files	ISO/IEC 29341-11-1 ISO/IEC 29341-11-2
OF THE GOOD VE OCHERINA FIRES	100/100 2004 1-11-2

UPnP Document Title	ISO/IEC 29341 Part
UPnP QosDevice:2 Service	ISO/IEC 29341-11-10
UPnP QosManager:2 Service	ISO/IEC 29341-11-11
UPnP QosPolicyHolder:2 Service	ISO/IEC 29341-11-12
UPnP RemoteUIClientDevice:1 Device	ISO/IEC 29341-12-1
UPnP RemoteUIServerDevice:1 Device	ISO/IEC 29341-12-2
UPnP RemoteUIClient:1 Service	ISO/IEC 29341-12-10
UPnP RemoteUIServer:1 Service	ISO/IEC 29341-12-11
UPnP DeviceSecurity:1 Service	ISO/IEC 29341-13-10
UPnP SecurityConsole:1 Service	ISO/IEC 29341-13-11

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 29341-8-10:2008

https://standards.iteh.ai/catalog/standards/sist/9f8c6bc9-87dc-4a0b-84ca-baf47811f2a7/iso-iec-29341-8-10-2008

1. Overview and Scope

This device definition is compliant with the UPnP Device Architecture version 1.0.

This service definition enables the remote control, monitoring, and configuration of a Dynamic Host Configuration Protocol (DHCP) and DNS server, serving a residential LAN. Variables specified in this service are derived from DHCP options¹ standardized in the Internet Engineering Task Force (IETF).

The **LANHostConfigManagement** is an OPTIONAL service specified in **urn:schemas-upnp-org:device:LANDevice**, one or more instances of which may be specified under the root device **urn:schemas-upnp-org:device:InternetGatewayDevice**

NOTES:

- It is assumed that each DHCP server instance defined in the context of a *LANDevice* and modeled by this service, manages exactly one subnet. Changes / vendor extensions may be required to the specification if this assumption is not true.
- Currently this service does not model any DNS or Dynamic DNS specific functions.
- This service essentially performs administrative operations on the DHCP server component of an Internet gateway. As such, Out-of-Band mechanisms may be needed to enforce such as administrative mode and provide authentication and/or access control. Implementation details of such mechanisms are outside the scope of this document.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 29341-8-10:2008 https://standards.iteh.ai/catalog/standards/sist/9f8c6bc9-87dc-4a0b-84ca-baf47811f2a7/iso-iec-29341-8-10-2008

[•]

¹ Refer to RFCs 2132, 2939 and 3011. Other RFCs or Internet drafts may also be applicable – Attributes from those documents may be implemented as vendor extensions.

2. Service Modeling Definitions

2.1. ServiceType

The following service type identifies a service that is compliant with this template:

urn:schemas-upnp-org:service:<u>LANHostConfigManagement:1</u>.

2.2. State Variables

Table 1: State Variables

Variable Name	Req. or Opt. ¹	Data Type	Allowed Value ²	Default Value ²	Eng. Units
DHCPServerConfigurable	R	boolean	1, 0	Not specified	N/A
DHCPRelay	R	boolean	1, 0	Not specified	N/A
SubnetMask	R	string	IP Address	Not specified	N/A
DNSServers	R	string	Undefined	Empty string	N/A
DomainName	R	string	<= 21 characters	Empty string	N/A
MinAddress II en SI	RNDA	string	Undefined	Not specified	N/A
MaxAddress	tandai	stringteh	Undefined	Not specified	N/A
IPRouters	R	string	Undefined	Empty string	N/A
ReservedAddresses	RSO/IEC 2	9 string 10:2008	Undefined	Empty string	N/A
Non-standard state variables implemented by an UPnP vendor go here.	_	nd FB19 /sist/9f8c61 -iec-29341-8-10		4 TB D	TBD

 $^{^{1}}$ R = Required, O = Optional, X = Non-standard.

NOTE: Default values are not specified in the DCP. A vendor may however choose to provide default values for SST variables where appropriate.

2.2.1. DHCPServerConfigurable

This variable enables the configuration of the DHCP server on the LAN interface. If set to 1, the DHCP server is configurable via actions defined in this service. If 0, the DHCP server configuration cannot be modified.

2.2.2. DHCPRelay

This variable indicates if the DHCP server performs the role of a server or a relay on the LAN interface. If this variable is set to 1, the DHCP server is configured to relay DHCP requests.

2.2.3. SubnetMask

This variable specifies the client's network subnet mask.

2.2.4. DNSServers

This variable specifies a comma-separated list of available DNS servers offered to DHCP clients. An empty string indicates that no servers are being offered.

² Values listed in this column are required. To specify standard optional values or to delegate assignment of values to the vendor, you must reference a specific instance of an appropriate table below.

2.2.5. DomainName

This variable sets the Domain name to provide to clients on the residential LAN connected to the LAN interface. An empty string means no domain name suggestion will be made.

2.2.6. MinAddress

This variable specifies the first address in the pool to be assigned by the DHCP server on the LAN interface.

2.2.7. MaxAddress

This variable specifies the last address in the pool to be assigned by the DHCP server on the LAN interface.

2.2.8. IPRouters

This variable specifies a comma-separated list of IP addresses of routers on this subnet. It is also referred to as DefaultGateway.

2.2.9. ReservedAddresses

This variable specifies a comma-separated list of addresses marked reserved from the address allocation pool. If the list is non-empty, specified addresses will not be assigned to clients on the residential LAN connected to the LAN interface. When this is empty, no addresses are excluded.

2.2.10.Relationships Between State Variables h.ai)

If DHCPServerConfigurable is set to 0, other Set actions will return error code 501. If DHCPRelay is set to 1, the DHCP server will ignore other SST variable settings and forward DHCP requests upstream to another DHCP server.

DHCP server.

baf47811t2a7/iso-jec-29341-8-10-2008