

INTERNATIONAL STANDARD

iTeh STANDARD PREVIEW

**Information technology – UPnP Device Architecture –
Part 8-20: Internet Gateway Device Control Protocol – Wide Area Network Point-
to-Point Protocol Connection Service**

ISO/IEC 29341-8-20:2008

<https://standards.iteh.ai/catalog/standards/sist/9cbafa00-b1ca-4f72-964c-61fec5196ee5/iso-iec-29341-8-20-2008>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2008 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00



ISO/IEC 29341-8-20

Edition 1.0 2008-11

INTERNATIONAL STANDARD

Information technology – UPnP Device Architecture –
Part 8-20: Internet Gateway Device Control Protocol – Wide Area Network Point-
to-Point Protocol Connection Service

ISO/IEC 29341-8-20:2008

<https://standards.iteh.ai/catalog/standards/sist/9cbafa00-b1ca-4f72-964c-61fec5196ee5/iso-iec-29341-8-20-2008>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE



ICS 35.200

ISBN 978-2-88910-890-9

CONTENTS

FOREWORD	5
ORIGINAL UPNP DOCUMENTS (informative)	7
1. Overview and Scope	9
2. Service Modeling Definitions	10
2.1. ServiceType	10
2.2. State Variables	11
2.2.1. ConnectionType	15
2.2.2. PossibleConnectionTypes	15
2.2.3. ConnectionStatus	15
2.2.4. Uptime	15
2.2.5. UpstreamMaxBitRate	15
2.2.6. DownstreamMaxBitRate	15
2.2.7. LastConnectionError	15
2.2.8. AutoDisconnectTime	15
2.2.9. IdleDisconnectTime	15
2.2.10. WarnDisconnectDelay	16
2.2.11. RSIPAvailable	16
2.2.12. NATEnabled	16
2.2.13. UserName	16
2.2.14. Password	16
2.2.15. PPPEncryptionProtocol	16
2.2.16. PPPCompressionProtocol	16
2.2.17. PPPAuthenticationProtocol	16
2.2.18. ExternalIPAddress	16
2.2.19. PortMappingNumberOfEntries	17
2.2.20. PortMappingEnabled	17
2.2.21. PortMappingLeaseDuration	17
2.2.22. RemoteHost	17
2.2.23. ExternalPort	17
2.2.24. InternalPort	17
2.2.25. PortMappingProtocol	17
2.2.26. InternalClient	17
2.2.27. PortMappingDescription	18
2.2.28. Relationships Between State Variables	19
2.3. Eventing and Moderation	20
2.3.1. Event Model	20
2.4. Actions	21
2.4.1. SetConnectionType	22
2.4.2. GetConnectionTypeInfo	22
2.4.3. ConfigureConnection	23
2.4.4. RequestConnection	23
2.4.5. RequestTermination	24
2.4.6. ForceTermination	25
2.4.7. SetAutoDisconnectTime	25
2.4.8. SetIdleDisconnectTime	26
2.4.9. SetWarnDisconnectDelay	26
2.4.10. GetStatusInfo	27
2.4.11. GetLinkLayerMaxBitRates	27
2.4.12. GetPPPEncryptionProtocol	28
2.4.13. GetPPPCompressionProtocol	28
2.4.14. GetPPPAuthenticationProtocol	28
2.4.15. GetUserName	29
2.4.16. GetPassword	29
2.4.17. GetAutoDisconnectTime	30
2.4.18. GetIdleDisconnectTime	30

2.4.19.	GetWarnDisconnectDelay	31
2.4.20.	GetNATRSIPStatus	31
2.4.21.	GetGenericPortMappingEntry	32
2.4.22.	GetSpecificPortMappingEntry	33
2.4.23.	AddPortMapping	33
2.4.24.	DeletePortMapping	35
2.4.25.	GetExternalIPAddress	35
2.4.26.	Non-Standard Actions Implemented by a UPnP Vendor	36
2.4.27.	Relationships Between Actions	36
2.4.28.	Common Error Codes	36
2.5.	Theory of Operation	37
2.5.1.	Connection Initiation	38
2.5.2.	Connection Termination	40
2.5.3.	Connection Scenarios	41
2.5.4.	Non-UPnP compliant clients	42
2.5.5.	VPN connections	42
3.	XML Service Description	44
4.	Test	53

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 29341-8-20:2008](https://standards.iteh.ai/catalog/standards/sist/9cbafa00-b1ca-4f72-964c-61fec5196ee5/iso-iec-29341-8-20-2008)

<https://standards.iteh.ai/catalog/standards/sist/9cbafa00-b1ca-4f72-964c-61fec5196ee5/iso-iec-29341-8-20-2008>

LIST OF TABLES

Table 1: State Variables	11
Table 1.1: AllowedValueList for PossibleConnectionTypes	12
Table 1.2: AllowedValueList for ConnectionStatus	13
Table 1.3: AllowedValueList for LastConnectionError	14
Table 1.4: AllowedValueList for PortMappingProtocol	14
Table 2: Event Moderation.....	20
Table 3: Actions	21
Table 4: Arguments for SetConnectionType	22
Table 5: Arguments for GetConnectionTypeInfo	22
Table 6: Arguments for ConfigureConnection.....	23
Table 7: Arguments for SetAutoDisconnectTime	25
Table 8: Arguments for SetIdleDisconnectTime	26
Table 9: Arguments for SetWarnDisconnectDelay	26
Table 10: Arguments for GetStatusInfo.....	27
Table 11: Arguments for GetLinkLayerMaxBitRates	27
Table 12: Arguments for GetPPPEncryptionProtocol	28
Table 13: Arguments for GetPPPCompressionProtocol.....	28
Table 14: Arguments for GetPPPAAuthenticationProtocol	29
Table 15: Arguments for GetUserName	29
Table 16: Arguments for GetPassword.....	29
Table 17: Arguments for GetAutoDisconnectTime	30
Table 18: Arguments for GetIdleDisconnectTime	30
Table 19: Arguments for GetWarnDisconnectDelay	31
Table 20: Arguments for GetNATRSIPStatus	31
Table 21: Arguments for GetGenericPortMappingEntry	32
Table 22: Arguments for GetSpecificPortMappingEntry	33
Table 23: Arguments for AddPortMapping.....	34
Table 24: Arguments for DeletePortMapping	35
Table 25: Arguments for GetExternalIPAddress.....	35
Table 26: Common Error Codes.....	36

INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

Part 8-20: Internet Gateway Device Control Protocol – Wide Area Network Point-to-Point Protocol Connection Service

FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

IEC and ISO draw attention to the fact that it is claimed that compliance with this document may involve the use of patents as indicated below.

ISO and IEC take no position concerning the evidence, validity and scope of the putative patent rights. The holders of the putative patent rights have assured IEC and ISO that they are willing to negotiate free licences or licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of the putative patent rights are registered with IEC and ISO.

Intel Corporation has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Intel Corporation
Standards Licensing Department
5200 NE Elam Young Parkway
MS: JFS-98
USA – Hillsboro, Oregon 97124

Microsoft Corporation has informed IEC and ISO that it has patent applications or granted patents as listed below:

6101499 / US; 6687755 / US; 6910068 / US; 7130895 / US; 6725281 / US; 7089307 / US; 7069312 / US; 10/783 524 / US

Information may be obtained from:

Microsoft Corporation
One Microsoft Way
USA – Redmond WA 98052

Philips International B.V. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Philips International B.V. – IP&S
High Tech campus, building 44 3A21
NL – 5656 Eindhoven

NXP B.V. (NL) has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

NXP B.V. (NL)
High Tech campus 60
NL – 5656 AG Eindhoven

Matsushita Electric Industrial Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Matsushita Electric Industrial Co. Ltd.
1-3-7 Shiromi, Chuoh-ku
JP – Osaka 540-6139

Hewlett Packard Company has informed IEC and ISO that it has patent applications or granted patents as listed below:

5 956 487 / US; 6 170 007 / US; 6 139 177 / US; 6 529 936 / US; 6 470 339 / US; 6 571 388 / US; 6 205 466 / US

<https://standards.iteh.ai/catalog/standards/sist/9cbafa00-b1ca-4f72-964c-61fec5196ee5/iso-iec-29341-8-20-2008>

Information may be obtained from:

Hewlett Packard Company
1501 Page Mill Road
USA – Palo Alto, CA 94304

Samsung Electronics Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Digital Media Business, Samsung Electronics Co. Ltd.
416 Maetan-3 Dong, Yeongtang-Gu,
KR – Suwon City 443-742

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 29341-8-20 was prepared by UPnP Implementers Corporation and adopted, under the PAS procedure, by joint technical committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Universal plug and play (UPnP) architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

ORIGINAL UPnP DOCUMENTS (informative)

Reference may be made in this document to original UPnP documents. These references are retained in order to maintain consistency between the specifications as published by ISO/IEC and by UPnP Implementers Corporation. The following table indicates the original UPnP document titles and the corresponding part of ISO/IEC 29341:

UPnP Document Title	ISO/IEC 29341 Part
UPnP Device Architecture 1.0	ISO/IEC 29341-1
UPnP Basic:1 Device	ISO/IEC 29341-2
UPnP AV Architecture:1	ISO/IEC 29341-3-1
UPnP MediaRenderer:1 Device	ISO/IEC 29341-3-2
UPnP MediaServer:1 Device	ISO/IEC 29341-3-3
UPnP AVTransport:1 Service	ISO/IEC 29341-3-10
UPnP ConnectionManager:1 Service	ISO/IEC 29341-3-11
UPnP ContentDirectory:1 Service	ISO/IEC 29341-3-12
UPnP RenderingControl:1 Service	ISO/IEC 29341-3-13
UPnP MediaRenderer:2 Device	ISO/IEC 29341-4-2
UPnP MediaServer:2 Device	ISO/IEC 29341-4-3
UPnP AV Datastructure Template:1	ISO/IEC 29341-4-4
UPnP AVTransport:2 Service	ISO/IEC 29341-4-10
UPnP ConnectionManager:2 Service	ISO/IEC 29341-4-11
UPnP ContentDirectory:2 Service	ISO/IEC 29341-4-12
UPnP RenderingControl:2 Service	ISO/IEC 29341-4-13
UPnP ScheduledRecording:1	ISO/IEC 29341-4-14
UPnP DigitalSecurityCamera:1 Device	ISO/IEC 29341-5-1
UPnP DigitalSecurityCameraMotionImage:1 Service	ISO/IEC 29341-5-10
UPnP DigitalSecurityCameraSettings:1 Service	ISO/IEC 29341-5-11
UPnP DigitalSecurityCameraStillImage:1 Service	ISO/IEC 29341-5-12
UPnP HVAC_System:1 Device	ISO/IEC 29341-6-1
UPnP HVAC_ZoneThermostat:1 Device	ISO/IEC 29341-6-2
UPnP ControlValve:1 Service	ISO/IEC 29341-6-10
UPnP HVAC_FanOperatingMode:1 Service	ISO/IEC 29341-6-11
UPnP FanSpeed:1 Service	ISO/IEC 29341-6-12
UPnP HouseStatus:1 Service	ISO/IEC 29341-6-13
UPnP HVAC_SetpointSchedule:1 Service	ISO/IEC 29341-6-14
UPnP TemperatureSensor:1 Service	ISO/IEC 29341-6-15
UPnP TemperatureSetpoint:1 Service	ISO/IEC 29341-6-16
UPnP HVAC_UserOperatingMode:1 Service	ISO/IEC 29341-6-17
UPnP BinaryLight:1 Device	ISO/IEC 29341-7-1
UPnP DimmableLight:1 Device	ISO/IEC 29341-7-2
UPnP Dimming:1 Service	ISO/IEC 29341-7-10
UPnP SwitchPower:1 Service	ISO/IEC 29341-7-11
UPnP InternetGatewayDevice:1 Device	ISO/IEC 29341-8-1
UPnP LANDevice:1 Device	ISO/IEC 29341-8-2
UPnP WANDevice:1 Device	ISO/IEC 29341-8-3
UPnP WANConnectionDevice:1 Device	ISO/IEC 29341-8-4
UPnP WLANAccessPointDevice:1 Device	ISO/IEC 29341-8-5
UPnP LANHostConfigManagement:1 Service	ISO/IEC 29341-8-10
UPnP Layer3Forwarding:1 Service	ISO/IEC 29341-8-11
UPnP LinkAuthentication:1 Service	ISO/IEC 29341-8-12
UPnP RadiusClient:1 Service	ISO/IEC 29341-8-13
UPnP WANCableLinkConfig:1 Service	ISO/IEC 29341-8-14
UPnP WANCommonInterfaceConfig:1 Service	ISO/IEC 29341-8-15
UPnP WANDSLLinkConfig:1 Service	ISO/IEC 29341-8-16
UPnP WANEthernetLinkConfig:1 Service	ISO/IEC 29341-8-17
UPnP WANIPConnection:1 Service	ISO/IEC 29341-8-18
UPnP WANPOTSLinkConfig:1 Service	ISO/IEC 29341-8-19
UPnP WANPPPConnection:1 Service	ISO/IEC 29341-8-20
UPnP WLANConfiguration:1 Service	ISO/IEC 29341-8-21
UPnP Printer:1 Device	ISO/IEC 29341-9-1
UPnP Scanner:1.0 Device	ISO/IEC 29341-9-2
UPnP ExternalActivity:1 Service	ISO/IEC 29341-9-10
UPnP Feeder:1.0 Service	ISO/IEC 29341-9-11
UPnP PrintBasic:1 Service	ISO/IEC 29341-9-12
UPnP Scan:1 Service	ISO/IEC 29341-9-13
UPnP QoS Architecture:1.0	ISO/IEC 29341-10-1
UPnP QoSDevice:1 Service	ISO/IEC 29341-10-10
UPnP QoSManager:1 Service	ISO/IEC 29341-10-11
UPnP QoSPolicyHolder:1 Service	ISO/IEC 29341-10-12
UPnP QoS Architecture:2	ISO/IEC 29341-11-1
UPnP QOS v2 Schema Files	ISO/IEC 29341-11-2

UPnP Document Title	ISO/IEC 29341 Part
UPnP QosDevice:2 Service	ISO/IEC 29341-11-10
UPnP QosManager:2 Service	ISO/IEC 29341-11-11
UPnP QosPolicyHolder:2 Service	ISO/IEC 29341-11-12
UPnP RemoteUIClientDevice:1 Device	ISO/IEC 29341-12-1
UPnP RemoteUIServerDevice:1 Device	ISO/IEC 29341-12-2
UPnP RemoteUIClient:1 Service	ISO/IEC 29341-12-10
UPnP RemoteUIServer:1 Service	ISO/IEC 29341-12-11
UPnP DeviceSecurity:1 Service	ISO/IEC 29341-13-10
UPnP SecurityConsole:1 Service	ISO/IEC 29341-13-11

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 29341-8-20:2008

<https://standards.iteh.ai/catalog/standards/sist/9cbafa00-b1ca-4f72-964c-61fec5196ee5/iso-iec-29341-8-20-2008>

1. Overview and Scope

This service definition is compliant with the UPnP Device Architecture version 1.0.

This service-type enables a UPnP control point to configure and control PPP connections on the WAN interface of a UPnP compliant **InternetGatewayDevice**^{*}. Any type of WAN interface (for e.g., DSL or POTS) that can support a PPP connection can use this service.

The service is REQUIRED if a PPP connection is used for WAN access, and is specified in

urn:schemas-upnp-org:device:WANConnectionDevice

one or more instances of which are specified under the device

urn:schemas-upnp-org:device:WANDevice

An instance of **WANDevice** is specified under the root device

urn:schemas-upnp-org:device:InternetGatewayDevice

Generally, Internet connections are set up from a WAN interface of the **InternetGatewayDevice** to Internet Service Providers (ISPs). However, an implementation MAY support PPP connections that are bridged or relayed (as in the case of some DSL modems) through the gateway device. **WANDevice** is a container for all UPnP services associated with a physical WAN device. It is assumed that clients are connected to **InternetGatewayDevice** via a LAN (IP-based network).

An instance of a **WANPPPConnection** service is activated (refer to SST below) for each actual Internet Connection instance on a **WANConnectionDevice**. **WANPPPConnection** service provides PPP-level connectivity with an ISP for networked clients on the LAN. More than one instance of **WANPPPConnection** service may be defined on a **WANConnectionDevice** – representing multiple user accounts using the same link (username / password) to an ISP.

Multiple instances of this service will be distinguished based on the ServiceID for each service instance.

<https://standards.iteh.ai/catalog/standards/sist/9cbafa00-b1ca-4f72-964c->

In accordance with UPnP Architecture version 1.0, the maximum number of **WANPPPConnection** service instances is static and specified in the **InternetGatewayDevice** description document.

A **WANConnectionDevice** MAY include a **WAN{POTS/DSL/Cable/Ethernet}LinkConfig** service that encapsulates Internet access properties pertaining to the physical link of a particular WAN access type. These properties are common to all instances of **WANPPPConnection** in a **WANConnectionDevice**.

A **WANDevice** provides a **WANCommonInterfaceConfig** service that encapsulates Internet access properties common across all **WANConnectionDevice** instances.

* Refer to companion documents defined by the UPnP Internet Gateway working committee for more details on specific devices and services referenced in this document.

2. Service Modeling Definitions

2.1. ServiceType

The following service type identifies a service that is compliant with this template:

urn:schemas-upnp-org:service:*WANPPPConnection:1.*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 29341-8-20:2008

<https://standards.iteh.ai/catalog/standards/sist/9cbafa00-b1ca-4f72-964c-61fec5196ee5/iso-iec-29341-8-20-2008>

2.2. State Variables

Table 1: State Variables

Variable Name	Req. or Opt. ¹	Data Type	Allowed Value ¹	Default Value ²	Eng. Units
ConnectionType	R	string	Depends on PossibleConnectionTypes	Not specified	N/A
PossibleConnectionTypes	R	string	See Table 1.1	Not specified	N/A
ConnectionStatus	R	string	See Table 1.2	Not specified	N/A
Uptime	R	ui4	Undefined	Not specified	seconds
UpstreamMaxBitRate	R	ui4	>= 0	Not specified	bitspersecond
DownstreamMaxBitRate	R	ui4	>= 0	Not specified	bitspersecond
LastConnectionError	R	string	See Table 1.3	Not specified	N/A
AutoDisconnectTime	O	ui4	>= 0	Not specified	seconds
IdleDisconnectTime	O	ui4	>= 0	Not specified	seconds
WarnDisconnectDelay	O	ui4	>= 0	Not specified	seconds
RSIPAvailable	R	boolean	0, 1	Not specified	N/A
NATEnabled	R	boolean	0,1	Not specified	N/A
UserName	O	string	Undefined	Empty string	N/A
Password	O	string	Undefined	Empty string	N/A
PPPEncryptionProtocol	O	string	Undefined	Empty string	N/A
PPPCompressionProtocol	O	string	Undefined	Empty string	N/A
PPPAuthenticationProtocol	O	string	Undefined	Empty string	N/A
ExternalIPAddress	R	string	String of the type "x.x.x.x"	Empty string	N/A
PortMappingNumberOfEntries	R	ui2	>=0	Not specified	N/A
PortMappingEnabled	R	boolean	0,1	Not specified	N/A
PortMappingLeaseDuration	R	ui4	0 to maximum value of ui4	Not specified	seconds
RemoteHost	R	string	String of the type "x.x.x.x" or empty string	Empty string	N/A
ExternalPort	R	ui2	Between 0 and 65535 inclusive	Not specified	N/A
InternalPort	R	ui2	Between 1 and 65535 inclusive	Not specified	N/A
PortMappingProtocol	R	string	See Table 1.4	Empty string	N/A
InternalClient	R	string	String of the type "x.x.x.x"	Empty string	N/A
PortMappingDescription	R	string	Undefined	Empty string	N/A
<i>Non-standard state variables implemented by an UPnP vendor go here.</i>	<i>X</i>	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>

¹ R = Required, O = Optional, X = Non-standard.

² Values listed in this column are required. To specify standard optional values or to delegate assignment of values to the vendor, you must reference a specific instance of an appropriate table below.

NOTE: Default values are not specified in the DCP. A vendor may however choose to provide default values for SST variables where appropriate.

Table 1.1: AllowedValueList for PossibleConnectionTypes

PLEASE NOTE: PossibleConnectionTypes is defined as a comma-separated string. However, the values within the string are restricted to the list given in the table below. We have used the allowedValueList table format only as a convenience to represent these values.

Value	Req. or Opt.	Description
<i>Unconfigured</i>	<u>R</u>	Valid connection types cannot be identified. This may be due to the fact that the LinkType variable (if specified in the WAN*LinkConfig service) is unspecified. THIS VALUE IS DEPENDENT ON THE DEPLOYMENT AND TESTING SHOULD BE DEFERED TO THE VENDOR.
<i>IP_Routed</i>	<u>R</u>	The Internet Gateway is an IP router between the LAN and the WAN connection. THIS VALUE IS ONLY APPLICABLE FOR AN IGD DEVICE SUPPORTING NAT. SHOULD NOT BE TESTED IN OTHER DEVICE CONFIGURATIONS.
<i>DHCP_Spoofed</i>	<u>R</u>	The Internet Gateway is an IP router with a DHCP spoofer. This DHCP spoofer is a proxy between IPCP (the IP configuration mechanism used by PPP) or DHCP on the WAN connection and DHCP on the LAN. The IP address obtained via IPCP or DHCP from the ISP is relayed back as a DHCP response to a CP on the LAN.
<i>PPPoE_Bridged</i>	<u>R</u>	The Internet Gateway is an Ethernet bridge between the LAN and the WAN connection. A PPPoE RAS server at the end of the WAN connection terminates PPPoE connections initiated by control points on the LAN. ONLY VALID IF IGD SUPPORTS THE CONFIGURATION AS DESCRIBED.
<i>PPTP_Relay</i>	<u>R</u>	The Internet Gateway relays PPP sessions originating via PPTP on the LAN over the WAN configured as PPPoA. The gateway hosts a PPTP PNS to terminate the PPTP connection. ONLY VALID IF IGD SUPPORTS THE CONFIGURATION AS DESCRIBED.
<i>L2TP_Relay</i>	<u>R</u>	The Internet Gateway relays PPP sessions originating via L2TP on the LAN over the WAN configured as PPPoA. The gateway hosts a L2TP LNS to terminate the L2TP connection. ONLY VALID IF IGD SUPPORTS THE CONFIGURATION AS DESCRIBED.
<i>PPPoE_Relay</i>	<u>R</u>	The Internet Gateway relays a PPPoE tunnel on the LAN over the WAN configured as PPPoA. The gateway hosts a PPPoE server / access concentrator to terminate the PPPoE connection on the LAN. ONLY VALID IF IGD SUPPORTS THE CONFIGURATION AS DESCRIBED.

NOTE: Refer to the **WANConnectionDevice** specification for valid combinations of LinkType and PossibleConnectionTypes for different modems that can support PPP based connections.

The expected behavior of connection related actions for the different connection types is described in the Theory of Operation section.

Table 1.2: AllowedValueList for ConnectionStatus

Value	Req. or Opt.	Description
<i>Unconfigured</i>	<u>R</u>	This value indicates that other variables in the service table are either uninitialized or in an invalid state. Examples of such variables include PossibleConnectionTypes, ConnectionType, UserName and Password.
<i>Connecting</i>	<u>Q</u>	The WANConnectionDevice is in the process of initiating a connection for the first time after the connection became disconnected.
<i>Authenticating</i>	<u>Q</u>	The gateway is in the process of authenticating to the ISP for establishing the connection.
<i>Connected</i>	<u>R</u>	At least one client has successfully initiated an Internet connection using this instance.
<i>PendingDisconnect</i>	<u>Q</u>	The connection is active (packets are allowed to flow through), but will transition to <i>Disconnecting</i> state after a certain period (indicated by WarnDisconnectDelay).
<i>Disconnecting</i>	<u>Q</u>	The WANConnectionDevice is in the process of terminating a connection. On successful termination, ConnectionStatus transitions to <i>Disconnected</i> .
<i>Disconnected</i>	<u>R</u>	No ISP connection is active (or being activated) from this connection instance. No packets are transiting the gateway.

NOTE: Whether or not a control point gets notified of the intermediary states of a connection transition may depend on the gateway implementation.

ISO/IEC 29341-8-20:2008
<https://standards.iteh.ai/catalog/standards/sist/9cbafa00-b1ca-4f72-964c-61fec5196ee5/iso-iec-29341-8-20-2008>