

# INTERNATIONAL STANDARD

iTeh STANDARD PREVIEW

Information technology – UPnP Device Architecture –  
Part 11-1: Quality of Service Device Control Protocol – Level 2 – Quality of  
Service Architecture

[ISO/IEC 29341-11-1:2008](https://standards.iso.org/standards/catalog/standards/sist/27696ee9-c140-4c42-9097-080335ac9b83/iso-iec-29341-11-1-2008)

<https://standards.iteh.ai/catalog/standards/sist/27696ee9-c140-4c42-9097-080335ac9b83/iso-iec-29341-11-1-2008>



**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2008 ISO/IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Email: [inmail@iec.ch](mailto:inmail@iec.ch)  
Web: [www.iec.ch](http://www.iec.ch)

### **About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### **About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre [www.iec.ch/webstore/custserv](http://www.iec.ch/webstore/custserv)

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: [csc@iec.ch](mailto:csc@iec.ch)  
Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00



ISO/IEC 29341-11-1

Edition 1.0 2008-11

# INTERNATIONAL STANDARD

---

Information technology – UPnP Device Architecture –  
Part 11-1: Quality of Service Device Control Protocol – Level 2 – Quality of  
Service Architecture

**STANDARD PREVIEW**  
(standards.iteh.ai)

ISO/IEC 29341-11-1:2008  
<https://standards.iteh.ai/catalog/standards/sist/27696ee9-c140-4c42-9097-080335ac9b83/iso-iec-29341-11-1-2008>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE

**M**

---

ICS 35.200

ISBN 978-2-88910-902-9

## CONTENTS

FOREWORD .....	4
ORIGINAL UPNP DOCUMENTS (informative) .....	6
<b>1. Glossary .....</b>	<b>8</b>
<b>2. Introduction .....</b>	<b>10</b>
2.1. Referenced Specifications .....	10
<b>3. Architecture Overview .....</b>	<b>11</b>
3.1. Motivation .....	12
3.1.1. Policy-based QoS .....	12
3.2. Key Concepts .....	13
3.2.1. Admission Control .....	13
3.2.2. Admission Policy .....	13
3.2.3. Traffic Descriptor .....	13
<b>4. UPnP QoS Services .....</b>	<b>14</b>
4.1. QosPolicyHolder Service .....	14
4.1.1. Role .....	14
4.1.2. Traffic Stream QoS Policy Description .....	14
4.2. QoS Manager .....	15
4.2.1. Role .....	15
4.2.2. Behavior .....	15
4.2.3. Dealing with Policy .....	15
4.2.4. QoS Update .....	16
4.3. QosDevice Service .....	16
4.3.1. Role .....	16
4.3.2. Behavior .....	16
4.3.3. Setup Traffic QoS .....	17
4.3.4. Traffic Admission Control .....	17
4.3.5. Path Information .....	17
4.3.6. Events .....	17
<b>5. System Operation .....</b>	<b>18</b>
5.1. Initiation of QoS Setup .....	18
5.1.1. Integrated Control Point .....	18
5.1.2. Independent AV Control Point .....	19
5.1.3. Determination of TrafficId .....	19
5.1.4. Creation of Optional Traffic Specification (Tspec) .....	20
5.2. Determination of Policy for the Traffic Stream .....	20
5.2.1. QosPolicyHolder Service .....	20
5.2.2. Default Policy .....	21
5.3. Determination of QosDevice Services that should be configured .....	22
5.3.1. Path Determination (Optional) .....	22
5.3.2. Setup Capabilities Determination .....	22
5.4. Configuration of QoS Devices .....	22
5.4.1. Priority Setup Strategy .....	23
5.4.2. Admission Control Strategy .....	23
5.4.3. Traffic Observation Strategy .....	23
5.5. Run time Operation .....	23
5.5.1. Lease Management .....	23
5.5.2. Traffic revocation .....	23
5.5.3. Violation of TSPEC .....	23

ITeH STANDARD PREVIEW  
 (standards.iteh.ai)  
 ISO/IEC 29341-11-1:2008  
<https://standards.iteh.ai/catalog/standards/sist/27696ee9-c140-4c42-9097-080335ac9b83/iso-iec-29341-11-1-2008>

5.5.4. The Use of Traffic Descriptor.....	23
5.6. Relationship to other UPnP Services and non UPnP Traffic Streams .....	24
5.6.1. UPnP IGD .....	24
5.6.2. Legacy Devices .....	24
<b>6. Prioritized QoS .....</b>	<b>25</b>
6.1. Management of Packet Priorities .....	25
<b>7. Usage of Tspec.....</b>	<b>27</b>
<b>Annex A (normative) Layer 2 Implementation Guidelines .....</b>	<b>28</b>
A.1 IEEE 802.1D, Annex G.....	28
A.2 HomePlug .....	28
A.3 HPNA .....	29
A.4 DSCP .....	29
<b>Annex B (normative) XML Namespaces .....</b>	<b>30</b>

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 29341-11-1:2008](https://standards.iteh.ai/catalog/standards/sist/27696ee9-c140-4c42-9097-080335ac9b83/iso-iec-29341-11-1-2008)

<https://standards.iteh.ai/catalog/standards/sist/27696ee9-c140-4c42-9097-080335ac9b83/iso-iec-29341-11-1-2008>

## INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

### Part 11-1: Quality of Service Device Control Protocol – Level 2 – Quality of Service Architecture

#### FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

IEC and ISO draw attention to the fact that it is claimed that compliance with this document may involve the use of patents as indicated below.

ISO and IEC take no position concerning the evidence, validity and scope of the putative patent rights. The holders of the putative patent rights have assured IEC and ISO that they are willing to negotiate free licences or licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of the putative patent rights are registered with IEC and ISO.

Intel Corporation has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Intel Corporation  
Standards Licensing Department  
5200 NE Elam Young Parkway  
MS: JFS-98  
USA – Hillsboro, Oregon 97124

Microsoft Corporation has informed IEC and ISO that it has patent applications or granted patents as listed below:

6101499 / US; 6687755 / US; 6910068 / US; 7130895 / US; 6725281 / US; 7089307 / US; 7069312 / US; 10/783 524 / US

Information may be obtained from:

Microsoft Corporation  
One Microsoft Way  
USA – Redmond WA 98052

Philips International B.V. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Philips International B.V. – IP&S  
High Tech campus, building 44 3A21  
NL – 5656 Eindhoven

NXP B.V. (NL) has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

NXP B.V. (NL)  
High Tech campus 60  
NL – 5656 AG Eindhoven

Matsushita Electric Industrial Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Matsushita Electric Industrial Co. Ltd.  
1-3-7 Shiromi, Chuoh-ku  
JP – Osaka 540-6139

Hewlett Packard Company has informed IEC and ISO that it has patent applications or granted patents as listed below:

5 956 487 / US; 6 170 007 / US; 6 139 177 / US; 6 529 936 / US; 6 470 339 / US; 6 571 388 / US; 6 205 466 / US

Information may be obtained from:

Hewlett Packard Company  
1501 Page Mill Road  
USA – Palo Alto, CA 94304

Samsung Electronics Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Digital Media Business, Samsung Electronics Co. Ltd.  
416 Maetan-3 Dong, Yeongtang-Gu,  
KR – Suwon City 443-742

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 29341-11-1 was prepared by UPnP Implementers Corporation and adopted, under the PAS procedure, by joint technical committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Universal plug and play (UPnP) architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

## ORIGINAL UPnP DOCUMENTS (informative)

Reference may be made in this document to original UPnP documents. These references are retained in order to maintain consistency between the specifications as published by ISO/IEC and by UPnP Implementers Corporation. The following table indicates the original UPnP document titles and the corresponding part of ISO/IEC 29341:

UPnP Document Title	ISO/IEC 29341 Part
UPnP Device Architecture 1.0	ISO/IEC 29341-1
UPnP Basic:1 Device	ISO/IEC 29341-2
UPnP AV Architecture:1	ISO/IEC 29341-3-1
UPnP MediaRenderer:1 Device	ISO/IEC 29341-3-2
UPnP MediaServer:1 Device	ISO/IEC 29341-3-3
UPnP AVTransport:1 Service	ISO/IEC 29341-3-10
UPnP ConnectionManager:1 Service	ISO/IEC 29341-3-11
UPnP ContentDirectory:1 Service	ISO/IEC 29341-3-12
UPnP RenderingControl:1 Service	ISO/IEC 29341-3-13
UPnP MediaRenderer:2 Device	ISO/IEC 29341-4-2
UPnP MediaServer:2 Device	ISO/IEC 29341-4-3
UPnP AV Datastructure Template:1	ISO/IEC 29341-4-4
UPnP AVTransport:2 Service	ISO/IEC 29341-4-10
UPnP ConnectionManager:2 Service	ISO/IEC 29341-4-11
UPnP ContentDirectory:2 Service	ISO/IEC 29341-4-12
UPnP RenderingControl:2 Service	ISO/IEC 29341-4-13
UPnP ScheduledRecording:1	ISO/IEC 29341-4-14
UPnP DigitalSecurityCamera:1 Device	ISO/IEC 29341-5-1
UPnP DigitalSecurityCameraMotionImage:1 Service	ISO/IEC 29341-5-10
UPnP DigitalSecurityCameraSettings:1 Service	ISO/IEC 29341-5-11
UPnP DigitalSecurityCameraStillImage:1 Service	ISO/IEC 29341-5-12
UPnP HVAC_System:1 Device	ISO/IEC 29341-6-1
UPnP HVAC_ZoneThermostat:1 Device	ISO/IEC 29341-6-2
UPnP ControlValve:1 Service	ISO/IEC 29341-6-10
UPnP HVAC_FanOperatingMode:1 Service	ISO/IEC 29341-6-11
UPnP FanSpeed:1 Service	ISO/IEC 29341-6-12
UPnP HouseStatus:1 Service	ISO/IEC 29341-6-13
UPnP HVAC_SetpointSchedule:1 Service	ISO/IEC 29341-6-14
UPnP TemperatureSensor:1 Service	ISO/IEC 29341-6-15
UPnP TemperatureSetpoint:1 Service	ISO/IEC 29341-6-16
UPnP HVAC_UserOperatingMode:1 Service	ISO/IEC 29341-6-17
UPnP BinaryLight:1 Device	ISO/IEC 29341-7-1
UPnP DimmableLight:1 Device	ISO/IEC 29341-7-2
UPnP Dimming:1 Service	ISO/IEC 29341-7-10
UPnP SwitchPower:1 Service	ISO/IEC 29341-7-11
UPnP InternetGatewayDevice:1 Device	ISO/IEC 29341-8-1
UPnP LANDevice:1 Device	ISO/IEC 29341-8-2
UPnP WANDevice:1 Device	ISO/IEC 29341-8-3
UPnP WANConnectionDevice:1 Device	ISO/IEC 29341-8-4
UPnP WLANAccessPointDevice:1 Device	ISO/IEC 29341-8-5
UPnP LANHostConfigManagement:1 Service	ISO/IEC 29341-8-10
UPnP Layer3Forwarding:1 Service	ISO/IEC 29341-8-11
UPnP LinkAuthentication:1 Service	ISO/IEC 29341-8-12
UPnP RadiusClient:1 Service	ISO/IEC 29341-8-13
UPnP WANCableLinkConfig:1 Service	ISO/IEC 29341-8-14
UPnP WANCommonInterfaceConfig:1 Service	ISO/IEC 29341-8-15
UPnP WANDSLLinkConfig:1 Service	ISO/IEC 29341-8-16
UPnP WANEthernetLinkConfig:1 Service	ISO/IEC 29341-8-17
UPnP WANIPConnection:1 Service	ISO/IEC 29341-8-18
UPnP WANPOTSLinkConfig:1 Service	ISO/IEC 29341-8-19
UPnP WANPPPoEConnection:1 Service	ISO/IEC 29341-8-20
UPnP WLANConfiguration:1 Service	ISO/IEC 29341-8-21
UPnP Printer:1 Device	ISO/IEC 29341-9-1
UPnP Scanner:1.0 Device	ISO/IEC 29341-9-2
UPnP ExternalActivity:1 Service	ISO/IEC 29341-9-10
UPnP Feeder:1.0 Service	ISO/IEC 29341-9-11
UPnP PrintBasic:1 Service	ISO/IEC 29341-9-12
UPnP Scan:1 Service	ISO/IEC 29341-9-13
UPnP QoS Architecture:1.0	ISO/IEC 29341-10-1
UPnP QoSDevice:1 Service	ISO/IEC 29341-10-10
UPnP QoSManager:1 Service	ISO/IEC 29341-10-11
UPnP QoSPolicyHolder:1 Service	ISO/IEC 29341-10-12
UPnP QoS Architecture:2	ISO/IEC 29341-11-1
UPnP QOS v2 Schema Files	ISO/IEC 29341-11-2



<b>UPnP Document Title</b>	<b>ISO/IEC 29341 Part</b>
UPnP QosDevice:2 Service	ISO/IEC 29341-11-10
UPnP QosManager:2 Service	ISO/IEC 29341-11-11
UPnP QosPolicyHolder:2 Service	ISO/IEC 29341-11-12
UPnP RemoteUIClientDevice:1 Device	ISO/IEC 29341-12-1
UPnP RemoteUIServerDevice:1 Device	ISO/IEC 29341-12-2
UPnP RemoteUIClient:1 Service	ISO/IEC 29341-12-10
UPnP RemoteUIServer:1 Service	ISO/IEC 29341-12-11
UPnP DeviceSecurity:1 Service	ISO/IEC 29341-13-10
UPnP SecurityConsole:1 Service	ISO/IEC 29341-13-11

## **iTeh STANDARD PREVIEW** **(standards.iteh.ai)**

[ISO/IEC 29341-11-1:2008](https://standards.iteh.ai/catalog/standards/sist/27696ee9-c140-4c42-9097-080335ac9b83/iso-iec-29341-11-1-2008)

<https://standards.iteh.ai/catalog/standards/sist/27696ee9-c140-4c42-9097-080335ac9b83/iso-iec-29341-11-1-2008>

# 1. Glossary

## Access Domain

A set of LAN or MAN stations together with interconnecting data transmission media and related equipment (e.g., connectors, repeaters), in which the LAN or MAN stations use the same MAC protocol to establish the sequence of stations that are in temporary control of the shared transmission media.

## Access Priority

The Access Priority is a parameter that indicates the priority handling when accessing the communication resource. The range of access priorities is defined by the layer 2 networking technology.

## AV Control Point

A Control Point that is used in an AV scenario and utilizes UPnP AV.

## Best Effort

Best effort is a service of the Internet Protocol; i.e. it makes almost no guarantees about a packet other than attempting to transmit it. At the destination, the packet may arrive damaged, it may be out of order (compared to other packets sent between the same hosts), it may be duplicated, or it may be dropped entirely. If reliability is needed, it is provided by upper level protocols transported using IP.

With the introduction of IEEE 802.1D priority tagging the priority associated with untagged packets is also called "Best Effort".

## Bridge

A functional unit that interconnects two or more LANs that use the same Data Link layer protocols above the MAC sublayer, but can use different MAC protocols.

## Hub

A device, with two or more physical ports, that forwards all traffic received on any individual port to all other ports. This device is also referred to as a "repeater". In a home network, a hub connects networks segments of the same physical medium.

## IGD

Internet Gateway Device: a border device that physically connects the Home Network with a WAN. This device performs routing. QoS mechanisms associated with routing are not addressed by this architecture; the IGD may present a QoSDevice interface on the Home Network.

## Intermediate Device

An intermediate device is physically connected between the Source and Sink device data flow. There may be more than one intermediate device in the Source to Sink connection.

## Path

A path is the physical course that traffic will flow on from source to sink. For UPnP QoS, a path must reside within a single IP subnet, but a path may comprise multiple segments.

## Packet Priority

The Packet Priority is a layer 2 parameter that indicates the priority handling requested by the originating service. Typically this parameter is part of a packet header and indicates the relative importance of the packet compared to other packets. It is used to differentiate packets to determine which are given preferential access to the communication medium. This parameter is typically mapped to an Access Priority value supported by the network device.

## Policy Management

A function that makes decisions on the traffic streams allowed to use network resources.

### **Prioritized Services**

Prioritized services refer to a general methodology for providing QoS by differentiating traffic. Messages types are grouped by order of importance and assigned a priority. Message types assigned a higher priority are given preferential access to the communications medium.

### **Quality of Service (QoS)**

The term QoS refers to a broad collection of networking capabilities and techniques. The goal of QoS is to improve the user experience of a network's ability to deliver predictable results for sensitive applications such as audio, video, and voice applications. Elements of network performance within the scope of QoS often include bandwidth (throughput), latency (delay), and error rate. There are two broad classes of QoS: data reliability and temporal reliability. Each makes different demands on network technologies. This architecture is primarily concerned with delivering temporal reliability

### **Router**

A device, with two or more physical ports, that makes port to port traffic forwarding decisions based on layer 3 information (source and destination IP addresses).

### **Segment**

A segment refers to a section of a network that shares a common physical medium. The boundaries of a network segment are established by devices capable of regulating the flow of traffic into and out of the segment. This includes routers, bridges, hubs, switches, and adapters (e.g., PCI, PCCard, or USB NICs). With particular relevance to UPnP QoS, a segment is typically a physically distinct portion of a larger network that is in turn defined logically by devices residing on a common IP subnet.

### **Sink Device**

A Sink device provides media data receiving, playback, storage, or rendering capabilities. Some examples include TV monitors, Stereo and Home Theaters, PDAs, Wireless Monitors, DVD Recorders, and Printers.

### **Source Device**

A Source device provides media transmission and data sourcing capabilities. Examples include STBs, PVRs, PCs, Music Servers, Broadcast Tuners and Video Imaging Capture Devices. A source device acts as the source of a traffic stream, regardless of other functions on the device.

### **Subnet**

Subnet as defined in IETF RFC 3927 [RFC3927].

### **Traffic Class**

The Traffic Class indicates the kind of traffic in the traffic stream. The Traffic Class is used to distinguish, for example, audio from video. The distinction is at the application layer and the Traffic Class is mapped into the applicable layer 2 representations for the technology bearing the stream. An example is the mapping in IEEE 802.1D, Annex G.

### **Traffic Identifier (TID)**

A Traffic Identifier is a set of information that uniquely identifies a set of data packets as belonging to a traffic stream. This information is typically used by a packet classifier function to associate a Traffic Specification's QoS contract to the service provided to the Traffic stream. Other technologies may refer to this as a Filter Spec (RFC2205) or Traffic Classifier (IEEE 802.11e).

### **Traffic Specification (TSPEC)**

A Traffic Specification contains a set of parameters that define the characteristics of the traffic stream. The TSPEC may be used to define the operating requirement for carrying the traffic stream and may define the operation of the packet scheduling function.

### **Traffic Stream (TS)**

Traffic Stream is a unidirectional flow of data that originates at a source device and terminates at one or more sink device(s).

## 2. Introduction

This architecture document describes the motivation, use and interaction of the three services that comprise the UPnP QoS Framework:

- QosDevice
- QosPolicyHolder
- QosManager

It should be noted that while UPnP QoS defines three services (listed above), it does not define a new device type.

Since Quality of Service issues need to be solved for multiple usage scenarios, it is expected that vendors may use any UPnP device as a container for the services defined by UPnP QoS. The Control Points and QoS Management Entities must look for UPnP QoS Services embedded in all UPnP device types.

The UPnP QoS Framework is compliant with the UPnP Device Architecture version 1.0.

### 2.1. Referenced Specifications

Unless explicitly stated otherwise herein, implementation of the mandatory provisions of any standard referenced by this specification shall be mandatory for compliance with this specification.

[Annex\_G] – IEEE 802.1D-2004, Annex G, *IEEE Standard for Information technology - Telecommunications and information exchange between systems - IEEE standard for local and metropolitan area networks - Common specifications - Media access control (MAC) Bridges*, 2004.

[XML] – *Extensible Markup Language (XML) 1.0 (Second Edition)*, T. Bray, J. Paoli, C. M. Sperberg-McQueen, E. Maler, eds. W3C Recommendations, 6 October 2000.

[QM] – UPnP QosManager:2 Service Document:  
<https://standards.iteh.ai/catalog/standards/sist/27696ee9-c140-4c42-9097-080335ac9b83/iso-iec-29341-11-1-2008>

[QD] – UPnP QosDevice:2 Service Document:

[QPH] – UPnP QosPolicyHolder:2 Service Document:

[AV] – UPnP AV Architecture Document V0.83

[DEVICE] - [UPnP Device Architecture, version 1.0](#).

[DSCP] - [IETF RFC 2474](#), *Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers*, K. Nichols, Cisco Systems, S. Blake, Torrent Networking Technologies, F. Baker, Cisco Systems, D. Black, EMC Corporation, December 1998.

[RFC3927] IETF RFC 3927, Dynamic Configuration of IPv4 Link-Local Addresses.

[RFC3339] – *Date and Time on the Internet: Timestamps*, G. Klyne, July 2002.  
<http://www.ietf.org/rfc/rfc3339.txt>

[RFC2474] - Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers.  
<http://www.ietf.org/rfc/rfc2474.txt>