



SLOVENSKI STANDARD SIST ETS 300 576 E1:2003

01-december-2003

9 j fcdg]'X][]HJb]'WV] b]'h'Y_ca i b]_UW'g_]]g]ghYa 'fZJhU&L'Ë'AcXi `UW'Uf} GA
\$)'\$(Ł

European digital cellular telecommunications system (Phase 2); Modulation (GSM 05.04)

iTeh STANDARD PREVIEW (standards.iteh.ai)

Ta slovenski standard je istoveten z: **ETS 300 576 Edition 1**

<https://standards.iteh.ai/catalog/standards/sist/fl73b224-cdae-444b-a24f-df22c8fa3ac3/sist-ets-300-576-e1-2003>

ICS:

33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)
-----------	---	--

SIST ETS 300 576 E1:2003

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ETS 300 576 E1:2003

<https://standards.iteh.ai/catalog/standards/sist/f173b224-cdae-444b-a24f-df22c8fa3ac3/sist-ets-300-576-e1-2003>



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 576

September 1994

Source: ETSI TC-SMG

Reference: GSM 05.04

ICS: 33.060.30

Key words: European digital cellular telecommunications system, Global System for Mobile communications (GSM)

iTeh STANDARD PREVIEW
(standards.iteh.ai)
European digital cellular telecommunications system (Phase 2);
Modulation

[SIST ETS 300.576 E1:2003](https://standards.iteh.ai/catalog/standards/sist/300-576-e1-2003/cdae-444b-a24f-df22c8fa3ac3/sist-ets-300-576-e1-2003)
(GSM 05.04)
<https://standards.iteh.ai/catalog/standards/sist/300-576-e1-2003/cdae-444b-a24f-df22c8fa3ac3/sist-ets-300-576-e1-2003>

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1994. All rights reserved.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 576 E1:2003](https://standards.iteh.ai/catalog/standards/sist/fl73b224-cdae-444b-a24f-df22c8fa3ac3/sist-ets-300-576-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/fl73b224-cdae-444b-a24f-df22c8fa3ac3/sist-ets-300-576-e1-2003>

Contents

Foreword	5
1.1 Scope	7
1.2 Normative references	7
1.3 Definitions and abbreviations	7
2 Modulation format.....	7
2.1 Modulating bit rate	7
2.2 Start and stop of the burst	7
2.3 Differential encoding	8
2.4 Filtering	8
2.5 Output phase	9
2.6 Modulation	9
History.....	10

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 576 E1:2003](https://standards.iteh.ai/catalog/standards/sist/fl73b224-cdae-444b-a24f-df22c8fa3ac3/sist-ets-300-576-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/fl73b224-cdae-444b-a24f-df22c8fa3ac3/sist-ets-300-576-e1-2003>

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 576 E1:2003](https://standards.iteh.ai/catalog/standards/sist/fl73b224-cdae-444b-a24f-df22c8fa3ac3/sist-ets-300-576-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/fl73b224-cdae-444b-a24f-df22c8fa3ac3/sist-ets-300-576-e1-2003>

Foreword

This European Telecommunication Standard (ETS) has been produced by the Special Mobile Group (SMG) Technical Committee (TC) of the European Telecommunications Standards Institute (ETSI).

This ETS specifies the modulation format used within the European digital cellular telecommunications system (Phase 2).

This ETS corresponds to GSM technical specification, GSM 05.04 version 4.0.3.

The specification from which this ETS has been derived was originally based on CEPT documentation, hence the presentation of this ETS may not be entirely in accordance with the ETSI/PNE rules.

Reference is made within this ETS to GSM Technical Specifications (GSM-TSs) (NOTE).

NOTE: TC-SMG has produced documents which give the technical specifications for the implementation of the European digital cellular telecommunications system. Historically, these documents have been identified as GSM Technical Specifications (GSM-TSs). These TSs may have subsequently become I-ETTs (Phase 1), or ETSS (Phase 2), whilst others may become ETSI Technical Reports (ETRs). GSM-TSs are, for editorial reasons, still referred to in GSM ETSS.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 576 E1:2003](https://standards.iteh.ai/catalog/standards/sist/fl73b224-cdae-444b-a24f-df22c8fa3ac3/sist-ets-300-576-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/fl73b224-cdae-444b-a24f-df22c8fa3ac3/sist-ets-300-576-e1-2003>

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 576 E1:2003](https://standards.iteh.ai/catalog/standards/sist/fl73b224-cdae-444b-a24f-df22c8fa3ac3/sist-ets-300-576-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/fl73b224-cdae-444b-a24f-df22c8fa3ac3/sist-ets-300-576-e1-2003>

1.1 Scope

The modulator receives the bits from the encryption unit, see GSM 05.01, and produces an RF signal. The filtering of the RF signal necessary to obtain the spectral purity is not defined, neither are the tolerances associated with the theoretical filter requirements specified. These are contained in GSM 05.05.

1.2 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication referred to applies.

- [1] GSM 01.04 (ETR 100): "European digital cellular telecommunication system (Phase 2); Definitions, abbreviations and acronyms".
- [2] GSM 05.01 (ETS 300 573): "European digital cellular telecommunication system (Phase 2); Physical layer on the radio path General description".
- [3] GSM 05.02 (ETS 300 574): "European digital cellular telecommunication system (Phase 2); Multiplexing and multiple access on the radio path".
- [4] GSM 05.05 (ETS 300 577): "European digital cellular telecommunication system (Phase 2); Radio transmission and reception".

1.3 Definitions and abbreviations

Definitions and abbreviations used in this specification are listed in GSM 01.04.

2 Modulation format

2.1 Modulating bit rate

[SIST ETS 300 576 E1:2003](http://standards.iteh.ai/catalog/standards/sist/fl73b224-cdae-444b-a24f-df22c8fa3ac3/sist-ets-300-576-e1-2003)

The modulating bit rate is $1/T = 1625/6$ kbit/s (ie app. 270.833 kbit/s).

2.2 Start and stop of the burst

Before the first bit of the bursts as defined in GSM 05.02 enters the modulator, the modulator has an internal state as if a modulating bit stream consisting of consecutive ones ($d_j = 1$) had entered the differential encoder. Also after the last bit of the time slot, the modulator has an internal state as if a modulating bit stream consisting of consecutive ones ($d_j = 1$) had continued to enter the differential encoder. These bits are called dummy bits and define the start and the stop of the active and the useful part of the burst as illustrated in Fig.1. Nothing is specified about the actual phase of the modulator output signal outside the useful part of the burst.