

Edition 1.0 2012-03

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE

Electric and optical fibre cables Test methods for hon-metallic materials – Part 410: Miscellaneous tests – Test method for copper-catalyzed oxidative degradation of polyolefin insulated conductors

Câbles électriques et à fibres optiques – Méthodes d'essai pour les matériaux non-métalliques – 009110957d6d/ec-60811-410-2012 Partie 410: Essais divers – Méthode d'essai pour la mesure de la dégradation par oxydation catalytique par le cuivre des conducteurs isolés aux polyoléfines





# THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2012 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur. Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office	Tel.: +41 22 919 02 11
CH-1211 Geneva 20	info@iec.ch
Switzerland	www.iec.ch

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

#### **Useful links:**

## IEC publications search - www.iec.ch/searchpub

The advanced search enables you to find **IEC publications FCLS**. The world's leading online dictionary of electronic and by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced endossi1-41(additional languages. Also known as the International withdrawn publications. https://standards.iteh.ai/catalog/standards/sist/480c800e-ad32-482-

IEC Just Published - webstore.iec.ch/justpublished 0957d6d/iec-608custome2Service Centre - webstore.iec.ch/csc

Stay up to date on all new IEC publications. Just Published details all new publications released. Available on-line and also once a month by email.

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

#### A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

#### A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

#### Liens utiles:

Recherche de publications CEI - www.iec.ch/searchpub

La recherche avancée vous permet de trouver des publications CEI en utilisant différents critères (numéro de référence, texte, comité d'études,...).

Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

#### Just Published CEI - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications de la CEI. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

#### Electropedia - www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (VEI) en ligne.

#### Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.



Edition 1.0 2012-03

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE

Electric and optical fibre cables Test methods for non-metallic materials – Part 410: Miscellaneous tests – Test method for copper-catalyzed oxidative degradation of polyolefin insulated conductors

IEC 60811-410:2012

Câbles électriques et à fibres optigues d'essai pour les matériaux non-métalliques – 009110957d6d/iec-60811-410-2012 Partie 410: Essais divers – Méthode d'essai pour la mesure de la dégradation par oxydation catalytique par le cuivre des conducteurs isolés aux polyoléfines

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

PRICE CODE CODE PRIX

L

ICS 29.035.01; 29.060.20

ISBN 978-2-88912-972-0

Warning! Make sure that you obtained this publication from an authorized distributor. Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

 Registered trademark of the International Electrotechnical Commission Marque déposée de la Commission Electrotechnique Internationale

## CONTENTS

FOI	REWC	)RD	3		
INT	RODI	JCTION	5		
1	Scop	e	6		
2	Norm	ative references	6		
3	Terms and definitions6				
4	Test	method	6		
	4.1	General	6		
	4.2	Apparatus	6		
	4.3	Sample and test pieces preparation	7		
	4.4	Test procedure	7		
	4.5	Measurements	8		
5	Test	report	8		
Annex A (normative) Instrument calibration10					
Bib	Bibliography11				

Figure 1 – Evaluation of OIT from	n recorded-time-based thermogram	9
Figure A.1 – Representative men	ting endothermic for indiumE.V.I.E.W.	10
	standards.iteh.ai)	

<u>IEC 60811-410:2012</u> https://standards.iteh.ai/catalog/standards/sist/48bc8b0e-ad53-4b82-b248-009110957d6d/iec-60811-410-2012

### INTERNATIONAL ELECTROTECHNICAL COMMISSION

### ELECTRIC AND OPTICAL FIBRE CABLES – TEST METHODS FOR NON-METALLIC MATERIALS –

## Part 410: Miscellaneous tests – Test method for copper-catalyzed oxidative degradation of polyolefin insulated conductors

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees. A DARD PRE VIEW
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60811-410 has been prepared by IEC technical committee 20: Electric cables.

This Part 410 of IEC 60811 cancels and replaces Annex B of IEC 60811-4-2:2004, which is withdrawn. Full details of the replacements are shown in Annex A of IEC 60811-100:2012.

There are no specific technical changes with respect to the previous edition, but see the Foreword to IEC 60811-100:2012.

The text of this standard is based on the following documents:

FDIS	Report on voting
20/1294/FDIS	20/1343/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This part of IEC 60811 shall be used in conjunction with IEC 60811-100.

A list of all the parts in the IEC 60811 series, published under the general title Electric and optical fibre cables - Test methods for non-metallic materials, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, TANDARD PREVIEW
- amended.

(standards.iteh.ai)

IEC 60811-410:2012 https://standards.iteh.ai/catalog/standards/sist/48bc8b0e-ad53-4b82-b248-009110957d6d/iec-60811-410-2012

#### INTRODUCTION

The IEC 60811 series specifies the test methods to be used for testing non-metallic materials of all types of cables. These test methods are intended to be referenced in standards for cable construction and for cable materials.

NOTE 1 Non-metallic materials are typically used for insulating, sheathing, bedding, filling or taping within cables.

NOTE 2 These test methods are accepted as basic and fundamental and have been developed and used over many years principally for the materials in all energy cables. They have also been widely accepted and used for other cables, in particular optical fibre cables, communication and control cables and cables for ships and offshore applications.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>IEC 60811-410:2012</u> https://standards.iteh.ai/catalog/standards/sist/48bc8b0e-ad53-4b82-b248-009110957d6d/iec-60811-410-2012

### ELECTRIC AND OPTICAL FIBRE CABLES – TEST METHODS FOR NON-METALLIC MATERIALS –

## Part 410: Miscellaneous tests – Test method for copper-catalyzed oxidative degradation of polyolefin insulated conductors

#### 1 Scope

This Part 410 of IEC 60811 gives the procedure for copper-catalyzed oxidative degradation of a polyolefin, which is typically used for insulation in communication cables.

Full test conditions, such as temperature, duration, etc. and full test requirements are not specified in this standard; it is intended that they should be specified by the standard dealing with the relevant type of cable.

### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60811-100:2012, Electric and optical Stibrel Cables – Test methods for non-metallic materials – Part 100p General stehai/catalog/standards/sist/48bc8b0e-ad53-4b82-b248-009110957d6d/iec-60811-410-2012

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60811-100 apply.

#### 4 Test method

#### 4.1 General

The need for a manufacturer to monitor his cable production to ensure that it has adequate resistance to oxidation is well established. The Oxidation Induction Time (OIT) test has been found suitable for monitoring both raw materials and cables for compliance with this requirement, once suitable materials have been selected. The OIT test is not suitable for the selection of materials. For this purpose, long-term thermal ageing tests are preferred.

#### 4.2 Apparatus

For the purposes of this test, the different equipment used is as follows:

- a) A differential thermal analyser or differential scanning calorimeter, capable of heating at rates of up to at least (20 ± 1) K/min and maintaining the test temperature isothermally within 0,2 K and of automatic recording of differences in temperature (or differences in heat transfer) between the sample and a reference material to the required sensitivity and precision.
- b) A recorder capable of displaying heat flow or temperature difference on the Y-axis, and time on the X-axis. The time base shall be accurate to  $\pm$  1 % and be readable to 0,1 min.
- c) A gas-selector switch and regulators for high-purity nitrogen and oxygen.

- d) An analytical balance capable of weighing 30 g, and readable and repeatable to  $\pm 0.1$  mg.
- e) Test pieces holders: aluminium holders, each of approximately 6 mm to 7 mm in diameter, or of similar dimensions as supplied by the manufacturer of the instrument.

#### 4.3 Sample and test pieces preparation

From a sample of the cable, prepare an appropriate number, e.g. four test pieces of different colours, of approximately 4 mm length containing the core. The test pieces shall be cut from an insulated core to yield 3 mg to 5 mg of insulating material.

Insert one test piece in an aluminium holder.

#### 4.4 Test procedure

Before carrying out a test series, the instrument shall be calibrated and prepared as described in Annex A.

Open valves on both the nitrogen and oxygen gas cylinders. Place the gas selector switch to the nitrogen (N<sub>2</sub>) position and adjust the flow rate to (50  $\pm$  5) ml/min using a flowmeter.

Place the prepared test piece holder (see 4.3) in the differential thermal analyser and an empty aluminium holder in the reference position.

NOTE Crimping the test piece with a suitable aluminium or stainless steel screen is optional. It may provide a better contact with the test piece holder.

Purge with nitrogen for 5 min. Check the flow rate and readjust to  $(50 \pm 5)$  ml/min if required.

Set signal amplification and recorder sensitivity-to the full scale pen deflection associated with the exothermic reaction and set the temperature base at zero ad53-4b82-b248-009110957d6d/iec-60811-410-2012

Set the heating rate to 20 K/min and start the programmed heating.

Continue heating until the specified test temperature, controlled to  $\pm$  1 °C, is reached. Discontinue programmed heating and equilibrate the test piece to a constant temperature. Start to record the thermogram. A test temperature of 200 °C has been found appropriate for polyethylene. To simplify the procedure, it is allowed to omit the programmed pre-heating and start directly at the test temperature.

Once temperature equilibrium has been established (steady recorder signal), change purge gas to oxygen, and adjust the flow rate to (50  $\pm$ 5) ml/min. Mark this point on the recorder. This change-over point to oxygen purge is considered the zero time of the experiment ( $T_0$ ).

Continue the isothermal operation until maximum pen deflection is attained after commencement of the oxidative exotherm as shown on the recorder (see Figure 1).

In the case of a multi-step exotherm, continue the isothermal operation until maximum pen deflection occurs.

When the test is completed, turn off the recorder and switch the gas selector back to nitrogen.

Allow the differential thermal analyser to cool to the ambient temperature.

Repeat the entire test on a new test piece, three more times, thus generating a total of four thermograms. The use of a fresh aluminium reference holder for each test piece is optional.

#### 4.5 Measurements

Extend the recorded base line from time zero to beyond the oxidative exotherm. Extrapolate the steepest part of the exotherm to intercept the extended baseline (see Figure 1).

The OIT shall be measured from zero to the smallest time interval practical, not exceeding 1 min.

### 5 Test report

The test report shall be in accordance with that given in IEC 60811-100.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

IEC 60811-410:2012 https://standards.iteh.ai/catalog/standards/sist/48bc8b0e-ad53-4b82-b248-009110957d6d/iec-60811-410-2012



4 isothermal mode (oxygen)

Figure 1 – Evaluation of OIT from recorded-time-based thermogram