

PUBLICLY AVAILABLE SPECIFICATION

PRE-STANDARD



**Low-voltage switchgear and controlgear – Controller-Device Interfaces (CDIs) –
Part 7: CompoNet**

(standards.iteh.ai)

IEC PAS 62026-7:2009

<https://standards.iteh.ai/en/standards/sist/55c4d6a7-1ad2-4f14-a06b-3f1ccceca2d8/iec-pas-62026-7-2009>

Withhold



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

PUBLICLY AVAILABLE SPECIFICATION

PRE-STANDARD



**Low-voltage switchgear and controlgear – Controller-Device Interfaces (CDIs) –
Part 7: CompoNet**

<https://standards.iteh.ai/catalog/standards/sist/557ad61a7-1ad2-4f14-a06b-3f1ccceca2d8/iec-pas-62026-7-2009>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XH**

ICS 29.130.20, 33.200

ISBN 978-2-88910-808-4

CONTENTS

| | |
|---|----|
| FOREWORD..... | 12 |
| INTRODUCTION..... | 14 |
| 1 Scope..... | 16 |
| 2 Normative references | 16 |
| 3 Terms, definitions, symbols, abbreviated terms and conventions | 17 |
| 3.1 Terms and definitions | 17 |
| 3.2 Symbols and abbreviated terms..... | 20 |
| 4 Classification..... | 20 |
| 4.1 General..... | 20 |
| 4.2 Network specifications..... | 22 |
| 4.3 Components..... | 23 |
| 4.4 CompoNet communication model | 24 |
| 4.5 CompoNet and CIP | 24 |
| 5 Characteristics | 24 |
| 5.1 Communication cycle | 24 |
| 5.1.1 General | 24 |
| 5.1.2 Time domains..... | 24 |
| 5.1.3 A typical communication cycle..... | 25 |
| 5.2 Messaging protocol..... | 25 |
| 5.2.1 Message frame format..... | 25 |
| 5.2.2 Message frame types | 28 |
| 5.2.3 Explicit messaging..... | 50 |
| 5.2.4 Explicit messaging client/server timing requirement..... | 61 |
| 5.3 CompoNet communication object classes..... | 62 |
| 5.3.1 General | 62 |
| 5.3.2 Identity object class definition (class ID code: 01 _{Hex}) | 62 |
| 5.3.3 Message router object class definition (class ID code: 02 _{Hex})..... | 62 |
| 5.3.4 Connection object class definition (class ID code: 05 _{Hex}) | 62 |
| 5.3.5 CompoNet Link object class definition (class ID code: F7 _{Hex})..... | 72 |
| 5.3.6 CompoNet Repeater object (class ID code: F8 _{Hex}) | 79 |
| 5.4 Network access state machine | 81 |
| 5.4.1 General | 81 |
| 5.4.2 Network access events..... | 81 |
| 5.4.3 State transition diagram..... | 82 |
| 5.4.4 Data rate auto-detection | 84 |
| 5.4.5 Duplicate MAC ID detection..... | 85 |
| 5.4.6 Repeater behaviour | 86 |
| 5.5 I/O connection..... | 87 |
| 5.6 TDMA..... | 87 |
| 5.6.1 General | 87 |
| 5.6.2 Data link timing features | 88 |
| 5.6.3 Calculation of Time Domain..... | 91 |
| 5.7 Physical layer..... | 97 |

| | | |
|--------|--|-----|
| 5.7.1 | General | 97 |
| 5.7.2 | Physical signalling | 97 |
| 5.7.3 | Master port requirements..... | 97 |
| 5.7.4 | Slave port requirements..... | 100 |
| 5.7.5 | Receiving signal requirements for master and slave ports | 103 |
| 5.7.6 | Requirements for digital processing | 105 |
| 5.7.7 | Recommended circuits and component parameters | 108 |
| 5.7.8 | Isolation | 114 |
| 5.7.9 | Transmission medium..... | 115 |
| 5.7.10 | Topology | 116 |
| 5.7.11 | Link power..... | 121 |
| 5.7.12 | Repeater implementation..... | 125 |
| 6 | Product information | 125 |
| 7 | Normal service, mounting and transport conditions..... | 126 |
| 7.1 | Normal service conditions | 126 |
| 7.1.1 | General | 126 |
| 7.1.2 | Ambient air temperature | 126 |
| 7.1.3 | Altitude..... | 126 |
| 7.1.4 | Climatic conditions | 126 |
| 7.2 | Conditions during transport and storage..... | 126 |
| 7.3 | Mounting | 126 |
| 8 | Constructional and performance requirements..... | 127 |
| 8.1 | Indicators and configuration switches..... | 127 |
| 8.1.1 | Status indicators..... | 127 |
| 8.1.2 | Switches..... | 128 |
| 8.1.3 | CompoNet marking..... | 129 |
| 8.2 | CompoNet cable..... | 131 |
| 8.2.1 | Overview..... | 131 |
| 8.2.2 | Cable profile template..... | 131 |
| 8.2.3 | Round cable I profile | 132 |
| 8.2.4 | Round cable II profile | 134 |
| 8.2.5 | Flat cable I profile..... | 136 |
| 8.2.6 | Flat cable II profile..... | 138 |
| 8.3 | Terminators..... | 140 |
| 8.3.1 | General | 140 |
| 8.3.2 | Terminating resistors | 140 |
| 8.3.3 | Terminating capacitors | 140 |
| 8.4 | Connectors..... | 140 |
| 8.4.1 | General | 140 |
| 8.4.2 | Template | 141 |
| 8.4.3 | Engaging specification for connector profiles: open, flat I, flat II | 142 |
| 8.4.4 | Specifications of hooks for connector profiles: open, flat I, flat II..... | 144 |
| 8.4.5 | Open connector profile | 146 |
| 8.4.6 | Profile of flat connector I | 150 |
| 8.4.7 | Profile of flat connector II | 155 |
| 8.4.8 | Profile of sealed M12 connector | 158 |
| 8.5 | Node power supply implementation | 159 |
| 8.5.1 | General | 159 |
| 8.5.2 | Requirement for node power supply connection..... | 159 |

| | | |
|---------------------|--|-----|
| 8.5.3 | Requirements for nodes powered by network power supplies | 160 |
| 8.6 | Miswiring protection | 161 |
| 9 | Tests | 161 |
| 9.1 | General | 161 |
| 9.2 | Electrical testing | 161 |
| 9.2.1 | Slave port operation voltage test | 161 |
| 9.2.2 | Reverse connected power supply line | 162 |
| 9.2.3 | Momentary power interruption | 163 |
| 9.2.4 | Isolation | 163 |
| 9.2.5 | Input impedance | 164 |
| 9.2.6 | Output waveform | 164 |
| 9.2.7 | Minimum input waveform | 165 |
| 9.2.8 | Electromagnetic compatibility testing | 166 |
| 9.3 | Mechanical test | 167 |
| 9.4 | Logical test | 167 |
| 9.4.1 | General | 167 |
| 9.4.2 | Term definitions | 167 |
| 9.4.3 | Test of slaves and repeaters | 168 |
| 9.4.4 | Test of master | 171 |
| Annex A (normative) | CompoNet common services | 174 |
| Annex B (normative) | CompoNet error codes | 175 |
| Annex C (normative) | Connection path attribute definition | 176 |
| Annex D (normative) | Data type specification and encoding | 177 |
| Annex E (normative) | Communication objects library | 181 |
| Annex F (normative) | Value ranges | 182 |
| Annex G (normative) | CN default time domain | 183 |
| | Bibliography | 187 |
| Figure 1 | – Segment layer | 21 |
| Figure 2 | – CompoNet components | 23 |
| Figure 3 | – Time domains | 25 |
| Figure 4 | – A typical communication cycle | 25 |
| Figure 5 | – A general frame | 26 |
| Figure 6 | – Preamble of frames | 26 |
| Figure 7 | – Transmission direction | 27 |
| Figure 8 | – Transmission direction | 27 |
| Figure 9 | – OUT frame format | 28 |
| Figure 10 | – OUT command code | 29 |
| Figure 11 | – TRG frame format | 30 |
| Figure 12 | – TRG command code | 31 |
| Figure 13 | – CN frame format | 31 |
| Figure 14 | – CN command code | 31 |
| Figure 15 | – IN frame format | 33 |
| Figure 16 | – IN command code | 33 |
| Figure 17 | – A_EVENT frame format | 34 |

Figure 18 – A_EVENT command code 35

Figure 19 – B_EVENT frame format 36

Figure 20 – B_EVENT command code meanings 36

Figure 21 – B_EVENT message format 37

Figure 22 – E_CMD block 38

Figure 23 – Group block 38

Figure 24 – Item block 39

Figure 25 – Status Read (STR Response) event data 41

Figure 26 – Configuration event data (STW Request) 43

Figure 27 – Poll data 44

Figure 28 – B_EVENT general decoding phase 45

Figure 29 – Flow chart for processing a matched STW request 48

Figure 30 – BEACON frame format 49

Figure 31 – BEACON command code 49

Figure 32 – Object diagram of A_Event message flow 51

Figure 33 – A_EVENT message format 51

Figure 34 – Compact message type request format (non-fragmented frame/first fragment frame) 52

Figure 35 – Expanded message type request format (non-fragmented frame/first fragment frame) 52

Figure 36 – Compact/Expanded message successful response format (unfragmented frame/first fragment frame) 53

Figure 37 – Compact/Expanded message unsuccessful response format (unfragmented frame/first fragment frame) 53

Figure 38 – Compact/Expanded message request format for fragments 53

Figure 39 – Compact/Expanded message response format for fragments 54

Figure 40 – Service data format 54

Figure 41 – Predefined master/slave I/O connection state transition diagram 68

Figure 42 – Predefined master/slave I/O connection state transition diagram 70

Figure 43 – Connection flow 71

Figure 44 – Allocate request service data 77

Figure 45 – Allocate response service data 78

Figure 46 – Release request service data 78

Figure 47 – Reset service parameter 80

Figure 48 – State transition diagram 83

Figure 49 – Sub-state of non-participated state 84

Figure 50 – Sub-state of participated state 84

Figure 51 – Data rate detection diagram 85

Figure 52 – BEACON changed by repeaters 87

Figure 53 – Multicast I/O connections 87

Figure 54 – Master MAC and Phy. circuit diagram 88

Figure 55 – Slave MAC and Phy. circuit diagram 89

Figure 56 – Repeater MAC and Phy. circuit diagram 89

Figure 57 – Transmission process 91

| | |
|--|-----|
| Figure 58 – Transmission cycle model | 92 |
| Figure 59 – CnDefaultTimeDomain cycle model | 93 |
| Figure 60 – Master event communication model | 95 |
| Figure 61 – Slave event communication model | 96 |
| Figure 62 – Manchester encoding (inverted) | 97 |
| Figure 63 – Master port transmit mask | 99 |
| Figure 64 – Output waveform test circuit for master or slave port | 100 |
| Figure 65 – Slave port transmit mask | 102 |
| Figure 66 – Receive mask 1 | 104 |
| Figure 67 – Receive mask 2 | 104 |
| Figure 68 – Receive mask 3 | 105 |
| Figure 69 – PHY/MAC interface diagram | 105 |
| Figure 70 – Digital receive mask 1 | 106 |
| Figure 71 – Digital receive mask 2 | 106 |
| Figure 72 – Digital receive mask 3 | 107 |
| Figure 73 – Logical transmit mask | 108 |
| Figure 74 – Recommended circuit for a master port | 109 |
| Figure 75 – Recommended circuit for a slave port | 110 |
| Figure 76 – Transformer symbol | 111 |
| Figure 77 – Driver voltage measurement circuit | 113 |
| Figure 78 – Propagation delay test circuit | 113 |
| Figure 79 – An isolation example of a master port | 114 |
| Figure 80 – An isolation example of an I/O module with connectivity to other power sources | 114 |
| Figure 81 – An isolation example of a simple slave that requires connection to devices with ungrounded signal wiring | 115 |
| Figure 82 – An isolation example of a non-network powered slave | 115 |
| Figure 83 – Media topology | 116 |
| Figure 84 – Position of a terminator | 117 |
| Figure 85 – Number of devices per segment | 117 |
| Figure 86 – Cable length limitation Illustration | 118 |
| Figure 87 – Branch restriction | 119 |
| Figure 88 – Wiring selection | 119 |
| Figure 89 – General wiring method | 120 |
| Figure 90 – Flexible wiring method | 121 |
| Figure 91 – Power dispatching method | 123 |
| Figure 92 – Network segment powered by the master | 123 |
| Figure 93 – Connection with power supply | 123 |
| Figure 94 – Network segments powered by repeaters | 124 |
| Figure 95 – A simplified diagram for a repeater | 125 |
| Figure 96 – Outline of round cable II | 136 |
| Figure 97 – Outline of flat cable I | 137 |
| Figure 98 – Dimension of flat cable I | 138 |
| Figure 99 – Outline of flat cable II | 139 |

| | |
|---|-----|
| Figure 100 – Dimension of flat cable II | 140 |
| Figure 101 – Engaging dimensions of plug connector | 142 |
| Figure 102 – Contact space for plug connector | 143 |
| Figure 103 – Engaging dimensions of jack connector | 144 |
| Figure 104 – Connector hook | 145 |
| Figure 105 – Open connector plug (informative) | 147 |
| Figure 106 – Open connector jack (informative) | 148 |
| Figure 107 – Method to measure contact resistance (open connectors) | 149 |
| Figure 108 – De-rating current for connectors | 149 |
| Figure 109 – Flat connector I plug | 152 |
| Figure 110 – Flat connector I jack (informative) | 153 |
| Figure 111 – Method to measure contact resistance (flat I, II connectors) | 154 |
| Figure 112 – Flat connector II plug (informative) | 156 |
| Figure 113 – Flat connector II jack (informative) | 157 |
| Figure 114 – Marking connector for trunk lines | 157 |
| Figure 115 – M12 connector pinout | 159 |
| Figure 116 – Link power circuits | 159 |
| Figure 117 – Power-drop along a cable | 160 |
| Figure 118 – Power design for a node (informative) | 161 |
| Figure 119 – Operating voltage test circuit | 162 |
| Figure 120 – Reverse connected power supply line | 162 |
| Figure 121 – Isolation | 163 |
| Figure 122 – Input impedance | 164 |
| Figure 123 – Output slave test circuit for slave port | 165 |
| Figure 124 – Minimum input waveform test circuit | 165 |
| Figure 125 – Minimum input waveform test system | 166 |
| Figure 126 – Data link test for slave and repeater DUT | 168 |
| Figure 127 – Test configuration for minimum traffic of master DUT | 171 |
| Figure 128 – Test configuration for proxy of master DUT | 173 |
| Figure D.1 – An example to generate CRC | 180 |
| Table 1 – Network specifications | 22 |
| Table 2 – OSI reference model and CompoNet | 24 |
| Table 3 – Command codes | 26 |
| Table 4 – Command restrictions for slave MAC | 28 |
| Table 5 – Block name description | 29 |
| Table 6 – CN target | 29 |
| Table 7 – I/O refresh | 29 |
| Table 8 – Block name description | 30 |
| Table 9 – Block name description | 31 |
| Table 10 – Duplication checking function status | 32 |
| Table 11 – A_EVENT sending request | 32 |
| Table 12 – Status of CN frames | 32 |

| | |
|---|----|
| Table 13 – Warning bit of CN frames | 32 |
| Table 14 – Alarm bit of CN frames | 33 |
| Table 15 – Block name description | 33 |
| Table 16 – Encoded length | 34 |
| Table 17 – Block name description | 34 |
| Table 18 – Acknowledgement bit of A_EVENT | 35 |
| Table 19 – Command type of A_EVENT | 35 |
| Table 20 – Block name description | 36 |
| Table 21 – Acknowledgement bit of B_EVENT | 37 |
| Table 22 – Command type of B_EVENT | 37 |
| Table 23 – E_CMD block meanings | 38 |
| Table 24 – Group block meanings | 39 |
| Table 25 – Item block meanings | 39 |
| Table 26 – Processing rules for a STR request | 46 |
| Table 27 – Processing rules for an A_EVENT poll request | 46 |
| Table 28 – Processing rules for a STW request | 47 |
| Table 29 – STW request commands | 48 |
| Table 30 – Block name description | 49 |
| Table 31 – Control code of BEACON frames | 49 |
| Table 32 – Speed Code of BEACON frames | 50 |
| Table 33 – Control code format | 54 |
| Table 34 – A Data encoding example | 56 |
| Table 35 – Fragment type values | 57 |
| Table 36 – Fragmented transmission | 58 |
| Table 37 – Fragmented reception | 59 |
| Table 38 – Explicit message timeout values | 61 |
| Table 39 – Maximum value of expected packet rate | 63 |
| Table 40 – CompoNet connection object attribute access rules | 64 |
| Table 41 – CompoNet Link object specific additional error codes | 66 |
| Table 42 – Connection instance ID for predefined master/slave connections | 67 |
| Table 43 – Default multicast poll connection object attribute values | 67 |
| Table 44 – Predefined master/slave I/O connection state event matrix | 69 |
| Table 45 – CompoNet Link class attributes | 72 |
| Table 46 – CompoNet Link class services | 72 |
| Table 47 – CompoNet Link instance attributes | 73 |
| Table 48 – MAC ID range | 74 |
| Table 49 – Data rate | 74 |
| Table 50 – Allocation choice | 74 |
| Table 51 – Data rate switch value | 75 |
| Table 52 – Bit definitions for node state octet | 75 |
| Table 53 – Bit definitions for node network state | 76 |
| Table 54 – CompoNet Link object common services | 76 |
| Table 55 – CompoNet Link Object class specific services | 76 |

| | |
|---|-----|
| Table 56 – Allocation choice octet contents | 77 |
| Table 57 – EPR value | 77 |
| Table 58 – Explicit message timer | 77 |
| Table 59 – Release master/slave connection set request parameters | 78 |
| Table 60 – Release choice octet contents | 78 |
| Table 61 – Repeater class attribute | 79 |
| Table 62 – Repeater class services | 79 |
| Table 63 – Instance attributes of repeater class | 79 |
| Table 64 – Repeater common service | 80 |
| Table 65 – Reset attributes | 80 |
| Table 66 – Data rate and network watchdog time periods | 82 |
| Table 67 – Description of the state machine | 83 |
| Table 68 – Duplicate MAC ID detection mechanism | 86 |
| Table 69 – Repeating directions of frames | 86 |
| Table 70 – Master timing features | 88 |
| Table 71 – Slave timing features | 89 |
| Table 72 – Repeater timing features | 90 |
| Table 73 – Cable propagation delay | 90 |
| Table 74 – Maximum cable length | 90 |
| Table 75 – Parameters in TimeDomain calculation | 91 |
| Table 76 – Frame marks | 92 |
| Table 77 – TimeDomain settings for nodes at first segment layer | 93 |
| Table 78 – TimeDomain settings for nodes at 2 nd and 3 rd segment layers | 93 |
| Table 79 – Repeater delay for CnDefaultTimeDomain calculation | 94 |
| Table 80 – Parameters for CnDefaultTimeDomain calculation | 94 |
| Table 81 – First segment layer settings | 95 |
| Table 82 – Settings for 2 nd and 3 rd segment layers | 95 |
| Table 83 – Parameters for Event Time Domain calculations | 96 |
| Table 84 – CompoNet Manchester encoding | 97 |
| Table 85 – Allowable connectors for the master port | 98 |
| Table 86 – Master port impedance during receive | 98 |
| Table 87 – Master port impedance during transmit | 98 |
| Table 88 – Master port transmit specifications for data rate of 4 Mbit/s; 3 Mbit/s and 1,5 Mbit/s | 99 |
| Table 89 – Master port transmit specifications for data rate of 93,75 kbit/s | 100 |
| Table 90 – Allowable connectors for permanently attached cables | 101 |
| Table 91 – Allowable connectors for the slave port | 101 |
| Table 92 – Slave port impedance during receive | 101 |
| Table 93 – Slave port impedance during transmit | 102 |
| Table 94 – Slave port transmit specifications for data rate of 4 Mbit/s; 3 Mbit/s and 1,5 Mbit/s | 103 |
| Table 95 – Slave port transmit specifications for data rate of 93,75 kbit/s | 103 |
| Table 96 – Specifications for digital receive mask 1 | 106 |
| Table 97 – Specifications for digital receive mask 2 | 107 |

| | |
|--|-----|
| Table 98 – Specifications for digital receive mask 3 | 107 |
| Table 99 – Specifications for logical transmit | 108 |
| Table 100 – Specification for pulse transformer | 111 |
| Table 101 – Specifications for transformer core | 112 |
| Table 102 – Specifications for transceiver..... | 112 |
| Table 103 – Sending | 113 |
| Table 104 – Receiving | 113 |
| Table 105 – Cable types | 115 |
| Table 106 – Cable conductor colours | 115 |
| Table 107 – CompoNet round cable I: network limitations | 118 |
| Table 108 – CompoNet 4-conductor cables: network limitations | 118 |
| Table 109 – Resistance characteristics | 121 |
| Table 110 – Network power supply specifications | 121 |
| Table 111 – Local power supply specifications..... | 122 |
| Table 112 – Node external power supply specifications | 122 |
| Table 113 – Module status indicator..... | 127 |
| Table 114 – CDI status indicator | 127 |
| Table 115 – Data rate switch encoding | 128 |
| Table 116 – Addresses switches | 129 |
| Table 117 – Indicator marking..... | 129 |
| Table 118 – Node address switch and device type marking..... | 130 |
| Table 119 – Connector marking | 131 |
| Table 120 – Cable profile: data pair specification..... | 131 |
| Table 121 – Cable profile: d.c. power pair specification | 132 |
| Table 122 – Cable profile: general specification..... | 132 |
| Table 123 – Round cable I: data pair specification | 133 |
| Table 124 – Round cable I: d.c. power pair specification..... | 133 |
| Table 125 – Round cable I: general specification | 134 |
| Table 126 – Round cable II: data pair specification | 134 |
| Table 127 – Round cable II: d.c. power pair specification..... | 135 |
| Table 128 – Round cable II: general specification | 135 |
| Table 129 – Flat cable I: data pair specification | 136 |
| Table 130 – Flat cable I: d.c. power pair specification | 137 |
| Table 131 – Flat cable I: general specification | 137 |
| Table 132 – Flat cable II: data pair specification | 138 |
| Table 133 – Flat cable II: d.c. power pair specification | 139 |
| Table 134 – Flat cable II: general specification | 139 |
| Table 135 – Connector profile template..... | 141 |
| Table 136 – Specification of open connector..... | 146 |
| Table 137 – Specification of flat connector I..... | 150 |
| Table 138 – Specification of flat connector II..... | 155 |
| Table 139 – Specification of sealed M12 connector..... | 158 |
| Table 140 – Input impedance for master | 164 |

Table 141 – Input impedance for slave..... 164

Table B.1 – Newly defined CompoNet error codes 175

Table F.1 – MAC ID and node address ranges 182

Table G.1 – CN default time domain table for 4 Mbit/s data rate 183

Table G.2 – CN default time domain table for 3 Mbit/s data rate 184

Table G.3 – CN default time domain table for 1,5 Mbit/s data rate..... 185

Table G.4 – CN default time domain table for 93,75 kbit/s data rate..... 186



iTeh STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/55c46a7-1ad2-4f14-a06b-3f1ccceca2d8/iec-pas-62026-7-2009>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**LOW-VOLTAGE SWITCHGEAR AND CONTROLGEAR –
CONTROLLER-DEVICE INTERFACES (CDIs) –**

Part 7: CompoNet

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

A PAS is a technical specification not fulfilling the requirements for a standard, but made available to the public.

IEC/PAS 62026-7 has been processed by subcommittee 17B: Low-voltage switchgear and controlgear, of IEC technical committee 17: Switchgear and controlgear.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

| Draft PAS | Report on voting |
|--------------|------------------|
| 17B/1650/PAS | 17B/1658/RVD |

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

This PAS shall remain valid for an initial maximum period of 3 years starting from the publication date. The validity may be extended for a single 3-year period, following which it shall be revised to become another type of normative document, or shall be withdrawn.

The list of all parts of the IEC 62026 series, under the general title: *Low-voltage switchgear and controlgear – Controller-device interfaces (CDIs)*, can be found on the IEC website.

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

IEC PAS 62026-7:2009
<https://standards.iteh.ai/catalog/standards/sist/55c40fa7-1ad2-4f14-a06b-3f1ccceca2d8/iec-pas-62026-7-2009>