



CISPR 16-1-6

Edition 1.2 2022-03
CONSOLIDATED VERSION

INTERNATIONAL STANDARD

NORME INTERNATIONALE



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE
COMITÉ INTERNATIONAL SPÉCIAL DES PERTURBATIONS RADIOÉLECTRIQUES

BASIC EMC PUBLICATION
PUBLICATION FONDAMENTALE EN CEM

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Specification for radio disturbance and immunity measuring apparatus and
methods –

Part 1-6: Radio disturbance and immunity measuring apparatus – EMC antenna
calibration

16-1-6-2014

Spécification des méthodes et des appareils de mesure des perturbations
radioélectriques et de l'immunité aux perturbations radioélectriques –
Partie 1-6: Appareils de mesure des perturbations radioélectriques et de
l'immunité aux perturbations radioélectriques – Étalonnage des antennes CEM





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2022 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC - webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 300 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 19 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.



CISPR 16-1-6

Edition 1.2 2022-03
CONSOLIDATED VERSION

INTERNATIONAL STANDARD

NORME INTERNATIONALE



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE
COMITÉ INTERNATIONAL SPÉCIAL DES PERTURBATIONS RADIOÉLECTRIQUES

BASIC EMC PUBLICATION
PUBLICATION FONDAMENTALE EN CEM

ITEH STANDARD PREVIEW

(standards.iteh.ai)

Specification for radio disturbance and immunity measuring apparatus and
methods –

Part 1-6: Radio disturbance and immunity measuring apparatus – EMC antenna
calibration

16-1-6-2014

Spécification des méthodes et des appareils de mesure des perturbations
radioélectriques et de l'immunité aux perturbations radioélectriques –
Partie 1-6: Appareils de mesure des perturbations radioélectriques et de
l'immunité aux perturbations radioélectriques – Étalonnage des antennes CEM

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 33.100.10; 33.100.20

ISBN 978-2-8322-3993-3

Warning! Make sure that you obtained this publication from an authorized distributor.

Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

REDLINE VERSION

VERSION REDLINE



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE
COMITÉ INTERNATIONAL SPÉCIAL DES PERTURBATIONS RADIOÉLECTRIQUES

BASIC EMC PUBLICATION
PUBLICATION FONDAMENTALE EN CEM

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Specification for radio disturbance and immunity measuring apparatus and
methods –

Part 1-6: Radio disturbance and immunity measuring apparatus – EMC antenna
calibration

16-1-6-2014

Spécification des méthodes et des appareils de mesure des perturbations
radioélectriques et de l'immunité aux perturbations radioélectriques –
Partie 1-6: Appareils de mesure des perturbations radioélectriques et de
l'immunité aux perturbations radioélectriques – Étalonnage des antennes CEM



CONTENTS

FOREWORD	11
1 Scope	13
2 Normative references	13
3 Terms, definitions and abbreviations	14
3.1 Terms and definitions	14
3.1.1 Antenna terms	14
3.1.2 Antenna factor terms	17
3.1.3 Measurement site terms	18
3.1.4 Other terms	19
3.2 Abbreviations	20
4 Fundamental concepts	21
4.1 General	21
4.2 The concept of antenna factor	21
4.3 Calibration methods for 30 MHz and above	22
4.3.1 General	22
4.3.2 Antenna minimum separation distances	22
4.3.3 General considerations for the TAM	22
4.3.4 General considerations for the SSM	22
4.3.5 General considerations for the SAM	23
4.4 Measurement uncertainties for antenna calibration measurement results	23
4.5 Summary of methods of measurement to obtain AF	24
5 Calibration methods for the frequency range 9 kHz to 30 MHz	26
5.1 Calibration of monopole antennas	26
5.1.1 General	26
5.1.2 Calibration by the ECSM	27
5.2 Calibration of loop antennas	33
5.2.1 General	33
5.2.2 TEM (Crawford) cell method	34
5.2.3 Three antenna method (TAM)	37
5.2.4 Current probe method (CPM)	47
5.2.5 Standard antenna method	50
6 Frequencies, equipment and functional checks for calibrations at or above 30 MHz	52
6.1 Calibration frequencies	52
6.1.1 Calibration frequency ranges and increments	52
6.1.2 Transition frequency for hybrid antennas	53
6.2 Measurement instrumentation requirements for antenna calibrations	53
6.2.1 Equipment types	53
6.2.2 Mismatch	55
6.2.3 Dynamic range and reproducibility of SIL measurement	56
6.2.4 Signal-to-noise ratio	57
6.2.5 Antenna masts and cables	57
6.3 Functional checks of an AUC	58
6.3.1 General	58
6.3.2 Balance of an antenna	58
6.3.3 Cross-polar performance of an antenna	58
6.3.4 Radiation patterns of an antenna	59

7	Basic parameters and equations common to antenna calibration methods for frequencies above 30 MHz	59
7.1	Summary of methods for measurements to obtain AF	59
7.2	Site insertion loss measurements.....	60
7.2.1	General	60
7.2.2	SIL and SA measurement procedure.....	60
7.2.3	Common uncertainty components of a SIL measurement.....	61
7.3	Basic equations for the calculation of AF from SIL and SA measurements	63
7.3.1	Antenna factor from SIL measurements	63
7.3.2	Relationship of AF and SIL for a free-space calibration site	63
7.3.3	Relationship of AF and SIL for a calibration site with a metal ground plane	63
7.4	Equations for AF and measurement uncertainties using the TAM, SSM, and SAM.....	65
7.4.1	TAM	65
7.4.2	SSM	70
7.4.3	SAM	72
7.5	Parameters for specifying antenna phase centre and position.....	74
7.5.1	General	74
7.5.2	Reference position and phase centres of LPDA and hybrid antennas.....	75
7.5.3	Phase centres of horn antennas	78
8	Details for TAM, SAM, and SSM calibration methods for frequencies of 30 MHz and above	80
8.1	General.....	80
8.2	Considerations for F_a calibrations using TAM	80
8.2.1	General considerations	80
8.2.2	Calibration site and antenna set-up considerations for use with the TAM	80
8.2.3	Antenna parameters for a free-space environment or a ground-plane site	82
8.2.4	Validation of calibration method.....	83
8.3	Considerations for F_a calibrations using the SAM	83
8.3.1	General considerations and calibration site for use of the SAM.....	83
8.3.2	Calibration procedures and antenna set-ups for F_a by the SAM	84
8.3.3	Parameters of the STA	84
8.4	SSM calibrations at a ground-plane site, 30 MHz to 1 GHz	85
8.4.1	General considerations and calibration site for SSM	85
8.4.2	Calibration procedure for SSM.....	86
8.4.3	Calculation of F_a	86
8.4.4	Uncertainties of F_a obtained using SSM	87
9	Calibration procedures for specific antenna types for frequencies of 30 MHz and above	88
9.1	General.....	88
9.2	Calibrations for biconical and hybrid antennas in a free-space environment for 30 MHz to 300 MHz, and tuned dipoles for 60 MHz to 1 000 MHz	88
9.2.1	General considerations and calibration site requirements	88
9.2.2	Calibration procedure and antenna set-up for use with the SAM	88
9.2.3	Uncertainties of F_a determined by the SAM	89
9.2.4	Antenna set-up for use with the TAM (alternative)	91
9.3	Calibration of biconical (30 MHz to 300 MHz) and hybrid antennas, using the SAM and VP at a ground-plane site.....	91

9.3.1	General considerations and calibration site requirements	91
9.3.2	Calibration procedure and antenna set-up	92
9.3.3	Uncertainties of F_a determined with the SAM.....	93
9.4	Calibration of LPDA, hybrid, and horn antennas in a free-space environment, 200 MHz to 18 GHz.....	94
9.4.1	General considerations and calibration site for a free-space environment.....	94
9.4.2	Calibrations using the TAM.....	96
9.4.3	Antenna set-up for use with the SAM.....	97
9.4.4	Alternative antenna set-up for site with absorber on the ground.....	97
9.5	Calibration of horn and LPDA antennas in a FAR, 1 GHz to 18 GHz	98
9.5.1	Calibration using the TAM.....	98
9.5.2	Calibration and antenna set-up for the SAM.....	102
Annex A (informative)	Background information and rationale for the methods of antenna calibration	103
A.1	Rationale for the need for several calibration methods and for use of a ground-plane site	103
A.2	Special measures for calibration of omnidirectional antennas.....	104
A.2.1	General	104
A.2.2	Difficulties with calibration of omnidirectional antennas.....	105
A.2.3	Minimizing reflections from antenna supports and radiation from cables	105
A.2.4	Field taper and monocone set-up for VP biconical calibration	106
A.2.5	Use of HP or VP in a FAR.....	107
A.2.6	Substitution where the STA is the same model as the AUC.....	107
A.3	Calibrations using broadband calculable dipole antennas	107
A.3.1	Disadvantages of tuned dipole antennas.....	107
A.3.2	Advantages of broadband calculable dipole antennas.....	108
A.3.3	Disadvantages of calculable dipole antennas	108
A.4	Rationale for F_a and biconical/LPDA antenna cross-over frequency	108
A.4.1	Rationale for F_a	108
A.4.2	Cross-over frequency from biconical to LPDA antennas.....	109
A.4.3	Biconical element designs	109
A.5	Sources of increased uncertainty in measurement of F_a by the SSM.....	110
A.6	Calibration of LPDA antennas using smaller separation distances.....	112
A.6.1	Calibration of LPDA antennas using smaller separation distances	112
A.6.2	Correction of electric field strength to account for phase centre of LPDA antennas	113
A.7	Cross-polar discrimination of LPDA antennas	114
A.8	Tips for measurement instrumentation	115
A.8.1	Signal-to-noise ratio	115
A.8.2	Connector pin depth	117
A.8.3	Effect of added adaptor in a “cable-through” measurement	117
A.8.4	Compression level	118
A.8.5	Source power slope function above 6 GHz.....	118
A.8.6	Frequency increment for detection of resonances	118
A.8.7	Return loss or VSWR	118
A.9	Uncertainty considerations	119
A.9.1	General	119
A.9.2	Achievable uncertainties for F_a	119
A.9.3	Uncertainties of dipoles above a ground plane	119

A.9.4 Verification of uncertainty by comparison of methods	120
Annex B (normative) Calibration of biconical antennas and tuned dipole antennas above a ground plane using the TAM and the SAM	121
B.1 General.....	121
B.2 Characteristics of biconical antennas and dipole antennas.....	121
B.3 Frequencies	121
B.4 Measurement of $F_a(h,p)$ of biconical and tuned dipole antennas and derivation of F_a by averaging $F_a(h,p)$, 30 MHz to 300 MHz	122
B.4.1 General	122
B.4.2 Measurement of $F_a(h,H)$ by the SAM and derivation of F_a	122
B.4.3 Measurement of $F_a(h,H)$ by the TAM and derivation of F_a	125
B.5 Measurement of F_a of tuned dipoles placed high above a ground plane in the frequency range 30 MHz to 1 000 MHz.....	127
B.5.1 General	127
B.5.2 Measurement of F_a by the SAM.....	127
B.5.3 Measurement of F_a by the TAM	129
Annex C (informative) Rationale for the equations used in antenna calibration and relevant information about antenna characteristics for uncertainty analysis in the frequency range 30 MHz to 1 GHz	131
C.1 General.....	131
C.2 Antenna factor and antenna gain	131
C.2.1 Relationship between AF and gain for antennas in a free-space environment.....	131
C.2.2 Relationship between AF and gain for monopole antennas on a large ground plane	133
C.3 Equations for the insertion loss between antennas.....	133
C.3.1 Site insertion loss measured at a free-space calibration site.....	133
C.3.2 Site insertion loss measured at a metal ground-plane site	135
C.3.3 Site attenuation measured at a metal ground-plane site.....	137
C.4 Uncertainty contribution caused by near-field effects	138
C.5 Uncertainty contribution due to the antenna proximity coupling	139
C.6 Uncertainty contribution due to the ground plane reflection	141
C.6.1 Coupling to image in ground plane.....	141
C.6.2 Correction factors $\Delta F_a,SSM$ for F_a of biconical antenna	146
C.7 Uncertainty contribution due to the antenna radiation pattern.....	147
C.7.1 General	147
C.7.2 Biconical antennas	148
C.7.3 LPDA antennas.....	148
C.7.4 Hybrid antennas	149
C.7.5 Horn and LPDA antennas from 1 GHz to 18 GHz	150
Annex D (informative) Background information and rationale for calibration of antennas at frequencies above 1 GHz.....	153
D.1 Mismatch uncertainty	153
D.2 Mutual coupling between antennas and chamber reflection.....	153
D.3 Antenna separation distance and phase centre	153
D.4 Example gain of DRH at 1 m distance	155
Annex E (informative) Notes for measurement uncertainty budgets.....	157
E.1 General.....	157
E.2 Notes for measurement uncertainty budgets	157

Annex F (informative) Mismatch uncertainties from a two-port device connected between a transmit port and a receive port	167
Annex G (informative) Verification method for calibration of monopole antennas and uncertainty analysis of the ECSM.....	169
G.1 Verification method for calibration of monopole antennas by the plane wave method from 5 MHz to 30 MHz.....	169
G.1.1 Calibration procedure	169
G.1.2 Uncertainty evaluation for the calibration of monopole antennas by the plane wave method.....	170
G.2 Uncertainty analysis of the ECSM	170
G.2.1 Effect of rod length longer than $\lambda/8$	170
G.2.2 Effect on AF of monopole antenna mounted on a tripod	172
G.2.3 Monopole antenna receiving an electric field	173
G.2.4 Equivalent capacitance substitution method (ECSM)	173
G.2.5 Uncertainties associated with the ECSM	175
G.2.6 An alternative to the dummy antenna, for which $F_{ac} = V_D - V_L$	177
Annex H (informative) Helmholtz coil method for calibration of loop antennas up to 150 kHz	178
H.1 Measurement procedure	178
H.2 Uncertainties.....	180
Annex I (normative) Antenna pattern measurement method in the frequency range above 1 GHz, with measurement uncertainty budget.....	182
I.1 General.....	182
I.2 Test set-up	182
I.3 Test method.....	184
I.4 Test report	187
I.5 Uncertainty budget.....	187
Annex J (informative) Monte Carlo simulation of TAM loop antenna calibration measurement uncertainty – Example source code.....	189
Bibliography.....	192
 Figure 1 – Set-up for AF determination using a network analyzer.....	30
Figure 2 – Set-up for AF determination using a measuring receiver and signal generator	30
Figure 3 – Example of mounting a capacitor in the dummy antenna	31
Figure 4 – Block diagram of TEM cell set-up for passive loop antennas	35
Figure 5 – Block diagram of TEM cell set-up for active loop antennas.....	36
Figure 21 – Loop antenna pair arrangements for the TAM.....	41
Figure 22 – Accuracy of Greene's formula and integral formula vs. frequency for $r_i = 0,05$ m, $r_j = 0,3$ m, and $d = 0,39$ m	42
Figure 23 – Examples of influence of ground plane on SIL in free-space condition.....	43
Figure 24 – Definitions of the parameters used in measurement uncertainty evaluation for $K(i,j)$	45
Figure 25 – Antenna arrangement for the current probe method (CPM).....	47
Figure 26 – Antenna arrangement for the standard antenna method	51
Figure 6 – Example of resonant spike due to poor biconical element connections, using 2 MHz increment.....	53
Figure 7 – Antenna set-up for SIL measurement at a free-space calibration site	61

Figure 8 – Antenna set-up for SIL and SA measurement at a ground-plane calibration site	61
Figure 9 – Antenna set-up for the TAM at a free-space calibration site	66
Figure 10 – Antenna set-up for the TAM at a calibration site with a metal ground plane	69
Figure 11 – Antenna set-up for the SSM	71
Figure 12 – Antenna set-up for the SAM at a calibration site with a metal ground plane	73
Figure 13 – Separation distance relative to the phase centre of an LPDA antenna	76
Figure 14 – LPDA antenna with a tapered curved geometry	78
Figure 15 – Separation distance with respect to the phase centre of horn antennas (see [49] for details).....	79
Figure 16 – Schematic of a DRH showing relative locations of field point and phase centre of the DRH	80
Figure 17 – Biconical antenna set-up for SAM using vertical polarization, showing the paired monocone antenna and an example collapsible-element biconical AUC	93
Figure 18 – Test set-up for the calibration of LPDA and hybrid antennas positioned at a large height.....	96
Figure 19 – Set-up for LPDA antennas above absorber.....	98
Figure 20 – Set-up for transmission measurements using a network analyzer	100
Figure A.1 – Illustration of the angles of the electromagnetic rays subtended from the scanned LPDA antenna to the fixed height LPDA antenna and to the ground plane	111
Figure A.2 – F_a of biconical antenna with 200Ω balun measured by the VP method of 9.3, and by the SSM method of 8.4 without correction.....	112
Figure A.3 – F_a of biconical antenna with 200Ω balun measured by the VP method of 9.3, and by the SSM method of 8.4 with correction	112
Figure A.4 – Separation distance relative to the phase centre of an LPDA antenna.....	114
Figure A.5 – Statistical properties of multiple S_{21} sweeps (minimum, maximum, and mean value).....	116
Figure A.6 – Standard deviation of S_{21}	116
Figure A.7 – Normalized standard deviation of S_{21}	117
Figure C.1 – Simplified model of a receive antenna	132
Figure C.2 – Insertion loss measurement for antenna calibration at a free-space calibration site	134
Figure C.3 – Insertion loss measurement for antenna calibration at a calibration site with a metal ground plane	136
Figure C.4 – Comparison of field strength given by Equation (C.17) versus in near-field region given by Equation (C.31).....	139
Figure C.5 – Theoretical calculations of proximity coupling effects on the AF from the TAM (free-space conditions)	141
Figure C.6 – Deviation of AF from free-space value, F_a , caused by mutual coupling to the image in a metal ground plane (theoretical results)	143
Figure C.7 – Variation of $F_a(h,H)$ of biconical antenna with 50Ω balun, 30 MHz to 320 MHz at heights every 0,5 m above a ground plane from 1 m to 4 m	144
Figure C.8 – AF of Figure C.7 normalized to free-space AF	144
Figure C.9 – Variation of $F_a(h,H)$ of biconical antenna with 200Ω balun, 30 MHz to 320 MHz at heights every 0,5 m above a ground plane from 1 m to 4 m	145
Figure C.10 – Diagram of one triangular section of a biconical antenna element.....	147
Figure C.11 – Examples of radiation patterns (relative realized gain) of two example biconical antennas compared to ideal half-wave tuned dipole antenna	148

Figure C.12 – Examples of radiation patterns (relative realized gain) of three example LPDA antennas, compared to ideal half-wave tuned dipole antenna.....	149
Figure C.13 – Examples of radiation patterns (relative realized gain) of an example hybrid antenna, compared to ideal half-wave tuned dipole antenna.....	150
Figure C.14 – Example radiation patterns for classical DRH antenna	151
Figure C.15 – Example radiation patterns for novel DRH antenna	151
Figure C.16 – Example radiation patterns for classical LPDA antenna	152
Figure C.17 – Example radiation patterns for V-type LPDA antenna.....	152
Figure D.1 – Relative phase centres of a DRH antenna and an LPDA antenna	154
Figure D.2 – A transmission system between a horn antenna and an LPDA antenna	155
Figure D.3 – Measured AFs of a DRH antenna at 4,5 GHz	155
Figure D.4 – Graph showing the realized gain at 1 m for a DRH antenna	156
Figure E.1 – Comparison of measured and predicted SIL for calculable dipole antenna – 60 MHz element.....	160
Figure E.2 – Comparison of measured and predicted SIL for calculable dipole antenna – 180 MHz element.....	161
Figure E.3 – Reflectivity of chamber absorbing materials	165
Figure E.4 – Laser alignment system	165
Figure F.1 – Flow graph representation of a two-port device between a transmit port and a receiver port.....	167
Figure F.2 – Signal flow reduction.....	167
Figure G.1 – Diagram showing how the brass rod connects to the type N male bulkhead connector.....	170
Figure G.2 – Graph of the magnitude of the $\tan(\dots)$ ratio term in Equation (4) of 5.1.2.2	171
Figure G.3 – Graphical presentation of Equation (4) of 5.1.2.2 self-capacitance C_a of a 1 m monopole	171
Figure G.4 – Graphical presentation of Equation (5) of 5.1.2.2 height correction factor L_h	172
Figure G.5 – Calibration set-up consisting of a biconical and a loop antenna, and an elevated monopole antenna with vertical feed wires.....	173
Figure G.6 – Equivalent circuit representation for a monopole antenna system	173
Figure G.7 – Monopole antenna calibration using the ECSM	174
Figure G.8 – Equivalent circuit representation for the ECSM	174
Figure G.9 – Simplified circuit representation for Figure G.8	175
Figure G.10 – Circuit for dummy antenna simulating the effects of the antenna effective height, h_e	177
Figure H.1 – Diagram of Helmholtz coil method set-up	178
Figure H.2 – Variation of H/I across the central plane between the coils	180
Figure I.1 – Typical set-up for antenna pattern measurement	183
Figure I.2 – Definition of d_1	183
Figure I.3 – Definition of d_2	184
Figure I.4 – With d_1 held constant, d_2 is increased in x cm steps	185
Figure I.5 – With d_2 held constant, d_1 is increased in x cm steps	185
Figure I.6 – Distance and angle correction	187
Table 1 – Summary of calibration methods above 30 MHz for F_a	25

Table 2 – Calibration methods above 30 MHz by subclause number	26
Table 3 – Frequency increments for monopole antenna calibration	27
Table 4 – Example measurement uncertainty budget for F_{ac} of a monopole antenna calibrated by the ECSM using Equation (9)	33
Table 5 – Example measurement uncertainty budget for F_{aH} of a loop antenna measured in a TEM cell	37
Table 15 – Examples for valid use of Equation (65)	41
Table 16 – Example of an uncertainty budget for site insertion loss $A_j(i,j)$	45
Table 17 – Example of an uncertainty budget for $K(i,j)$ as used by the TAM	46
Table 18 – Example of an uncertainty budget for F_{aH} of a loop antenna determined by the TAM – expanded uncertainty at 30 MHz	46
Table 19 – Example of an uncertainty budget for F_{aH} of a loop antenna determined by the current probe method – expanded uncertainty at 30 MHz	49
Table 20 – Example of an uncertainty budget for transfer impedance $ Z $ according to the jig method of CISPR 16-1-2	50
Table 21 – Example of an uncertainty budget for $F_{aH}(\text{AUC})$ of a loop antenna determined by the standard antenna method – expanded uncertainty at 30 MHz	51
Table 6 – Frequency increments for broadband antenna calibration	52
Table 7 – Example measurement uncertainty budget for common components of a SIL measurement result evaluated from Equation (20)	62
Table 8 – Parameters used to determine phase centres of segments A and B	78
Table 9 – Example measurement uncertainty budget for F_a of a horizontally-polarized biconical antenna measured by the SSM	87
Table 10 – Example measurement uncertainty budget for F_a of a biconical antenna measured by the SAM in a FAR over the frequency range 30 MHz to 300 MHz	90
Table 11 – Example measurement uncertainty budget for F_a of a tuned dipole antenna obtained by the SAM in a FAR at a free-space calibration site, using a calculable tuned dipole as the STA in the frequency range above 60 MHz	91
Table 12 – Example measurement uncertainty budget for F_a of a biconical antenna measured using the SAM for vertical polarization over the frequency range 30 MHz to 300 MHz	94
Table 13 – Example measurement uncertainty budget for F_a of LPDA and hybrid antennas measured by the TAM at 4 m height for the frequency range 200 MHz to 3 GHz	97
Table 14 – Example measurement uncertainty budget for F_a of a horn antenna measured by the TAM above 1 GHz for 3 m separation in free space	101
Table A.1 – Example type N male and female connector pin depths and tolerances using a type N pin-depth gauge	117
Table A.2 – Typical type N adaptor characteristics	118
Table B.1 – Antenna set-up for the SAM for tuned dipole antennas with averaging of $F_a(h,H)$	122
Table B.2 – Antenna set-up for the SAM for biconical antennas with averaging of $F_a(h,H)$	123
Table B.3 – Example measurement uncertainty budget for $F_a(h,H)$ of a biconical antenna measured by the SAM over the frequency range 30 MHz to 300 MHz	123
Table B.4 – Example measurement uncertainty budget for F_a of a biconical antenna obtained by the SAM with averaging of $F_a(h,H)$ in the frequency range below 300 MHz	125
Table B.5 – Example measurement uncertainty budget for $F_a(h,H)$ of a biconical antenna obtained by the TAM with the antenna set-up specified in Table B.2	126

Table B.6 – Example measurement uncertainty budget for F_a of a biconical antenna obtained by the TAM with averaging of $F_a(h, H)$ in the frequency range below 300 MHz	126
Table B.7 – Antenna set-ups for the SAM for determining F_a of tuned dipole antennas at specific frequencies in the range 30 MHz to 1 000 MHz	128
Table B.8 – Example measurement uncertainty budget for F_a of a tuned dipole antenna obtained by the SAM using the antenna set-ups specified in Table B.7	129
Table B.9 – Example measurement uncertainty budget for F_a of a tuned dipole antenna obtained by the TAM using the antenna set-ups specified in Table B.7	130
Table C.1 – Examples of the antenna height range h for horizontal polarization for an error $\leq 0,3$ dB	145
Table C.2 – Correction factors $\Delta F_{a,SSM}$ to convert AF measured by SSM to F_a	146
Table C.3 – Mechanical dimensions for the biconical antenna [52].....	147
Table G.1 – Example measurement uncertainty budget for F_a of a monopole antenna measured by the SAM.....	170
Table H.1 – Example measurement uncertainty budget for F_{aH} of a loop antenna measured by the Helmholtz coil method for the frequency range 50 kHz to 150 kHz	181
Table I.1 – Correction of angle α for a distance of $d_1 = 3$ m (refer to Figure I.6).....	186
Table I.2 – Example measurement uncertainty budget for antenna pattern measurement above 1 GHz.....	188

iTeh STANDARD PREVIEW (standards.iteh.ai)

[CISPR 16-1-6:2014](#)

<https://standards.iteh.ai/catalog/standards/sist/a13cbc14-2d50-43d0-a556-13b669ccfd00/cispr-16-1-6-2014>

INTERNATIONAL ELECTROTECHNICAL COMMISSION
INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

**SPECIFICATION FOR RADIO DISTURBANCE AND IMMUNITY
MEASURING APPARATUS AND METHODS –**

**Part 1-6: Radio disturbance and immunity measuring apparatus –
EMC antenna calibration**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendments has been prepared for user convenience.

CISPR 16-1-6 edition 1.2 contains the first edition (2014-12) [documents CISPR/A/1087/FDIS and CISPR/A/1098/RVD], its amendment 1 (2017-01) [documents CISPR/A/1195/FDIS and CISPR/A/1204/RVD] and its amendment 2 (2022-03) [documents CIS/A/1362/FDIS and CIS/A/1365/RVD].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendments 1 and 2. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.