



Edition 3.0 2010-08

TECHNICAL REPORT





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Email: inmail@iec.ch

About the IEC

Web: www.iec.ch

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

■ Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

■ IEC Just Published: www.iec.ch/online news/justqub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00



CISPR/TR 16-3

Edition 3.0 2010-08

TECHNICAL REPORT



INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE XH

ICS 33.100.10; 33.100.20 ISBN 978-2-88912-147-2

CONTENTS

F	OREW	ORD		14
1	Sco	ре		16
2	Norr	native re	eferences	16
3	B Terr	ns. defin	nitions and abbreviations	17
	3.1		and definitions	
	3.2		viations	
4	_		ports	
	4.1	Correl charac	ation between measurements made with apparatus having cteristics differing from CISPR characteristics and measurements made	20
		4.1.1	General	20
		4.1.2	Critical interference-measuring instrument parameters	21
		4.1.3	Impulse interference – correlation factors	23
		4.1.4	Pandom noico	25
		4.1.5	The root mean square (rms) detector	25
		4.1.6	Discussion Application to typical noise sources	25
		4.1.7	Application to typical noise sources	25
		4.1.8	Conclusions	26
	4.2	Interfe	erence simulators	27
		4.2.1	General	27
		4.2.2	Types of interference signals	27
		4.2.3	Circuits for simulating broadband interference	
	4.3	Relation	onship between limits for open-area test site and the reverberation	
		chamb	per	32
		4.3.1	General	1.6.32
		4.3.2	Correlation between measurement results of the reverberation chamber and QATS	32
		4.3.3	Limits for use with the reverberation chamber method	33
		4.3.4	Procedure for the determination of the reverberation chamber limit	33
	4.4	induce	cterization and classification of the asymmetrical disturbance source to the phone subscriber lines by AM broadcasting transmitters in	
			V, MW and SW bands	
		4.4.1	Gerreral	
		4.4.2	Experimental characterization	
		4.4.3	Prediction models and classification	
	_	4.4.4	Characterization of the immunity-test disturbance source	
	4.5		etability of radiation in vertical directions at frequencies above 30 MHz	
		4.5.1	Summary	
		4.5.2	Range of application	
		4.5.3	General	
		4.5.4	Method used to calculate field patterns in the vertical plane	
		4.5.5	Limitations of predictability of radiation at elevated angles	59
		4.5.6	Differences between the fields over a real ground and the fields over a perfect conductor	87
		4.5.7	Uncertainty ranges	93
		4.5.8	Conclusions	96

	4.6		edictability of radiation in vertical directions at frequencies up to	97
		4.6.1	Range of application	97
		4.6.2	General	
		4.6.3	Method of calculation of the vertical radiation patterns	
		4.6.4	The source models	
		4.6.5	Electrical constants of the ground	100
		4.6.6	Predictability of radiation in vertical directions	
		4.6.7	Conclusions	109
		4.6.8	Figures associated with predictability of radiation in vertical directions	110
	4.7		ation between amplitude probability distribution (APD) characteristics urbance and performance of digital communication systems	139
		4.7.1	General	139
		4.7.2	Influence on a wireless LAN system	139
		4.7.3	Influence on a Bluetooth system	142
		4.7.4	Influence on a W-CDMA system	146
		4.7.5	Influence on Personal Handy Phone System (PHS)	149
		4.7.6	Quantitative correlation between noise parameters and system performance	153
		4.7.7	Quantitative correlation between noise parameters of repetition pulse and system performance of RHS and W-CDMA (BER)	157
	4.8		round material on the definition of the rms-average weighting detector asuring receivers	
		4.8.1	General purpose of weighted measurement of disturbance	
		4.8.2	General principle of weighting the CISPR quasi-peak detector	
		4.8.3	Other detectors defined in CISPR 16-1-1	
		4.8.4	Procedures for measuring pulse weighting characteristics of digital radiocommunications services	162
		4.8.5	Pheoretical studies	
		4.8.6	Experimental results.	
		4.8.7	Effects of spread-spectrum clock interference on wideband radiocommunication signal reception	
	<	4.8.8	Analysis of the various weighting characteristics and proposal of a weighting detector	
		4.8.9	Properties of the rms-average weighting detector	189
	4.9	Comm	on mode absorption devices (CMAD)	
		4.9.1	General	191
		4.9.2	CMAD as a two-port device	193
		4.9.3	Measurement of CMAD	197
	4.10	Backgr	ound on the definition of the FFT-based receiver	207
		_	General	
		4.10.2	Tuned selective voltmeters and spectrum analyzers	208
			General principle of a tuned selective voltmeter	
			FFT-based receivers – digital signal processing	
			Measurement errors specific to FFT processing	
			FFT-based receivers – examples	
5	Back		and history of CISPR	
	5.1	•	story of CISPR	
	•		The early years: 1034-1084	228

5.1.2 The division of work	230
5.1.3 The computer years: 1984 to 1998	230
5.1.4 The people in CISPR	231
5.2 Historical background to the method of measurement of the interference power produced by electrical household and similar appliances in the VHF	
range	
5.2.1 Historical detail	
5.2.2 Development of the method	
Annex A (informative) Derivation of the formula	
Annex B (informative) The field-strength distribution	
Annex C (informative) The induced asymmetrical open-circuit voltage distribution	
Annex D (informative) The outlet-voltage distribution	245
Annex E (informative) Some mathematical relations	247
Annex F (informative) Harmonic fields radiated at elevated angles from 27 MHz ISM equipment over real ground	249
Bibliography	255
Figure 1 – Relative response of various detectors to impulse interference	
Figure 2 – Pulse rectification coefficient $P(\alpha)$	23
Figure 3 – Pulse repetition frequency	24
Figure 4 – Block diagram and waveforms of a simulator generating noise bursts	30
Figure 5 – Block diagram of a simulator generating noise bursts according to the pulse principle	
Figure 6 – Details of a typical output stage	32
Figure 7 – Scatter plot of the measured outdoor magnetic field strength H_0 (dB μ A/m) versus the calculated outdoor magnetic field strength H_0 dB(μ A/m)	36
https Figure 8 - Measured outdoor magnetic versus distance, and probability of the building-	r-16-3-2
effect parameter	_
Figure 9 – Normal probability plot of the building-effect parameter A_{b} dB	38
Figure 10 – Scatter plot of the outdoor antenna factor G_{0} dB(Ω m) versus the indoor antenna factor G_{1}	39
Figure 11 - Normal probability plots of the antenna factors	40
Figure 12 – Normal probability plot of the equivalent asymmetrical resistance R_a dB(Ω)	
Figure 13 – Examples of the frequency dependence of some parameters	
Figure 14 – Example of the frequency histogram $\Delta N(E_{\mathbf{O}}, \Delta E_{\mathbf{O}})$	
Figure 15 – Example of $n_{\rm m}(E_{\rm O})$, i.e. the distribution of the outlets experiencing a maximum field strength $E_{\rm O}$ resulting from a given number of transmitters in (or near)	
the respective geographical region	
Figure 17 – Examples of number (left-hand scale) and relative number (right-hand scale) of outlets with $U_L \le U_h \le U_{max}$	
_	
Figure 18 – Vertical polar patterns of horizontally polarized E_x field strengths emitted around small vertical loop (horizontal magnetic dipole) over three different types of real	l
ground	
Figure 19 – Height scan patterns of vertically oriented E_z field strengths emitted from small vertical loop (horizontal magnetic dipole) over three different types of real ground	I61

Figure 20 – Vertical polar patterns of horizontally polarized E_{χ} field strengths emitted around small vertical loop (horizontal magnetic dipole), over three different types of real ground	63
Figure 21 – Vertical polar patterns of vertically oriented E_z field strengths emitted around small vertical loop (horizontal magnetic dipole) over three different types of real ground	63
Figure 22 – Height scan patterns of vertically oriented E_z field strengths emitted at 1 000 MHz from the small vertical loop (horizontal magnetic dipole), at horizontal distance of 10 m, 30 m and 300 m in the Z-X plane over three different types of real ground	64
Figure 23 – Vertical polar patterns of horizontally polarized E_x and vertically oriented E_z field strengths emitted around small horizontal electric dipole, in Y-Z and Z-X planes respectively	66
Figure 24 – Height scan patterns of horizontally polarized E_x field strengths emitted from small horizontal electric dipole	66
Figure 25 – Vertical polar patterns of horizontally polarized E_x and vertically oriented E_z field strengths emitted around small horizontal electric dipole in Y-Z and Z-X planes respectively	69
Figure 26 – Height scan patterns of horizontally polarized E_{χ} field strengths emitted small horizontal electric dipole	69
Figure 27 – Vertical polar patterns of horizontally polarized E_{λ} and vertically oriented E_{z} field strengths emitted around small vertical toop (horizontal magnetic dipole) in Y-Z and Z-X planes respectively	70
Figure 28 – Height scan patterns of vertically oriented E_z and horizontally oriented E_χ field strengths emitted from small vertical loop (horizontal magnetic dipole)	70
Figure 29 – Vertical polar patterns of vertically oriented E_z and horizontally oriented E_x field strengths emitted around small vertical electric dipole	73
Figure 30 – Height scan patterns of vertically oriented E_z and horizontally oriented E_χ field strengths emitted from small vertical electric dipole	73
Figure 31 – Vertical polar patterns of horizontally polarized E_X and vertically oriented E_Z field strengths emitted around small vertical loop (horizontal magnetic dipole) in Y-Z and Z-X planes respectively	6-3-20 74
Figure 32 – Height scan patterns of vertically oriented E_z and horizontally oriented E_χ field strengths emitted from small vertical loop (horizontal magnetic dipole)	74
Figure 33 – Vertical polar patterns of horizontally polarized <i>E</i> -field strength emitted around small horizontal loop (vertical magnetic dipole)	75
Figure 34 – Height scan patterns of horizontally polarized <i>E</i> -field strength emitted from small horizontal loop (vertical magnetic dipole)	75
Figure 35 – Vertical polar patterns of vertically oriented E_z and horizontally oriented E_χ field strengths emitted around small vertical electric dipole	78
Figure 36 – Height scan patterns of vertically oriented E_z and horizontally oriented E_χ field strengths emitted from the small vertical electric dipole	78
Figure 37 – Vertical polar patterns of horizontally polarized E_{χ} and vertically oriented E_{Z} field strengths emitted around small vertical loop (horizontal magnetic dipole) in Y-Z and Z-X planes respectively	79
Figure 38 – Height scan patterns of vertically oriented E_z and horizontally oriented E_χ field strengths emitted from small vertical loop (horizontal magnetic dipole)	79
Figure 39 – Vertical polar patterns of horizontally polarized <i>E</i> -field strength emitted around small horizontal loop (vertical magnetic dipole)	80
Figure 40 – Height scan patterns of horizontally polarized <i>E</i> -field strength emitted from small horizontal loop (vertical magnetic dipole)	80

Figure 41 – Vertical polar patterns of horizontally polarized <i>E</i> -field strength emitted around the small horizontal loop (vertical magnetic dipole)	83
Figure 42 – Height scan patterns of horizontally polarized <i>E</i> -field strength emitted from small horizontal loop (vertical magnetic dipole)	
Figure 43 – Height scan patterns of horizontally polarized <i>E</i> -field strength emitted from small horizontal loop (vertical magnetic dipole)	87
Figure 44 – Height scan patterns of the vertical component of the <i>E</i> -fields emitted from a small vertical electric dipole	90
Figure 45 – Height scan patterns of the vertical component of the <i>E</i> -fields emitted from a small vertical electric dipole	90
Figure 46 – Height scan patterns of the horizontally polarized <i>E</i> -fields emitted in the vertical plane normal to the axis of a small horizontal electric dipole	92
Figure 47 – Height scan patterns of the horizontally polarized <i>E</i> -fields emitted in the vertical plane normal to the axis of a small horizontal electric dipole	92
Figure 48 – Ranges of uncertainties in the predictability of radiation in vertical directions from electrically small sources located at a height of 1 m or 2 m above	0.4
Figure 49 – Ranges of uncertainties in the predictability of radiation in vertical directions from electrically small sources located at a height of 1 m or 2 m above ground	94
Figure 50 – Ranges of uncertainties in the predictability of radiation in vertical directions from electrically small sources located at a height of 1 m or 2 m above ground	96
Figure 51 – Geometry of the small vertical electric dipole model	. 100
Figure 52 - Geometry of the small horizontal electrical dipole model	. 100
Figure 53 – Geometry of the small horizontal magnetic dipole model (small vertical loop)	. 100
Figure 54 – Geometry of the small vertical magnetic dipole model (small horizontal loop)	.100
Figure 55 – Ranges of errors in the predictability of radiation in vertical directions from electrically small sources located close to the ground, based on measurements of the horizontally oriented <i>H</i> -field near ground at a distance of 30 m from the sources	108
Figure 56 – Ranges of errors in the predictability of radiation in vertical directions from electrically small sources located close to the ground, based on measurements of the horizontally oriented H -field at the ground supplemented with measurements of the vertically oriented H -field in a height scan up to 6 m at a distance of 30 m from the sources.	109
Figure 57 – Vertical radiation patterns of horizontally oriented <i>H</i> -fields emitted by a small vertical electric dipole located close to the ground	
Figure 58 – Vertical radiation patterns of horizontally oriented <i>H</i> -fields emitted by a small vertical electric dipole located close to the ground	.111
Figure 59 – Vertical radiation patterns of <i>E</i> -fields emitted by a small vertical electric dipole located close to the ground	.112
Figure 60 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical electric dipole located close to the ground	.112
Figure 61 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 113
Figure 62 – Influence of a wide range of values of the electrical constants of the ground on the vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 113
Figure 63 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	

Figure 64 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 114
Figure 65 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 115
Figure 66 – Vertical radiation patterns of <i>H</i> -fields emitted by small horizontal magnetic dipole (vertical loop) located close to ground	. 115
Figure 67 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	. 116
Figure 68 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	. 116
Figure 69 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	. 117
Figure 70 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	. 117
Figure 71 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 118
Figure 72 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 118
Figure 73 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 119
Figure 74 – Vertical radiation patterns of the H-fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 119
Figure 75 – Vertical radiation pattern of the <i>E</i> -field emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 120
Figure 76 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 120
Figure 77 – Vertical radiation patterns of the horizontally oriented H-fields emitted by a small vertical electric dipole located close to the ground	. 121
Figure 78 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical electric dipole located close to the ground	6-3-2 . 121
Figure 79 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical electric dipole located close to the ground	. 122
Figure 80 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small horizontal electric gipole located close to the ground	. 122
Figure 81 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 123
Figure 82 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 123
Figure 83 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 124
Figure 84 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	. 124
Figure 85 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	. 125
Figure 86 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	. 125
Figure 87 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	. 126
Figure 88 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	. 126

Figure 89 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	.127
Figure 90 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 127
Figure 91 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 128
Figure 92 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 128
Figure 93 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small vertical electric dipole located close to the ground	. 129
Figure 94 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical electric dipole located close to the ground	. 129
Figure 95 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical electric	. 130
Figure 96 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 130
Figure 97 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 131
Figure 98 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 131
Figure 99 – Vertical radiation patterns of the H-field emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	. 132
Figure 100 – Vertical radiation patterns of the vertically polarized <i>E</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	. 132
Figure 101 – Vertical radiation patterns of the H field emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 133
Figure 102 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical magnetic dipole (porizontal loop) located close to the ground	
Figure 103 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small vertical electric dipole located close to the ground	6-3-2 . 134
Figure 104 – Vertical radiation patterns of the vertically polarized <i>E</i> -fields emitted by a small vertical electric dipole located close to the ground	. 134
Figure 105 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small horizontal electric gipole located close to the ground	. 135
Figure 106 - Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 135
Figure 107 – Influence of a wide range of values of the electrical constants of the ground on the vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 136
Figure 108 – Vertical radiation patterns of the vertically polarized <i>E</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 136
Figure 109 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	. 137
Figure 110 – Vertical radiation patterns of the vertically polarized <i>E</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	. 137
Figure 111 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 138
Figure 112 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 138
Figure 113 – Set-up for measuring communication quality degradation of a wireless LAN	139

Figure 114 – APD characteristics of disturbance	141
Figure 115 – Wireless LAN throughput influenced by noise	142
Figure 116 – Set-up for measuring the communication quality degradation of Bluetooth	143
Figure 117 – APD of disturbance of actual MWO (2 441MHz)	143
Figure 118 – APD characteristics of disturbance (2 460 MHz)	144
Figure 119 – Throughput of Bluetooth influenced by noise	146
Figure 120 – Set-up for measuring the BER of W-CDMA	147
Figure 121 – APD characteristics of disturbance	148
Figure 122 – BER of W-CDMA caused by radiation noise	149
Figure 123 – Set-up for measuring the PHS throughput	150
Figure 124 – Set-up for measuring the BER of PHS	150
Figure 125 – APD characteristics of disturbance	151
Figure 126 – PHS throughput caused by radiation	152
Figure 127 – BER of PHS caused by radiation noise	153
Figure 128 – Correlation of the disturbance voltages with the system performance (C/N_0)	154
Figure 129 – Correlation of the disturbance voltages with the system performance	155
Figure 130 – Correlation of the disturbance voltages with the system performance	
Figure 131 – Correlation of the disturbance voltages with the system performance	
(C/N_0)	156
Figure 132 – Correlation of the disturbance voltages with the system performance (C/N_0)	156
Figure 133 – Experimental set-up for measuring communication quality degradation of a PHS or W-CDMA	157
Figure 134 – Simulation set-up for estimating communication quality degradation of a PHS or W-CDMA	157
Figure 135 – APD of pulse disturbance.	158
Figure 136 – BER degradation of PHS and W-CDMA caused by repetition pulse (Carrier power, 35 dBm)	158
Figure 137 – Evaluation method of the correlation between BER and APD	159
Figure 138 – Correlation between measured Δ $L_{\sf BER}$ and Δ $L_{\sf APD}$	
Figure 139 – Correlation between measured p_{BER} and p_{APD}	
Figure 140 – Weighting curves of quasi-peak measuring receivers for the different	
frequency ranges as defined in CISPR 16-1-1	161
Figure 141 – Weighting curves for peak, quasi-peak, rms and linear average detectors for CISPR bands C and D	162
Figure 142 – Test setup for the measurement of the pulse weighting characteristics of a digital radiocommunication system	163
Figure 143 – Example of an interference spectrum: pulse modulated carrier with a pulse duration of 0,2 μs and a PRF < 10 kHz	164
Figure 144 – The rms and peak levels for constant BEP for three <i>K</i> = 3, convolutional codes of different rate	
Figure 145 – The rms and peak levels for constant BEP for two rate ½, convolutional code	
Figure 146 – Test setup for the measurement of weighting curves for Digital Radio	160

Figure 147 – Weighting characteristics for DRM signals for various pulse widths of the pulse-modulated carrier	170
Figure 148 – Weighting characteristics for DRM protection level 0: average of results for two receivers	171
Figure 149 – Weighting characteristics for DRM protection level 1: average of results for two receivers	171
Figure 150 – Weighting characteristics for DVB-T with 64 QAM 2k, CR 3/4 (as used in France and UK)	173
Figure 151 – Weighting characteristics for DVB-T with 64 QAM 8k, <i>CR</i> 3/4 (as used in Spain)	174
Figure 152 – Weighting characteristics for DVB-T with 16 QAM 8k, CR 2/3 (as used in Germany)	174
Figure 153 – Average weighting characteristics of 6 receiver types for DVB-T with 16QAM	175
Figure 154 – Average weighting characteristics of 6 receiver types for DVB-T with 64QAM	176
Figure 155 – Weighting characteristics for DAB (signal level -71 dBm) with a flat response down to approximately 1 kHz	177
Figure 156 – Weighting characteristics for DAB: average of two different commercial receiver types	177
Figure 157 – Weighting characteristics for TETRA (signal level – 80 dBm) for a code rate of 1	_
Figure 158 – Weighting characteristics for RBER 16 of GSM (signal level –90 dBm)	
Figure 159 – Weighting characteristics for RBER 2 of GSM	179
Figure 160 – Carrier-to-interference improvements with decreasing PRF in dB computed for GSM using CQSSAP	180
Figure 161 – Rms and quasi peak values of pulse level for constant effect on FM radio reception	180
Figure 162 - Weighting characteristics for RBER 1b of GSM (signal level -90 dBm)	
Figure 163 – Weighting characteristics for DECT (signal level –83 dBm)	182
Figure 164 – Weighting characteristics for IS-95 (signal level -97 dBm) with comparatively high immunity to interference	183
Figure 165 - Weighting characteristics for J-STD 008 (signal level –97 dBm)	183
Figure 166 - Weighting characteristics for the Frame Error Ratio (FER) of CDMA2000 (measured at a receive signal level of -112 dBm) for a low data rate of 9,6 kb/s	184
Figure 167 – Weighting characteristics for the Frame Error Ratio (FER) of CDMA2000 (measured at a receive signal level of –106 dBm) for two different data rates (9,6 kb/s and 76,8 kb/s)	185
Figure 168 – The proposed rms-average detector for CISPR Bands C and D with a corner frequency of 100 Hz	188
Figure 169 – Rms-average detector function by using an rms detector followed by a linear average detector and peak reading	188
Figure 170 – Rms-average weighting functions for CISPR Bands A, B, C/D and E for the shortest pulse widths allowed by the measurement bandwidths	189
Figure 171 – Shift of the rms-average weighting function for CISPR band C/D by using a bandwidth of 1 MHz instead of 120 kHz, if the shortest possible pulse widths are applied	190
Figure 172 – Example of a simple EUT model	
Figure 173 – Representation of a CMAD as a two-port device	

Figure 174 – Conformal mapping between z -plane and f -plane	196
Figure 175 – Conversion from 50 Ω coaxial system to the geometry of the two-port device-under-test	198
Figure 176 – Basic model for the TRL calibration	
Figure 177 – The four calibration configurations necessary for the TRL calibration	
Figure 178 – Measurement of CMAD characteristics	
Figure 179 – Preliminary measurements of the test set-up	
Figure 180 – Position of the reference planes for the measurement with SOLT calibration and $ABCD$ transformation to Z_{ref} level	
Figure 181 – Superheterodyne EMI receiver	
Figure 182 – An example spectrogram $Z[m,k]$	
()	213
	214
Figure 185 – IF signal for different overlapping factors for the same sequence of pulses	215
Figure 186 – FFT-based baseband system	
Figure 187 – Real-time FFT-based measuring instrument	
Figure 188 – Digital down-converter	217
Figure 189 – Short time fast Fourier transform – An example of implementation	
Figure 190 – Floating-point analogue-to-digital conversion	
Figure 191 – Example of a 120 kHz Gaussian filter	
Figure 192 – Essential parts of an EFT-based heterodyne receiver	
Figure 193 – Dynamic range for broadband emission as measured with the peak detector	
Figure 194 – Set-up of FFT-based system type 2	222
Figure 195 - FFT Søftware ("FFTemi") screen shot	.1225201
Figure 196 – Example of pulse generator measurement with antenna	226
Figure 197 – Radiated emission measurement of a motor – peak detector	227
Figure 198 – Angular characterization of a PC	227
Figure 199 Example FFT IF analysis display	228
Figure A.1 – Example plot using the expression $P_t + G = P_q + 2$	235
Figure A.2 – Examples of a number of microwaves measured for P_q and P_t	
Figure B.1 – Definition of the ring-shaped area round the transmitter T	
Figure C.1 – The permissible ranges of U_h and G are within the polygon $\{G_L, U_a\}$, $\{G_L, U_b\}$, $\{G_U, U_d\}$, $\{G_I, U_C\}$ and $\{G_L, U_a\}$. For the given value U_L the double-shaded area represents $pr\{U_h \ge U_L\}$	
Figure F.1 – Vertical radiation patterns of horizontally polarized fields, 109 MHz, 300 m	470
scan radius (adapted from [34])	251
Figure F.2 – Vertical radiation patterns of horizontally polarized fields, 109 MHz, 300 m scan radius (adapted from [34])	252
Figure F.3 – Vertical radiation patterns of horizontally polarized fields, 109 MHz, 300 m scan radius (adapted from [34])	253
Figure F.4 – Vertical radiation patterns of horizontally polarized fields, 109 MHz, 300 m scan radius (adapted from [34])	254

to sine wave, periodic pulse and Gaussian waveform	22
Table 2 – Characteristics of gate generator and modulator to simulate various types of broadband interference	28
Table 3 – Summary results of building-effect, A_{b} , analysis	38
Table 4 – Summary of results of <i>G</i> -factor analysis	
Table 5 – Summary of L_{0} factors (far-field)	
Table 6 – Summary of truncation parameters of $f(G)$	
Table 7 – Summary results of equivalent-resistance analysis	
Table 8 – Example of field-strength classification	46
Table 9 – Example of voltage classification assuming for the outdoor field strength: E_{max} = 60 V/m and E_{min} = 0,01 V/m	47
Table 10 – Summary of the parameters used in the numerical examples presented in Figures 16 and 17	51
Table 11 – Frequencies of interest in ITU designated bands from Table 9 of CISPR 11:2009	58
Table 12 – Electrical constants for "medium dry ground" [31] (CCIR: medium dry ground; rocks; sand; medium sized towns[32])	59
Table 13 – Electrical constants for "wet ground" [31] (CCIR: marshes (fresh water); cultivated land [24]) and "very dry ground" [31] (CCIR: very dry ground; granite mountains in cold regions; industrial areas [32])	59
Table 14 – Estimates of the errors in prediction of radiation in vertical directions based on a measurement height scan from 1 m to 4 m at known distances, d; frequency = 75 MHz (adapted from [39])	67
Table 15 – Estimates of the errors in prediction of radiation in vertical directions based on a measurement height scan from 1 m to 4 m at known distances, d; frequency = 110 MHz (adapted from [39])	71
Table 16 – Estimates of the errors in prediction of radiation in vertical directions based on a measurement height scan from 1 m to 4 m at known distances, d; frequency = 243 MHz (adapted from [39])	16-3-201 76
Table 17 – Estimates of the errors in prediction of radiation in vertical directions based on a measurement height scan from 1 m to 4 m at known distances, d; frequency = 330 MHz (adapted from [39])	81
Table 18 – Estimates of the errors in prediction of radiation in vertical directions based on a measurement height scan from 1 m to 4 m at known distances, <i>d</i> ; frequency = 1 000 MHz (adapted from [39])	
Table 19 – Predictability of radiation in vertical directions at 100 kHz, using ground-based measurements of horizontally oriented <i>H</i> -field at distances up to 3 km from the source (figures are located in 4.6.8)	101
Table 20 – Predictability of radiation in vertical directions at 1 MHz, using ground-based measurements of horizontally oriented <i>H</i> -field at distances up to 300 m from the source (figures are located in 4.6.8)	103
Table 21 – Predictability of radiation in vertical directions at 10 MHz, using ground-based measurements of horizontally oriented <i>H</i> -field at distances up to 300 m from the source (figures are located in 4.6.8)	104
Table 22 – Predictability of radiation in vertical directions at 30 MHz, using ground-based measurements of horizontally oriented <i>H</i> -field at distances up to 300 m from the source (figures are located in 4.6.8)	105
Table 23 – Conditions for measuring communication quality degradation	140
Table 24 – Average and rms values of noise level normalized by N_0	141
Table 25 – Conditions for measuring communication quality degradation of Bluetooth	143