

CISPR TR 16-3

Edition 3.2 2015-09 CONSOLIDATED VERSION

TECHNICAL REPORT



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

Specification for radio disturbance and immunity measuring apparatus and methods –

Part 3: CISPR technical reports

NAME AT CVICVO

ttps://standards.iteh.ai/ca/alog/standards/ec/33280338-27d7-4f65-928d-811284ab3c97/cispr-tr-16-3-2010





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2015 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office Tel.: +41 22 919 02 11 3, rue de Varembé Fax: +41 22 919 03 00

CH-1211 Geneva 20 info@iec.ch Switzerland www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

「**№** 16-3:2010

https://standards.iteh.au.sa/alk/standards/xc/3N280338-27d7-4f65-928d-811284ab3c97/cispr-tr-16-3-2010



CISPR TR 16-3

Edition 3.2 2015-09 CONSOLIDATED VERSION

TECHNICAL VERSION



Specification for radio disturbance and immunity measuring apparatus and methods –

Part 3: CISPR technical reports

uviely ryeview

XSPR TX 16-3:2010

nttps://standards.iteh.ai/walvextandards/rec/38/280338-27d7-4t65-928d-811284ab3c97/cispr-tr-16-3-2010

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 33.100.10; 33.100.20 ISBN 978-2-8322-2905-7

Warning! Make sure that you obtained this publication from an authorized distributor.



<u>X 16-3:2010</u> 338-27d7-4f65-928d-811284ab3c97/cispr-tr-16-3-2010



CISPR TR 16-3

Edition 3.2 2015-09 CONSOLIDATED VERSION

REDLINE VERSION



-2-

CONTENTS

FC	DREW	ORD	14
1	Scop	oe	16
2	Norm	native references	16
3	Term	ns, definitions and abbreviations	17
	3.1	Terms and definitions	17
	3.2	Abbreviations	20
4	Tech	nical reports	20
	4.1	Correlation between measurements made with apparatus having characteristics differing from CISPR characteristics and measurements made with CISPR apparatus	20
		4.1.1 General	
		4.1.2 Critical interference-measuring instrument parameters	
		4.1.4 Random noise	25
		4.1.5 The root mean square (rms) detector	25
		4.1.6 Discussion	
		4.1.7 Application to typical noise sources	25
		4.1.8 Conclusions Interference simulators	26
	4.2	Interference simulators	27
		4.2.1 General	27
		4.2.2 Types of interference signals	27
		4.2.3 Circuits for simulating broadband interference	28
		4.1.3 Impulse interference – correlation factors	
	4.3	Relationship between limits for open-area test site and the reverberation chamber	32
		4.3.1 General	
		4.3.2 Correlation between measurement results of the reverberation chamber and OATS.	r-16-3 32
		4.3.3 Limits for use with the reverberation chamber method	33
		4.3.4 Procedure for the determination of the reverberation chamber limit	33
	4.4	Characterization and classification of the asymmetrical disturbance source induced in telephone subscriber lines by AM broadcasting transmitters in	•
		the LW MW and SW bands	
		4.4.1 General	
		4.4.2 Experimental characterization.	
		4.4.4 Characterization of the immunity-test disturbance source	
	4 -	4.4.3 Prediction models and classification	
	4.5	Predictability of radiation in vertical directions at frequencies above 30 MHz	
		4.5.1 Summary	
		4.5.2 Range of application	
		4.5.3 General	
		4.5.4 Method used to calculate field patterns in the vertical plane	
		4.5.5 Limitations of predictability of radiation at elevated angles	59
		4.5.6 Differences between the fields over a real ground and the fields over a perfect conductor	87
		4.5.7 Uncertainty ranges	93
		4.5.8 Conclusions	96

4.6		edictability of radiation in vertical directions at frequencies up to	97
	4.6.1	Range of application	
	4.6.2	General	
	4.6.3	Method of calculation of the vertical radiation patterns	
	4.6.4	The source models	
	4.6.5	Electrical constants of the ground	
	4.6.6	Predictability of radiation in vertical directions	
	4.6.7	Conclusions	
	4.6.8	Figures associated with predictability of radiation in vertical directions	
4.7	Correlation of distri	ation between amplitude probability distribution (APD) characteristics urbance and performance of digital communication systems	139
	4.7.1	General	139
	4.7.2		139
	4.7.3	Influence on a Bluetooth system	142
	4.7.4	Influence on a W-CDMA system	146
	4.7.5	Influence on Personal Handy Phone System (PHS)	149
	4.7.6	Quantitative correlation between noise parameters and system performance	153
	4.7.7	Quantitative correlation between noise parameters of repetition pulse and system performance of RHS and W-CDMA (BER)	157
4.8		round material on the definition of the rms-average weighting detector asuring receivers	160
	4.8.1	General purpose of weighted measurement of disturbance	160
	4.8.2	General principle of weighting the CISPR quasi-peak detector	
	4.8.3	Other detectors defined in CISPR 16-1-1	161
	4.8.4	Procedures for measuring pulse weighting characteristics of digital radjocommunications services	162
	4.8.5	Theoretical studies	165
	4.8.6	Experimental results	
	4.8.7	Effects of spread-spectrum clock interference on wideband radiocommunication signal reception	185
	4.8.8	Analysis of the various weighting characteristics and proposal of a	
<	10.0	weighting detector	186
	4.8.9	Properties of the rms-average weighting detector	189
4.9	Comm	on mode absorption devices (CMAD)	191
	4.9.1	General	191
	4.9.2	CMAD as a two-port device	193
	4.9.3	Measurement of CMAD	197
4.10	Backg	round on the definition of the FFT-based receiver	207
	4.10.1	General	207
	4.10.2	Tuned selective voltmeters and spectrum analyzers	208
	4.10.3	General principle of a tuned selective voltmeter	208
	4.10.4	FFT-based receivers – digital signal processing	210
	4.10.5	Measurement errors specific to FFT processing	213
	4.10.6	FFT-based receivers – examples	215
4.11	Param	eters of signals at telecommunication ports	228
		General	
	4.11.2	Estimation of common mode disturbance levels	229

		4.12	Backgro	ound	on CDNE equipment and measurement method	230
			4.12.1	Gene	eral	230
			4.12.2	Histo	rical overview	231
			4.12.3	From	CDN to CDNE	235
•	5	Back	ground a	nd h	story of CISPR	238
		5.1	The hist	tory o	of CISPR	238
			5.1.1	The	early years: 1934-1984	238
			5.1.2	The	division of work	240
			5.1.3	The	computer years: 1984 to 1998	240
					people in CISPR	241
		5.2	power p	rodu	ckground to the method of measurement of the interference ced by electrical household and similar appliances in the VNF	241
			_		rical detail	241
					\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	241
	Anr	nex A			Derivation of the formula	244
					The field-strength distribution	
			`	,	The induced asymmetrical open-circuit voltage distribution	
			•	•	The outlet-voltage distribution	
			`	,	Some mathematical relations	257
					Harmonic fields radiated at elevated angles from 27 MHz ISM ound	259
	Bib	liograp	ohy	\	100000000000000000000000000000000000000	265
					Peview	
	Fig	ure 1 -	- Relativ	e res	ponse of various detectors to impulse interference	22
	Fig	ure 2 -	– Pulse r	ectifi	cation coefficient $\mathcal{L}(\alpha)$	23
			/		tron frequency	
	// 5 🗷		3.11C11.d1/	\vee /	am and waveforms of a simulator generating noise bursts	
				/ \ \	am of a simulator generating noise bursts according to the pulse	
						31
	Fig	ure 6 -	_ Details	of a	typical output stage	32
	Fig	ure 7	Scatter	plot	of the measured outdoor magnetic field strength $H_{ m O}$ (dB $_{ m H}$ A/m) outdoor magnetic field strength $H_{ m C}$ dB($_{ m H}$ A/m)	
					utdoor magnetic versus distance, and probability of the building-	
						37
	Fig	ure 9 -	– Normal	prob	pability plot of the building-effect parameter A_{b} dB	38
					of the outdoor antenna factor $G_{f 0}$ dB(Ω m) versus the indoor	39
	Fig	ure 11	– Norma	al pro	obability plots of the antenna factors	40
	Fig	ure 12	– Norma	al pro	bbability plot of the equivalent asymmetrical resistance	
	•				of the frequency dependence of some parameters	
	_			•	f the frequency histogram $\Delta N(E_{\mathbf{O}}, \Delta E_{\mathbf{O}})$	
					$f_{m}(E_{0})$, i.e. the distribution of the outlets experiencing a	
	ma	ximum	field str	engtl	n $H_0(E_0)$, i.e. the distribution of the outlets experiencing an E_0 resulting from a given number of transmitters in (or near) whical region	50

Figure 16 – Example of the number of outlets with an induced asymmetrical open-circuit voltage $U_L \le U_h \le U_{max}$ = 79 V (see Table 10)	52
Figure 17 – Examples of number (left-hand scale) and relative number (right-hand scale) of outlets with $U_{\rm L} \leq U_{\rm h} \leq U_{\rm max}$	53
Figure 18 – Vertical polar patterns of horizontally polarized E_{χ} field strengths emitted around small vertical loop (horizontal magnetic dipole) over three different types of real ground	61
Figure 19 – Height scan patterns of vertically oriented E_z field strengths emitted from small vertical loop (horizontal magnetic dipole) over three different types of real ground	61
Figure 20 – Vertical polar patterns of horizontally polarized E_{χ} field strengths emitted around small vertical loop (horizontal magnetic dipole), over three different types of real ground	63
Figure 21 – Vertical polar patterns of vertically oriented E_z field strengths emitted around small vertical loop (horizontal magnetic dipole) over three different types of real ground	63
Figure 22 – Height scan patterns of vertically oriented E_z field strengths emitted at 1 000 MHz from the small vertical loop (horizontal magnetic dipole), at horizontal distance of 10 m, 30 m and 300 m in the Z-X plane over three different types of real ground	64
Figure 23 – Vertical polar patterns of horizontally polarized E_{χ} and vertically oriented E_{Z} field strengths emitted around small horizontal electric dipole, in Y-Z and Z-X planes respectively	66
Figure 24 – Height scan patterns of horizontally polarized E_x field strengths emitted from small horizontal electric dipole	66
Figure 25 – Vertical polar patterns of horizontally polarized E_{χ} and vertically oriented E_{z} field strengths emitted around small horizontal electric dipole in Y-Z and Z-X planes respectively	69
Figure 26 – Height scan patterns of horizontally polarized E_{χ} field strengths emitted small horizontal electric dipole.	69
Figure 27 – Vertical polar patterns of horizontally polarized E_x and vertically oriented E_z field strengths emitted around small vertical loop (horizontal magnetic dipole) in Y-Z and Z-X planes respectively.	16-3-201 70
Figure 28 – Height scan patterns of vertically oriented E_z and horizontally oriented E_x field strengths emitted from small vertical loop (horizontal magnetic dipole)	70
Figure 29 – Vertical polar patterns of vertically oriented E_z and horizontally oriented E_χ field strengths emitted around small vertical electric dipole	73
Figure 30 – Height scan patterns of vertically oriented E_z and horizontally oriented E_x field strengths emitted from small vertical electric dipole	73
Figure 31 – Vertical polar patterns of horizontally polarized E_X and vertically oriented E_Z field strengths emitted around small vertical loop (horizontal magnetic dipole) in Y-Z and Z-X planes respectively	74
Figure 32 – Height scan patterns of vertically oriented E_z and horizontally oriented E_χ field strengths emitted from small vertical loop (horizontal magnetic dipole)	74
Figure 33 – Vertical polar patterns of horizontally polarized <i>E</i> -field strength emitted around small horizontal loop (vertical magnetic dipole)	75
Figure 34 – Height scan patterns of horizontally polarized <i>E</i> -field strength emitted from small horizontal loop (vertical magnetic dipole)	75
Figure 35 – Vertical polar patterns of vertically oriented E_z and horizontally oriented E_χ field strengths emitted around small vertical electric dipole	78
Figure 36 – Height scan patterns of vertically oriented E_z and horizontally oriented E_χ field strengths emitted from the small vertical electric dipole	78

Figure 37 – Vertical polar patterns of horizontally polarized E_x and vertically oriented E_z field strengths emitted around small vertical loop (horizontal magnetic dipole) in Y-Z and Z-X planes respectively	79
Figure 38 – Height scan patterns of vertically oriented E_z and horizontally oriented E_χ field strengths emitted from small vertical loop (horizontal magnetic dipole)	79
Figure 39 – Vertical polar patterns of horizontally polarized <i>E</i> -field strength emitted around small horizontal loop (vertical magnetic dipole)	80
Figure 40 – Height scan patterns of horizontally polarized <i>E</i> -field strength emitted from small horizontal loop (vertical magnetic dipole)	80
Figure 41 – Vertical polar patterns of horizontally polarized <i>E</i> -field strength emitted around the small horizontal loop (vertical magnetic dipole)	83
Figure 42 – Height scan patterns of horizontally polarized <i>E</i> -field strength emitted from small horizontal loop (vertical magnetic dipole)	83
Figure 43 – Height scan patterns of horizontally polarized <i>E</i> -field strength emitted from small horizontal loop (vertical magnetic dipole)	87
Figure 44 – Height scan patterns of the vertical component of the <i>E</i> -fields emitted from a small vertical electric dipole	90
Figure 45 – Height scan patterns of the vertical component of the Evields emitted from a small vertical electric dipole	90
Figure 46 – Height scan patterns of the horizontally polarized <i>E</i> -fields emitted in the vertical plane normal to the axis of a small horizontal electric gipole	92
Figure 47 – Height scan patterns of the horizontally polarized <i>E</i> -fields emitted in the vertical plane normal to the axis of a small horizontal electric dipole	92
Figure 48 – Ranges of uncertainties in the predictability of radiation in vertical directions from electrically small sources located at a height of 1 m or 2 m above ground	94
Figure 49 – Ranges of uncertainties in the predictability of radiation in vertical directions from electrically small sources located at a height of 1 m or 2 m above ground	95
Figure 50 – Ranges of uncertainties in the predictability of radiation in vertical directions from electrically small sources located at a height of 1 m or 2 m above ground	:-16-3-2 96
Figure 51 – Geometry of the small vertical electric dipole model	100
Figure 52 Geometry of the small horizontal electrical dipole model	100
Figure 53 - Geometry of the small horizontal magnetic dipole model (small vertical loop)	100
Figure 54 – Geometry of the small vertical magnetic dipole model (small horizontal loop)	100
Figure 55 – Ranges of errors in the predictability of radiation in vertical directions from electrically small sources located close to the ground, based on measurements of the horizontally oriented H -field near ground at a distance of 30 m from the sources	108
Figure 56 – Ranges of errors in the predictability of radiation in vertical directions from electrically small sources located close to the ground, based on measurements of the horizontally oriented H -field at the ground supplemented with measurements of the vertically oriented H -field in a height scan up to 6 m at a distance of 30 m from the sources.	100
Figure 57 – Vertical radiation patterns of horizontally oriented <i>H</i> -fields emitted by a small vertical electric dipole located close to the ground	
Figure 58 – Vertical radiation patterns of horizontally oriented <i>H</i> -fields emitted by a small vertical electric dipole located close to the ground	
Figure 59 – Vertical radiation patterns of <i>E</i> -fields emitted by a small vertical electric	
dipole located close to the ground	112

Figure 60 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical electric dipole located close to the ground	. 112
Figure 61 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 113
Figure 62 – Influence of a wide range of values of the electrical constants of the ground on the vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 113
Figure 63 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 114
Figure 64 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 114
Figure 65 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 115
Figure 66 – Vertical radiation patterns of <i>H</i> -fields emitted by small horizontal magnetic dipole (vertical loop) located close to ground	. 115
Figure 67 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	.116
Figure 68 – Vertical radiation patterns of the horizontally oriented A fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	.116
Figure 69 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	. 117
Figure 70 – Vertical radiation patterns of the E-fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	. 117
Figure 71 – Vertical radiation patterns of the H-fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 118
Figure 72 – Vertical radiation patterns of the H-fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 118
Figure 73 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 119
Figure 74 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	
Figure 75 – Vertical radiation pattern of the <i>E</i> -field emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 120
Figure 76 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	. 120
Figure 77 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small vertical electric dipole located close to the ground	. 121
Figure 78 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical electric dipole located close to the ground	. 121
Figure 79 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical electric dipole located close to the ground	. 122
Figure 80 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 122
Figure 81 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 123
Figure 82 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 123
Figure 83 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal electric dipole located close to the ground	. 124
Figure 84 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	124

Figure 85 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	125
Figure 86 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	125
Figure 87 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	126
Figure 88 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	126
Figure 89 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	127
Figure 90 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	
Figure 91 – Vertical radiation patterns of the H-fields emitted by a small vertical	128
Figure 92 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	128
Figure 93 – Vertical radiation patterns of the horizontally oriented W-fields emitted by a small vertical electric dipole located close to the ground	
Figure 94 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical electric dipole located close to the ground	
Figure 95 – Vertical radiation patterns of the E-fields emitted by a small vertical electric dipole located close to the ground	130
Figure 96 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	
Figure 97 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small horizontal electric dipole located close to the ground	
Figure 98 – Vertical radiation patterns of the E-fields emitted by a small horizontal electric dipole located close to the ground	
Figure 99 – Vertical radiation patterns of the <i>H</i> -field emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	
Figure 100 – Vertical radiation patterns of the vertically polarized <i>E</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	
Figure 101 – Vertical radiation patterns of the <i>H</i> -field emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	
Figure 102 Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	133
Figure 103 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small vertical electric dipole located close to the ground	
Figure 104 – Vertical radiation patterns of the vertically polarized <i>E</i> -fields emitted by a small vertical electric dipole located close to the ground	134
Figure 105 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	135
Figure 106 – Vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	135
Figure 107 – Influence of a wide range of values of the electrical constants of the ground on the vertical radiation patterns of the horizontally oriented <i>H</i> -fields emitted by a small horizontal electric dipole located close to the ground	136
Figure 108 – Vertical radiation patterns of the vertically polarized <i>E</i> -fields emitted by a small horizontal electric dipole located close to the ground	
Figure 109 – Vertical radiation patterns of the <i>H</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	
g	

Figure 110 – Vertical radiation patterns of the vertically polarized <i>E</i> -fields emitted by a small horizontal magnetic dipole (vertical loop) located close to the ground	137
Figure 111 – Vertical radiation patterns of the H -fields emitted by a small vertical	
magnetic dipole (horizontal loop) located close to the ground	138
Figure 112 – Vertical radiation patterns of the <i>E</i> -fields emitted by a small vertical magnetic dipole (horizontal loop) located close to the ground	138
Figure 113 – Set-up for measuring communication quality degradation of a wireless LAN	120
Figure 114 – APD characteristics of disturbance	
· ·	
Figure 115 – Wireless LAN throughput influenced by noise	
Figure 116 – Set-up for measuring the communication quality degradation of Bluetooth	
Figure 117 – APD of disturbance of actual MWO (2 441MHz)	
` ' \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	144
	146
Figure 120 – Set-up for measuring the BER of W-CDMA	
Figure 121 – APD characteristics of disturbance	
Figure 122 – BER of W-CDMA caused by radiation noise	
Figure 123 – Set-up for measuring the PHS throughput	
Figure 124 – Set-up for measuring the BER of PNS	
Figure 125 – APD characteristics of disturbance	
Figure 126 – PHS throughput caused by radiation	
Figure 127 – BER of PHS caused by radiation noise	153
Figure 128 – Correlation of the disturbance voltages with the system performance (C/N_0)	154
Figure 129 - Correlation of the disturbance voltages with the system performance	155
Figure 130 - Correlation of the disturbance voltages with the system performance	155
Figure 131 – Correlation of the disturbance voltages with the system performance (C/N_0)	156
Figure 132 – Correlation of the disturbance voltages with the system performance (C/N_0)	156
Figure 133 - Experimental set-up for measuring communication quality degradation of a PHS or W-CDMA	157
Figure 134 – Simulation set-up for estimating communication quality degradation of a PHS or W-CDMA	
Figure 135 – APD of pulse disturbance	158
Figure 136 – BER degradation of PHS and W-CDMA caused by repetition pulse (Carrier power, –35 dBm)	158
Figure 137 – Evaluation method of the correlation between BER and APD	159
Figure 138 – Correlation between measured Δ $L_{\sf BFR}$ and Δ $L_{\sf APD}$	159
Figure 139 – Correlation between measured p_{BER} and p_{APD}	
Figure 140 – Weighting curves of quasi-peak measuring receivers for the different frequency ranges as defined in CISPR 16-1-1	
Figure 141 – Weighting curves for peak, quasi-peak, rms and linear average detectors for CISPR bands C and D	
Figure 142 – Test setup for the measurement of the pulse weighting characteristics of	
a digital radiocommunication system	163

Figure 143 – Example of an interference spectrum: pulse modulated carrier with a pulse duration of 0,2 μs and a PRF < 10 kHz	164
Figure 144 – The rms and peak levels for constant BEP for three <i>K</i> = 3, convolutional codes of different rate	166
Figure 145 – The rms and peak levels for constant BEP for two rate ½, convolutional code	167
Figure 146 – Test setup for the measurement of weighting curves for Digital Radio Mondiale (DRM)	169
Figure 147 – Weighting characteristics for DRM signals for various pulse widths of the pulse-modulated carrier	170
Figure 148 – Weighting characteristics for DRM protection level 0: average of results for two receivers	171
Figure 149 – Weighting characteristics for DRM protection level 1: average of results	171
Figure 150 – Weighting characteristics for DVB-T with 64 QAM 2k, CR 3/4 (as used in France and UK)	173
Figure 151 – Weighting characteristics for DVB-T with 64 CAM 8k, CR 3/4 (as used in Spain)	174
Figure 152 – Weighting characteristics for DVB-T with 16 QAM 8k, CR 2/3 (as used in Germany)	174
Figure 153 – Average weighting characteristics of 6 receiver types for DVB-T with 16QAM	
Figure 154 – Average weighting characteristics of 6 receiver types for DVB-T with 64QAM	176
Figure 155 – Weighting characteristics for DAB (signal level -71 dBm) with a flat response down to approximately 1 kHz	
Figure 156 – Weighting characteristics for DAB: average of two different commercial receiver types	
Figure 157 – Weighting characteristics for TETRA (signal level – 80 dBm) for a code rate of 1	r-16-3-201 178
Figure 158 - Weighting characteristics for RBER 1b of GSM (signal level -90 dBm)	
Figure 159 – Weighting characteristics for RBER 2 of GSM	179
Figure 160 – Carrier-to-interference improvements with decreasing PRF in dB computed for GSM using COSSAP	180
Figure 161 – Rms and quasi-peak values of pulse level for constant effect on FM radio reception	180
Figure 162 – Weighting characteristics for RBER 1b of GSM (signal level –90 dBm)	
Figure 163 – Weighting characteristics for DECT (signal level –83 dBm)	182
Figure 164 – Weighting characteristics for IS-95 (signal level -97 dBm) with comparatively high immunity to interference	183
Figure 165 – Weighting characteristics for J-STD 008 (signal level –97 dBm)	183
Figure 166 – Weighting characteristics for the Frame Error Ratio (FER) of CDMA2000 (measured at a receive signal level of –112 dBm) for a low data rate of 9,6 kb/s	184
Figure 167 – Weighting characteristics for the Frame Error Ratio (FER) of CDMA2000 (measured at a receive signal level of –106 dBm) for two different data rates (9,6 kb/s	
and 76,8 kb/s)	185
corner frequency of 100 Hz	188
Figure 169 – Rms-average detector function by using an rms detector followed by a linear average detector and peak reading	188