

# INTERNATIONAL STANDARD

## NORME INTERNATIONALE

Electricity metering data exchange – The DLMS/COSEM suite –  
Part 3-1: Use of local area networks on twisted pair with carrier signalling

Échange des données de comptage de l'électricité – La suite DLMS/COSEM –  
Partie 3-1: Utilisation des réseaux locaux sur paire torsadée avec signal de  
porteuse



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2013 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

#### Useful links:

IEC publications search - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The advanced search enables you to find IEC publications by a variety of criteria (reference number, text, technical committee,...).

It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available on-line and also once a month by email.

Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary (IEV) on-line.

Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [csc@iec.ch](mailto:csc@iec.ch).

### A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

### A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

#### Liens utiles:

Recherche de publications CEI - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

La recherche avancée vous permet de trouver des publications CEI en utilisant différents critères (numéro de référence, texte, comité d'études,...).

Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

Just Published CEI - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Restez informé sur les nouvelles publications de la CEI. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - [www.electropedia.org](http://www.electropedia.org)

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (VEI) en ligne.

Service Clients - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: [csc@iec.ch](mailto:csc@iec.ch).



IEC 62056-3-1

Edition 1.0 2013-08

# INTERNATIONAL STANDARD

## NORME INTERNATIONALE

Electricity metering data exchange – The DLMS/COSEM suite –  
Part 3-1: Use of local area networks on twisted pair with carrier signalling

Échange des données de comptage de l'électricité – La suite DLMS/COSEM –  
Partie 3-1: Utilisation des réseaux locaux sur paire torsadée avec signal de  
porteuse

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

PRICE CODE  
CODE PRIX

**XE**

ICS 17.220; 35.110; 91.140.50

ISBN 978-2-8322-1046-8

**Warning! Make sure that you obtained this publication from an authorized distributor.**  
**Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

## CONTENTS

FOREWORD .....	7
1 Scope .....	9
2 Normative references .....	9
3 Abbreviations .....	10
4 General description .....	11
4.1 Basic vocabulary .....	11
4.2 Profiles, layers and protocols .....	11
4.2.1 Overview .....	11
4.2.2 Base profile (without DLMS) .....	12
4.2.3 Profile with DLMS .....	12
4.2.4 Profile with DLMS/COSEM .....	13
4.3 Specification language .....	13
4.4 Communication services for local bus data exchange without DLMS .....	13
4.4.1 Overview .....	13
4.4.2 Remote reading exchange .....	14
4.4.3 Remote programming exchange .....	14
4.4.4 Point to point remote transfer exchange .....	16
4.4.5 Broadcast remote transfer frame .....	16
4.4.6 Bus initialization frame .....	16
4.4.7 Forgotten station call exchange .....	17
4.4.8 Frame fields .....	17
4.4.9 Principle of the energy remote supply .....	18
4.4.10 Non-energized station preselection exchange .....	19
4.4.11 Communication exchange after preselection .....	20
4.4.12 Alarm function .....	20
4.5 Communication services for local bus data exchange with DLMS .....	21
4.6 Systems management .....	22
5 Local bus data exchange without DLMS .....	22
5.1 Physical layer .....	22
5.1.1 Physical-62056-3-1 protocol .....	22
5.1.2 Physical parameters .....	23
5.1.3 Timing diagrams .....	25
5.1.4 Physical services and service primitives .....	26
5.1.5 State transitions .....	27
5.1.6 List and processing of errors .....	34
5.2 Data Link layer .....	35
5.2.1 Link-62056-3-1 protocol .....	35
5.2.2 Management of exchanges .....	35
5.2.3 Data Link services and service primitives .....	35
5.2.4 Data Link parameters .....	36
5.2.5 State transitions .....	36
5.2.6 List and processing of errors .....	41
5.3 Application layer .....	42
5.3.1 Application-62056-3-1 protocol .....	42
5.3.2 Application services and service primitives .....	42
5.3.3 Application parameters .....	42

5.3.4	State transitions .....	43
5.3.5	List and processing of errors .....	45
6	Local bus data exchange with DLMS .....	45
6.1	Physical layer .....	45
6.2	Data Link layer .....	46
6.2.1	Link-E/D protocol .....	46
6.2.2	Management of exchanges .....	46
6.2.3	Data Link services and service primitives .....	47
6.2.4	Data Link parameters .....	47
6.2.5	State transitions .....	48
6.2.6	List and processing of errors .....	54
6.3	Application layer .....	54
6.3.1	General .....	54
6.3.2	Transport sub-layer .....	54
6.3.3	Application sub-layer .....	54
7	Local bus data exchange with DLMS/COSEM .....	55
7.1	Model .....	55
7.2	Physical Layer .....	55
7.2.1	General .....	55
7.2.2	Physical Parameters .....	55
7.2.3	Speed negotiation .....	55
7.2.4	E/COSEM Physical Services and service primitives .....	56
7.2.5	State transitions .....	57
7.3	Data Link layer .....	65
7.3.1	General .....	65
7.3.2	Identification of data units .....	66
7.3.3	Role of the Data Link layer .....	66
7.3.4	Management of exchanges .....	66
7.3.5	Data Link services and service primitives .....	66
7.3.6	Data Link parameters .....	68
7.3.7	State transitions .....	68
7.4	Support Manager layer .....	75
7.4.1	Overview .....	75
7.4.2	Initialisation of the bus .....	75
7.4.3	Discover service .....	76
7.4.4	Speed negotiation .....	76
7.4.5	Support Manager parameters .....	76
7.4.6	State transitions .....	77
7.5	Transport Layer .....	78
7.5.1	General .....	78
7.5.2	Transport Data Units .....	78
7.5.3	State transitions .....	80
7.6	Application Layer .....	82
7.6.1	General .....	82
7.6.2	Broadcast Management .....	82
7.6.3	Management of EventNotifications or InformationReports .....	83
7.6.4	Priority Management .....	83
7.6.5	Management of releasing Application Associations .....	83
8	Local bus data exchange – Hardware .....	83

8.1	General .....	83
8.2	General characteristics .....	83
8.2.1	Signal transmission at 50 kHz .....	83
8.2.2	Energy supply signal transmission .....	84
8.2.3	Simple Secondary Station and multiple Secondary Station .....	87
8.3	Bus specification .....	88
8.3.1	General characteristics .....	88
8.3.2	Cable characteristics .....	88
8.3.3	Wiring .....	89
8.4	Magnetic plug .....	90
8.4.1	Function .....	90
8.4.2	Common mechanical characteristics .....	90
8.4.3	Electrical block diagram with simple plug .....	91
8.4.4	Electrical Block Diagram with energy supply plug .....	92
8.5	Functional specifications of Primary Station transmitter (for 50 kHz signal) .....	93
8.6	Functional specifications of Primary Station receiver (for 50 kHz signal) .....	93
8.7	Functional specification of Secondary Station transmitter (for 50 kHz signal) .....	94
8.8	Functional specifications of Secondary Station receiver (for 50 kHz signal) .....	95
Annex A	(normative) Specification language .....	97
Annex B	(normative) Timing types and characteristics .....	100
Annex C	(normative) List of fatal errors .....	102
Annex D	(normative) Coding the command and code field of frames .....	103
Annex E	(normative) Principle of the CRC .....	105
Annex F	(normative) Random integer generation for response from forgotten stations .....	106
Annex G	(normative) Random number generation for authentication (profile without DLMS) .....	107
Annex H	(normative) Systems management implementation .....	108
Annex I	(informative) Information about exchanges .....	109
Bibliography	.....	113
Figure 1	– IEC 62056-3-1 communication profiles .....	12
Figure 2	– Alarm mechanism .....	21
Figure 3	– Exchanges in continuous operation .....	25
Figure 4	– Alarm event without any communication in progress .....	25
Figure 5	– Alarm event with a communication in progress .....	25
Figure 6	– Signal envelope on the bus .....	84
Figure 7	– Bus representation .....	85
Figure 8	– Power supply characteristics .....	85
Figure 9	– States associated to a session: for selected Secondary station .....	86
Figure 10	– States associated to a session: for non-selected Secondary station .....	86
Figure 11	– Simple and multiple Secondary stations .....	87
Figure 12	– Equivalent diagram of the test equipment .....	89
Figure 13	– Ferrite pot and bobbin .....	90
Figure 14	– Associated components of the magnetic plug .....	91
Figure 15	– Associated components of the energy supply plug .....	92
Figure B.1	– Logical timing type .....	100

Figure B.2 – Physical timing type .....	100
Figure B.3 – Results processing for timing defined with low and high limits .....	101
Figure B.4 – Results processing for timing defined by a nominal value .....	101
Figure I.1 – Non-energized station session .....	109
Figure I.2 – Remote reading and programming exchanges .....	110
Figure I.3 – Bus initialization .....	111
Figure I.4 – Forgotten station call exchange .....	112
Table 1 – Primary Station timing .....	23
Table 2 – Secondary station timing .....	24
Table 3 – Physical services and service primitives .....	26
Table 4 – <i>Physical-62056-3-1</i> state transitions: Primary station .....	27
Table 5 – Power supply management state transitions (only for non-energized secondary station) .....	29
Table 6 – <i>Physical-62056-3-1</i> state transitions: Secondary station .....	31
Table 7 – Meaning of the states listed in the previous tables .....	32
Table 8 – Definition of the procedures, functions and events classified in alphabetical order .....	33
Table 9 – Error summary table .....	34
Table 10 – Data Link services and service primitives .....	35
Table 11 – <i>Link-62056-3-1</i> state transitions: Primary station .....	36
Table 12 – <i>Link-62056-3-1</i> State transitions: Secondary station .....	39
Table 13 – Meaning of the states listed in the previous tables .....	40
Table 14 – Definition of the procedures and functions classified in alphabetical order .....	40
Table 15 – Error summary table .....	41
Table 16 – Application services and service primitives .....	42
Table 17 – <i>Application-62056-3-1</i> state transitions: Primary station .....	43
Table 18 – <i>Application-62056-3-1</i> state transitions: Secondary station .....	44
Table 19 – Meaning of the states listed in the previous tables .....	44
Table 20 – Definition of the procedures and functions classified in alphabetical order .....	45
Table 21 – Error summary table .....	45
Table 22 – Data Link services and service primitives .....	47
Table 23 – <i>Link-E/D</i> state transitions: Primary station .....	48
Table 24 – <i>Link-E/D</i> state transitions: Secondary station .....	50
Table 25 – Meaning of the states listed in the previous tables .....	52
Table 26 – Definition of the procedures and functions classified in alphabetical order .....	52
Table 27 – Error summary table .....	54
Table 28 – Client_connect function definition .....	54
Table 29 – E/COSEM Physical services and service primitives .....	56
Table 30 – <i>E/COSEM Physical</i> state transitions: Primary station .....	57
Table 31 – Power supply management state transitions (only for non-energized Secondary station) .....	60
Table 32 – <i>E/COSEM Physical</i> State transitions: Secondary station .....	61
Table 33 – Meaning of the states listed in the previous tables .....	63



Table 34 – Definition of the procedures, functions and events classified in alphabetical order .....	64
Table 35 – Error summary table .....	65
Table 36 – Data Link services and service primitives .....	66
Table 37 – <i>DLMS/COSEM Data Link E/D</i> state transitions: Primary station .....	68
Table 38 – <i>DLMS/COSEM Link E/D</i> state transitions: Secondary station .....	71
Table 39 – Meaning of the states listed in the previous tables .....	73
Table 40 – Definition of the procedures and functions classified in alphabetical order .....	74
Table 41 – Commands managed by the Support Manager layer .....	75
Table 42 – List of parameters .....	76
Table 43 – Support Manager layer state transitions: Primary station .....	77
Table 44 – Support Manager layer state transitions: Secondary station .....	77
Table 45 – Meaning of the states listed in the previous table .....	77
Table 46 – Definition of procedures, functions and events .....	78
Table 47 – Transport services and services primitive .....	79
Table 48 – Transport state transitions .....	80
Table 49 – Meaning of the states listed in the previous table .....	81
Table 50 – Definition of the procedures and functions classified in alphabetical order .....	82
Table 51 – Primary station transmitter: Tev0 and Tev1 values .....	93
Table 52 – Primary station receiver: Tev0 and Tev1 values .....	94
Table 53 – Secondary station transmitter: Tev0 and Tev1 values .....	94
Table 54 – Secondary station receiver: Tev0 and Tev1 values .....	95
Table C.1 – FatalError error numbers .....	102
Table D.1 – Command codes for local bus data exchange .....	103
Table D.2 – Command codes with DLMS and DLMS/COSEM .....	104
Table H.1 – Discovery service .....	108
Table H.2 – Service specification .....	108



## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ELECTRICITY METERING DATA EXCHANGE –  
THE DLMS/COSEM SUITE –****Part 3-1: Use of local area networks on twisted pair  
with carrier signalling**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62056-3-1 has been prepared by IEC technical committee 13: Electrical energy measurement, tariff- and load control.

This first edition cancels and replaces the first edition of IEC 62056-31, issued in 1999, and constitutes a technical revision.

The main technical changes with regard to the previous edition are as follows:

- addition of a profile which makes use of the IEC 62056 DLMS/COSEM Application layer and COSEM object model,
- review of the data link layer which is split into two parts:
  - a pure Data Link layer;
  - a “Support Manager” entity managing the communication media;
- ability to negotiate the communication speed, bringing baud rate up to 9 600 bauds.

The text of this standard is based on the following documents:

FDIS	Report on voting
13/1546/FDIS	13/1552/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

A list of all parts of IEC 62056 series, published under the general title *Electricity metering data exchange – The DLMS/COSEM suite*, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

The numbering scheme has changes from IEC 62056-XY to IEC 62056-X-Y. For example, IEC 62056-31 becomes IEC 62056-3-1.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**  
<https://standards.iteh.ai/catalog/standards/sist/5c3981f1-588a-4173-a7da-5c22fb7f82f9/iec-62056-3-1-2013>

## ELECTRICITY METERING DATA EXCHANGE – THE DLMS/COSEM SUITE –

### Part 3-1: Use of local area networks on twisted pair with carrier signalling

#### 1 Scope

This part of IEC 62056 describes three profiles for local bus data exchange with stations either energized or not. For non-energized stations, the bus supplies energy for data exchange.

Three different profiles are supported:

- base profile: this three-layer profile provides remote communication services;  
NOTE This first profile has been published in IEC 61142:1993 and became known as the Euridis standard.
- profile with DLMS: this profile allows using DLMS services as specified in IEC 61334-4-41;  
NOTE This second profile has been published in IEC 62056-31 Ed. 1.0:1999;
- profile with DLMS/COSEM: this profile allows using the DLMS/COSEM Application layer and the COSEM object model as specified in IEC 62056-5-3 Ed. 1.0:— and in IEC 62056-6-2 Ed. 1.0:— respectively.

The three profiles use the same physical layer and they are fully compatible, meaning that devices implementing any of these profiles can be operated on the same bus.

The transmission medium is twisted pair using carrier signalling and it is known as the Euridis Bus.

#### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61334-4-41:1996, *Distribution automation using distribution line carrier systems – Part 4: Data communication protocol – Section 41: Application protocols – Distribution line message specification*

IEC 62056-51:1998 *Electricity Metering – Data exchange for meter reading, tariff and load control – Part 51: Application Layer Protocols*

IEC 62056-5-3 Ed. 1.0:—, *Electricity metering data exchange – The DLMS/COSEM suite – Part 5-3: DLMS/COSEM application layer*

ISO/IEC 8482:1993, *Information technology – Telecommunications and information exchange between systems – Twisted pair multipoint interconnections*

EIA 485 – *Standard for Electrical Characteristics of Generators and Receivers for Use in Balanced Digital Multipoint Systems*

### 3 Abbreviations

Abbreviation	English rendering
ADP	Primary Station Address
ADG	General Secondary Address. Broadcast Address
ADS	Secondary Station Address
AGN	Normal Wakeup
AGT	General call for a General Energized Station
APDU	Application Protocol Data Unit
APG	General Primary Address
ARJ	COM field value: Rejection of authentication in remote programming exchange
ASDU	Application Service Data Unit
ASO	COM field value: Call to Forgotten Stations
AUT	COM field value: Authentication command
COM	Control field of the Data Link layer
COSEM	Companion Specification for Energy Metering
DAT	COM field value: Response of remote reading exchange
DES	Data Encryption Standard
DLMS	Distribution Line Message Specification (IEC 61334-4-41) Device Language Message Specification (IEC 62056-5-3)
DSDU	Data link Service Data Unit
DRJ	COM field value: Data Rejected Value of COM notifying the rejection of remote programming exchange data
Dsap	Transport data unit label. Coded over 3 bits. Its value is 6.
DTSAP	Destination of Transport Service Access Point
ECH	COM field value: Echo of remote programming exchange data
ENQ	Remote reading exchange request
EOS	COM field value: End of remote programming exchange
IB	Initialisation of the bus
MaxRetry	Maximum number retransmissions. Limited to 2.
MaxRSO	Maximum number of RSO listening windows. Fixed at 3.
PDU	Protocol Data Unit
PRE	COM field value: Pre-selection of energised stations
REC	COM field value: Remote programming exchange request
RSO	COM field value: Response to a call to forgotten stations
SEL	COM field value: Acknowledgement of the pre-selection of energized stations
STSAP	Source Transport Service Access Point
TAB	In the case of the Euridis profiles without DLMS and without DLMS/COSEM: data code. In the case of profiles using DLMS or DLMS/COSEM: value at which the equipment is programmed for Discovery
TABi	List of TAB field
TASB	Duration of an Alarm Signal on the Bus
TOAG	Maximum wait time for an energized station once selected, to recognise a general call AGN
TOALR	Wait before sending an AGN after reception of an AGN or AGT
TOL	Maximum waiting time for a request from the upper layer

Abbreviation	English rendering
TOPRE	Maximum waiting time for a response to a pre-selection.
TPDU	Transport Protocol Data Unit
TSDU	Transport Protocol Service Unit
TRA	COM field value: Acknowledgement of point to point transfer
TRB	COM field value: Broadcast remote transfer frame not acknowledged
TRF	COM field value: Point to point remote transfer exchange
T1	Time out to wait for a response according to a request
XBA	COM field value: Response to a change of speed request
XBR	COM field value: Change of speed request
ZA1	Field reserved for bidirectional programming authentication
ZA2	Field reserved for bidirectional programming authentication

## 4 General description

### 4.1 Basic vocabulary

All communication calls upon two systems called Primary Station and Secondary Station. The Primary Station is the system that decides to initialize a communication with a remote system called Secondary Station; these designations remain valid throughout the duration of the communication.

A communication is broken down into a certain number of transactions. Each transaction consists of a transmission from the Transmitter to the Receiver. During the sequence of transactions, the Primary Station and Secondary Station systems take turns to act as Transmitter and Receiver.

For the local bus data exchange profile with DLMS or DLMS/COSEM, the terms Client and Server have the same meaning as for the DLMS model (refer to IEC 61334-4-41 or IEC 62056-5-3 Ed. 1.0:—). The Server (which is a Secondary Station) receives and processes all submissions of specific service requests. The Client (which is a Primary Station) is the system that uses the Server for a specific purpose by means of one or more service requests.

### 4.2 Profiles, layers and protocols

#### 4.2.1 Overview

This standard specifies three profiles as shown in Figure 1.

- the base profile (without DLMS), see 4.2.2;
- the profile with DLMS, see 4.2.3;
- the profile with DLMS/COSEM; see 4.2.4.

The physical layer in the three profiles is the same except that in the DLMS/COSEM profile speed negotiation is available. This common physical layer allows stations using different profiles to be installed on the same bus.




Figure 1 – IEC 62056-3-1 communication profiles

IEC 2066/13

#### 4.2.2 Base profile (without DLMS)

The base profile (without DLMS) uses three protocol layers:

- the physical layer with the *Physical-62056-3-1* protocol specified in 5.1;
- the data link layer with the *Link-62056-3-1* protocol, specified in 5.2, and
- the application layer with the *Application-62056-3-1* protocol specified in 5.3.

This profile allows remote reading, remote programming, point-to-point remote transfer – which is a simplified remote programming service – broadcast remote transfer, remote supply of secondary stations, detecting forgotten stations and alarm functions. The related communication services are specified in 4.4.

#### 4.2.3 Profile with DLMS

The profile with DLMS uses three protocol layers:

- the same physical layer as the base profile, specified in 5.1;
- the data link layer using the *Link-E/D* protocol, specified in 6.2; and
- the application layer specified in IEC 62056-51, using the *Transport+*, *Application+* and *DLMS+* protocols, see 6.3.

This profile also allows using DLMS as specified in IEC 61334-4-41. The related communication services are specified in 4.5.

#### 4.2.4 Profile with DLMS/COSEM

The profile with DLMS/COSEM uses four protocol layers:

- the physical layer, similar to the one used in the base profile and the profile with DLMS, specified in 5.1, but with speed negotiation, see 7.2;
- the data link layer using the *Link-E/D* protocol. This is the same as the data link layer of the profile with DLMS, except that it interfaces with the support manager layer and the transport layer. See 7.3;
- the support manager layer supports some specific process for the management of the bus, see 0;
- the transport layer provides segmentation and reassembly of APDUs, see 0;
- the application layer as specified in IEC 62056-5-3 Ed. 1.0:—taking into account some restrictions of the Euridis bus, see 0.

The profile with DLMS/COSEM allows using the COSEM object model and the DLMS services accessing the COSEM objects over the Euridis bus.

#### 4.3 Specification language

In this standard, the protocol of each layer is described by state transitions represented in the form of tables. The syntax used in making up these tables is defined by a specification language described in Annex A.

In the event of a difference in interpretation between part of the text and a state transition table, the table is always taken as the reference.

#### 4.4 Communication services for local bus data exchange without DLMS

##### 4.4.1 Overview

<https://standards.iteh.ai/catalog/standards/sist/5c3981f1-588a-4173-a7da-5c22fb7f82f9/iec-62056-3-1-2013>

The list of available services at the Application level layer is:

- a) remote reading of data, see 0;
- b) remote programming of data, see 4.4.3;
- c) point to point remote transfer, which is a simplified remote programming service, see 4.4.4;
- d) broadcast remote transfer, 4.4.5;
- e) bus initialization, 4.4.6;
- f) forgotten station call, 4.4.7.