



## Standard Specification for Toluene for Toluene Diisocyanate (TDI) Feedstock<sup>1</sup>

This standard is issued under the fixed designation D 5606; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

### 1. Scope

1.1 This specification covers toluene for toluene diisocyanate (TDI) feedstock.

1.2 The following applies to all specified limits in this specification: for purposes of determining conformance with this specification, an observed value or a calculated value shall be rounded off to the nearest unit in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E 29.

1.3 Consult OSHA regulations and suppliers' material safety data sheets for all materials used in this specification.

1.4 The values stated in SI units are to be regarded as the standard.

### 2. Referenced Documents

#### 2.1 ASTM Standards:

D 848 Test Method for Acid Wash Color of Industrial Aromatic Hydrocarbons<sup>2</sup>

D 1209 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)<sup>2</sup>

D 2360 Test Method for Trace Impurities in Monocyclic Aromatic Hydrocarbons by Gas Chromatography<sup>2</sup>

D 3437 Practice for Sampling and Handling Cyclic Products<sup>2</sup>

D 5386 Test Method for Color Using Tristimulus Colorimetry<sup>2</sup>

E 29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications<sup>3</sup>

#### 2.2 Other Document:

OSHA Regulations, 29 CFR, paragraphs 1910.1000 and 1910.1200<sup>4</sup>

### 3. Properties

3.1 Toluene for TDI feedstock shall conform to the following requirements:

Property	Specification	ASTM Test Method
Purity, min, wt%	99.9	D 2360
Acid wash color, max	pass with 2	D 848
Benzene, max, mg/kg	300	D 2360
Nonaromatics, max, wt %	0.1	D 2360
Ethylbenzene, max, mg/kg	300	D 2360
Xylenes, max, mg/kg	500	D 2360
Appearance	<sup>A</sup>	...
Color, max, Pt-Co scale	10	D 1209 or D5386

<sup>A</sup>Clear liquid free of sediment and haze when observed at 18.3 to 25.6°C (65 to 78°F).

### 4. Sampling

4.1 Sample the material in accordance with Practice D 3437.

### 5. Keywords

5.1 impurities in toluene; toluene; toluene diisocyanate feedstock

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee D-16 on Aromatic Hydrocarbons and Related Chemicals and is the direct responsibility of Subcommittee D16.0A on Benzene, Toluene, Xylenes, Cyclohexane, and Their Derivatives.

Current edition approved April 10, 1998. Published August 1998. Originally published as D 5609-94. Last previous edition D 5606-94.

<sup>2</sup> Annual Book of ASTM Standards, Vol 06.04.

<sup>3</sup> Annual Book of ASTM Standards, Vol 14.02.

<sup>4</sup> Available from Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

*The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, 100 Barr Harbor Drive, West Conshohocken, PA 19428.*