

# INTERNATIONAL STANDARD



**Industrial communication networks – Fieldbus specifications – WIA-PA  
communication network and communication profile**

<https://standards.iteh.ai/catalog/standards/sist/60328520-3aeb-4739-b7c4-e1de50727cd7/iec-62601-2011>



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2011 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Email: [inmail@iec.ch](mailto:inmail@iec.ch)  
Web: [www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: [www.iec.ch/webstore/custserv](http://www.iec.ch/webstore/custserv)

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: [csc@iec.ch](mailto:csc@iec.ch)  
Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00

# INTERNATIONAL STANDARD



**Industrial communication networks – Fieldbus specifications – WIA-PA  
communication network and communication profile**

<https://standards.iteh.ai/catalog/standards/sist/60728520-3aeb-4739-b7c4-e1de50727cd7/iec-62601-2011>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE **XH**

ICS 25.040.40; 35.100.05

ISBN 978-2-88912-788-7

## CONTENTS

FOREWORD.....	13
1 Scope.....	15
2 Normative references .....	15
3 Terms, definitions and abbreviations .....	15
3.1 Terms and definitions .....	15
3.2 Abbreviations .....	19
4 Specification of data types.....	21
4.1 Representation of boolean type .....	21
4.2 Representation of unsigned integer type .....	21
4.3 Representation of octet type.....	21
4.4 Representation of floating point number type.....	21
5 WIA-PA overview.....	22
5.1 Device types .....	22
5.2 Network topology.....	22
5.3 Protocol architecture .....	24
5.4 Interconnection .....	25
6 System management.....	25
6.1 General.....	25
6.2 Framework of system management .....	27
6.3 Joining process .....	28
6.3.1 Joining process of routing device.....	28
6.3.2 Joining process of field device.....	30
6.3.3 Addressing and address assignment .....	31
6.4 Virtual Communication Relationship (VCR).....	31
6.4.1 Definition.....	31
6.4.2 Protocol support for VCR.....	32
6.4.3 VCR establishment .....	33
6.4.4 VCR release.....	33
6.5 Routing configuration and communication resource allocation .....	33
6.5.1 Routing configuration.....	33
6.5.2 Framework of communication resource allocation .....	33
6.5.3 DLPPDU priority and scheduling rules .....	34
6.5.4 Communication resource allocation to routing device .....	35
6.5.5 Communication resource allocation to field device.....	35
6.6 Aggregation and disaggregation .....	36
6.6.1 Aggregation .....	36
6.6.2 Disaggregation .....	38
6.6.3 An example of the two level aggregation process .....	39
6.6.4 Management of aggregation and disaggregation objects.....	41
6.7 Performance monitoring .....	43
6.7.1 Path failure report.....	43
6.7.2 Device status report .....	43
6.7.3 Channel condition report.....	44
6.8 Leaving process .....	44
6.8.1 General .....	44
6.8.2 Leaving process of routing device.....	44

6.8.3	Leaving process of field device .....	46
6.9	Management information base and services .....	47
6.9.1	Management information base .....	47
6.9.2	MIB services .....	59
7	Physical Layer .....	61
8	Data link layer .....	62
8.1	General .....	62
8.2	Protocol stack .....	62
8.3	MAC overview and function extension .....	62
8.3.1	MAC overview .....	62
8.3.2	MAC function extension .....	63
8.4	DLSL function description .....	66
8.4.1	General .....	66
8.4.2	Coexistence .....	67
8.4.3	Timeslot communication .....	67
8.4.4	WIA-PA superframe .....	68
8.4.5	Frequency hopping .....	68
8.4.6	Transmission of long cycle data .....	70
8.4.7	Retry strategy .....	71
8.4.8	Management service .....	71
8.4.9	Radio link quality and channel condition measurement .....	71
8.4.10	Security .....	71
8.4.11	DLSL state machine .....	71
8.5	Data link sub-layer data services .....	73
8.5.1	General .....	73
8.5.2	DLDE-DATA.request .....	73
8.5.3	DLDE-DATA.confirm .....	74
8.5.4	DLDE-DATA.indication .....	75
8.5.5	Time sequence of DLSL data service .....	76
8.6	Data link sub-layer management services .....	77
8.6.1	General .....	77
8.6.2	Network discovery services .....	77
8.6.3	Device joining services .....	79
8.6.4	Device leaving services .....	81
8.6.5	DLME-CHANNEL-CONDITION.indication .....	82
8.6.6	DLME-NEIGHBOR-INFO.indication .....	83
8.6.7	DLME-COMM-STATUS.indication .....	83
8.6.8	Keep-alive services .....	84
8.6.9	Time synchronization services .....	85
8.7	DLSL frame formats .....	86
8.7.1	General frame format .....	86
8.7.2	Date frame format .....	86
8.7.3	Command frame format .....	87
9	Network layer .....	87
9.1	General .....	87
9.2	Protocol stack .....	87
9.3	Function description .....	88
9.3.1	General .....	88
9.3.2	Addressing .....	88

9.3.3	Routing.....	89
9.3.4	Packet lifecycle management .....	89
9.3.5	Joining and leaving network of device .....	89
9.3.6	End-to-end network performance monitoring.....	89
9.3.7	Fragmentation and reassembly.....	90
9.3.8	Network layer state machine.....	90
9.4	Network layer data services .....	91
9.4.1	General .....	91
9.4.2	NLDE-DATA.request.....	91
9.4.3	NLDE-DATA.confirm.....	91
9.4.4	NLDE-DATA.indication .....	92
9.4.5	Time sequence of NL data services .....	92
9.5	Network layer management services .....	93
9.5.1	General .....	93
9.5.2	Network communication status report services .....	93
9.5.3	Network joining services.....	95
9.5.4	Network leaving services .....	101
9.5.5	Cluster member report services .....	107
9.5.6	Neighbor information report services .....	109
9.5.7	Route allocation services.....	110
9.5.8	Communication resource allocation services .....	116
9.5.9	Aggregation and disaggregation services .....	131
9.5.10	Device status report services.....	132
9.5.11	Channel condition report services.....	134
9.5.12	Failure path report services .....	136
9.5.13	Network attribute getting services.....	137
9.5.14	Network attribute setting services .....	140
9.6	Network layer packet formats .....	143
9.6.1	Common packet format.....	143
9.6.2	Data packet format .....	144
9.6.3	Aggregated packet format.....	144
9.6.4	Command packet format.....	145
10	Application Layer.....	160
10.1	Overview .....	160
10.1.1	General .....	160
10.1.2	AL structure.....	160
10.1.3	Functions of UAP.....	161
10.1.4	Functions of ASL .....	161
10.2	UAP .....	161
10.2.1	General .....	161
10.2.2	UAO .....	162
10.2.3	Method definition .....	163
10.3	Application sub-layer.....	166
10.3.1	General .....	166
10.3.2	Application sub-layer data entity.....	166
10.4	Application sub-layer packet formats .....	171
10.4.1	General .....	171
10.4.2	ASL general packet format .....	172
10.4.3	Packet formats .....	173

11 Security.....	175
11.1 General.....	175
11.2 Security management framework.....	175
11.3 Secure communication protocol stack.....	176
11.3.1 General.....	176
11.3.2 MAC layer security.....	177
11.3.3 Data link sub-layer security.....	177
11.3.4 Application sub-layer security.....	179
11.4 Key management.....	180
11.4.1 Key type.....	180
11.4.2 Key distribution.....	181
11.4.3 Key update.....	181
11.4.4 Key status.....	182
11.5 Secure joining process.....	182
11.5.1 Secure joining process of a new WIA-PA device.....	182
11.5.2 Device security material getting services.....	183
11.6 Secure transportation.....	187
11.6.1 Process of secure transportation from field device to host configuration computer.....	187
11.6.2 Process of secure transportation from host configuration computer to field device.....	188
Annex A (informative) Security strategy for WIA-PA network.....	189
Annex B (informative) Format description for WIA-PA standard.....	191
Annex C (informative) Example of UAO.....	193
Bibliography.....	195
<a href="https://standards.iteh.ai/catalog/standards/sist/6c78520-3aeb-4739-b7c4-e1de50727cd7/iec-62601-2011">https://standards.iteh.ai/catalog/standards/sist/6c78520-3aeb-4739-b7c4-e1de50727cd7/iec-62601-2011</a>	
Figure 1 – Example of WIA-PA physical topology (combination of star and mesh).....	23
Figure 2 – Example of WIA-PA physical topology (star-only).....	23
Figure 3 – OSI basic reference model mapped to WIA-PA.....	24
Figure 4 – The architecture of WIA-PA gateway.....	25
Figure 5 – DMAP in system management.....	26
Figure 6 – Hybrid centralized and distributed system management scheme.....	28
Figure 7 – Joining process of routing device through the gateway device.....	29
Figure 8 – Joining process of routing device through an online routing device.....	29
Figure 9 – Joining process of field device through a gateway device.....	30
Figure 10 – Joining process of field device through a routing device.....	30
Figure 11 – Long address structure of device.....	31
Figure 12 – Short address structure of routing device.....	31
Figure 13 – Short address structure of field device.....	31
Figure 14 – An example of resource allocation.....	34
Figure 15 – Allocation process of routing device’s communication resources.....	35
Figure 16 – Allocation process of field device’s communication resources.....	36
Figure 17 – Example of aggregation and disaggregation.....	40
Figure 18 – Process of path failure report.....	43
Figure 19 – Device status report process of field device.....	43
Figure 20 – Device status report process of routing device.....	44

Figure 21 – Process of channel condition report .....	44
Figure 22 – Active leaving process of routing device .....	45
Figure 23 – Passive leaving process of routing device .....	45
Figure 24 – Active leaving process of field device (leaving from gateway device).....	46
Figure 25 – Active leaving process of field device (leaving from routing device).....	46
Figure 26 – Passive leaving process of field device (leaving from gateway device).....	47
Figure 27 – Passive leaving process of field device (leaving from routing device) .....	47
Figure 28 – WIA-PA DLL protocol stack .....	62
Figure 29 – WIA-PA DLSL reference model .....	67
Figure 30 – WIA-PA superframe .....	68
Figure 31 – R1, R2 and R3 superframe structures .....	70
Figure 32 – An example of long cycle data transmission .....	70
Figure 33 – DLSL state machine .....	72
Figure 34 – Time sequence of data service .....	76
Figure 35 – Time sequence of network discovery .....	79
Figure 36 – General frame format .....	86
Figure 37 – WIA-PA network layer protocol stack.....	87
Figure 38 – WIA-PA Network layer reference model.....	88
Figure 39 – Network layer state machine.....	90
Figure 40 – Time sequence of NL data services.....	93
Figure 41 – Time sequence for field device joining through routing device .....	98
Figure 42 – One-hop joining process for routing device.....	99
Figure 43 – Multi-hop join process of routing device .....	100
Figure 44 – Active leaving process of field device (leaving routing device).....	103
Figure 45 – Passive leaving of field device .....	104
Figure 46 – Active leaving process of routing device .....	105
Figure 47 – Passive leaving process of routing device .....	106
Figure 48 – Cluster member reporting process.....	108
Figure 49 – Neighbor information reporting process .....	110
Figure 50 – Time sequence for route adding .....	112
Figure 51 – Time sequence for route updating .....	114
Figure 52 – Time sequence for route deleting .....	116
Figure 53 – Adding a link originated from gateway device to routing device .....	119
Figure 54 – Adding a link originated from routing device to field device.....	119
Figure 55 – Updating a link originated by gateway device to routing device .....	121
Figure 56 – Updating a link originated from routing device to field device .....	121
Figure 57 – Releasing a link originated from gateway device to routing device.....	123
Figure 58 – Releasing a link originated from routing device to field device.....	124
Figure 59 – Adding a superframe originated from gateway device to routing device .....	126
Figure 60 – Adding a superframe originated from routing device to field device .....	126
Figure 61 – Updating a superframe originated from gateway device to routing device .....	128
Figure 62 – Updating a superframe originated from routing device to field device .....	128
Figure 63 – Releasing a superframe originated from gateway device to routing device .....	130



Figure 64 – Releasing a superframe originated from routing device to field device .....	130
Figure 65 – Device status reporting process from field device to routing device .....	133
Figure 66 – Device status reporting process from routing device to gateway device .....	134
Figure 67 – Channel condition reporting process from field device to routing device .....	135
Figure 68 – Channel condition reporting process from routing device to gateway device .....	136
Figure 69 – Failure path reporting process .....	137
Figure 70 – Network layer common packet format .....	143
Figure 71 – Network layer data packet format .....	144
Figure 72 – Aggregated packet format .....	144
Figure 73 – Format of NL command packet .....	145
Figure 74 – AL structure .....	160
Figure 75 – User application process .....	161
Figure 76 – C/S communication process .....	169
Figure 77 – P/S communication process (disable aggregation function) .....	170
Figure 78 – P/S communication process (enable aggregation function) .....	171
Figure 79 – R/S communication process .....	171
Figure 80 – Application sub-layer general packet format .....	172
Figure 81 – ASL data packet format .....	173
Figure 82 – Acknowledgement packet format .....	174
Figure 83 – Security management framework of WIA-PA network .....	175
Figure 84 – Security communication protocol stack .....	177
Figure 85 – MPDU structure .....	177
Figure 86 – Security DLPDU structure .....	178
Figure 87 – Security APDU structure .....	179
Figure 88 – Key lifecycle .....	181
Figure 89 – Secure joining process of WIA-PA device .....	182
Figure 90 – Time sequence for field device joining (Field device to routing device ) .....	185
Figure 91 – Time sequence for field device joining (Routing device to gateway device) .....	185
Figure 92 – One-hop joining process for routing device .....	186
Figure 93 – Multi-hop join process of routing device (new routing device to routing device) .....	186
Figure 94 – Multi-hop join process of routing device (routing device to gateway device) .....	187
Figure B.1 – Time sequence diagram .....	191
Table 1 – Protocol support for VCR .....	32
Table 2 – Relations between VCR and aggregation function .....	37
Table 3 – Format of aggregated data followed by field device's DAGO .....	38
Table 4 – Format of aggregated packet followed by routing device's PAGO .....	38
Table 5 – DAGO class attributes .....	41
Table 6 – DAGO instance attributes .....	41
Table 7 – MEM_STRUCT structure .....	42
Table 8 – PAGO class attributes .....	42
Table 9 – PAGO instance attributes .....	42

Table 10 – DGO class attributes .....	42
Table 11 – DGO instance attributes .....	43
Table 12 – Unstructured attributes .....	48
Table 13 – Structured attributes .....	51
Table 14 – NLRoute_Struct structure .....	52
Table 15 – Superframe_Struct structure .....	52
Table 16 – Link_Struct structure .....	53
Table 17 – Neighbor_Struct structure .....	54
Table 18 – ChanCon_Struct structure .....	54
Table 19 – Device_struct structure .....	55
Table 20 – VCR_Struct structure .....	57
Table 21 – DevConRep_Struct structure .....	58
Table 22 – Key_Struct structure .....	58
Table 23 – ObjList_Struct structure .....	59
Table 24 – DMAP-MIB-GET.request parameters .....	59
Table 25 – DMAP-MIB-GET.confirm parameters .....	60
Table 26 – DMAP-MIB-SET.request parameters .....	61
Table 27 – DMAP-MIB-SET.confirm parameters .....	61
Table 28 – MAC extended PIB attributes .....	63
Table 29 – MAC extended command frame .....	63
Table 30 – MLME-KEEP-LIVE.confirm parameters .....	64
Table 31 – MLME-KEEP-LIVE.indication parameters .....	64
Table 32 – MLME-TIME-SYN.request parameters .....	64
Table 33 – MLME-TIME-SYN.confirm parameters .....	65
Table 34 – MLME-TIME-SYN.indication parameters .....	65
Table 35 – Beacon payload .....	65
Table 36 – Format of keep-alive command frame .....	66
Table 37 – Format of time synchronization command frame .....	66
Table 38 – Hopping mechanisms .....	69
Table 39 – DLSE state transitions .....	72
Table 40 – DLDE-DATA.request parameters .....	74
Table 41 – DLDE-DATA.confirm parameters .....	75
Table 42 – Status table .....	75
Table 43 – DLDE-DATA.indication parameters .....	76
Table 44 – DLME-DISCOVERY.request parameters .....	77
Table 45 – DLME-DISCOVERY.confirm parameters .....	78
Table 46 – Network descriptor list .....	78
Table 47 – DLME-JOIN.request parameters .....	79
Table 48 – DLME-JOIN.indication parameters .....	80
Table 49 – DLME-JOIN.response parameters .....	80
Table 50 – DLME-JOIN.confirm parameters .....	81
Table 51 – DLME-LEAVE.request parameters .....	81
Table 52 – DLME-LEAVE.indication parameters .....	82

Table 53 – DLME-LEAVE.confirm parameters .....	82
Table 54 – DLME-CHANNEL-CONDITION.indication parameters .....	83
Table 55 – DLME-NEIGHBOR-INFO.indication parameters .....	83
Table 56 – DLME-COMM-STATUS.indication parameters .....	84
Table 57 – DLME -KEEP-LIVE.confirm parameters .....	84
Table 58 – DLME -KEEP-LIVE.indication parameters .....	85
Table 59 – DLME-TIME-SYN.request parameters .....	85
Table 60 – DLME -TIME-SYN.confirm parameters .....	85
Table 61 – DLME-TIME-SYN.indication parameters .....	86
Table 62 – DLSL frame control field .....	86
Table 63 – Date frame format .....	87
Table 64 – General command frame format .....	87
Table 65 – DLSL command frame .....	87
Table 66 – Example of a routing table .....	89
Table 67 – Network layer states .....	90
Table 68 – NL state transitions .....	90
Table 69 – NLDE-DATA.request parameters .....	91
Table 70 – NLDE-DATA.confirm parameters .....	92
Table 71 – NLDE-DATA.indication parameters .....	92
Table 72 – NLME-COMM-STATUS.request parameters .....	93
Table 73 – NLME-COMM-STATUS.indication parameters .....	94
Table 74 – NLME-COMM-STATUS.confirm parameters .....	94
Table 75 – NLME-JOIN.request parameters .....	95
Table 76 – NLME-JOIN.indication parameters .....	96
Table 77 – NLME-JOIN.response parameters .....	96
Table 78 – NLME-JOIN.confirm parameters .....	97
Table 79 – NLME-LEAVE.request parameters .....	101
Table 80 – NLME-LEAVE.indication parameters .....	101
Table 81 – NLME-LEAVE.response parameters .....	101
Table 82 – NLME-LEAVE.confirm parameters .....	102
Table 83 – NLME-RPT-CLRMEM.request parameters .....	107
Table 84 – NLME-RPT-CLRMEM.confirm parameter .....	107
Table 85 – NLME-RPT-CLRMEM.response parameters .....	108
Table 86 – NLME-NEIGHBOR-INFO.request parameters .....	109
Table 87 – NLME-NEIGHBOR-INFO.confirm parameter .....	110
Table 88 – NLME-ADD_ROUTE.request parameters .....	110
Table 89 – NLME-ADD_ROUTE.confirm parameters .....	111
Table 90 – NLME-UPDATE_ROUTE.request parameters .....	112
Table 91 – NLME-UPDATE_ROUTE.confirm parameter .....	113
Table 92 – NLME-UPDATE_ROUTE.request parameters .....	114
Table 93 – NLME-DELETE_ROUTE.confirm parameters .....	115
Table 94 – NLME-ADD-LINK.request parameters .....	117
Table 95 – NLME-ADD-LINK.confirm parameters .....	118

Table 96 – NLME-UPDATE-LINK.request parameters .....	120
Table 97 – NLME-UPDATE-LINK.confirm parameters .....	120
Table 98 – NLME-RELEASE-LINK.request parameters .....	122
Table 99 – NLME-RELEASE-LINK.confirm parameters .....	122
Table 100 – NLME-ADD-SFR.request parameters.....	124
Table 101 – NLME-ADD-SFR.confirm parameters.....	125
Table 102 – NLME-UPDATA-SFR.request parameters .....	127
Table 103 – NLME-UPDATE-SFR.confirm parameters .....	127
Table 104 – NLME-RELEASE-SFR.request parameters .....	129
Table 105 – NLME-RELEASE-SFR.confirm parameters .....	129
Table 106 – NLME-AGG.indication parameters .....	131
Table 107 – NLME-AGO-SEND.request parameters.....	131
Table 108 – NLME-DAG.indication parameter.....	132
Table 109 – NLME- DEVICE -STATUS.request parameters .....	132
Table 110 – NLME- DEVICE -STATUS.indication parameters .....	133
Table 111 – NLME- DEVICE -STATUS.confirm parameter .....	133
Table 112 – NLME-CHANNEL-CONDITION.request parameters .....	134
Table 113 – NLME-CHANNEL-CONDITION.indication parameters .....	135
Table 114 – NLME-CHANNEL-CONDITION.confirm parameter .....	135
Table 115 – NLME-PATH_FAILURE.request parameters .....	136
Table 116 – NLME-PATH_FAILURE.indication parameters .....	137
Table 117 – NLME-PATH_FAILURE.confirm parameters .....	137
Table 118 – NLME-INFO_GET.request parameters.....	138
Table 119 – NLME-INFO_GET indication parameters .....	139
Table 120 – NLME-INFO_GET.response parameters .....	139
Table 121 – NLME-INFO_GET.response parameters .....	140
Table 122 – NLME-INFO_SET.request parameters .....	141
Table 123 – NLME-INFO_SET.indication parameters.....	141
Table 124 – NLME-SET. response parameters .....	142
Table 125 – NLME-SET.confirm parameters .....	143
Table 126– Control field format.....	143
Table 127 – Network layer command packet.....	146
Table 128 – Execution results of commands .....	147
Table 129 – Format of joining request packet.....	147
Table 130 – Format of joining response packet.....	147
Table 131 – Format of communication status report request packet.....	148
Table 132 – Format of leaving request packet.....	148
Table 133 – Value of leaving reason .....	148
Table 134 – Format of leaving response packet.....	149
Table 135 – Format of cluster member report request packet.....	149
Table 136 – Format of cluster member report response packet .....	149
Table 137 – Format of neighbor information report request packet.....	150
Table 138 – Format of route adding request packet .....	150

Table 139 – Format of route adding response packet.....	150
Table 140 – Format of route update request packet .....	151
Table 141 – Format of route update response packet.....	151
Table 142 – Format of route deleting request packet .....	151
Table 143 – Format of route deleting response packet.....	152
Table 144 – Format of link adding request packet .....	152
Table 145 – Format of link adding response packet .....	152
Table 146 – Format of link update request packet.....	153
Table 147 – Format of link update response packet .....	153
Table 148 – Format of link release request packet.....	154
Table 149 – Format of link release response packet .....	154
Table 150 – Format of superframe adding request packet.....	154
Table 151 – Format of superframe adding response packet .....	155
Table 152 – Format of superframe update request packet.....	155
Table 153 – Format of superframe update response packet.....	155
Table 154 – Format of superframe release request packet.....	156
Table 155 – Format of superframe release response packet .....	156
Table 156 – Format of device condition report request packet.....	156
Table 157 – Format of device condition information .....	157
Table 158 – Format of channel condition report request packet .....	157
Table 159 – Format of channel quality information .....	157
Table 160 – Format of path failure report request packet .....	158
Table 161 – Format of attribute getting request packet .....	158
Table 162 – Format of attribute getting response packet.....	159
Table 163 – Format of attribute setting request packet.....	159
Table 164 – Format of attribute setting response packet.....	160
Table 165 – Method definition .....	163
Table 166 – Request format of READ .....	163
Table 167 – Response format of READ method .....	163
Table 168 – Request format of WRITE method .....	164
Table 169 – Response format of WRITE method.....	164
Table 170 – Format of PUBLISH method .....	165
Table 171 – Format of REPORT method .....	165
Table 172 – Format of REPORT ACK method .....	165
Table 173 – ASLDE-DATA.request parameters .....	167
Table 174 – ASLDE-DATA.confirm parameters .....	167
Table 175 – ASLDE-DATA.indication parameters.....	168
Table 176 – ASLDE-AGG.request parameters .....	168
Table 177 – ASLDE-DAG.indication parameters .....	169
Table 178 – Packet control field format.....	172
Table 179 – Packet type subfield value .....	172
Table 180 – Structure of DLSL security header .....	178
Table 181 – Structure of security control field in DLSL security header.....	179

Table 182 – Structure of security material control field in DLSL security header..... 179

Table 183 – Structure of ASL security header field ..... 180

Table 184 – DLME-SEC.request parameters..... 183

Table 185 – DLME-SEC.indication parameters ..... 183

Table 186 – DLME-SEC.response parameters ..... 184

Table 187 – DLME-SEC.confirm parameters..... 184

Table A.1 – Graded and layered security measures for WIA-PA network..... 190

Table A.2 – Security levels of data packets..... 190

Table B.1 – Packet or frame format in octet(s) ..... 191

Table B.2 – Subfield format in bit(s)..... 192

Table C.1 – AIO Class Attribute ..... 193

Table C.2 – AIO Instance Attributes ..... 194

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/60728520-3aeb-4739-b7c4-e1de50727cd7/iec-62601-2011>

Withhold

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL COMMUNICATION NETWORKS –  
 FIELDBUS SPECIFICATIONS –  
 WIA-PA COMMUNICATION NETWORK  
 AND COMMUNICATION PROFILE**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62601 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial process measurement, control and automation.

This standard cancels and replaces IEC/PAS 62601 published in 2009. This first edition constitutes a technical revision.

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/663/FDIS	65C/671/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.