



SLOVENSKI STANDARD
SIST EN 300 444 V1.4.2:2003
01-december-2003

8 [[]HJbY]nVc`ýUbYVfYnj fj] bYHfY_ca i b]_UMfY'fB 97 HLË`DfcZ`[YbYf] bY[U
XcghcdUfj 5 DŁ

Digital Enhanced Cordless Telecommunications (DECT); Generic Access Profile (GAP)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: EN 300 444 Version 1.4.2

<https://standards.iteh.ai/catalog/standards/sist/7a18bf27-75c9-472b-ba59-b78d41de6335/sist-en-300-444-v1-4-2-2003>

ICS:

33.070.30 Öä ää) ^/ä à[|za) ^ Digital Enhanced Cordless
à!^: çicã} ^/ä |^ \ { ~ } ä ää) Telecommunications (DECT)
ÖÖÓVD

SIST EN 300 444 V1.4.2:2003 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 444 V1.4.2:2003](https://standards.iteh.ai/catalog/standards/sist/7a18bf27-75c9-472b-ba59-b78d41de6335/sist-en-300-444-v1-4-2-2003)

<https://standards.iteh.ai/catalog/standards/sist/7a18bf27-75c9-472b-ba59-b78d41de6335/sist-en-300-444-v1-4-2-2003>

ETSI EN 300 444 V1.4.2 (2003-02)

European Standard (Telecommunications series)

Digital Enhanced Cordless Telecommunications (DECT); Generic Access Profile (GAP)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 444 V1.4.2:2003](https://standards.iteh.ai/catalog/standards/sist/7a18bf27-75c9-472b-ba59-b78d41de6335/sist-en-300-444-v1-4-2-2003)

<https://standards.iteh.ai/catalog/standards/sist/7a18bf27-75c9-472b-ba59-b78d41de6335/sist-en-300-444-v1-4-2-2003>



Reference

REN/DECT-000219

Keywords

access, DECT, generic, profile, radio,
synchronization

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 444 V1.4.2:2003

<https://standards.iteh.ai/catalog/standards/sist/7a18bf27-75c9-472b-ba59-b78d41de6778/sist-en-300-444-v1-4-2-2003>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.org

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2003.
All rights reserved.

DECT™, **PLUGTESTS™** and **UMTS™** are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	9
Foreword.....	9
1 Scope	10
2 References	10
3 Definitions, symbols and abbreviations	11
3.1 Definitions	11
3.2 Symbols.....	13
3.3 Abbreviations	14
4 Feature definitions.....	15
4.1 Network (NWK) features	15
4.2 Application features	16
5 Service definitions.....	17
5.1 DLC service definitions.....	17
5.2 MAC service definitions	17
6 Inter-operability requirements.....	18
6.1 General	18
6.2 NWK features.....	19
6.3 DLC services.....	20
6.4 MAC services.....	20
6.5 Physical layer (PHL) services	20
6.6 Application features	21
6.7 NWK feature to procedure mapping	21
6.8 Service to procedure mapping	23
6.8.1 DLC service to procedure mapping	23
6.8.2 MAC service to procedure mapping	24
6.8.3 Application feature to procedure mapping.....	25
6.9 General requirements	25
6.9.1 NWK layer message contents	25
6.9.2 Transaction identifier.....	25
6.9.3 Length of a NWK layer message	25
6.9.4 Handling of error and exception conditions.....	25
6.9.5 GAP default setup attributes	26
6.9.6 Coexistence of MM and CC procedures.....	26
6.9.7 Coding rules for information elements	26
7 Procedure description.....	26
8 NWK layer procedures.....	27
8.1 Summary of outgoing call messages, normal cases.....	27
8.2 Outgoing call request.....	28
8.2.1 Associated procedures	29
8.2.1.1 Timer P-<CC.03> management	29
8.2.2 Exceptional cases.....	30
8.2.2.1 Timer P-<CC.03> expiry	30
8.2.2.2 PT releases the outgoing call request	30
8.2.2.3 FT rejects the outgoing call request	31
8.3 Overlap sending.....	31
8.3.1 Associated procedure.....	32
8.3.1.1 Timer F-<CC.01> management	32
8.3.2 Exceptional cases.....	32
8.3.2.1 PT releases the outgoing call request	32
8.3.2.2 FT rejects the outgoing call request	32
8.3.2.3 Timer F-<CC.01> expiry	33

8.3.2.4	FT releases the outgoing call request	33
8.4	Outgoing call proceeding	34
8.4.1	Exceptional cases	34
8.4.1.1	PT releases the outgoing call request	34
8.4.1.2	FT releases the outgoing call request	35
8.5	Outgoing call confirmation.....	35
8.5.1	Exceptional cases	36
8.5.1.1	PT releases the outgoing call request	36
8.5.1.2	FT releases the outgoing call request	36
8.6	Outgoing call connection.....	37
8.7	Normal call release	37
8.7.1	Associated procedures	38
8.7.1.1	Timer P-<CC.02> management	38
8.7.1.2	Timer F-<CC.02> management	38
8.7.2	Exceptional cases.....	39
8.7.2.1	Release collisions.....	39
8.7.2.2	Timer F-<CC.02> expiry	39
8.7.2.3	Timer P-<CC.02> expiry	40
8.8	Abnormal call release.....	40
8.9	Partial release	41
8.10	Sending keypad information.....	42
8.11	Summary of incoming call related messages, normal cases	43
8.12	Incoming call request	43
8.12.1	Associated procedure.....	44
8.12.1.1	Timer F-<CC.03> management	44
8.12.2	Exceptional cases.....	45
8.12.2.1	FT releases the incoming call request	45
8.12.2.2	PT rejects the incoming call request	45
8.12.2.3	Timer F-<CC.03> expiry	46
8.12.3	Collective and group ringing	46
8.13	Incoming call confirmation	46
8.13.1	Exceptional cases.....	47
8.13.1.1	FT releases the incoming call transaction	47
8.13.1.2	PT releases the incoming call transaction	47
8.14	PT alerting.....	48
8.15	Incoming call connection	48
8.15.1	Associated procedure.....	49
8.15.1.1	Timer P-<CC.05> management	49
8.15.2	Exceptional cases.....	49
8.15.2.1	FT releases the incoming call transaction	49
8.15.2.2	PT releases the incoming call transaction	50
8.15.2.3	Timer P-<CC.05> expiry	50
8.16	Display	50
8.17	Terminal capability indication.....	51
8.18	Internal call setup	52
8.19	Internal call keypad	52
8.20	Service call setup.....	53
8.21	Service call keypad.....	53
8.22	Identification of PP.....	53
8.22.1	Associated procedure.....	54
8.22.1.1	Timer F-<MM_ident.2> management.....	54
8.22.2	Exceptional cases	54
8.22.2.1	Identity not existing in the PT	54
8.22.2.2	Timer F-<MM_ident.2> expiry.....	54
8.23	Authentication of FT	55
8.23.1	Associated procedure.....	55
8.23.1.1	Timer P-<MM_auth.1> management.....	55
8.23.2	Exceptional cases	56
8.23.2.1	Authentication algorithm/key not supported	56
8.23.2.2	Authentication challenge RES has wrong value	56
8.23.2.3	Timer P-<MM_auth.1> expiry.....	56
8.24	Authentication of PP	57

8.24.1	Associated procedure.....	58
8.24.1.1	Timer F-<MM_auth.1> management.....	58
8.24.2	Exceptional cases.....	58
8.24.2.1	Authentication algorithm/key not supported.....	58
8.24.2.2	Timer F-<MM_auth.1> expiry.....	58
8.25	Authentication of user.....	58
8.25.1	Associated procedure.....	59
8.25.1.1	Timer F-<MM_auth.2> management.....	59
8.25.2	Exceptional cases.....	59
8.25.2.1	Authentication algorithm/key not supported.....	59
8.25.2.2	Timer F-<MM_auth.2> expiry.....	59
8.26	Incrementing the ZAP value.....	59
8.27	Storing the DCK.....	60
8.28	Location registration.....	60
8.28.1	Associated procedures.....	62
8.28.1.1	Timer P-<MM_locate.1> management.....	62
8.28.1.2	Timer F-<MM_ident.1> management.....	62
8.28.2	Exceptional cases.....	62
8.28.2.1	FT rejects the location registration procedure.....	62
8.28.2.2	Failure of location registration procedure.....	63
8.28.2.3	PT rejects the identity assignment.....	63
8.28.2.4	Timer F-<MM_identity.1> expiry.....	63
8.29	Location update.....	64
8.30	Obtaining access rights.....	65
8.30.1	Associated procedure.....	67
8.30.1.1	Timer P-<MM_access.1> management.....	67
8.30.2	Exceptional cases.....	67
8.30.2.1	FT rejects the access rights.....	67
8.30.2.2	Timer P-<MM_access.1> expiry.....	67
8.31	FT terminating access rights.....	68
8.31.1	Associated procedure.....	69
8.31.1.1	Timer F-<MM_access.2> management.....	69
8.31.2	Exceptional cases.....	69
8.31.2.1	PT rejects the termination request.....	69
8.31.2.2	Timer F-<MM_access.2> expiry.....	69
8.32	Key allocation.....	69
8.32.1	Associated procedures.....	71
8.32.1.1	Timer F-<MM_key.1> management.....	71
8.32.1.2	Timer P-<MM_auth.1> management.....	71
8.32.2	Exceptional cases.....	71
8.32.2.1	Timer F-<MM_key.1> expiry.....	71
8.32.2.2	Timer P-<MM_auth.1> expiry.....	71
8.32.2.3	Allocation-type element is unacceptable.....	71
8.32.2.4	Authentication of PT fails.....	72
8.32.2.5	Authentication of FT fails.....	72
8.33	Cipher-switching initiated by FT.....	72
8.33.1	Associated procedure.....	73
8.33.1.1	Timer F-<MM_cipher.1> management.....	73
8.33.2	Exceptional cases.....	74
8.33.2.1	PT rejects the cipher request.....	74
8.33.2.2	Timer F-<MM_cipher.1> expiry.....	74
8.34	Cipher-switching initiated by PT.....	75
8.34.1	Associated procedure.....	76
8.34.1.1	Timer P-<MM_cipher.2> management.....	76
8.34.2	Exceptional cases.....	76
8.34.2.1	FT rejects the cipher request.....	76
8.34.2.2	Timer P-<MM_cipher.2> expiry.....	76
8.35	Indirect FT initiated link establishment.....	76
8.35.1	Associated procedure.....	77
8.35.1.1	Timer F-<LCE.03> management.....	77
8.35.2	Exceptional cases.....	78
8.35.2.1	The IPUI received in the {LCE-PAGE-RESPONSE} does not match.....	78

8.35.2.2	Timer <LCE.03> expiry	78
8.35.2.3	Release from the higher entity	79
8.36	Direct PT initiated link establishment	79
8.36.1	Exceptional case	80
8.36.1.1	Link establishment failure	80
8.37	Link release "normal"	80
8.37.1	Associated procedure	82
8.37.1.1	Timer <LCE.01> management	82
8.37.2	Exceptional cases	82
8.37.2.1	Timer <LCE.01> expiry	82
8.37.2.2	Outstanding data has been discarded	82
8.38	Link release "abnormal"	83
8.39	Link release "maintain"	83
8.39.1	Associated procedure	83
8.39.1.1	Timer <LCE.02> management	83
8.40	Enhanced FT initiated U- plane connection	84
9	DLC layer procedures	84
9.1	Class A link establishment	84
9.1.1	Associated procedures	86
9.1.1.1	Timer P<DL.07> management	86
9.1.1.2	Re-transmission counter management	86
9.1.1.3	Multiple frame operation variables management	86
9.1.1.4	Lower Layer Management Entity (LLME) establishment of a MAC connection	86
9.1.2	Exceptional cases	87
9.1.2.1	Timer P<DL.07> expiry	87
9.1.2.2	Receipt of a request for link release	88
9.1.2.3	Receipt of an indication for a connection release	88
9.2	Class A Acknowledged Information transfer	88
9.2.1	Acknowledgement with an L_frame	88
9.2.2	Acknowledgement with a RR_frame	89
9.2.3	Class A acknowledged information transfer with segment reassemble	90
9.2.4	Associated procedures	90
9.2.4.1	Timer <DL.04> management	90
9.2.4.2	Re-transmission counter management	90
9.2.4.3	Multiple frame operation variables management	90
9.2.5	Exceptional cases	91
9.2.5.1	Timer <DL.04> expiry	91
9.2.5.2	Receipt of a request for link release	91
9.2.5.3	Receipt of an indication for a connection release	91
9.2.5.4	DLC wants to make a connection handover	91
9.3	Class A link release	91
9.3.1	Associated procedures	92
9.3.1.1	LLME U-plane release	92
9.3.1.2	LLME release a MAC connection	92
9.4	Class A link re-establishment	92
9.5	C _s channel fragmentation and recombination	92
9.6	Normal broadcast	92
9.7	Class A basic connection handover	93
9.7.1	Voluntary handover	94
9.7.2	Associated procedure	94
9.7.2.1	LLME connection handover management	94
9.7.3	Exceptional case	94
9.7.3.1	Receipt of a request for link release	94
9.8	Encryption switching	94
9.8.1	Associated procedure	95
9.8.1.1	Providing Encryption key to the MAC layer	95
9.8.2	Exceptional cases	95
9.8.2.1	Encryption fails	95
9.8.2.2	Connection handover of ciphered connections	95
9.9	U-plane class 0/min delay	95
9.9.1	Associated procedure	95

9.9.1.1	LLME U-plane establishment	95
9.10	FU1 frame operation	96
10	MAC layer procedures	96
10.1	General	96
10.2	Downlink broadcast.....	97
10.2.1	N _T message	97
10.2.2	Q _T - static system information	97
10.2.3	Q _T - FP capabilities.....	98
10.2.4	Q _T - SARI list contents.....	98
10.3	Paging broadcast	98
10.3.1	Short page, normal/extended paging.....	99
10.3.2	Zero page normal/extended paging.....	99
10.3.3	Blind slot information.....	99
10.3.4	Bearer handover information	100
10.4	Setup of basic connection, basic bearer setup (A-field)	100
10.4.1	M _T message.....	101
10.4.2	Associated procedures	101
10.4.2.1	Timer T200 management	101
10.4.2.2	Counter N200 management.....	101
10.4.3	Exceptional cases	102
10.4.3.1	Bearer setup attempt fails N200+1 times	102
10.4.3.2	Timer T200 expiry	103
10.5	Connection/bearer release	103
10.5.1	M _T message.....	104
10.6	Bearer handover request.....	104
10.6.1	M _T message.....	104
10.7	Connection handover request.....	104
10.7.1	M _T message.....	105
10.8	C _S channel data.....	105
10.9	Q2 bit setting	105
10.10	RFPI handshake.....	105
10.11	Antenna diversity.....	105
10.12	Sliding collision.....	105
10.13	Encryption process - initialization and synchronization.....	105
10.14	Encryption mode control	106
10.14.1	M _T message.....	106
10.15	Handover encryption process	106
10.16	Extended frequency allocation	106
11	PHL layer requirements.....	107
11.1	General	107
11.2	Minimum Normal Transmit Power (NTP)	107
11.3	Radio receiver sensitivity	107
11.4	Z-field.....	107
11.5	Sliding collision detection	107
11.6	Physical channel availability	107
11.7	Synchronization window	107
12	Requirements regarding the speech transmission.....	108
12.1	General	108
12.2	User controlled volume control	108
13	Management procedures.....	108
13.1	Management of MM procedures	108
13.2	Location registration initiation	108
13.3	Assigned individual TPUI management.....	108
13.4	PMID management.....	109
13.5	DCK management	109
13.6	Broadcast attributes management.....	109
13.7	Storage of subscription related data	109
14	Application procedures.....	110
14.1	Subscription control	110

14.2	AC to bitstring mapping	110
14.3	Manual entry of the PARK.....	111
Annex A (informative):	PP locking procedure for on-air subscription.....	112
Annex B (informative):	Tones, progress indicator and U-plane connection.....	114
B.1	General	114
B.2	Connection of U-plane and provision of tones.....	114
B.3	Provision of tones before connection of the U-plane	114
B.4	Provision of tones and <<Progress indicator>> information element.....	114
B.5	Summary	115
Annex C (normative):	Synchronization requirements for fixed parts	116
Annex D (informative):	Bibliography.....	117
History		118

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 444 V1.4.2:2003](https://standards.iteh.ai/catalog/standards/sist/7a18bf27-75c9-472b-ba59-b78d41de6335/sist-en-300-444-v1-4-2-2003)

<https://standards.iteh.ai/catalog/standards/sist/7a18bf27-75c9-472b-ba59-b78d41de6335/sist-en-300-444-v1-4-2-2003>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

All published ETSI deliverables shall include information which directs the reader to the above source of information.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Project Digital Enhanced Cordless Telecommunications (DECT).

The present document is based on EN 300 175, parts 1 [1] to 8 [8]. General attachment requirements and speech attachment requirements are based on EN 301 406 [11] (replacing TBR 006) and EN 300 176-2 [10] (previously covered by TBR 010).

The present document has been developed in accordance to the rules of documenting a profile specification as described in ISO/IEC 9646-6 [12].

National transposition dates	
Date of latest announcement of this EN (doa):	May 2003
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	August 2003
Date of withdrawal of any conflicting National Standard (dow):	August 2003

1 Scope

The present document specifies that set of technical requirements for Digital Enhanced Cordless Telecommunications (DECT) Fixed Part (FP) and DECT Portable Part (PP) necessary for the support of the Generic Access Profile (GAP).

The GAP is applicable to all DECT Portable radio Terminations (PT) and Fixed radio Terminations (FT) which under the scope of EN 300 176-2 [10] (i.e. 3,1 kHz telephony teleservice) and specifies the minimum functionality that is supported by all other 3,1 kHz voice profiles.

The objective of the present document is to ensure the Air Interface (AI) inter-operability of DECT equipment capable of 3,1 kHz telephony applications, in such a way that any DECT PT conforming to the procedures described in the present document is inter-operable with any DECT FT conforming to the procedures described in the present document.

The profile consists of the minimum mandatory requirements that allow a 3,1 kHz teleservice connection to be established, maintained and released between a FT and a PT with the appropriate access rights, irrespective of whether the FP provides residential, business or public access services.

In addition, the present document defines the features, services, procedures etc. for both the FT and the PT, which are provision mandatory either in the PT or in the FT, as well as some elements that are provision optional but still process mandatory.

Mobility Management (MM) procedures at the DECT AI to support incoming calls and outgoing calls are included.

Inter-working between the FT and the attached network is outside the scope of the present document.

2 References

ITeH STANDARD PREVIEW
(standards.iteh.ai)

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

[SIST EN 300 444 V1.4.2:2003](https://standards.iteh.ai/catalog/standards/sist/7a18b27-75e9-472b-ba59-678d41dc6335/sist-en-300-444-v1-4-2-2003)

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

- [1] ETSI EN 300 175-1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [2] ETSI EN 300 175-2: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical layer (PHL)".
- [3] ETSI EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [4] ETSI EN 300 175-4: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer".
- [5] ETSI EN 300 175-5: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer".
- [6] ETSI EN 300 175-6: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and addressing".
- [7] ETSI EN 300 175-7: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 7: Security features".

- [8] ETSI EN 300 175-8: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 8: Speech coding and transmission".
- [9] ETSI EN 300 176-1: "Digital Enhanced Cordless Telecommunications (DECT); Approval test specification; Part 1: Radio".
- [10] ETSI EN 300 176-2: "Digital Enhanced Cordless Telecommunications (DECT); Approval test specification; Part 2: Speech".
- [11] ETSI EN 301 406: "Digital Enhanced Cordless Telecommunications (DECT); Harmonized EN for Digital Enhanced Cordless Telecommunications (DECT) covering essential requirements under article 3.2 of the R&TTE Directive; Generic radio".
- [12] ISO/IEC 9646-6: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 6: Protocol profile test specification".
- [13] ISO/IEC 9646-7: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".
- [14] ISO/IEC 8073 (1997): "Information technology - Open Systems Interconnection - Protocol for providing the connection-mode transport service".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

attach: process whereby a PP within the coverage area of a FP to which it has access rights, notifies this FP that it is operative

NOTE 1: The reverse process is detach, which reports the PP as inoperative.

NOTE 2: An operative PP is assumed to be ready to receive calls.

authentication: process whereby a DECT subscriber is positively verified to be a legitimate user of a particular FP

NOTE: Authentication is generally performed at call setup, but may also be done at any other time (e.g. during a call).

bearer service: type of telecommunication service that provides a defined capability for the transmission of signals between user-network interfaces

NOTE: The DECT user-network interface corresponds to the top of the Network (NWK) layer (layer 3).

C-plane: control plane of the DECT protocol stacks, which contains all of the internal DECT protocol control, but may also include some external user information

NOTE: The C-plane stack always contains protocol entities up to and including the NWK layer.

call: all of the NWK layer processes involved in one NWK layer peer-to-peer association

NOTE: Call may sometimes be used to refer to processes of all layers, since lower layer processes are implicitly required.

DECT network: network that uses the DECT AI to interconnect a local network to one or more portable applications. The logical boundaries of the DECT network are defined to be at the top of the DECT NWK layer.

NOTE: A DECT network is a logical grouping that contains one or more FTs plus their associated PT. The boundaries of the DECT network are not physical boundaries.

Fixed Part (DECT Fixed Part) (FP): physical grouping that contains all of the elements in the DECT network between the local network and the DECT AI

NOTE: A DECT FP contains the logical elements of at least one FT, plus additional implementation specific elements.

Fixed radio Termination (FT): logical group of functions that contains all of the DECT processes and procedures on the fixed side of the DECT AI

NOTE: A FT only includes elements that are defined in the DECT Common Interface (CI) standard. This includes radio transmission elements together with a selection of layer 2 and layer 3 elements.

geographically unique identity: related to FP identities, PARIs and RFPIs, it indicates that two systems with the same PARI, or respectively two RFPs with the same RFPI, cannot be reached or listened to at the same geographical position

NOTE: For PARI and RFPI, see abbreviations.

global network: telecommunication network capable of offering a long distance telecommunication service

NOTE: The term does not include legal or regulatory aspects, nor does it indicate if the network is a public or a private network.

globally unique identity: identity is unique within DECT (without geographical or other restrictions)

handover: process of switching a call in progress from one physical channel to another physical channel

NOTE: There are two physical forms of handover, intra-cell handover and inter-cell handover.

incoming call: call received at a PP

inter-cell handover: switching of a call in progress from one cell to another cell

internal handover: handover processes that are completely internal to one FT

Internal handover reconnects the call at the lower layers, while maintaining the call at the NWK layer

NOTE: The lower layer reconnection can either be at the Data Link Control (DLC) layer (connection handover) or at the Medium Access Control (MAC) layer (bearer handover)

inter-operability: capability of FPs and PPs, that enable a PP to obtain access to teleservices in more than one Location Area (LA) and/or from more than one operator (more than one service provider)

inter-operator roaming: roaming between FP coverage areas of different operators (different service providers)

InterWorking Unit (IWU): unit that is used to interconnect sub networks

NOTE: The IWU will contain the interworking functions necessary to support the required sub-network interworking.

intra-cell handover: switching of a call in progress from one physical channel of one cell to another physical channel of the same cell

intra-operator roaming: roaming between different FP coverage areas of the same operator (same service provider)

Local Network (LNW): telecommunication network capable of offering local telecommunication services

NOTE: The term does not include legal or regulatory aspects, nor does it indicate if the network is a public network or a private network.

locally unique identity: unique identity within one FP or LA, depending on application

Location Area (LA): domain in which a PP may receive (and/or make) calls as a result of a single location registration

location registration: process whereby the position of a DECT PT is determined to the level of one LA, and this position is updated in one or more databases

NOTE: These databases are not included within a DECT FT.

MAC connection (connection): association between one source MAC Multiple Bearer Control (MBC) entity and one destination MAC MBC entity

NOTE: This provides a set of related MAC services (a set of logical channels), and it can involve one or more underlying MAC bearers.

outgoing call: call originating from a PP

Portable Application (PA): logical grouping that contains all the elements that lie beyond the DECT network boundary on the portable side

NOTE: The functions contained in the PA may be physically distributed, but any such distribution is invisible to the DECT network.

Portable Part (DECT Portable Part) (PP): physical grouping that contains all elements between the user and the DECT AI

NOTE 1: PP is a generic term that may describe one or several physical pieces.

NOTE 2: A DECT PP is logically divided into one PT plus one or more PAs.

Portable radio Termination (PT): logical group of functions that contains all of the DECT processes and procedures on the portable side of the DECT AI

NOTE: A PT only includes elements that are defined in the DECT CI standard. This includes radio transmission elements (layer 1) together with a selection of layer 2 and layer 3 elements.

Radio Fixed Part (RFP): one physical sub-group of a FP that contains all the radio end points (one or more) that are connected to a single system of antennas

registration: ambiguous term that should always be qualified. See either location registration or subscription registration

roaming: movement of a PP from one FP coverage area to another FP coverage area, where the capabilities of the FPs enable the PP to make or receive calls in both areas

NOTE: Roaming requires the relevant FPs and PP to be inter-operable.

RS: value used to establish authentication session keys

subscription registration: infrequent process whereby a subscriber obtains access rights to one or more FPs

NOTE: Subscription registration is usually required before a user can make or receive calls.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

M	mandatory to support (provision mandatory, process mandatory)
O	optional to support (provision optional, process mandatory)
I	out-of-scope (provision optional, process optional) not subject for testing
C	conditional to support (process mandatory)
N/A	not applicable (in the given context the specification makes it impossible to use this capability)

Provision mandatory, process mandatory means that the indicated feature service or procedure shall be implemented as described in the present document, and may be subject to testing.

Provision optional, process mandatory means that the indicated feature, service or procedure may be implemented, and if implemented, the feature, service or procedure shall be implemented as described in the present document, and may be subject to testing.

NOTE: The used notation is based on the notation proposed in ISO/IEC 9646-7 [13].