

INTERNATIONAL STANDARD

NORME INTERNATIONALE

AC motor capacitors –
Part 2: Motor start capacitors

ITeH STANDARD PREVIEW
(standards.iteh.ai)

Condensateurs des moteurs à courant alternatif –
Partie 2: Condensateurs de démarrage de moteurs

IEC 60252-2:2010
<https://standards.iteh.ai/catalog/standards/sist/60252-2-2010-a77d-4baa-8fd4-43e6f5ec0d50/iec-60252-2-2010>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch

Tel.: +41 22 919 02 11

Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

- Just Published CEI: www.iec.ch/online_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

- Electropedia: www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

- Service Clients: www.iec.ch/webstore/custserv/custserv_entry-f.htm

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch

Tél.: +41 22 919 02 11

Fax: +41 22 919 03 00



IEC 60252-2

Edition 2.0 2010-12

INTERNATIONAL STANDARD

NORME INTERNATIONALE

AC motor capacitors –
Part 2: Motor start capacitors

Condensateurs des moteurs à courant alternatif –
Partie 2: Condensateurs de démarrage de moteurs

STANDARD PREVIEW
(standards.iteh.ai)

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX



ICS 31.060.30; 31.060.70

ISBN 978-2-88912-293-6

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references.....	6
3 Terms and definitions.....	7
4 Service conditions	10
4.1 Normal service conditions	10
4.2 Preferred tolerances on capacitance	10
5 Self-healing motor start capacitors	10
5.1 Quality requirements and tests	10
5.1.1 Test requirements	10
5.1.2 Nature of tests	11
5.1.3 Type tests	11
5.1.4 Routine tests	13
5.1.5 Tangent of the loss-angle measurement	13
5.1.6 Visual examination	13
5.1.7 Voltage test between the terminals	14
5.1.8 Voltage test between terminals and case	14
5.1.9 Capacitance measurement.....	14
5.1.10 Check of dimensions	14
5.1.11 Mechanical tests	15
5.1.12 Sealing test	17
5.1.13 Endurance test	17
5.1.14 Damp heat test	19
5.1.15 Self-healing test.....	19
5.1.16 Destruction test.....	19
5.1.17 Resistance to heat, fire and tracking	22
5.2 Overloads	23
5.2.1 Maximum permissible voltage.....	23
5.2.2 Maximum permissible current.....	23
5.2.3 Maximum permissible reactive output.....	23
5.3 Safety requirements	23
5.3.1 Creepage distances and clearances.....	23
5.3.2 Terminals and connecting cables.....	24
5.3.3 Earth connections	24
5.3.4 Discharge devices.....	25
5.3.5 Pollution.....	25
5.4 Marking.....	25
6 Electrolytic motor start capacitors.....	26
6.1 Quality requirements and tests	26
6.1.1 Test requirements	26
6.1.2 Nature of tests	26
6.1.3 Type tests	27
6.1.4 Routine tests	29
6.1.5 Visual examination	29
6.1.6 Voltage test between the terminals	29
6.1.7 Voltage test between terminals and case	29

6.1.8	Capacitance and power factor measurement.....	30
6.1.9	Check of dimensions	31
6.1.10	Mechanical tests	31
6.1.11	Sealing test	33
6.1.12	Endurance test	33
6.1.13	Damp heat test	35
6.1.14	Pressure relief test.....	35
6.1.15	Resistance to heat, fire and tracking	36
6.2	Overloads	36
6.2.1	Maximum permissible voltage.....	36
6.2.2	Maximum permissible current.....	36
6.2.3	Maximum permissible reactive output.....	37
6.3	Safety requirements	37
6.3.1	Creepage distances and clearances.....	37
6.3.2	Terminals and connecting cables.....	37
6.3.3	Earth connections	37
6.3.4	Discharge devices.....	38
6.3.5	Pollution.....	38
6.4	Marking.....	38
7	Guidance for installation and operation	39
7.1	General.....	39
7.2	Choice of rated voltage.....	39
7.2.1	Measurement of working voltage.....	39
7.2.2	Influence of capacitance.....	40
7.3	Checking capacitor temperature.....	40
7.3.1	Choice of maximum permissible capacitor operating temperature.....	40
7.3.2	Choice of minimum permissible capacitor operating temperature.....	40
7.4	Checking transients.....	40
7.5	Storage of electrolytic capacitors	41
Annex A (normative)	Test voltage.....	42
Figure 1	– Test apparatus for d.c. conditioning	20
Figure 2	– Test apparatus for a.c. destruction test	20
Figure 3	– Arrangement to produce the variable inductor L in Figure 2.....	21
Figure 4	– Test circuit for measurement of capacitance and power factor	30
Table 1	– Type test schedule.....	12
Table 2	– Test voltages.....	14
Table 3	– Torque.....	15
Table 4	– Minimum creepage distances and clearances	25
Table 5	– Type test schedule.....	28
Table 6	– Test voltages.....	29
Table 7	– Torque.....	32
Table 8	– Minimum creepage distances and clearances	38

INTERNATIONAL ELECTROTECHNICAL COMMISSION

AC MOTOR CAPACITORS –**Part 2: Motor start capacitors**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60252-2 has been prepared by IEC technical committee 33: Power capacitors and their applications.

This second edition cancels and replaces the first edition of IEC 60252-2, published in 2003, and constitutes a technical revision.

The main changes with respect to the previous edition are listed below:

- definition of segmented film capacitors;
- clearer definition of the purpose of d.c. conditioning in destruction test.

The text of this standard is based on the following documents:

FDIS	Report on voting
33/476/FDIS	33/480/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 60252 series, published under the general title *AC motor capacitors*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[IEC 60252-2:2010](https://standards.iteh.ai/catalog/standards/sist/62b27af3-a77d-4baa-8fd4-43e6f5ec0d50/iec-60252-2-2010)

<https://standards.iteh.ai/catalog/standards/sist/62b27af3-a77d-4baa-8fd4-43e6f5ec0d50/iec-60252-2-2010>

AC MOTOR CAPACITORS –

Part 2: Motor start capacitors

1 Scope

This part of IEC 60252 applies to motor start capacitors intended for connection to windings of asynchronous motors supplied from a single-phase system having the frequency of the mains.

This standard covers impregnated or unimpregnated metallized motor start capacitors having a dielectric of paper or plastic film, or a combination of both and electrolytic motor start capacitors with non-solid electrolyte, with rated voltages up to and including 660 V.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60062, *Marking codes for resistors and capacitors*

IEC 60068-2 (all parts), *Environmental testing – Part 2: Tests*

IEC 60068-2-6, *Environmental testing – Part 2-6: Tests – Test Fc: Vibration (sinusoidal)*

IEC 60068-2-14, *Environmental testing – Part 2-14: Tests – Test N: Change of temperature*

IEC 60068-2-20, *Environmental testing – Part 2-20: Tests – Test T: Soldering*

IEC 60068-2-21, *Environmental testing – Part 2-21: Tests – Test U: Robustness of terminations and integral mounting devices*

IEC 60068-2-78:2001, *Environmental testing – Part 2-78: Tests – Test Cab: Damp heat, steady state*

IEC 60112, *Method for determining the comparative and the proof tracking indices of solid insulating materials under moist conditions*

IEC 60309-1:1999, *Plugs, socket-outlets and couplers for industrial purposes – Part 1: General requirements*

IEC 60529, *Degrees of protection provided by enclosures (IP Code)*

IEC 60695-2-10:2000, *Fire hazard testing – Part 2-10: Glowing/hot-wire based test methods – Glow-wire apparatus and common test procedure*

IEC 60695-2-11:2000, *Fire hazard testing – Part 2-11: Glowing/hot-wire based test methods – Glow-wire flammability test method for end-products*

ISO 4046, *Paper, board, pulps and related terms – Vocabulary*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

motor running capacitor

power capacitor which, when used in conjunction with an auxiliary winding of a motor, assists the motor to start and improves the torque under running conditions

NOTE The running capacitor is usually connected permanently to the motor winding and remains in circuit throughout the running period of the motor. During the starting period, if it is in parallel with the starting capacitor, it helps to start the motor.

3.2

motor starting capacitor

power capacitor which provides a leading current to an auxiliary winding of a motor and which is switched out of circuit once the motor is running

3.3

metal foil capacitor

capacitor, whose electrodes consist of metal foils or strips separated by a dielectric

3.4

metallized capacitor

capacitor, in which the electrodes consist of a metallic deposit on the dielectric

3.5

self-healing capacitor

capacitor, whose electrical properties, after local breakdown of the dielectric, are rapidly and essentially self-restored

3.6

segmented film capacitor

metallised capacitor with a repeating pattern on the metallic deposit on at least one layer, designed to isolate sections of the capacitor in the event of localised faults occurring in the dielectric

3.7

discharge device of a capacitor

device which may be incorporated in a capacitor, capable of reducing the voltage between the terminals effectively to zero, within a given time, after the capacitor has been disconnected from a network

3.8

continuous operation

operation with no time limit within the normal life of the capacitor

3.9

intermittent operation

operation in which periods with the capacitor energized are followed by intervals during which the capacitor is unenergized

3.10

starting operation

special type of intermittent operation in which the capacitor is energized for only a very short period while the motor is accelerating to rated speed

3.11**rated duty cycle**

rated value indicating the rate of intermittent or starting duty for which a capacitor is suitable

NOTE It is specified by the duty cycle duration, in minutes, and the percentage of the time during which the capacitor is energized.

3.12**duty cycle duration**

total time of one energized and one unenergized interval during the intermittent operation

3.13**relative operation time**

percentage of the cycle duration in which the capacitor is energized

3.14**capacitor for continuous and starting operation**

capacitor designed to operate at one voltage when in continuous operation and at a different (usually higher) voltage when in starting operation

3.15**minimum permissible capacitor operating temperature**

minimum permissible temperature on the outside of the case at the moment of switching on the capacitor

iTeh STANDARD PREVIEW

3.16**maximum permissible capacitor operating temperature**

t_c

maximum permissible temperature of the hottest area of the outside of the capacitor case during operation

<https://standards.iteh.ai/catalog/standards/sist/62b27af3-a77d-4baa-8fd4-43e6f5ec0d50/iec-60252-2-2010>

3.17**rated voltage of a capacitor**

U_N

r.m.s. value of the alternating voltage for which the capacitor has been designed

3.18**maximum voltage**

maximum r.m.s. voltage permissible at the starting capacitor terminals between the point of starting and the instant at which the capacitor is disconnected

3.19**rated frequency of a capacitor**

f_N

highest frequency for which the capacitor has been designed

3.20**rated capacitance of a capacitor**

C_N

capacitance value for which the capacitor has been designed

3.21**rated current of a capacitor**

I_N

r.m.s. value of the alternating current at the rated voltage and frequency

3.22 rated output of a capacitor

Q_N
reactive power derived from the rated values of capacitance, frequency and voltage (or current)

3.23 capacitor losses

active power dissipated by a capacitor

NOTE Unless otherwise stated, the capacitor losses will be understood to include losses in fuses and discharge resistors forming an integral part of the capacitor.

3.24 tangent of loss angle (tan delta) of a capacitor

ratio between the equivalent series resistance and the capacitive reactance of a capacitor at specified sinusoidal alternating voltage and frequency

3.25 power factor

ratio between the active power and the apparent power of a capacitor

3.26 capacitive leakage current (only for capacitors with a metal case)

current flowing through a conductor connecting the metallic case to earth, when the capacitor is energized from an a.c. supply system with an earthed neutral

3.27 type of capacitor

capacitors are considered to be of the same type when of similar constructional form, the same constructional technology, same rated voltage, same climatic category and same kind of operation

NOTE 1 Capacitors of the same type can differ only in rated capacitance and size; minor differences between terminations and mounting devices are permitted.

NOTE 2 The same construction includes, for example, the same dielectric material, dielectric thickness and type of case (metal or plastic).

3.28 model of capacitor

capacitors are considered to be of the same model when they are of the same construction and have the same functional and dimensional characteristics within the tolerance limits and are consequently interchangeable

3.29 class of safety protection

degree of safety protection identified by one of three codes to be marked on the capacitor

(P2) indicates that the capacitor type has been designed to fail in the open-circuit mode only and is protected against fire or shock hazard. Compliance is verified by the test described in 5.1.16

(P1) indicates that the capacitor type may fail in the open-circuit or short-circuit mode and is protected against fire or shock hazard. Compliance is verified by the test described in 5.1.16

(P0) indicates that the capacitor type has no specific failure protection

This subclause does not apply to electrolytic capacitors.

4 Service conditions

4.1 Normal service conditions

This standard gives requirements for capacitors intended for use under the following conditions:

- a) altitude: not exceeding 2 000 m;
- b) residual voltage at energization: shall not exceed 10 % rated voltage (see notes to 5.3.4 and 6.3.4);
- c) pollution: capacitors included in the scope of this standard are designed for operation in lightly polluted atmospheres;

NOTE The IEC has not yet established a definition for "lightly polluted". When this definition is established by the IEC, it will be incorporated in this standard.

- d) operating temperature: between $-40\text{ }^{\circ}\text{C}$ and $+100\text{ }^{\circ}\text{C}$ (see 3.15 and 3.16).

The preferred minimum and maximum permissible capacitor operating temperatures are as follows:

- minimum temperatures: $-40\text{ }^{\circ}\text{C}$, $-25\text{ }^{\circ}\text{C}$, $-10\text{ }^{\circ}\text{C}$ and $0\text{ }^{\circ}\text{C}$;
- maximum temperatures: $55\text{ }^{\circ}\text{C}$, $70\text{ }^{\circ}\text{C}$, $85\text{ }^{\circ}\text{C}$ and $100\text{ }^{\circ}\text{C}$.

Capacitors shall be suitable for transport and storage at temperatures down to $-25\text{ }^{\circ}\text{C}$, or the minimum operating temperature, whichever is the lower, without adverse effect on their quality;

- e) damp heat severity: between 4 days and 56 days. The preferred severity is 21 days.

(The damp heat severity shall be selected from the values indicated by IEC 60068-2-78, i.e.: 4 days, 10 days, 21 days and 56 days.)

Capacitors are classified in climatic categories defined by the minimum and maximum permissible capacitor operating temperatures and damp heat severity: i.e. 10/70/21 indicates that the minimum and the maximum permissible capacitor operating temperatures are $-10\text{ }^{\circ}\text{C}$ and $70\text{ }^{\circ}\text{C}$ and the damp heat severity is 21 days.

4.2 Preferred tolerances on capacitance

Preferred tolerances are as follows: $\pm 5\%$, $\pm 10\%$ and $\pm 15\%$.

Asymmetric tolerances are permitted but no tolerance shall exceed 15 %.

5 Self-healing motor start capacitors

5.1 Quality requirements and tests

5.1.1 Test requirements

5.1.1.1 General

This clause gives the test requirements for self-healing motor start capacitors.

5.1.1.2 Test conditions

Unless otherwise specified for a particular test or measurement, the temperature of the capacitor dielectric shall be in the range $+15\text{ }^{\circ}\text{C}$ to $+35\text{ }^{\circ}\text{C}$ and shall be recorded.

If corrections are necessary, the reference temperature shall be $+20\text{ }^{\circ}\text{C}$.

NOTE It may be assumed that the dielectric temperature is the same as the ambient temperature, provided that the capacitor has been left in an unenergized state at this ambient temperature for an adequate period, depending on the size of the capacitor.

5.1.2 Nature of tests

The tests specified are of two sorts:

- a) type tests;
- b) routine tests.

5.1.2.1 Type tests

Type tests are intended to prove the soundness of the design of the capacitor and its suitability for operation under the conditions detailed in this standard.

Type tests are carried out by the manufacturer and/or the test authority if there is need for an approval.

These tests may be carried out under the supervision of a proper authority which will issue a certified record and/or type approval.

5.1.2.2 Routine tests

Routine tests shall be carried out by the manufacturer on every capacitor before delivery.

5.1.3 Type tests

5.1.3.1 Test procedure

The samples of each model selected for the type tests shall be divided into groups, as indicated in Table 1.

Capacitors forming the sample shall have successfully passed the routine tests indicated in 5.1.4.

Each test group shall contain equal numbers of capacitors of the highest capacitance and the lowest capacitance in the range.

The manufacturer shall provide data on the ratio of capacitance per outer total surface area of the case of each capacitance value in the range.

The capacitor with the maximum capacitance per unit surface area shall also be tested if this ratio exceeds that of the maximum capacitance value in the range by 10 % or more.

Similarly, the capacitor with the minimum capacitance per unit area shall also be tested if the ratio is less than that of the minimum capacitance value in the range by 10 % or more.

“Area” denotes total outer surface area of the capacitor case with the exception of small protrusions, terminals and fixing studs.

5.1.3.2 Extent of qualification

5.1.3.2.1 A type test on a single model qualifies only the model tested. When the type test is performed on two models of the same type but of different rated capacitance value, selected under the rules of 5.1.3.1, the qualification is valid for all models of the same type having rated capacitance between the two tested values.

5.1.3.2.2 The qualification tests carried out successfully on a capacitor model having a certain capacitance tolerance are valid also for capacitors of the same model but having a different capacitance tolerance of up to twice the limits of the declared tolerance. For example, ±5 % would cover up to ±10 %, and ±10 % would cover up to ±20 %. A smaller tolerance than the declared tolerance is not permitted. For example, a type approval for ±10 % would not cover ±5 %.

5.1.3.2.3 Occasionally, in current practice, capacitors are required with a capacitance tolerance that is not symmetrical with respect to the rated capacitance value.

When a type test is carried out successfully on a capacitor model having a symmetrical capacitance tolerance, the relevant qualification is valid also for capacitors of the same model having a non-symmetrical capacitance provided that the total range of non-symmetrical tolerance is

- a) within the total range of capacitance allowed in 5.1.3.2.2,
- and
- b) greater than, or equal to, that of the tested capacitor model. For example, qualification for ±5 would allow values such as $+10\%$, $+5\%$, $+8\%$, $+10\%$ but not $+15\%$.

Table 1 – Type test schedule

Group	Tests	Subclause	Number of samples to be inspected a	Number of failures allowed in first test b	Number of failures allowed in retest
1	Visual examination Check markings Check of dimensions Mechanical tests (excluding soldering) Sealing tests (if applicable)	5.1.6 5.4 5.1.10 5.1.11 5.1.12	8 [4]	1 ^c	0
2	Endurance test	5.1.13	42 [21]	2 ^d	0
3	Soldering (if applicable) Damp heat test Voltage test between terminals Voltage test between terminals and case	5.1.11.2 5.1.14 5.1.7 5.1.8	12 [6]	1 ^c	0
4	Self-healing test (if applicable)	5.1.15	20 [10]	1 ^c	0
5	Destruction test (if marked on the capacitor)	5.1.16	20 [10] 10 [5]	1 ^e	0
6	Resistance to heat, fire and tracking (not applicable to capacitors with lead terminations)	5.1.17	3 (terminal housing only) ^f	0	0

Table 1 (continued)

a	The number of samples specified allows for retest if required. The number in square brackets indicates the actual number required for the test. All numbers indicate the sample quantity for each capacitance value tested. If a range is tested, then the quantity indicated in the table will apply to both the highest capacitance, lowest capacitance and any other intermediate value required to be tested in the range according to 5.1.3.1.
b	A capacitor which fails on more than one test is counted as one defective capacitor.
c	For groups 1, 3 and 4 a retest is allowed with 1 failure. No failures are allowed in these retests.
d	For group 2, no retest is required with 1 failure. With two failures a retest is required, with no more failures allowed.
e	For group 5, see 5.1.16 which allows a retest under special conditions in the event of one failure.
f	Three samples of terminal housing (parts of insulating material retaining terminals in position) are needed for the tests described in 5.1.17. One sample is required for the ball-pressure test (5.1.17.1), one for the glow-wire test (5.1.17.2) and one for the tracking test (5.1.17.3).

When the number of defects for each group and the total number of defective capacitors do not exceed the figures indicated in Table 1, the capacitor model shall be deemed to comply with this standard.

When a capacitor is designed to operate under two or more different conditions (rated voltages, classes, rated duty cycles, etc.), the following tests shall be performed, once only, at the highest test voltage:

- i) voltage test between terminals (see 5.1.7);
- ii) voltage test between terminals and case (see 5.1.8);
- iii) self-healing test (see 5.1.15).

The endurance test shall be performed for every voltage rating and under every operating condition marked on the capacitor. The number of samples to be inspected shall be calculated accordingly.

5.1.4 Routine tests

5.1.4.1 Test procedure

Capacitors shall be subjected to the following tests in the stated order:

- a) sealing test, if applicable (see 5.1.12);
- b) voltage test between terminals (see 5.1.7);
- c) voltage test between terminals and case (see 5.1.8);
- d) visual examination (see 5.1.6);
- e) capacitance measurement (see 5.1.9);
- f) tangent of loss angle (see 5.1.5).

5.1.5 Tangent of the loss-angle measurement

The tangent of the loss-angle limit and the measuring frequency shall be defined by the manufacturer.

5.1.6 Visual examination

The condition, workmanship, marking and finish shall be satisfactory. The marking shall be legible during the life of the capacitor.

There shall be no seepage of any filling material or other visible damage.