

# SLOVENSKI STANDARD SIST EN 1185:1998

01-november-1998

Škrob in škrobni derivati - Določevanje žveplovega dioksida - Acidimetrijska metoda (ISO 5379:1983, spremenjen)

Starches and derived products - Determination of sulfur dioxide content - Acidimetric method (ISO 5379:1983 modified)

Stärken und Stärkederivate - Bestimmung des Schwefeldioxidgehaltes - Acidimetrisches Verfahren (ISO 5379:1983 modifiziert) DARD PREVIEW

(standards.iteh.ai)
Amidons, fécules et produits dérivés - Détermination de la teneur en dioxyde de soufre - Dosage acidimétrique (ISO 5379:1983 modifiée)

https://standards.iteh.ai/catalog/standards/sist/a89332b7-e706-40cc-90d5-

Ta slovenski standard je istoveten z: 75a09753debb/sist-en-1185-1998

ICS:

67.180.20 Škrob in izdelki iz njega Starch and derived products

SIST EN 1185:1998 en

SIST EN 1185:1998

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 1185:1998

https://standards.iteh.ai/catalog/standards/sist/a89332b7-e706-40cc-90d5-75a09753debb/sist-en-1185-1998

**EUROPEAN STANDARD** 

EN 1185

NORME EUROPÉENNE

**EUROPÄISCHE NORM** 

November 1994

TCS 67, 180, 20

Descriptors:

Carbohydrates, starches, food starch, tests, determination of content, sulfur dioxide

English version

Starches and derived products - Determination of sulfur dioxide content - Acidimetric method (ISO 5379:1983 modified)

Amidons, fécules et produits dérivés Détermination de la teneur en dioxyde de soufre Dosage acidimétrique (ISO 5379:1983 modifiée)

Stärken und Stärkederivate - Bestimmung des Schwefeldioxidgehaltes - Acidimetrisches Verfahren (ISO 5379:1983 modifiziert)

(standards.iteh.ai)

<u>SIST EN 1185:1998</u> https://standards.iteh.ai/catalog/standards/sist/a89332b7-e706-40cc-90d5-75a09753debb/sist-en-1185-1998

This European Standard was approved by CEN on 1994-11-10. CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

The European Standards exist in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

# CEN

European Committee for Standardization Comité Européen de Normalisation Europäisches Komitee für Normung

Central Secretariat: rue de Stassart, 36 B-1050 Brussels

Page 2 EN 1185:1994

#### Foreword

The text of the International Standard ISO 5379:1983, prepared by ISO/TC 93 "Starch (including derivatives and by-products)", was submitted to Formal Vote and was approved by CEN as EN 1185 with a common modification.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by May 1995, and conflicting national standards shall be withdrawn at the latest by May 1995.

According to the CEN/CENELEC Internal Regulations, the following countries are bound to implement this European Standard: Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, United Kingdom.

## **Endorsement notice**

The text of the International Standard ISO 5379:1983 was approved by CEN as a European Standard with agreed common modification as given below:

Common modification:

(standards.iteh.ai)

The nephelometric method has been deleted.

SIST EN 1185:1998

https://standards.iteh.ai/catalog/standards/sist/a89332b7-e706-40cc-90d5-75a09753debb/sist-en-1185-1998

Page 3 EN 1185:1994

# 1 Scope

This European Standard specifies a method for the determination of the sulfur dioxide content of starches and derived products.

#### 2 Normative references

ISO 1227, Starch, including derivatives and by-products – Vocabulary.

ISO 5725, Precision of test methods - Determination of repeatability and reproducibility for a standard test method by inter-laboratory tests.

## 3 Principle

https://standards.iteh.ai/catalog/standards/sist

SIST EN 1185:199

Entrainment in a current of nitrogen of the sulfur dioxidebexistentracted from the acidified and heated product, and fixing and oxidation of the sulfur dioxide by bubbling through a dilute solution of neutral hydrogen peroxide. Titration of the sulfuric acid formed with standard volumetric sodium hydroxide solution

# 4 Acidimetric method

## 4.1 Reagents

All reagents shall be of recognized analytical quality and sulfate free. The water shall be distilled water or water of at least equivalent purity, recently boiled.

#### 4.1.1 Nitrogen, oxygen-free.

**4.1.2** Hydrogen peroxide, solution containing approximately 9 to 10 g of H<sub>2</sub>O<sub>2</sub> per litre.

Place 150 ml of 20 volumes hydrogen peroxide solution or 30 ml of 30 % (m/m) (110 volumes) hydrogen peroxide solu-

tion in a 1 000 ml one-mark volumetric flask. Dilute to the mark with water.

NOTE - This solution should be freshly prepared.

#### 4.1.3 Hydrochloric acid.

Place 150 ml of concentrated hydrochloric acid, ( $\varrho_{20}=1,19~\mathrm{g/ml}$ ) in a 1 000 ml one-mark volumetric flask. Dilute to the mark with water.

# 4.1.4 Bromophenol blue indicator solution.

Dissolve 100 mg of bromophenol blue [ $\alpha$ ,  $\alpha$ -bis(3,5-dibromo-4-hydroxyphenyl) toluene-2, $\alpha$ -sultone] in 100 ml of 20 % (V/V) ethanol.

4.1.532 Tashiro indicator solution.

Dissolve 30 mg of methyl red [2-[[4-(dimethylamino)phenyl]-azo] benzoic acid] and 50 mg of methylene blue [3,7-bis(dimethylamino)phenothiazin-5-ium chloride] in 120 ml of 90 % (V/V) ethanol. Dilute to 200 ml with water, mix and filter.

NOTE — The Tashiro indicator (4.1.5) can only be used with the titrimetric method (4.3.4). The bromophenol blue indicator (4.1.4) is appropriate for the titrimetric method and does not hinder the further use of the nephelometric method (see clause 5). Nevertheless, with this indicator, it is more difficult to detect the end-point.

**4.1.6** Sodium hydroxide, standard volumetric solution,  $c(NaOH) = 0.1 \text{ mol/l}^{1}$ ; or

**4.1.7** Sodium hydroxide, standard volumetric solution, c(NaOH) = 0.01 mol/1.2)

In order to obtain a sharp end-point, prepare this solution using carbon dioxide-free water obtained by cooling boiled distilled water under a flow of nitrogen.

 $\mathsf{NOTE}$  — The use of solution (4.1.6) is recommended and a piston-burette is useful for small volumes. If necessary, increase the mass of the test portion.

<sup>1)</sup> Hitherto designated as "0,1 N standard volumetric solution".

<sup>2)</sup> Hitherto designated as "0,01 N standard volumetric solution".

Page 4 EN 1185:1994

**4.1.8 lodine**, standard volumetric solution,  $c(l_2) = 0.01 \text{ mol/l.}^{1)}$ 

4.1.9 Starch, 5 g/l solution.

Dissolve 0,5 g of Lintner starch (see ISO 1227) or similar in 100 ml of water. Heat to boiling while stirring. Add 20 g of sodium chloride, stir and boil until dissolution is complete. Allow to cool to ambient temperature before use.

4.1.10 Potassium disulfite and ethylenediaminetetraacetic acid (EDTA), disodium salt.<sup>2)</sup>

Dissolve in water 0,87 g of potassium disulfite  $(K_2S_2O_5)$  and 0,20 g of disodium dihydrogen ethylenediaminetetraacetate  $(Na_2H_2edta)$ . Transfer the solution quantitatively to a 1 000 ml one-mark volumetric flask. Dilute to the mark with water and mix.

# 4.2 Apparatus

Glass apparatus should preferably be fitted with ground glass joints.

4.2.7.1 Composition of apparatus

A: round-bottom flask, of capacity 250 ml or greater, with a ground tubulure allowing the introduction of a thermometer.

B: vertical condenser of high efficiency, to fit the flask (A).

C: separating funnel, fitted to the flask (A).

D: nitrogen inlet with an absorber containing an alkaline solution of pyrogallol.

E and E': 2 bubblers in series, connected to the condenser (B).

F: thermometer.

NOTE — Between two determinations, if the entrainment is sufficiently slow and moderate, only flask (A) need be cleaned.

**4.2.7.2** Check tests

The apparatus shall satisfy the following requirements:

Ordinary laboratory apparatus, and in particular TANDARD DREVIEW

4.2.7.2.1 Place in the flask (A) 100 ml of water and proceed as complying with the requirements of ISO 1042, class AII and specified in 4.3.3.

The contents of the bubblers shall remain neutral.

- **4.2.3 Semi-microburette**, of capacity 10 ml, complying with the requirements of ISO 385/2, class A.
- **4.2.4** Burettes, of capacities 25 and 50 ml, complying with the requirements of ISO 385/2, class A.
- 4.2.5 Analytical balance.
- **4.2.6 Magnetic stirrer**, efficient, with heating, for use with the flask (A) (see 4.2.7.1).
- **4.2.7** Entrainment apparatus, as shown in the figure<sup>3)</sup> or equivalent equipment for ensuring the displacement and entrainment of sulfur dioxide and its absorption in a solution of hydrogen peroxide.

NOTE — Avoid making connections with tubes between the condenser and the bubblers as this could lead to absorption of sulfur dioxide.

- a) Place in the flask (A) 100 ml of water. Introduce, using a pipette, 20 ml of the solution (4.1.10). Carry out the entrainment and the determination of sulfur dioxide as specified in 4.3.3 and 4.3.4.
- b) Transfer, using a pipette, 20 ml of the iodine solution (4.1.8), 5 ml of the hydrochloric acid (4.1.3) and 1 ml of the starch solution (4.1.9) into a 100 ml conical flask (4.1).

Titrate, using a burette (4.2.4), with the solution (4.1.10) until the first coloration is discharged.

The difference between the sulfur dioxide contents determined in a) and b) shall not exceed 1 % of their arithmetic mean.

Operation b) shall not be carried out more than 15 min after completion of operation a) in order to avoid a possible change in the amount of sulfur dioxide contained in the potassium disulfite/Na<sub>2</sub>H<sub>2</sub>edta solution.

<sup>1)</sup> Hitherto designated as "0,02 N standard volumetric solution".

<sup>2)</sup> This product is intended to protect the sulfite ion from oxidation by air by complexing traces of copper ion.

<sup>3)</sup> Apparatus of the Lieb and Zaccherl type.

Page 5 EN 1185:1994

#### 4.3 Procedure

## 4.3.1 Preparation of test sample

Thoroughly mix the laboratory sample.

#### 4.3.2 Test portion

Weigh, to the nearest 0,01 g, a mass of the test sample (see 4.3.1) as specified in the following table.

Expected sulfur dioxide content mg/kg	Approximate mass of test portion
< 50	100
50 to 200	50

This quantity may be increased, in particular in the case of D-glucose.

If the expected content is greater than 200 mg/kg, reduce the test portion accordingly so that it does not contain more than 10 mg of sulfur dioxide and transfer it quantitatively to the flask (A). In the case of certain derived products, the mass of the test portion can be determined by difference by weighing of the container. Add 100 ml of water to the test portion!) and mix well by shaking.

# 4.3.3 Entrainment

https://standards.iteh.ai/catalog/standards/sist/a85
4.3.3.1 Place in the funnel (C) 50 ml of the/hydrochloric acid-en-1185

(4.1.3).

**4.3.3.2** In each of the bubblers (E and E'), place, by means of a pipette, 3 ml of the hydrogen peroxide solution (4.1.2), 0,1 ml of the bromophenol blue indicator solution (4.1.4) (see the note to 4.1.5) and neutralize the hydrogen peroxide solution with the sodium hydroxide solution (4.1.7).

**4.3.3.3** Connect the condenser (B) and the bubblers (E and E') to the apparatus, and slowly pass a current of nitrogen to expel the air from the whole equipment. Start the flow of water to the condenser.

**4.3.3.4** Allow the hydrochloric acid contained in the funnel (C) to flow into the flask (A) (if necessary interrupt the flow of nitrogen for a moment).

**4.3.3.5** Bring the mixture to boiling point in 30 min. Boil for 30 min, while passing a current of nitrogen and stirring with the stirrer (4.2.6).

#### 4.3.4 Titration

Add quantitatively the content of the second bubbler to the content of the first bubbler, and titrate the sulfuric acid formed with the sodium hydroxide solution (4.1.6 or 4.1.7) depending on the expected sulfur dioxide content.

NOTE — If the end point is not sharp, owing to the presence of volatile organic acids, boil for 2 min and cool to room temperature before titrating.

#### 4.3.5 Check

If the volume V is less than 5 ml when the 0,01 mol/l sodium hydroxide solution is used, or less than 0,5 ml when the 0,1 mol/l sodium hydroxide solution is used, carry out the determination by the nephelometric method.

#### 4.3.6 Number of determinations

Carry out two determinations on the same test sample (4.3.1).

# 4.4 Expression of results

# 4.4.1 Method of calculation and formulae

If determination by the nephelometric method is not necessary SIST EN 1185:19d see 4.3.5), the sulfur dioxide content, expressed in milligrams along tandards (cist/aper kilogram of sample, is given by the formula

$$\frac{0,320\ 3\times V\times 1\ 000}{m_0}=\frac{320,3\times V}{m_0}$$

where

 $m_0$  is the mass, in grams, of the test portion (4.3.2);

V is the volume, in millilitres, of 0,01 mol/l (4.1.7) or 10 times the volume of 0,1 mol/l (4.1.6) sodium hydroxide solution used.

Take as the result the arithmetic mean of the values obtained in the two determinations (4.3.6), provided that the requirement for repeatability (see 4.4.2) is satisfied.

# 4.4.2 Repeatability<sup>2)</sup>

The absolute difference between the results of two determinations carried out simultaneously or in rapid succession by the same analyst on the same test sample shall not exceed 5 % of the mean value of the two determinations.

<sup>1)</sup> In the case of a test portion of more than 100 g (for example D-glucose), the quantity of water added should be equal to that of the test portion.

<sup>2)</sup> See ISO 5725.

Page 6 EN 1185:1994

# 4.4.3 Reproducibility<sup>1)</sup>

The difference between the results of two determinations carried out in different laboratories on the same test sample shall not exceed 10 % of the mean value of the two determinations.

# 5 Test report

The test report shall show the method used and the result obtained, clearly indicating the method of expression used. It shall also mention any operating conditions not specified in this European Standard or regarded as optional, together with any circumstances that may have influenced the results.

The test report shall contain all the details required for the complete identification of the sample.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 1185:1998</u> https://standards.iteh.ai/catalog/standards/sist/a89332b7-e706-40cc-90d5-75a09753debb/sist-en-1185-1998

<sup>&</sup>lt;sup>1</sup> See ISO 5725