

TECHNICAL REPORT

Information technology – **STANDARD PREVIEW**
Part 372: Fibre channel methodologies for interconnects-2 (FC-MI-2)
(standards.iteh.ai)

[ISO/IEC TR 14165-372:2011](#)

<https://standards.iteh.ai/catalog/standards/sist/16935caf-ded0-4cb7-8f07-9a6bb7dc2836/iso-iec-tr-14165-372-2011>





THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2011 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/customerservice

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00



ISO/IEC TR 14165-372

Edition 1.0 2011-02

TECHNICAL REPORT

Information technology – **STANDARD PREVIEW**
Part 372: Fibre channel methodologies for interconnects-2 (FC-MI-2)
(standards.iteh.ai)

[ISO/IEC TR 14165-372:2011](https://standards.iteh.ai/catalog/standards/sist/16935caf-ded0-4cb7-8f07-9a6bb7dc2836/iso-iec-tr-14165-372-2011)
<https://standards.iteh.ai/catalog/standards/sist/16935caf-ded0-4cb7-8f07-9a6bb7dc2836/iso-iec-tr-14165-372-2011>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE



ICS 35.200

ISBN 978-2-88912-342-1

CONTENTS

FOREWORD		5
INTRODUCTION		7
1 Scope		8
2 Normative references		8
3 Terms, definitions, abbreviations and other conventions		9
3.1 Overview		9
3.2 Terms and definitions		9
3.3 Editorial conventions		14
3.4 Abbreviations and acronyms		15
3.5 Symbols		16
3.6 Keywords		16
3.7 Applicability and use of this Technical Report		18
3.8 Feature Set table terms, definitions, and abbreviations		18
3.8.1 Overview		18
3.8.2 Feature Set table terms and definitions		19
3.8.3 Feature Set table abbreviations		19
3.9 Feature testing compliance		20
3.10 Timing Constraints		20
4 Structure and concepts		21
	iTeh STANDARD PREVIEW	
	(standards.iteh.ai)	
5 Loop behaviors		21
5.1 Loop Initialization		21
5.1.1 Power On Behavior	ISO/IEC TR 14165-372:2011	21
5.1.2 Loop Failure	https://standards.iteh.ai/catalog/standards/sist/16935caf-ded0-4cb7-8f07-9a6bb7dc2836/iso-iec-tr-14165-372-2011	21
5.1.3 Initialization at Power-on	9a6bb7dc2836/iso-iec-tr-14165-372-2011	22
5.1.4 FL_Port Time-out during Initialization		22
5.1.5 LIP Generation		22
5.1.6 Response to LIP		22
5.1.7 Origination of LISM Frames		22
5.1.8 Forwarding of LISM frames		22
5.1.9 Address Selection		23
5.1.10 Multi-port Initialization		23
5.1.11 AL_PA Position Map Support		23
5.1.12 Availability after LIP		23
5.2 Post Initialization		24
5.2.1 LIP Generation		24
5.2.2 FL_Port Unfair behavior and Transfer behavior		24
5.2.3 Responses to OPN		24
5.2.4 No response to OPN		25
6 Fx_Port Behaviors		26
6.1 Fx_Port Login responses		26
6.1.1 FLOGI ACC features and parameters for Fx_Ports		26
6.1.2 Nx_Port PLOGI		26
6.1.3 Fx_Port Common Service Parameters (FLOGI ACC)		27
6.1.4 Fx_Port Class 2 Service Parameters (FLOGI ACC)		29

6.1.5 Fx_Port Class 3 Service Parameters (FLOGI ACC)	30
6.2 Link Services	32
6.2.1 Basic Link Services	32
6.2.2 ELS requirements for well-known addresses	32
6.2.3 Extended Link Service Replies	32
6.3 FC-AL-2 features for FL_Ports	33
6.4 Loop Fabric Address	35
7 Fabric Behaviors	36
7.1 Overview	36
7.2 Switch-to-Switch Requirements	37
7.2.1 Overview	37
7.2.2 Switch Port Types	40
7.2.3 Exchange Link Parameters (ELP)	40
7.2.4 Principal Switch Selection	42
7.2.5 Fabric Shortest Path First (FSPF)	42
7.2.6 Distributed Services	43
7.2.7 Zoning	48
7.2.8 Distributed Event Notification	50
7.2.9 Additional Switch Requirements	50
7.3 Fabric Service Requirements	51
7.3.1 Overview	51
7.3.2 Name Server	51
7.3.3 Fabric Configuration Server	55
7.3.4 Fabric Zone Server	56
7.3.5 Registered State Change Notification	58
7.4 Domain Controller and Well-Known Addresses	60
7.4.1 Domain controller and well-known address support requirements for fabrics	60
7.4.2 N_Port domain controller and well-known address usage	61
7.4.3 Domain controller and well-known address (WKA) ELS login and address assignment requirements	63
https://standards.iteh.ai/catalog/standards/sist/16935caf-ded0-4cb7-8f07-9a6bb7dc2836/iso-iec-tr-14165-372-2011	
8 Discovery and Management	67
8.1 Overview	67
8.2 Management of Interconnect Components	67
8.2.1 Overview	67
8.2.2 Switch	67
8.2.3 Managed Hub	68
8.2.4 Gateway/Bridge	68
9 Conformance Environments	69
Bibliography	70

Tables

Table 1 ISO/IEC and American Conventions 15

Table 2 Feature Set table terms and definitions 19

Table 3 Feature Set table key abbreviations 19

Table 4 Feature testing compliance relationship to definitions 20

Table 5 FLOGI ACC features and parameters for Fx_Ports 26

Table 6 Fx_Port Common Service Parameters (FLOGI ACC) 27

Table 7 Class 2 Service Parameters (FLOGI ACC) 29

Table 8 Class 3 Service Parameters (FLOGI ACC) 30

Table 9 Extended Link Service Replies 32

Table 10 FC-AL features for FL_Ports 33

Table 11 FC-SW-3 Fabric Support Summary 37

Table 12 Switch Port Type Usage 40

Table 13 ELP SW_ILS Parameters 40

Table 14 Flow Control Parameters 42

Table 15 FC-SW-3 Defined Name Server Requests 43

Table 16 FC-GS-4 Defined Name Server Requests 43

Table 17 FC-GS-4 Common Requests 45

Table 18 Name Server Object Usage Summary 46

Table 19 FC-SW-3 Defined Management Server Requests 46

Table 20 FC-GS-4 Defined Management Server Requests 47

Table 21 Zoning Support 48

Table 22 FC-GS-4 Fabric Support 51

Table 23 Name Server Request Support 51

Table 24 Common Request Support 53

Table 25 Fabric Configuration Server Request Support 55

Table 26 Fabric Zone Server Basic Zoning Request Support 56

Table 27 Fabric Zone Server Enhanced Zoning Request Support 57

Table 28 Domain Controller and Well-Known Address Support Requirements for Fabrics 60

Table 29 ELS requirements for domain controller and well-known addresses 61

Table 30 Broadcast WKA (FFFFFFh) ELS login requirements 63

Table 31 Fabric F_Port WKA (FFFFFFEh) ELS address assignment requirements 64

Table 32 Fabric Controller WKA (FFFFFFDh) ELS login requirements 65

Table 33 Directory Service WKA (FFFFFFCh) ELS login requirements 65

Table 34 Management Service WKA (FFFFFFAh) ELS login requirements 66

Table 35 Domain Controller (FFFCxxh) ELS login requirements 66

Table 36 Loop Fabric Address ELS login requirements 67

Table 37 Switch Support Summary 67

Table 38 Conformance Environments 69

INFORMATION TECHNOLOGY – FIBRE CHANNEL –

Part 372: Fibre channel methodologies for interconnects-2 (FC-MI-2)

FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 10) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 14165-372, which is a technical report, has been prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 14165 series, under the general title *Information technology – Fibre Channel*, can be found on the IEC web site.

This Technical Report has been approved by vote of the member bodies and the voting results may be obtained from the address given on the second title page.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC TR 14165-372:2011](https://standards.iteh.ai/catalog/standards/sist/16935caf-ded0-4cb7-8f07-9a6bb7dc2836/iso-iec-tr-14165-372-2011)

<https://standards.iteh.ai/catalog/standards/sist/16935caf-ded0-4cb7-8f07-9a6bb7dc2836/iso-iec-tr-14165-372-2011>

INTRODUCTION

This technical report specifies common methodologies for both Arbitrated Loop and Switched environments. The goal of this technical report is to facilitate interoperability between devices whether they are connected in a loop or Fabric topology.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC TR 14165-372:2011](https://standards.iteh.ai/catalog/standards/sist/16935caf-ded0-4cb7-8f07-9a6bb7dc2836/iso-iec-tr-14165-372-2011)

<https://standards.iteh.ai/catalog/standards/sist/16935caf-ded0-4cb7-8f07-9a6bb7dc2836/iso-iec-tr-14165-372-2011>

INFORMATION TECHNOLOGY – FIBRE CHANNEL –

Part 372: Fibre channel methodologies for interconnects-2 (FC-MI-2)

1 Scope

This part of ISO/IEC 14165 is intended to document interoperability behavior for Fabric elements (i.e., E_Port, F_Port, FL_Port). This Technical Report includes a wide range of issues such as link initialization, error detection, error recovery, Fabric operation, management capabilities, and zoning.

This Technical Report serves as an implementation guide, whose primary objective is to maximize the likelihood of interoperability between conforming implementations. This Technical Report prohibits or requires some features that are in the referenced documents.

A second objective of this Technical Report is to simplify implementations and their associated documentation, testing, and support requirements. As a result there may be some optional features of the referenced documents that are not mutually exclusive, but are prohibited or required for the purpose of this simplification. Features that some but not all of the referenced documents require for compliance may be optional in this report. Each specification of such an optional feature in this report identifies the referenced document for which the feature is required.

Internal characteristics of conformant implementations are not defined by this Technical Report, but it incorporates features from the documents cited in clause 2.

2 Normative references iTeh STANDARD PREVIEW

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the of the referenced document (including any amendments) applies.

<https://standards.iteh.ai/catalog/standards/sist/16935caf-ded0-4cb7-8f07-9ab0716c2850/iso-iec-tr-14165-372-2011>

The provision of the referenced specification other than ISO/IEC, IEC, ISO and ITU documents, as identified in this clause, are valid within the context of this Technical Report. The reference of such a specification within this Technical Report does not give it any further status within ISO/IEC. In particular, it does not give the referenced specification the status of an International Standard.

ISO/IEC 14165-115, *Information technology – Fibre channel – Part 115: Physical Interfaces (FC-PI)*²

ISO/IEC 14165-122, *Information technology – Fibre Channel – Part 122: Arbitrated loop-2 (FC-AL-2)*³

ISO/IEC 14165-133, *Information technology – Fibre channel – Part 133: Fibre Channel Switch Fabric-3 (FC-SW-3)*⁴

T11/Project 1620D, *Fibre Channel - Link Services (FC-LS)*⁵

INCITS TR-36-2003, *Fibre Channel - Device Attach (FC-DA)*⁶

2. ANSI INCITS 352-2002, *Fibre Channel - Physical Interfaces (FC-PI)*

3. ANSI INCITS 332-1999, *Fibre Channel - Arbitrated Loop (FC-AL-2)*

4. ANSI INCITS 384-2004, *Fibre Channel - Switch Fabric - 3 (FC-SW-3)*

5. ISO/IEC 14165-261, *Information technology – Fibre Channel – Part 261: Link services (FC-LS)*
(under consideration)

6. ISO/IEC 14165-341, *Information technology – Fibre Channel – Part 341: Device attach (FC-DA)*
(under consideration)

ISO/IEC 14165-414, Information technology – Fibre Channel – Part 414: Generic services-4 (FC-GS-4) ⁷
ISO/IEC 14165-431, *Information technology – Fibre Channel – Part 431: Security Protocols (FC-SP)*
(to be published) ⁸

Internet Engineering Task Force RFC 791, Internet Protocol, September 1981

Internet Engineering Task Force RFC 2373, IP Version 6 Addressing Architecture, July 1998

Internet Engineering Task Force RFC 2460, Internet Protocol, Version 6 (IPv6) Specification, December 1998

Internet Engineering Task Force RFC 3410, Introduction and Applicability Statements for Internet Standard Management Framework, December 2002

Internet Engineering Task Force RFC 4044, Fibre Channel Management MIB, May 2005

3 Terms, definitions, abbreviations and other conventions

3.1 Overview

For the purpose of this document the following definitions, conventions, abbreviations, acronyms, and symbols apply.

3.2 Terms and definitions

3.2.1

address identifier

address value used to identify source (S_ID) or destination (D_ID) of a frame

3.2.2

AL_PA bit map

bit map that shows which ports are present on an Arbitrated Loop

NOTE See FC-AL-2.

[ISO/IEC TR 14165-372:2011](https://standards.iteh.ai/catalog/standards/sist/16935caf-ded0-4cb7-8f07-9a6bb7dc2836/iso-iec-tr-14165-372-2011)

[https://standards.iteh.ai/catalog/standards/sist/16935caf-ded0-4cb7-8f07-](https://standards.iteh.ai/catalog/standards/sist/16935caf-ded0-4cb7-8f07-9a6bb7dc2836/iso-iec-tr-14165-372-2011)

[9a6bb7dc2836/iso-iec-tr-14165-372-2011](https://standards.iteh.ai/catalog/standards/sist/16935caf-ded0-4cb7-8f07-9a6bb7dc2836/iso-iec-tr-14165-372-2011)

3.2.3

AL_PA position map

map that shows port ordering on an Arbitrated Loop

NOTE See FC-AL-2.

3.2.4

Arbitrated Loop time out value

AL_Time

time interval defined by FC-AL-2

3.2.5

Application

entity that makes requests of a Service

3.2.6

Arbitrated Loop Physical Address

AL_PA

one-byte address value

NOTE See FC-AL-2.

7. ANSI INCITS 387-2004, *Fibre Channel - Generic Services - 4 (FC-GS-4)*

8. T11/Project 1570D, *Fibre Channel - Security Protocols (FC-SP)*

3.2.7**ARO**

special AR (see 3.2.9) containing only the switch backbone network, that in general may consist of point-to-point links, broadcast links, and switching devices

NOTE See FC-AL-2.

3.2.8**Area Identifier**

second or middle level of the three-level addressing hierarchy, found in bits 15 through 8 of an address identifier

NOTE (see 3.2.1) and FC-SW-3.

3.2.9**Autonomous Region****AR**

one or more Fibre Channel address domains consisting of switches that all run a common routing protocol

NOTE See FC-SW-3.

3.2.10**B_Port**

Interconnect_Port used to connect bridge devices with E_Ports on a switch

NOTE See FC-SW-3.

3.2.11**Domain Identifier**

highest level of the three-level addressing hierarchy, found in bits 23 through 16 of an address identifier (see 3.2.1)

NOTE See FC-SW-3.

3.2.12**E_Port**

Fabric Expansion port that attaches to another Interconnect_Port to create an Inter-Switch Link

NOTE See FC-SW-3.

3.2.13**Entry Switch**

role that a switch assumes with respect to a distributed service request

NOTE The switch that is attached to an Nx_Port making a service request assumes the role of an entry switch with respect to that request. See FC-SW-3.

3.2.14**Error_Detect_Timeout value****E_D_TOV**

time interval defined in FC-FS-2

3.2.15**F_Port**

port through which non-loop N_Ports are attached to a Fabric, and it does not include FL_Ports

3.2.16**Fabric**

Fibre Channel frame transport infrastructure that includes switches and interconnects various Nx_Ports attached to it

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC TR 14165-372:2011
<https://standards.iteh.ai/catalog/standards/sist/16935ca1-dcd0-4cb7-8107-9a6bb7dc2836/iso-iec-tr-14165-372-2011>

3.2.17**Fabric F_Port**

entity at the well-known address FFFFFFFEh

NOTE See FC-SW-3.

3.2.18**Fabric_Name**

identifier associated with a Fibre Channel Fabric

NOTE See FC-FS-2.

3.2.19**Fabric Shortest Path First****FSPF**

link state protocol used for Path Selection

NOTE See FC-SW-3.

3.2.20**FC_Port**

port transmitting or receiving Fibre Channel frames

NOTE FC_Port includes any port type defined in the Fibre Channel family of standards (e.g., N_Port, F_Port, FL_Port, E_Port).

3.2.21**FL_Port**

L_Port that is able to perform the function of an F_Port, attached via a link to one or more NL_Ports in an Arbitrated Loop topology (see FC-AL -2)

NOTE The AL_PA of an FL_Port is 00h. In this Technical Report, an FL_Port is assumed to always refer to a port to which NL_Ports are attached to a Fabric; it does not include F_Ports.

3.2.22**Fx_Port**

Switch Port (see 3.2.52) capable of operating as an F_Port or FL_Port

[ISO/IEC TR 14165-372:2011](https://standards.iteh.ai/catalog/standards/sist/16935caf-ded0-4cb7-8f07-9a6bb7dc2836/iso-iec-tr-14165-372-2011)

3.2.23**Gateway/Bridge**

any device that interfaces FC to some other interface (see FC-FS-2)

NOTE The definition of such a device is outside the scope of this report.

3.2.24**Hub**

interconnect element used with Arbitrated Loops

NOTE A Hub may be a stand-alone enclosure, or part of an integrated system (e.g., such as the connection point within a JBOD). Typically a Hub is transparent to any connected Fibre Channel devices.

3.2.25**Interconnect_Port**

E_Port or a B_Port

3.2.26**Loop Fabric Address****LFA**

address identifier used to address an FL_Port (see FC-SW-3) for the purpose of loop management

NOTE See 6.4 and FC-LS.

3.2.27**L_Port**

port that contains Arbitrated Loop functions associated with the Arbitrated Loop topology

NOTE See FC-AL-2.

3.2.28

Managed Hub

Hub (see 3.2.24) that provides either in-band or out-of-band management functions

3.2.29

Name Server

Server (see 3.2.48) that allows registration and reporting of various objects

NOTE See FC-GS-4.

3.2.30

N_Port

direct Fabric-attached port that does not include NL_Ports

NOTE See FC-FS-2.

3.2.31

N_Port Identifier

1 Fabric unique address identifier by which an N_Port is known

NOTE The identifier is used in the S_ID and D_ID fields of a frame (see FC-FS-2).

2 Name Server object (see FC-GS-4) containing the Fibre Channel address identifier assigned to an N_Port or NL_Port

3.2.32

NL_Port

L_Port that is able to perform the function of an N_Port, attached to one or more NL_Ports and zero or more FL_Ports in an Arbitrated Loop topology

NOTE In this technical report, an NL_Port is assumed to always refer to a loop-attached port including both Private NL_Ports and Public NL_Ports, and does not include N_Ports.

3.2.33

Node_Name

identifier associated with a Fibre Channel node

NOTE See FC-FS-2.

[ISO/IEC TR 14165-372:2011](https://www.iso.org/obp/ui/#iso:code:372:14165-372:2011)

<https://www.iso.org/obp/ui/#iso:code:372:14165-372:2011>

3.2.34

Non-Participating mode

operational mode of an L_Port that does not have an AL_PA, but is enabled into the Loop

NOTE See FC-AL-2.

3.2.35

Nx_Port

port operating as an N_Port or NL_Port

3.2.36

OLD-PORT

state on a set of ports where two devices operate in a point-to-point mode utilizing FC-FS-2 protocols instead of FC-AL-2 protocols

NOTE See FC-AL-2 and FC-FS-2.

3.2.37

OPEN_INIT

state in the LPSM as defined in FC-AL-2

3.2.38**N_Port Name**

identifier associated with an FC_Port

NOTE See FC-FS-2.

3.2.39**Partial Response**

response from a Distributed Service that may not have a complete set of data

NOTE See FC-SW-3.

3.2.40**Participating mode**

operational mode of an L_Port that has an AL_PA and is enabled into the Loop

NOTE See FC-AL-2.

3.2.41**Platform**

association of one or more nodes for the purpose of discovery and management

3.2.42**Port**

N_Port, NL_Port, F_Port, FL_Port, B_Port, or E_Port, used in a context where the distinction between specific port types is clarified by other text or not significant

3.2.43**Port Identifier**

lowest level of the three-level addressing hierarchy, found in bits 7 through 0 of an address identifier (see 3.2.1)

NOTE See FC-SW-3.

3.2.44**Private NL_Port**

NL_Port that is observing the rules of private loop behavior

NOTE See FC-AL-2 and FC-DA.

3.2.45**Public NL_Port**

NL_Port that attempts a fabric login and may transfer frames through the FL_Port

NOTE A Public NL_Port observes the rules of public loop behavior and/or private loop behavior. See FC-AL-2 and FC-DA.

3.2.46**Receiver_Transmitter_Timeout value****R_T_TOV**

time interval defined in FC-FS-2

3.2.47**Resource_Allocation_Timeout value****R_A_TOV**

time interval defined in FC-FS-2

3.2.48**Server**

entity that accepts CT requests and provides CT responses

NOTE 1 A Server is accessed via a Service (e.g., the Name Server is accessed using the Directory Service).

NOTE 2 See FC-GS-4.