

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Maritime navigation and radiocommunication equipment and systems – Class B shipborne equipment of the automatic identification system (AIS) – Part 1: Carrier-sense time division multiple access (CSTDMA) techniques

Matériels et systèmes de navigation et de radiocommunication maritimes – Transpondeur embarqué du système d'identification automatique (AIS) de classe B – Partie 1: Technique d'accès multiple par répartition dans le temps avec écoute de porteuse (CSTDMA)



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 15 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

65 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Maritime navigation and radiocommunication equipment and systems – Class B shipborne equipment of the automatic identification system (AIS) – Part 1: Carrier-sense time division multiple access (CSTDMA) techniques

Matériels et systèmes de navigation et de radiocommunication maritimes – Transpondeur embarqué du système d'identification automatique (AIS) de classe B – Partie 1: Technique d'accès multiple par répartition dans le temps avec écoute de porteuse (CSTDMA)

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 47.020.70

ISBN 978-2-8322-3109-8

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	7
1 Scope.....	9
2 Normative references	9
3 Abbreviations	10
4 General requirements.....	11
4.1 General.....	11
4.1.1 Capabilities of the Class B“CS” AIS.....	11
4.1.2 Quality assurance.....	12
4.1.3 Safety of operation	12
4.1.4 Additional features.....	12
4.1.5 Modes of operation.....	12
4.2 Manuals	13
4.3 Marking and identification.....	13
5 Environmental, power supply, interference and safety requirements.....	13
6 Performance requirements	14
6.1 Composition	14
6.2 Operating frequency channels.....	14
6.3 GNSS receiver for position reporting	14
6.4 Identification.....	15
6.5 AIS information	15
6.5.1 Information content.....	15
6.5.2 Information reporting intervals.....	16
6.5.3 Permissible initialisation period.....	17
6.6 Alarms and indications, fall-back arrangements.....	17
6.6.1 Integrity and protection.....	17
6.6.2 Transmitter shutdown procedure.....	17
6.6.3 Position sensor fallback conditions	17
6.6.4 SOG/COG sensor fallback conditions	19
6.7 User interface.....	19
6.7.1 Indicators and display.....	19
6.7.2 Static data input	19
6.7.3 External interfaces.....	19
6.8 Protection from invalid control commands	19
7 Technical requirements	20
7.1 General.....	20
7.2 Physical layer.....	20
7.2.1 General	20
7.2.2 Transceiver characteristics.....	21
7.2.3 Transmitter requirements.....	22
7.2.4 Receiver requirements.....	22
7.3 Link layer	23
7.3.1 General	23
7.3.2 Link sublayer 1: Medium access control (MAC).....	23
7.3.3 Link sublayer 2: Data Link Service (DLS).....	26
7.3.4 Link sublayer 3: Link management entity (LME).....	30

7.4	Network layer	39
7.4.1	General	39
7.4.2	Dual channel operation	39
7.4.3	Channel management	40
7.4.4	Distribution of transmission packets	40
7.4.5	Data link congestion resolution	40
7.5	Transport layer	40
7.5.1	General	40
7.5.2	Transmission packets	41
7.5.3	Sequencing of data packets	41
7.6	Digital selective calling (DSC)	41
8	Test conditions	41
8.1	General	41
8.2	Normal and extreme test conditions	41
8.2.1	Normal test conditions	41
8.2.2	Extreme test conditions	41
8.3	Test signals	41
8.3.1	Standard test signal number 1	42
8.3.2	Standard test signal number 2	42
8.3.3	Standard test signal number 3	42
8.3.4	Standard test signal number 4	42
8.3.5	Standard test signal number 5	42
8.4	Test arrangements	43
8.4.1	Standard test environment	43
8.4.2	Modes of operation of the transmitter	44
8.4.3	Common test conditions for protection from invalid controls	44
8.4.4	Measurement uncertainties	44
9	Power supply, environmental and EMC tests	45
9.1	Test summary	45
9.2	Vibration/shock	46
9.2.1	Vibration	46
9.2.2	Shock	46
9.3	Performance tests/checks	46
9.4	Undervoltage test (brown out)	47
9.4.1	Purpose	47
9.4.2	Method of test	47
9.4.3	Required result	47
10	Operational tests	47
10.1	General	47
10.1.1	Quality assurance	47
10.1.2	Safety of operation	47
10.1.3	Additional features	47
10.2	Modes of operation	48
10.2.1	Autonomous mode	48
10.2.2	Assigned mode	49
10.2.3	Polled mode/interrogation response	50
10.3	Messages extending one time period	51
10.3.1	Method of measurement	51
10.3.2	Required results	51

10.4	Channel selection.....	51
10.4.1	Valid channels.....	51
10.4.2	Invalid channels.....	51
10.5	Internal GNSS receiver.....	51
10.6	AIS information.....	52
10.6.1	Information content.....	52
10.6.2	Information update rates.....	53
10.7	Initialisation period.....	54
10.7.1	Method of measurement.....	54
10.7.2	Required results.....	54
10.8	Alarms and indications, fall-back arrangements.....	54
10.8.1	Built-in integrity test.....	55
10.8.2	Transceiver protection.....	55
10.8.3	Transmitter shutdown procedure.....	55
10.8.4	Position sensor fallback conditions.....	55
10.8.5	Speed sensors.....	56
10.9	User interface.....	56
10.9.1	Display.....	56
10.9.2	Message display.....	56
10.9.3	Static data input.....	57
10.9.4	External interfaces.....	57
11	Physical tests.....	57
11.1	TDMA transmitter.....	57
11.1.1	Frequency error.....	57
11.1.2	Carrier power.....	58
11.1.3	Transmission spectrum.....	59
11.1.4	Modulation accuracy.....	60
11.1.5	Transmitter output power versus time function.....	61
11.2	TDMA receivers.....	62
11.2.1	Sensitivity.....	62
11.2.2	Error behaviour at high input levels.....	62
11.2.3	Co-channel rejection.....	63
11.2.4	Adjacent channel selectivity.....	64
11.2.5	Spurious response rejection.....	64
11.2.6	Intermodulation response rejection.....	67
11.2.7	Blocking or desensitisation.....	68
11.3	Conducted spurious emissions.....	69
11.3.1	Spurious emissions from the receiver.....	69
11.3.2	Spurious emissions from the transmitter.....	69
12	Specific tests of link layer.....	70
12.1	TDMA synchronisation.....	70
12.1.1	Synchronisation test sync mode 1.....	70
12.1.2	Synchronisation test sync mode 2.....	71
12.1.3	Synchronisation test with UTC.....	71
12.2	Carrier-sense tests.....	71
12.2.1	Threshold level.....	71
12.2.2	Carrier-sense timing.....	73
12.3	VDL state/reservations.....	74
12.3.1	Method of measurement.....	74

12.3.2	Required results	74
12.4	Data encoding (bit stuffing)	74
12.4.1	Method of measurement	74
12.4.2	Required results	74
12.5	Frame check sequence	74
12.5.1	Method of measurement	74
12.5.2	Required results	74
12.6	Slot allocation (channel access protocol)	74
12.6.1	Autonomous mode allocation	74
12.6.2	DSC listening periods	75
12.7	Assigned operation	75
12.7.1	Assignment priority	75
12.7.2	Entering rate assignment	75
12.7.3	Reverting from rate assignment	76
12.7.4	Reverting from quiet mode	76
12.7.5	Retry of interrogation response	76
12.8	Message formats	76
12.8.1	Received messages	76
12.8.2	Transmitted messages	77
13	Specific tests of network layer	77
13.1	Regional area designation by VDL message	77
13.1.1	Method of measurement	77
13.1.2	Required results	78
13.2	Regional area designation by serial message or manually	78
13.2.1	Method of measurement	78
13.2.2	Required result	78
13.3	Management of received regional operating settings	78
13.3.1	Replacement or erasure of dated or remote regional operating settings	78
13.3.2	Channel management by addressed Message 22	79
13.3.3	Invalid regional operating areas	79
13.3.4	Continuation of autonomous mode reporting rate	80
13.3.5	Other conditions	80
Annex A (informative)	Results of computer simulations and testing of CSTDMA technology	81
Annex B (informative)	Description of the system	84
Annex C (normative)	DSC channel management	85
Annex D (informative)	Channel management regions	92
Bibliography	93
Figure 1	– OSI layer model	20
Figure 2	– Carrier-Sense timing	24
Figure 3	– Power versus time mask	25
Figure 4	– Transmission packet	26
Figure 5	– Training sequence	28
Figure 6	– Transmission timing	30
Figure 7	– Example for CSTDMA access	31
Figure 8	– Format for repeating four-packet cluster	42

Figure 9 – Measurement arrangement for carrier power	58
Figure 10 – Emission mask	59
Figure 11 – Measurement arrangement for modulation accuracy.....	60
Figure 12 – Measurement arrangement.....	62
Figure 13 – Measurement arrangement with two generators	63
Figure 14 – SINAD or PER/BER measuring equipment	65
Figure 15 – Measurement arrangement for intermodulation.....	67
Figure 16 – Configuration for carrier-sense threshold test.....	72
Figure 17 – Regional area scenario	77
Figure A.1 – Effect on Class A AIS messages of Class B messages	81
Figure A.2 – Reception of messages by Class A AIS	82
Figure A.3 – Reception of messages by Class B AIS	82
Figure A.4 – Range achieved by a Class A AIS from Class B AIS	83
Figure D.1 – Channel management regions used for test given in 13.3.1	92
Table 1 – Position sensor fallback conditions.....	18
Table 2 – Use of accuracy (PA) flag.....	18
Table 3 – Transceiver characteristics.....	21
Table 4 – Transmitter parameters	22
Table 5 – Receiver parameters	23
Table 6 – Definition of timings for Figure 3.....	25
Table 7 – Start-buffer.....	27
Table 8 – Summary of the transmission packet	29
Table 9 – Transmission timing	29
Table 10 – Access parameters.....	31
Table 11 – Use of VDL messages by a Class B"CS" AIS.....	34
Table 12 – Number of data bits for use with Message 14	35
Table 13 – Contents of Message 18.....	36
Table 14 – Message 24 Part A.....	37
Table 15 – Message 24 Part B.....	37
Table 16 – Contents of Message 23.....	38
Table 17 – Reporting Interval Settings for use with Message 23	39
Table 18 – Channel management	40
Table 19 – Content of first two packets	42
Table 20 – Fixed PRS data derived from ITU-T.O.153	43
Table 21 – Test summary	45
Table 22 – Peak frequency deviation versus time	61
Table 23 – Frequencies for inter-modulation test	68
Table 24 – Required threshold test results.....	73
Table 25 – Required carrier-sense timing results	73
Table 26 – Required channels in use	78
Table C.1 – DSC monitoring times	86

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARITIME NAVIGATION AND RADIOCOMMUNICATION
EQUIPMENT AND SYSTEMS –
CLASS B SHIPBORNE EQUIPMENT OF
THE AUTOMATIC IDENTIFICATION SYSTEM (AIS) –****Part 1: Carrier-sense time division multiple access
(CSTDMA) techniques**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62287-1 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

This bilingual version (2016-01) corresponds to the English version, published in 2010-11.

This second edition cancels and replaces the first edition published in 2006, and constitutes a technical revision.

The major technical changes with respect to the first edition are the following. The reference to the relevant recommendation of the ITU has been updated from M.1371-1 to M.1371-4 with some consequential small changes. A previous option of providing short safety-related messages in 6.5.1.5 has been removed on advice from the IMO. A new requirement for a default MMSI has been added in 6.4 and a further new requirement for protection from invalid

control commands has been added in 6.8. Some test methods have been updated and, in particular, small revisions have been made to the frequencies used for testing in some of the test methods. The introduction has been deleted since it is only of historic interest.

Some editorial rearrangement has been made.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/605/FDIS	80/608/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The French version of this standard has not been voted upon.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 62287 series published under the general title *Maritime navigation and radiocommunication equipment and systems – Class B shipborne equipment of the automatic identification system (AIS)*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

**MARITIME NAVIGATION AND RADIOCOMMUNICATION
EQUIPMENT AND SYSTEMS –
CLASS B SHIPBORNE EQUIPMENT OF
THE AUTOMATIC IDENTIFICATION SYSTEM (AIS) –**

**Part 1: Carrier-sense time division multiple access
(CSTDMA) techniques**

1 Scope

This part of IEC 62287 specifies the minimum operational and performance requirements, methods of testing and required test results for Class B shipborne AIS equipment using CSTDMA techniques. This standard takes into account other associated IEC International Standards and existing national standards, as applicable.

It is applicable for AIS equipment used on craft that are not covered by the mandatory carriage requirement of AIS under SOLAS Chapter V.

An AIS station intended to operate in receive-only mode is not considered a Class B shipborne mobile AIS station.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945:2002, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61108 (all parts), *Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS)*

IEC 61162 (all parts), *Maritime navigation and radiocommunication equipment and systems – Digital interfaces*

IEC 61993-2, *Maritime navigation and radiocommunication equipment and systems – Automatic identification systems (AIS) – Part 2: Class A shipborne equipment of the universal automatic identification system (AIS) – Operational and performance requirements, methods of test and required test results*

IEC 62320-1, *Maritime navigation and radiocommunication equipment and systems – Automatic identification systems (AIS) – Part 1: AIS Base Stations – Minimum operational and performance requirements, methods of testing and required test results*

IMO MSC.140(76), *Recommendation for the protection of the AIS VHF data link*

ITU-R Recommendation M.493-13, *Digital selective-calling system for use in the maritime mobile service*

ITU-R Recommendation M.825-3, *Characteristics of a transponder system using digital selective calling techniques for use with vessel traffic services and ship-to-ship identification*

ITU-R Recommendation M.1084-4, *Interim solutions for improved efficiency in the use of the band 156-174 MHz by stations in the maritime mobile service*

ITU-R Recommendation M.1371-4, *Technical characteristics for a universal shipborne automatic identification system using time division multiple access in the VHF maritime mobile band*

ITU Radio Regulations, Appendix 18, <http://www.itu.int/publ/R-REG-RR/en>

3 Abbreviations

AIS	Automatic Identification System
BER	Bit Error Rate
BT	Bandwidth Time product
COG	Course Over Ground
CP	Candidate Period
CPU	Central Processing Unit
CRC	Cyclic Redundancy Check
CS	Carrier-Sense
CSTDMA	Carrier-Sense Time Division Multiple Access
DGNSS	Differential Global Navigation Satellite System
DLS	Data Link Service
DSC	Digital Selective Calling
ECDIS	Electronic Chart Display and Information System
EPFS	Electronic Position Fixing System
ETA	Estimated Time of Arrival
EUT	Equipment Under Test
FCS	Frame Check Sequence
FM	Frequency Modulation
GMSK	Gaussian Minimum Shift Keying
GNSS	Global Navigation Satellite System
HDG	Heading
HDLC	High level Data Link Control
HSC	High Speed Craft
IHO	International Hydrographic Office
IMO	International Maritime Organization
Lat	Latitude
LME	Link Management Entity
Lon	Longitude
LR	Long Range
MAC	Medium Access Control
MMSI	Maritime Mobile Service Identity
NM	Nautical Miles (1 NM = 1 852 m)
NRZI	Non Return to Zero Inverted
NTT	Nominal Transmission Time
NUC	Not Under Command

OSI	Open System Interconnection model
P_{ss}	Steady state RF output power
PER	Packet Error Rate
PI	Presentation Interface
PRS	Pseudo Random Sequence
RAIM	Receiver Autonomous Integrity Monitoring
RF	Radio Frequency
RI	Reporting Interval
Rx	Receive
SINAD	Signal Interference Noise and Distortion ratio
SOG	Speed Over Ground
SOLAS	International Convention for the Safety Of Life At Sea
TDMA	Time Division Multiple Access
TI	Transmission Interval
Tx	Transmit
UTC	Universal Time Co-ordinated
VDL	VHF Data Link
VHF	Very High Frequency
VSWR	Voltage Standing Wave Ratio
VTS	Vessel Traffic Services

NOTE Abbreviations related to the IEC 61162 series are not included in the above list. For their meaning refer to that standard.

4 General requirements

4.1 General

4.1.1 Capabilities of the Class B“CS” AIS

The Class B“CS” AIS shall improve the safety of navigation by assisting in the efficient navigation of ships and small craft, protection of the environment, and operation of Vessel Traffic Services (VTS). Small craft are vessels which are not required to comply with the mandatory carriage requirements of SOLAS Chapter V, Regulation 19.

The Class B“CS” AIS shall be capable of providing information from small craft, automatically, continuously and with the required accuracy and update rate:

- in a ship-to-ship mode for collision avoidance;
- as a means for littoral States to obtain information about the craft; and
- as a VTS tool, i.e. ship-to-shore (traffic management).

The Class B“CS” AIS station shall be inter-operable and compatible with Class A or other Class B shipborne mobile AIS stations or any other AIS station operating on the AIS VHF Data Link. In particular, Class B“CS” AIS stations shall receive other stations, shall be received by other stations and shall not degrade the integrity of the AIS VHF Data Link.

The Class B“CS” AIS shall only transmit if it has verified that the time period intended for transmission does not interfere with transmissions made by AIS equipment defined in ITU-R M.1371-4 A1/2 (excluding Class B“CS”). Transmissions of the Class B“CS” AIS shall not exceed one nominal time period (except when responding to a base station with Message 19).

4.1.2 Quality assurance

(see 10.1.1)

Manufacturers shall have a quality control system audited by a competent authority to ensure continuous compliance with the requirements of this standard. Alternatively, the manufacturer may use final product verification procedures where a competent authority verifies compliance with the requirements of this standard before the product is put to the market.

NOTE The ISO 9000 series, as applicable, meets the requirements of a quality control system.

4.1.3 Safety of operation

(see 10.1.2)

It shall not be possible for the operator to augment, amend or erase any program software in the equipment required for operation in accordance with the equipment standard. Data used during operation and stored in the system shall be protected in such a way, that necessary modifications and amendments by the user cannot affect its integrity and correctness.

4.1.4 Additional features

(see 10.1.3)

Where equipment provides a facility that is additional to the minimum requirements of this standard, the operation and, as far as is reasonably practicable, the malfunction of such an additional facility shall not degrade the performance of the equipment.

4.1.5 Modes of operation

4.1.5.1 General

The system shall be capable of operating in a number of modes as described below subject to the transmission of messages by a competent authority. It shall not retransmit received messages.

4.1.5.2 Autonomous and continuous mode

(see 10.2.1)

An "autonomous and continuous" mode for operation in all areas transmitting Message 18 for scheduled position reporting and Message 24 for static data.

The Class B"CS" AIS shall be able to receive and process messages at any time except during time periods of transmission.

4.1.5.3 Assigned mode

(see 10.2.2)

An "assigned" mode for operation in an area subject to a competent authority responsible for traffic monitoring so that the reporting interval, silent mode and/or transceiver behaviour may be set remotely by that authority using group assignment by Message 23.

4.1.5.4 Interrogation mode

(see 10.2.3)

A “polling” or “controlled” mode where the Class B“CS” AIS responds to interrogations by Messages 18 and 24 from a Class A AIS, a SAR aircraft or a base station. A base station interrogation for Message 19 specifying transmission offset shall also be answered. An interrogation overrides a silent period defined by Message 23 (see 7.3.4.4.4).

NOTE Since Message 19 is a message occupying two time periods, this requires the reservation of the respective time periods by Message 20 prior to interrogation.

A Class B“CS” AIS shall not interrogate other stations.

4.2 Manuals

The manuals shall include:

- the type of external connectors if applicable;
- the required information for correct siting of the antennas;
- the required information for compass safe distance.

4.3 Marking and identification

Each unit of the equipment shall be marked externally with the following information which, where practicable, shall be clearly visible when the equipment is installed in its recommended position:

- identification of the manufacturer;
- equipment type number or model identification;
- serial number of the unit;
- power supply requirements; and
- compass safe distance.

Alternatively, the marking may be presented on a display at equipment start-up.

The version of software shall be either marked or displayed on command on the equipment.

When the marking and the title and version of the software are presented only on the display, such information shall also be included in the equipment manual.

5 Environmental, power supply, interference and safety requirements

(see Clause 9)

In addition to the specific requirements of this standard, the Class B“CS” AIS shall fulfil the following general requirements as detailed in IEC 60945:

- inter-unit connection (interfaces other than IEC 61162 are allowed; see 6.7.3);
- power supply;
- extreme power supply;
- excessive conditions;
- power supply short-term variation and power supply failure (the Class B“CS” AIS shall not enter an undefined or unstable state in case of undervoltage);
- durability and resistance to environmental conditions;