

# SLOVENSKI STANDARD

## SIST ISO 10156:1996

01-maj-1996

---

**Plini in plinske mešanice - Določanje gorilne in oksidacijske sposobnosti za izbor izhodnih odprtih ventilov cilindrov**

Gases and gas mixtures -- Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets

### iTeh STANDARD PREVIEW

Gaz et mélanges de gaz -- Détermination du potentiel d'inflammabilité et d'oxydation pour le choix des raccords de sortie de robinets

[SIST ISO 10156:1996](https://standards.iteh.ai/catalog/standards/sist/b63428ed-32c8-4483-a915-70ddbd3725f8/sist-iso-10156-1996)

**Ta slovenski standard je istoveten z:**

**ISO 10156:1990**

---

**ICS:**

23.020.30	Tlačne posode, plinske jeklenke	Pressure vessels, gas cylinders
71.100.20	Industrijski plini	Gases for industrial application

**SIST ISO 10156:1996**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST ISO 10156:1996

<https://standards.iteh.ai/catalog/standards/sist/b63428ed-32c8-4483-a915-70ddb3725f/sist-iso-10156-1996>

# INTERNATIONAL STANDARD

**ISO  
10156**

First edition  
1990-12-15

---

---

## **Gases and gas mixtures — Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

*Gaz et mélanges de gaz — Détermination du potentiel d'inflammabilité  
et d'oxydation pour le choix des raccords de sortie de robinets*

SIST ISO 10156:1996

<https://standards.iteh.ai/catalog/standards/sist/b63428ed-32c8-4483-a915-70ddbdd3725f/sist-iso-10156-1996>



Reference number  
ISO 10156:1990(E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 10156 was prepared by Technical Committee ISO/TC 58, *Gas cylinders*.

Annex A forms an integral part of this International Standard.

[SIST ISO 10156:1996](https://standards.iteh.ai/catalog/standards/sist/b63428ed-32c8-4483-a915-70ddb3725f/sist-iso-10156-1996)

<https://standards.iteh.ai/catalog/standards/sist/b63428ed-32c8-4483-a915-70ddb3725f/sist-iso-10156-1996>

© ISO 1990

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization  
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

## Introduction

The purpose of ISO 5145 is to establish practical criteria for the determination of outlet connections of gas cylinders of water capacity 150 litres or less. These criteria are based on certain physical and chemical properties of the gases. In particular, the flammability in air and the oxidizing potential (with air as the reference) are considered.

One of the difficulties in the application of ISO 5145 resides in the fact that it is at times difficult to know if a gas or gas mixture is flammable in air or more oxidizing than air.

In fact,

in the case of pure gases, there is abundant data in the literature, although conflicting results are to be found, depending upon the test methods employed;

but, above all,

in the case of gas mixtures, data in the literature is often incomplete or even non-existent.

With standardized test methods, it will be possible

to eliminate the ambiguities in the case of conflicting results in the literature;

and, above all,

to supplement existing data (mainly in the case of gas mixtures).

In particular, the application of standardized test methods will eliminate the ambiguities concerning mixtures in groups 1, 3, 4, 6, 7, 8, 9, 12, 13 and 15, such as they are defined in ISO 5145, since it is necessary to know, in the case of those mixtures, whether or not they are flammable in air and/or more or less oxidizing than air.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST ISO 10156:1996

<https://standards.iteh.ai/catalog/standards/sist/b63428ed-32c8-4483-a915-70ddb3725f/sist-iso-10156-1996>

# Gases and gas mixtures — Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets

## 1 Scope

This International Standard specifies two test methods for determining whether or not a gas is flammable in air and whether a gas is more or less oxidizing than air, respectively, with the aim of eliminating difficulties entailed in the application of ISO 5145.

NOTE 1 For certain special applications, such as special gas mixtures produced to order (in small quantities), it might prove relatively complex to apply the method specified and to perform the special tests necessary to determine the flammability or oxidizing power of the gas mixture.

To avoid these difficulties, a simple method of calculation is recommended to determine rapidly the type of connection to be employed depending upon the characteristics (flammability, oxidizing power, etc.) of the gas mixture and the characteristics of the pure substances making up the mixture.

## 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 4589:1984, *Plastics — Determination of flammability by oxygen index*.

ISO 5145:1990, *Cylinder valve outlets for gases and gas mixtures — Selection and dimensioning*.

## 3 Definitions and symbols

### 3.1 Definitions

For the purposes of this International Standard, the following definitions apply:

**3.1.1 gas or gas mixture flammable in air:** A gas or gas mixture which will ignite in air at atmospheric pressure and a temperature of 20 °C.

**3.1.2 lower flammability limit in air:** The minimum content of a gas or gas mixture in air at which the gas or gas mixture will ignite. This limit is determined at atmospheric pressure and 20 °C.

**3.1.3 gas or gas mixture less oxidizing than air:** A gas or gas mixture which is not able, at atmospheric pressure, to support the combustion of substances which are flammable in air.

### 3.2 Symbols

$A_i$	molar fraction of a flammable gas in a mixture of gases
$B_i$	molar fraction of an inert gas in a mixture of gases
$C_i$	coefficient of oxygen equivalency
$F_i$	$i$ th flammable gas in a gas mixture
$I_i$	$i$ th inert gas in a gas mixture
$n$	number of flammable gases in a gas mixture
$p$	number of inert gases in a gas mixture
$K_i$	coefficient of equivalency of an inert gas relative to nitrogen
$A'_i$	equivalent content of a flammable gas
$N_2$	nitrogen

## ISO 10156:1990(E)

$T_{cl}$	maximum flammable-gas content for which a mixture of the flammable gas in nitrogen is not flammable in air
$H_2$	hydrogen
$CO_2$	carbon dioxide
$x_i$	minimum concentration of an oxidizing combustion gas, in a mixture with nitrogen, which will support combustion of a test piece
He	helium
Ar	argon
Ne	neon
Kr	krypton
Xe	xenon
$SO_2$	sulfur dioxide
$SF_6$	sulfur hexafluoride
$CF_4$	carbon tetrafluoride
$C_3F_8$	octafluoropropane
$CH_4$	methane
$N_2O$	nitrous oxide
$L_i$	lower flammability limit in air of a flammable gas
$O_2$	oxygen

## 4 Flammability of gases and gas mixtures in air

### 4.1 General

Gases and gas mixtures which are flammable shall be designated in accordance with ISO 5145:1990, annex A — category I — subdivision 2. Such gases and gas mixtures have flammable limits in air. The following sub-clauses outline a test method and a calculation method for determining whether a gas or gas mixture is flammable. In cases where the test result is different from that obtained by calculation, the test result shall take precedence.

### 4.2 Test method

#### 4.2.1 Principle

The gas is mixed in the desired proportions with air. Then ignition energy is supplied in the form of an electric arc between two electrodes.

#### 4.2.2 Apparatus and materials

The apparatus (see figure 1) includes:

- a mixer;
- a tube in which the reaction takes place;
- an ignition system;
- a system of analysis to determine the test-gas composition.

##### 4.2.2.1 Preparation

###### a) Test gas

The test gas shall be prepared to represent the most flammable composition that can occur in the normal course of production. The criteria to be used in establishing the composition of the test gas are manufacturing tolerances, i.e. the test gas shall contain the highest concentration of flammable gases encountered in the normal manufacturing process and the moisture content shall be less than or equal to 10 ppm by volume. The test gas shall be thoroughly mixed and carefully analysed to determine the exact composition.

###### b) Compressed air

The compressed air shall be analysed and shown to be free of moisture.

###### c) Test-gas/air mixture

The compressed air and the gas to be tested are mixed in a blender, controlling the flow rates. The air-flammable gas mixture shall be analysed using a chromatograph or a simple oxygen analyser.

##### 4.2.2.2 Reaction tube

This tube shall be made of thick pyrex glass (e.g. 5 mm), with an inside diameter of at least 50 mm and a length at least five times the diameter.

At one end of the tube, there shall be a cylindrical component designed to take:

- an ignition spark plug, located about 50 mm from the bottom of the tube;
- an inlet for the gas mixture to be tested;
- a relief valve at the bottom of the pyrex tube [see figure 1a)];
- two thermocouples, one located close to the ignition system, the other located close to the top of the tube, the purpose of these thermocouples being to allow easy detection of flame propa-



gation [see figure 1a)] (alternatively, gas ignition may be observed by an experienced operator in a dark room);

- a safety device to minimize the risk of destruction of the tube in the event of an explosion (preferably located close to the ignition system).

The tube and its accessories shall always be very clean in order to avoid any impurities, and particularly moisture resulting from a preceding test or from exposure to the atmosphere, from affecting the determination.

The gas mixture is vented at the top of the reaction tube by a tube fitted with a shut-off valve.

This apparatus is located inside a ventilated metal chamber, one side of which has a window made of high-strength transparent material.

Prior to ignition, the composition of the mixture shall be tested by analysing the gas leaving the reaction tube [see figure 1a), analysis at point 2] to ensure that the tube has been properly purged.

#### 4.2.2.3 Ignition system

A spark generator (e.g. 15 kV) shall be used which can supply sparks (across a 5 mm electrode gap, for instance) with an energy of 10 J per spark.

### 4.3 Procedure

Care shall be taken when carrying out flammability tests to ensure that the explosive range is avoided. This can be done by commencing the experimental work at "safe" concentrations of flammable gas in air ("safe" = below the expected lower flammable limit). Subsequently, the initial gas concentration can be slowly increased until ignition occurs.

Blend the desired mixture using the flowmeter (the efficiency of this step shall be checked by analysis). Close the gas inlets simultaneously. Just prior to ignition, ensure that the outlet valve (if there is one) is opened, to bring the mixture to atmospheric pressure.

There are several possible results:

- a) No combustion: the test-gas mixture is not flammable in air at this concentration. In this case, repeat the test at a slightly higher concentration.
- b) Partial combustion: a flame begins to burn around the spark plug, and then goes out. This

indicates that the flammability limit is close. In this case, repeat the test at least five times. If, in one of these repeat tests, the flame rises up the tube, it shall be considered that the flammability limit has been reached, i.e. the test gas is flammable.

- c) The flame rises slowly up the tube at 10 cm/s to 50 cm/s. In this case, it shall be considered that the limit has been reached, i.e. the test gas is flammable.

- d) The flame rises up the tube very rapidly. In this case, the test gas is flammable.

#### NOTES

2 Instead of flowmeters, other appropriate devices, such as metering pumps, etc., can be used.

3 With mixtures containing hydrogen, the flame is almost colourless. In order to confirm the presence of such flames, the use of temperature-measuring probes is recommended (see 4.2.2.2).

4 Although it is beyond the scope of this International Standard, if a precise value is required for the lower flammability limit of the test gas, then repeated tests must be carried out, varying the flammable-gas content until the threshold point is reached between ignition and no ignition of the flammable gas.

### 4.4 Key points concerning safety

Tests shall be carried out by trained and competent personnel working in accordance with authorized procedures (see also 4.3). The reaction tube and flowmeter shall be adequately screened to protect the personnel in the event of an explosion. Personnel shall wear safety glasses. During the ignition sequence, the reaction tube shall be open to the atmosphere and isolated from the gas supply. Care shall also be taken during the analysis of the test gas or mixture.

### 4.5 Results for pure gases

A list of flammable gases is given in annex A together with some lower flammability limits. These values have been obtained using similar test equipment to that described in 4.2.2.

### 4.6 Calculation method

This method is limited to gas mixtures produced in small quantities in cylinders to indicate if flammable in air.