

# TECHNICAL REPORT



**Electromagnetic performance of high voltage direct current (HVDC) overhead transmission lines**

(<https://standards.iteh.ai>)

Document Preview

IEC TR 62681:2014

<https://standards.iteh.ai/catalog/standards/iec/62681-2014>

WITHDRAWN





**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2014 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

**About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

**About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

**IEC Catalogue - [webstore.iec.ch/catalogue](http://webstore.iec.ch/catalogue)**

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

**IEC publications search - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)**

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

**IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

**Electropedia - [www.electropedia.org](http://www.electropedia.org)**

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

**IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)**

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

**IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [csc@iec.ch](mailto:csc@iec.ch).

# TECHNICAL REPORT



**Electromagnetic performance of high voltage direct current (HVDC) overhead transmission lines**

<https://standards.iteh.ai>  
Document Preview

IEC TR 62681:2014

<https://standards.iteh.ai/catalog/standards/iec/6d1d6c96f-544e-4b6c-bd6c-6dd218b22615/iec-tr-62681-2014>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE **XD**

ICS 29.240.20

ISBN 978-2-8322-1780-1

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
1 Scope.....	9
2 Terms and definitions .....	9
3 Electric field and ion current .....	10
3.1 Description of the physical phenomena .....	10
3.2 Calculation methods .....	13
3.2.1 General .....	13
3.2.2 Semi-analytic method .....	14
3.2.3 Finite element method .....	16
3.2.4 BPA method .....	17
3.2.5 Empirical methods of EPRI .....	18
3.2.6 Recent progress .....	18
3.3 Experimental data.....	19
3.3.1 General .....	19
3.3.2 Instrumentation and measurement methods.....	19
3.3.3 Experimental results for electric field and ion current.....	21
3.3.4 Discussion.....	21
3.4 Implication for human and natural environment.....	22
3.4.1 General .....	22
3.4.2 Static electric field .....	23
3.4.3 Research on space charge .....	23
3.4.4 Scientific review .....	28
3.5 Design practice of different countries .....	29
4 Magnetic field.....	30
4.1 Description of physical phenomena.....	30
4.2 Magnetic field of HVDC transmission lines .....	31
5 Radio interference (radio noise).....	32
5.1 Description of radio interference phenomena of HVDC transmission system .....	32
5.1.1 General .....	32
5.1.2 Physical aspects of d.c. corona .....	32
5.1.3 Mechanism of formation of a noise field of d.c. line.....	33
5.1.4 Characteristics of radio interference from d.c. line .....	33
5.1.5 Factors influencing the RI from d.c. line.....	34
5.2 Calculation methods .....	36
5.2.1 EPRI empirical formula .....	36
5.2.2 IREQ empirical method.....	37
5.2.3 CISPR bipolar line RI prediction formula.....	38
5.2.4 Comparison of different prediction formula.....	38
5.3 Experimental data.....	38
5.3.1 Measurement apparatus and methods .....	38
5.3.2 Experimental results for radio interference.....	39
5.4 Criteria of different countries.....	39
6 Audible noise.....	40
6.1 Basic principles of audible noise .....	40
6.2 Description of physical phenomena.....	41

6.2.1	Lateral profiles.....	42
6.2.2	Statistical distribution .....	44
6.2.3	Influencing factors .....	45
6.2.4	Effect of altitude above sea level .....	47
6.2.5	Concluding remarks.....	47
6.3	Calculation methods .....	48
6.3.1	General .....	48
6.3.2	Theoretical analysis of audible noise propagation.....	48
6.3.3	Empirical formulas of audible noise .....	49
6.3.4	Semi-empirical formulas of audible noise.....	49
6.3.5	CEPRI (China) research results .....	52
6.3.6	Concluding remarks.....	52
6.4	Experimental data.....	52
6.4.1	Measurement techniques and instrumentation .....	52
6.4.2	Experimental results for audible noise .....	53
6.5	Design practice of different countries .....	53
6.5.1	General .....	53
6.5.2	The effect of audible noise on people.....	53
6.5.3	The audible noise level and induced complaints .....	54
6.5.4	Limit values of audible noise of HVDC transmission lines in different countries .....	57
6.5.5	Recommended noise level limit.....	58
6.5.6	Main conclusion.....	58
Annex A (informative)	Experimental results for electric field and ion current.....	59
A.1	Bonneville Power Administration ±500 kV HVDC transmission line.....	59
A.2	FURNAS ±600 kV HVDC transmission line.....	59
A.3	Manitoba Hydro ±450 kV HVDC transmission line .....	60
A.4	Hydro-Québec – New England ±450 kV HVDC transmission line .....	62
A.5	IREQ test line study of ±450 kV HVDC line configuration .....	63
A.6	HVTRC test line study of ±400 kV HVDC line configuration .....	64
A.7	Test study in China.....	66
Annex B (informative)	Experimental results for radio interference .....	68
B.1	Bonneville power administration's 1 100 kV direct current test project.....	68
B.1.1	General .....	68
B.1.2	Lateral profile .....	68
B.1.3	Influence of conductor gradient.....	69
B.1.4	Percent cumulative distribution .....	70
B.1.5	Influence of wind .....	72
B.1.6	Spectrum.....	72
B.2	Hydro-Québec institute of research.....	74
B.2.1	General .....	74
B.2.2	Cumulative distribution .....	74
B.2.3	Spectrum.....	75
B.2.4	Lateral profiles.....	75
B.2.5	Cumulative distribution under different voltage .....	76
B.3	d.c. line of China.....	76
Annex C (informative)	Experimental results for audible noise.....	78
Bibliography	.....	81

Figure 1 – Unipolar and bipolar space charge regions of a HVDC transmission line [1] .....	11
Figure 2 – Lateral profile of magnetic field on the ground of ±800 kV HVDC lines .....	32
Figure 3 – The corona current and radio interference field .....	33
Figure 4 – RI tolerance tests: reception quality as a function of signal-to-noise ratio .....	40
Figure 5 – Attenuation of different weighting networks used in audible-noise measurements [14] .....	41
Figure 6 – Comparison of typical audible noise frequency spectra [129].....	42
Figure 7 – Lateral profiles of the AN .....	43
Figure 8 – Lateral profiles of the AN from a bipolar HVDC-line equipped with 8 × 4,6 cm (8 × 1,8 in) conductor bundles energized with ±1 050 kV [32] .....	43
Figure 9 – Lateral profiles of fair-weather A-weighted sound level.....	44
Figure 10 – All weather distribution of AN and RI at +15 m lateral distance of the positive pole from the upgraded Pacific NW/SW HVDC Intertie [32] .....	45
Figure 11 – Statistical distributions of fair weather Aweighted sound level measured at 27 m lateral distance from the line center during spring 1980.....	45
Figure 12 – Audible noise complaint guidelines [12].....	54
Figure 13 – Measured lateral profile of audible noise on a 330 kV AC transmission line [149].....	55
Figure 14 – Subjective evaluation of d.c. transmission line audible noise; EPRI test center study 1974 [31] .....	55
Figure 15 – Subjective evaluation of d.c. transmission line audible noise; OSU study 1975 [31] .....	56
Figure 16 – Results of the operators’ subjective evaluation of AN from HVDC lines .....	57
Figure 17 – Results of subjective evaluation of AN from d.c. lines.....	57
Figure A.1 – Electric field and ion current distributions for Manitoba Hydro ±450 kV Line [37] .....	61
Figure A.2 – Cumulative distribution of electric field for Manitoba Hydro ±450 kV Line [37] 62	
Figure A.3 – Cumulative distribution of ion current density for Manitoba Hydro ±450 kV line [37] .....	62
Figure A.4 – Test result for total electric field at different humidity [117] .....	67
Figure A.5 – Comparison between the calculation result and test result for the total electric field (minimum conductor height is 18 m) [117].....	67
Figure B.1 – Connection for 3-section d.c. test line [121] .....	68
Figure B.2 – Typical RI lateral profile at ±600kV, 4 × 30,5 mm conductor, 11,2 m pole spacing, 15,2 m average height [12] .....	69
Figure B.3 – Simultaneous RI lateral, midspan, in clear weather and light wind for three configurations, bipolar ±400 kV [121] .....	69
Figure B.4 – RI at 834kHz as a function of bipolar line voltage 4 × 30,5 mm conductor, 11,2 m pole spacing, 15,2 m average height .....	70
Figure B.5 – Percent cumulative distribution for fair weather, 2 × 46 mm, 18,3 m pole spacing, ±600 kV .....	70
Figure B.6 – Percent cumulative distribution for rain weather, 2 × 46 mm, 18,3 m pole spacing, ±600 kV .....	71
Figure B.7 – Percent cumulative distribution for fair weather, 4 × 30,5 mm, 13,2 m pole spacing, ±600 kV .....	71

Figure B.8 – Percent cumulative distribution for rain weather, 4 × 30,5 mm, 13,2 m pole spacing, ±600 kV .....	72
Figure B.9 – Radio interference frequency spectrum .....	73
Figure B.10 – RI vs. frequency at ±400 kV [121] .....	73
Figure B.11 – Cumulative distribution of RI measured at 15 m from the positive pole [122] .....	74
Figure B.12 – Conducted RI frequency spectrum measured with the line terminated at one end [122] .....	75
Figure B.13 – Lateral profile of RI [122] .....	76
Figure B.14 – Annual cumulative distribution of RI measured at 15 m from the positive pole [122] .....	76
Figure B.15 – Comparison between calculation result and test result for RI lateral profile [117] .....	77
Figure C.1 – Examples of statistical distributions of fair weather audible noise, dB(A) measured at 27 m from line center of a bipolar HVDC test line [14] .....	79
Table 1 – Electric field and ion current limits of ±800 kV d.c. lines in China .....	30
Table 2 – Electric field limits of d.c. lines in United States of America [119] .....	30
Table 3 – Electric field and ion current limits of d.c. lines in Canada .....	30
Table 4 – Electric field limits of d.c. lines in Brazil .....	30
Table 5 – Parameters of the IREQ excitation function [120] .....	38
Table 6 – Comparison of the EPRI and CISPR formula .....	38
Table 7 – Parameters defining regression equation for generated acoustic power density .....	51
Table 8 – Typical sound attenuation (in decibels) provided by buildings [155] .....	58
Table A.1 – BPA ±500 kV line: statistical summary of all-weather ground-level electric field intensity and ion current density [32] .....	59
Table A.2 – FURNAS ±600 kV line: statistical summary of ground-level electric field intensity and ion current density [36] .....	60
Table A.3 – Hydro-Québec–New England ±450 kV HVDC transmission line. Bath, NH; 1990-1992 (fair weather), 1992 (rain), All-season measurements of static electric E-field in kV/m [39] .....	63
Table A.4 – Hydro-Québec – New England ±450 kV HVDC Transmission Line. Bath, NH; 1990-1992, All-season fair-weather measurements of ion concentrations in kions/cm <sup>3</sup> [39] .....	63
Table A.5 – IREQ ± 450 kV test line: statistical summary of ground-level electric field intensity and ion current density [41] .....	64
Table A.6 – HVTRC ±400 kV test line: statistical summary of peak electric field and ion currents [42] .....	65
Table A.7 – Statistic results for the test data of total electric field at ground (50 % value) [117] .....	66
Table B.1 – Influence of wind on RI .....	72
Table B.2 – Statistical representation of the long term RI performance of the tested conductor bundle [122] .....	75
Table B.3 – RI at 0,5 MHz at lateral 20m from positive pole (fair weather) .....	77
Table C.1 – Audible Noise Levels of HVDC Lines according to [119] and [150] .....	80



## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ELECTROMAGNETIC PERFORMANCE OF HIGH VOLTAGE DIRECT CURRENT (HVDC) OVERHEAD TRANSMISSION LINES**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 62681, which is a technical report, has been prepared by IEC technical committee 115: High Voltage Direct Current (HVDC) transmission for d.c. voltages above 100 kV.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
115/71/DTR	115/84/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.



This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

**IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.**

iTech Standards  
(<https://standards.itih.ai>)  
Document Preview

[IEC TR 62681:2014](https://standards.itih.ai/standards/iec/62681-2014)

<https://standards.itih.ai/standards/iec/62681-2014>

## INTRODUCTION

Electric fields and magnetic fields are produced in the vicinity of an HVDC transmission line. When the electric field at the conductor surface exceeds a critical value, known as the corona onset gradient, positive or negative free charges leave the conductor and interact with the surrounding air and ionization takes place in the layer of surrounding air, leading to the formation of corona discharges. The corona discharge will not only bring out corona loss but also produce electromagnetic environment problems.

The parameters used to describe the electromagnetic environment of an HVDC transmission line mainly include the:

- 1) electric field,
- 2) ion current,
- 3) magnetic field,
- 4) radio interference,
- 5) audible noise.

To control these parameters in a reasonable and acceptable range, for years, a great deal of theoretical and experimental research was conducted in many countries, and relevant national standards or enterprise standards were developed. This Technical Report collects and records the status of study and progress of electric fields, ion current, magnetic fields, radio interference, and audible noise of HVDC transmission lines.

# ELECTROMAGNETIC PERFORMANCE OF HIGH VOLTAGE DIRECT CURRENT (HVDC) OVERHEAD TRANSMISSION LINES

## 1 Scope

This Technical Report provides general guidance on the electromagnetic environment issues of HVDC transmission lines. It concerns the major parameters adopted to describe the electromagnetic environment of a High-Voltage Direct Current (HVDC) transmission line, including electric fields, ion current, magnetic fields radio interference, and audible noise generated as a consequence of such effects. Engineers in different countries can refer to this Technical Report to:

- ensure the safe operation of HVDC transmission lines,
- limit the influence on the environment within acceptable ranges, and
- optimize engineering costs.

## 2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 2.1

#### **corona**

set of partial discharges in a gas, immediately adjacent to an uninsulated or lightly insulated conductor which creates a highly divergent field remote from other conductors

[SOURCE: IEC 60050-212:2010, 212-11-44, modified – Note 1 has been deleted.]

### 2.2

#### **electric field**

constituent of an electromagnetic field which is characterized by the electric field strength  $E$  together with the electric flux density  $D$

Note 1 to entry: In the context of HVDC transmission lines, the electric field is affected not only by the geometry of the line and the potential of the conductor, but also by the space charge generated as a result of corona; consequently, electric field distribution may vary non-linearly with the line potential.

[SOURCE: IEC 60050-121:1998, 121-11-67, modified – Note 1 to entry has been added.]

### 2.3

#### **space-charge-free electric field**

electric field due to a system of energized electrodes, excluding the effect of space charge present in the inter-electrode space

### 2.4

#### **ion current**

flow of electric charge resulting from the motion of ions

### 2.5

#### **magnetic field**

constituent of an electromagnetic field which is characterized by the magnetic field strength  $H$  together with the magnetic flux density  $B$

[SOURCE: IEC 60050-121:1998, 121-11-69, modified – Note 1 has been deleted.]

## 2.6

### radio interference

degradation of the reception of a wanted signal caused by RF disturbance

## 2.7

### audible noise

unwanted sound with frequency range from 20 Hz to 20 kHz

[SOURCE: IEC 61973:2012, 3.1.14]

## 3 Electric field and ion current

### 3.1 Description of the physical phenomena

Electric fields are produced in the vicinity of a HVDC transmission line, with the highest electric fields existing at the surface of the conductor. When the electric field at the conductor surface exceeds a critical value, the air in the vicinity of the conductor becomes ionized, forming a corona discharge. Ions of both polarities are formed, but ions of opposite polarity to the conductor potential are attracted back towards the conductor, while ions of the same polarity as the conductor are repelled away from the conductor. Space charges include air ions and charged aerosols. Under the action of an electric field, space charge will move directionally and ion current will be formed. The physical phenomena of electric field and ion current are described in this clause.

The electric field and ion current in the vicinity of an HVDC transmission line are defined mainly by the operating voltage and line configuration. The voltage applied to line conductors produces an electric field distribution. Unlike High-voltage Alternating Current (HVAC) transmission lines, the electric field produced by HVDC transmission lines does not vary with time and, consequently, does not produce any significant currents in humans or objects immersed in these fields.

The electric field is another aspect of the electrical environment around an overhead HVDC transmission line. An electric field is present around any charged conductor, irrespective of whether corona discharge is taking place. However, the space charge created by corona discharge under d.c. conditions modifies the distribution of an electric field. The effect of space charge on electric fields is significant.

For the same HVDC transmission lines, the corona onset gradients of positive or negative polarities are different and the intensity and characteristics of corona discharges on positive or negative conductors are also different. Consequently, during the design of HVDC transmission lines, special consideration should be paid to the allowable values of the maximum ground-level electric field and ion current density [1]<sup>1</sup>.

Corona on a conductor of either positive or negative polarity produces ions of either the positive or negative polarities in a thin layer of air surrounding each conductor [1]. However, ions with a polarity opposite to that of the conductor are drawn to it and are neutralized on contact. Thus, a positive conductor in corona acts as a source of positive ions and vice-versa. For a unipolar d.c. transmission line, ions having the same polarity as the conductor voltage fill the entire inter-electrode space between the conductors and ground. For a bipolar d.c. transmission line, the ions generated on the conductors of each polarity are subject to an electric field driven drift motion either towards the conductor of opposite polarity or towards the ground plane, as shown in Figure 1. The influence of wind or the formation of charged aerosols are not considered at this stage. Three general space charge regions are created in this case:

---


<sup>1</sup> Numbers in square brackets refer to the bibliography.

- a) a positive unipolar region between the positive conductor and ground,
- b) a negative unipolar region between the negative conductor and ground,
- c) a bipolar region between the positive and negative conductors.

For practical bipolar HVDC lines, most of the ions are directed toward the opposite polarity conductor, but a significant fraction is also directed toward the ground. The ion drift velocity is such that it will take at least a few seconds for them to reach ground. Actually, the molecules traveling along ion paths are not always the same ions. In fact, collisions between ions and air molecules occur during the travel at a rate of billions per second and cause charge transfer and reactions between ions and neutral molecules, so the ions reaching the ground are quite different from those that were originally formed by corona near the conductor surface. The exact chemical identity of the ions, after a few seconds, will depend on the chemical composition and trace gases at the location.

Electric field is another component of the electrical environment around an overhead HVDC transmission line. Electric field is caused by electrical charges, both those residing on conductive surfaces (the transmission line conductors, the ground, and conducting objects) and the space charges. The effect of space charge on electric field is significant.

A nonlinear interaction takes place between electric field and space charge distributions in all three general space regions identified above in a), b), c).. The nonlinearity arises because ions flow from each conductor to ground or to the conductor of opposite polarity along the flux lines of the electric field distribution: while at the same time, the electric field distribution is influenced by the ionic space charge distribution. In addition to the nonlinear interaction described above, the space charge field in the bipolar region is affected by other factors. Mixing of ions of both polarities in the bipolar region leads firstly, to a reduction in the net space charge density and secondly, to recombination and neutralization of ions of both polarities.



**Figure 1 – Unipolar and bipolar space charge regions of a HVDC transmission line [1]**

The corona-generated space charge, being of the same polarity as the conductor, produces a screening effect on the conductor by lowering the electric field in the vicinity of the conductor surface and consequently reducing the intensity of corona discharges occurring on the conductor. In the unipolar regions, the space charge enhances the electric field at the ground surface. The extent of electric field reduction at the conductor surface and field enhancement at the ground surface depend on the conductor voltage as well as on the corona intensity at the conductor surface. In the case of the bipolar region, however, the mixture of ions of opposite polarity and ion recombination tend to reduce the screening effect on the conductor surface. This leads to a smaller reduction in the intensity of corona activity near the conductors than in the unipolar regions.

The electrical environment at ground level under a bipolar HVDC transmission line is, therefore defined mainly by three quantities:

- a) electric field,  $E$ ,
- b) ion current density,  $J$ ,
- c) space charge density,  $\rho$ .

The electric field produced by HVDC overhead transmission lines is a vector defined by its components along three orthogonal axes. The space charge density is a scalar. The ion current density is also a vector, and it is determined by the electric field and space charge density.

Very small currents in some cases may flow through an object or person located under the line because of exposure to the electric field and ion space charge. From the point of view of environmental impact on persons and objects located under the line, the main consideration is the combined exposure to the electric fields and ion currents. The scientific literature indicates that exposure to the levels of d.c. electric field and ion current density existing under operating HVDC transmission lines pose no risk to public health, but may cause some induced current and annoyance effects to humans. Consequently, during designing of HVDC transmission lines, special consideration should be paid for the allowable values of the maximum ground-level electric field and ion current density [1].

Design of HVDC transmission lines requires the ability to predict ground-level electric field and ion current distribution as functions of line design parameters such as the number and diameter of sub-conductors in the bundle, height above ground of conductors and pole spacing. Prediction methods are based on a combination of analytical techniques to calculate the space charge fields and accurate long-term measurements under experimental as well as operating HVDC transmission lines.

As described and illustrated in Figure 1, the ground-level electric field and ion current environment under a bipolar HVDC transmission line can be thought primarily as a unipolar space charge field under each pole. The bipolar space charge field between the positive and negative conductors, however, has no significant impact on the ground-level electrical environment. For the purpose of calculating the ground-level electric field and ion current distributions, therefore, analytical treatment of the unipolar space charge field between each of the positive and negative conductors and the ground plane is adequate.

Unipolar d.c. space charge fields are defined by the following equations:

$$\nabla \cdot E = \frac{\rho}{\varepsilon_0} \quad (1)$$

$$J = \mu\rho E \quad (2)$$

$$\nabla \cdot J = 0 \quad (3)$$

where

$E$  and  $J$  are the electric field and ion current density vectors at any point in space,

$\rho$  is the space charge density,

$\mu$  is the ionic mobility,

$\varepsilon_0$  is the permittivity of free space.

The first Equation (1) is Poisson's equation, the second Equation (2) defines the relationship between the current density and electric field vectors, and the third Equation (3) is the