

**SLOVENSKI STANDARD
SIST EN 28860-2:1997****01-december-1997**

Information processing - Data interchange on 90 mm (3.5 in) high density flexible disk cartridges using modified frequency modulation recording at 7958 ftprad, 5.3 tpmm (135 tpi) on both sides - Part 2: Track format (ISO 8860-2:1987)

Information processing - Data interchange on 90 mm (3.5 in) high density flexible disk cartridges using modified frequency modulation recording at 7958 ftprad, 5.3 tpmm (135 tpi) on both sides - Part 2: Track format (ISO 8860-2:1987, ed. 1)

Informationsverarbeitung - Datenaustausch auf 90 mm (3.5 in) Disketten unter Verwendung von modifizierter Wechseltaktschrift mit 7958 Flußwechseln je rad auf 90 Spuren auf jeder Seite - Teil 2: Spurformat (ISO 8860-2:1987, Ausg. 1)

Traitement de l'information - Echange de données sur cartouches a disquette de 90 mm (3,5 in) utilisant un enregistrement MFM a 7958 ftprad, 5,3 tpmm (135 tpi) sur deux faces - Partie 2: Schéma de piste (ISO 8860-2:1987, éd. 1)

Ta slovenski standard je istoveten z: EN 28860-2:1989

ICS:

35.220.21 Magnetni diski Magnetic disks

SIST EN 28860-2:1997 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 28860-2:1997](#)

<https://standards.iteh.ai/catalog/standards/sist/cdc81afb-00ca-4d16-9f79-e3b376a235ce/sist-en-28860-2-1997>



REPUBLIKA SLOVENIJA
 MINISTRSTVO ZA ZNANOST IN TEHNOLOGIJO
 Urad RS za standardizacijo in meroslovje
 LJUBLJANA

EUROPEAN STANDARD

NORME EUROPEENNE

EUROPAISCHE NORM

SIST... **EN 28860-2**
 PREVZET PO METODI RAZGLASITVE

EN 28 860

Part 2

CEN/CS

F12

-12- 1997 March 1989

UDC 681.327.634

Key words: Data processing, Information Interchange, Flexible Disk Cartridges, Magnetic Recording, Frequency Modulation, Track Format

English version

Information processing. Data interchange on 90 mm (3.5 in) high density flexible disk cartridges using modified frequency modulation recording at 7 958 ftprad, 5.3 tpmm (135;tpi) on both sides. Part 2: track format (ISO 8860-2, 1st edition, 1987)

Traitement de l'information. Echange de données sur cartouches à disquette de 90 mm (3.5 in) utilisant un enregistrement MFM à 7958 ftprad, 5.3 tpmm (135 tpi) sur deux faces. Partie 2: schéma de piste (ISO 8860-2, 1ère édition, 1987)	Informationsverarbeitung. Datenaustausch auf 90 mm (3.5 in) Disketten unter Verwendung von modifizierter Wechseltaktschrift mit 7 958 Flusswechseln je rad auf 90 Spuren auf jeder Seite. Teil 2: Spurformat (ISO 8860-2, 1. Ausgabe, 1987)
---	---

This European Standard was accepted by CEN on 1988-12-21 and is identical to the ISO standard as referred to. CEN members are bound to comply with the requirements of the CEN/CENELEC Common Rules which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language may be translation under the responsibility of a CEN member into its own language and notified to CEN Central Secretariat has the same status as the official versions.

CEN members are the national standards organizations of Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxemburg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CEN

European Committee for Standardization
 Comité Européen de Normalisation
 Europäisches Komitee für Normung

Central Secretariat: rue Bréderode 2, B-1000 Brussels

(c) CEN 1989 Copyright reserved to all CEN members

Ref. No. EN 28 860-2:1989 E

EN 28 860 Part 2 Page 2

BRIEF HISTORY

The Technical Board has decided to submit the International Standard

ISO 8860-2, 1st edition, 1987 "Information processing; Data interchange on 90 mm (3.5 in) flexible disk cartridges using modified frequency modulation recording at 7 958 frprad on 80 tracks each side; Part 2: Track format"

to the formal vote. The result of this vote was positive.

For the time being, this document exists only in the English and the French versions.

According to the CEN/CENELEC Common Rules, the following countries are bound to implement this standard: Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxemburg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

STATEMENT

The text of the International Standard ISO 8860-2, 1st edition, 1987, was approved by CEN as a European Standard without any modification.



INTERNATIONAL STANDARD

ISO
8860-2

First edition
1987-07-01



INTERNATIONAL ORGANIZATION FOR STANDARDIZATION
ORGANISATION INTERNATIONALE DE NORMALISATION
МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ

**Information processing — Data interchange on 90 mm
(3.5 in) flexible disk cartridges using modified
frequency modulation recording at 7 958 ftprad on
80 tracks on each side —**

iTeh STANDARD PREVIEW

Part 2 :
Track format

(standards.iteh.ai)

SIST EN 28860-2:1997

*Traitement de l'information — Échange de données sur cartouches à disquette de 90 mm
(3,5 in) utilisant un enregistrement à modulation de fréquence modifiée (MFM) à 7 958 ftprad
sur 80 pistes sur chaque face —*

Partie 2 : Schéma de piste

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 8860-2 was prepared by Technical Committee ISO/TC 97, *Information processing systems*.

Users should note that all International Standards undergo revision from time to time and that any reference made herein to any other International Standard implies its latest edition, unless otherwise stated.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/cdc81afb-00ca-4d16-9f79-e3b376a235cc/sist-en-28860-2-1997>

Contents

	Page
0 Introduction	1
1 Scope and field of application	1
2 Conformance	1
3 References	1
4 General requirements	1
4.1 Mode of recording	1
4.2 Track location tolerance of the recorded flexible disk cartridge	1
4.3 Recording offset angle	1
4.4 Density of recording	2
4.5 Flux transition spacing	2
4.6 Average Signal Amplitude	3
4.7 Byte	3
4.8 Sector	3
4.9 Cylinder	3
4.10 Cylinder number	3
4.11 Data capacity of a track	3
4.12 Hexadecimal notation	3
4.13 Error Detection Characters (EDC)	3
5 Track layout	3
5.1 Index Gap	3
5.2 Sector Identifier	3
5.3 Identifier Gap	4
5.4 Data Block	4
5.5 Data Block Gap	4
5.6 Track Gap	4

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 28860-2:1997
<https://standards.iteh.ai/catalog/standards/sist/cdc81afb-00ca-4d16-9f79-e3b37c235f4a/iso-8860-2-1987>

ISO 8860-2 : 1987 (E)

6	Coded representation of data	4
6.1	Standards	4
6.2	Coding methods	4
Annexes		
A	EDC implementation	6
B	Procedure and equipment for measuring flux transition spacing	7
C	Data separators for decoding MFM recording	9
	Bibliography	10

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 28860-2:1997](https://standards.iteh.ai/catalog/standards/sist/cdc81afb-00ca-4d16-9f79-e3b376a235ce/sist-en-28860-2-1997)

<https://standards.iteh.ai/catalog/standards/sist/cdc81afb-00ca-4d16-9f79-e3b376a235ce/sist-en-28860-2-1997>

Information processing — Data interchange on 90 mm (3.5 in) flexible disk cartridges using modified frequency modulation recording at 7 958 ftprad on 80 tracks on each side —

Part 2 : Track format

0 Introduction

ISO 8860 specifies the characteristics of 90 mm (3.5 in) flexible disk cartridges recorded at 7 958 ftprad using Modified Frequency Modulation (MFM) recording on 80 tracks on each side.

ISO 8860-1 specifies the mechanical, physical and magnetic characteristics of the cartridge, so as to provide physical interchangeability between data processing systems.

ISO 8860-1 and ISO 8860-2, together with the labelling scheme specified in ISO 9293, provide for full data interchange between data processing systems.

ISO 8860-1, *Information processing — Data interchange on 90 mm (3.5 in) flexible disk cartridges using modified frequency modulation recording at 7 958 ftprad on 80 tracks on each side — Part 1 : Dimensional, physical and magnetic characteristics.*

ISO 9293, *Information processing — Volume and file structure of flexible disk cartridges for information interchange.*

1 Scope and field of application

This part of ISO 8860 specifies the track layout, the track format and the characteristics of recorded signals.

NOTE — Numeric values in the SI and/or Imperial measurement system in this part of ISO 8860 may have been rounded off and therefore are consistent with, but not exactly equal to, each other. Either system may be used, but the two should be neither intermixed nor re-converted. The original design was made using SI units.

2 Conformance

A 90 mm (3.5 in) flexible disk cartridge shall be in conformance with this part of ISO 8860 if it meets all mandatory requirements contained herein.

A prerequisite for conformance with this part of ISO 8860 is conformance with ISO 8860-1.

3 References

ISO 646, *Information processing — ISO 7-bit coded character set for information interchange.*

ISO 2022, *Information processing — ISO 7-bit and 8-bit coded character sets — Code extension techniques.*

ISO 4873, *Information processing — ISO 8-bit code for information interchange — Structure and rules for implementation.*

4 General requirements

4.1 Mode of recording

The mode of recording shall be Modified Frequency Modulation (MFM) for which the conditions are

- a) a flux transition shall be written at the centre of each bit cell containing a ONE;
- b) a flux transition shall be written at each cell boundary between consecutive bit cells containing ZEROs.

Exceptions to this are defined in 4.12.

4.2 Track location tolerance of the recorded flexible disk cartridge

The centrelines of the recorded tracks shall be within $\pm 0,028$ mm ($\pm 0,001$ 1 in) of the nominal positions and over the range of operating environment specified in ISO 8860-1.

4.3 Recording offset angle (see figure 1)

At the instant of writing or reading a magnetic transition, the transition shall have an angle of

$$\theta = \arcsin \left(\frac{d}{R_n} \right) \pm 18'$$

where R_n is the radius through that transition (see ISO 8860-1).