
Elektromagnetna združljivost in zadeve v zvezi z radijskim spektrom (ERM) – Radijska oprema za podatkovno povezavo VHF zrak-tla, 4. način – Tehnične karakteristike in merilne metode za talno opremo – 2. del: Plast podatkovnih povezav

Electromagnetic compatibility and Radio spectrum Matters (ERM); VHF air-ground Data Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment; Part 2: Data link layer

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 842-2 V1.3.1:2006](https://standards.iteh.ai/catalog/standards/sist/6211f3c7-7e8c-4cdd-b842-fc8a3635a400/sist-en-301-842-2-v1-3-1-2006)

<https://standards.iteh.ai/catalog/standards/sist/6211f3c7-7e8c-4cdd-b842-fc8a3635a400/sist-en-301-842-2-v1-3-1-2006>

Ta slovenski standard je istoveten z: EN 301 842-2 Version 1.3.1

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general
35.100.20	Podatkovni povezovalni sloj	Data link layer

SIST EN 301 842-2 V1.3.1:2006 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 842-2 V1.3.1:2006

<https://standards.iteh.ai/catalog/standards/sist/6211f3c7-7e8c-4cdd-b842-fc8a3635a400/sist-en-301-842-2-v1-3-1-2006>

ETSI EN 301 842-2 V1.3.1 (2005-04)

European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
VHF air-ground Data Link (VDL) Mode 4 radio equipment;
Technical characteristics and methods of measurement
for ground-based equipment;
Part 2: Data link layer**

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN 301 842-2 V1.3.1:2006](https://standards.iteh.ai/catalog/standards/sist/6211f3c7-7e8c-4cdd-b842-fc8a3635a400/sist-en-301-842-2-v1-3-1-2006)

<https://standards.iteh.ai/catalog/standards/sist/6211f3c7-7e8c-4cdd-b842-fc8a3635a400/sist-en-301-842-2-v1-3-1-2006>



Reference

REN/ERM-TG25-023

Keywords

aeronautical, digital, radio, testing, VHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 842-2 V1.3.1:2006<https://standards.iteh.ai/catalog/standards/sist/6211f3c7-7e8c-4cdd-b842-fc8a3635a444/etsi-en-301-842-2-v1-3-1-2006>**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2005.
All rights reserved.

DECT™, **PLUGTESTS™** and **UMTS™** are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	8
Foreword.....	8
Introduction	9
1 Scope	10
2 References	11
3 Definitions and abbreviations.....	12
3.1 Definitions	12
3.1.1 Basic reference model definitions.....	12
3.1.2 Service conventions definitions	13
3.1.3 General definitions.....	13
3.2 Abbreviations	16
4 General description of VDL Mode 4 ground station link layer.....	17
4.1 General	17
4.1.1 Overview of VDL Mode 4.....	17
4.1.2 Relationship to OSI reference model.....	18
4.1.3 VDL Mode 4 services	20
4.1.4 ADS-B Function	20
4.1.5 Operational scenarios.....	21
4.1.6 VDL Mode 4 fundamentals	21
4.1.7 Possible configuration of ground equipment	22
4.1.8 Overall structure of specifications for VDL Mode 4	22
4.1.9 Equipment performance verification	24
4.2 Ground quarantine	25
4.3 System timing.....	25
4.4 Net entry.....	25
4.5 Autotune capability	25
4.6 Autonomous and fixed access	26
5 Minimum performance specification under standard test conditions.....	26
5.1 MAC sublayer	26
5.1.1 Services.....	26
5.1.2 MAC sublayer services	26
5.1.3 MAC sublayer parameters	26
5.1.3.1 General	26
5.1.3.2 Parameter M1 (number of slots per superframe).....	27
5.1.4 Time synchronization	27
5.1.4.1 Primary.....	27
5.1.4.2 Secondary.....	27
5.1.4.3 Alignment to UTC second	27
5.1.4.4 Data quality level	27
5.1.5 Slot idle/busy notification.....	27
5.1.5.1 Slot idle detection.....	27
5.1.5.2 Slot busy detection	28
5.1.5.3 Slot occupied detection	28
5.1.5.4 Signal level indication.....	28
5.1.6 Transmission processing.....	28
5.1.7 Received transmission processing	28
5.2 VSS sublayer	28
5.2.1 Services.....	28
5.2.1.1 Error detection.....	28
5.2.1.2 Channel congestion	29
5.2.2 Burst format.....	29
5.2.2.1 VSS burst structure	29
5.2.2.2 Version number.....	29

5.2.2.3	Source address.....	30
5.2.2.4	Message ID	30
5.2.2.5	Information field	30
5.2.2.6	Reservation fields.....	31
5.2.2.7	Autonomous/directed flag	31
5.2.3	VSS sublayer parameters	32
5.2.3.1	General	32
5.2.3.2	Parameter VS1 (number of ground quarantined slots)	32
5.2.3.3	Parameter VS2 (minimum CCI performance).....	33
5.2.3.4	Parameter VS4 (quarantine slot re-use range).....	33
5.2.3.5	Parameter VS5 (maximum burst length).....	33
5.2.4	VSS quality of service parameters	33
5.2.4.1	General	33
5.2.4.2	Parameter Q1 (priority)	34
5.2.4.3	Parameters Q2a to Q2d (slot selection range constraint for level n)	34
5.2.4.4	Parameter Q3 (replace queued data)	35
5.2.4.5	Parameter Q4 (number of available slots)	35
5.2.5	Received transmission processing	35
5.2.6	Reserved access protocol specification	36
5.2.6.1	Reservation table	36
5.2.6.2	Selecting slots for transmission or reservation	36
5.2.6.3	Reserved transmissions	37
5.2.6.4	Reservation conflicts	37
5.2.7	Random access protocol specification	38
5.2.7.1	General	38
5.2.7.2	Random access parameters.....	38
5.2.7.3	Random access procedures.....	39
5.2.8	Fixed access protocol specification	40
5.2.8.1	General	40
5.2.8.2	Recommendation	40
5.2.9	Null reservation protocol specification	40
5.2.9.1	Null reservation burst format	40
5.2.10	Periodic broadcast protocol specification	40
5.2.10.1	Periodic broadcast reservation burst format	40
5.2.10.2	Periodic broadcast timers	41
5.2.10.3	Periodic broadcast parameters.....	41
5.2.10.4	Periodic broadcast reception procedures	42
5.2.10.5	Periodic broadcast transmission procedures.....	43
5.2.11	Incremental broadcast protocol specification	44
5.2.11.1	Incremental broadcast reservation burst format	44
5.2.11.2	Incremental broadcast parameters	45
5.2.11.3	Incremental broadcast reception procedures	45
5.2.11.4	Incremental broadcast transmission procedures	46
5.2.12	Combined periodic broadcast and incremental broadcast protocol specification	46
5.2.12.1	Combined periodic broadcast and incremental broadcast reservation burst	46
5.2.13	Big negative dither (BND) broadcast protocol specifications	47
5.2.13.1	BND reservation burst format	47
5.2.13.2	BND broadcast parameters.....	47
5.2.13.3	BND broadcast reception procedures	47
5.2.14	Unicast request protocol specification	47
5.2.14.1	Unicast request reservation burst format.....	47
5.2.14.2	Unicast request reception procedures	48
5.2.14.3	Slot selection criteria for unicast request with sdf = 1	49
5.2.15	Information transfer request protocol specification	49
5.2.15.1	Information transfer request reservation burst format	49
5.2.15.2	Information transfer request reception procedures	50
5.2.16	Directed request protocol specification.....	50
5.2.16.1	Directed request reservation burst format	50
5.2.16.2	Directed request parameters	54
5.2.16.3	Directed request reception procedures	54
5.2.16.4	Directed request transmission procedures	56
5.2.17	Block reservation protocols specification	57

5.2.17.1	Superframe block reservation burst format	57
5.2.17.2	Second frame block reservation burst format.....	58
5.2.17.3	Superframe block reservation parameters	58
5.2.17.4	Superframe block reservation reception procedures	59
5.2.17.5	Second frame block reservation parameters.....	59
5.2.17.6	Second frame block reservation reception procedures	60
5.2.17.7	Superframe block reservation transmission procedures	61
5.2.17.8	Second frame block reservation transmission procedures.....	61
5.2.18	Response protocol specification	62
5.2.18.1	Response burst format.....	62
5.2.19	General request protocol specification.....	62
5.2.19.1	General request burst format	62
5.2.19.2	General request procedures	63
5.2.20	General response protocol specification	63
5.2.20.1	General response burst format.....	63
5.2.20.2	General response procedures.....	64
5.3	DLS sublayer.....	65
5.3.1	Services.....	65
5.3.1.1	General	65
5.3.1.2	Data transfer	65
5.3.1.3	Station address encoding.....	65
5.3.1.4	DLS burst formats	66
5.3.2	DLS system parameters	67
5.3.2.1	Parameter ND4 (maximum length of a UDATA burst)	68
5.3.3	DLS procedures	68
5.3.3.1	Broadcast.....	68
5.3.3.2	DLS not supported.....	68
5.3.3.3	User data packet reception.....	68
5.4	Link Management Entity sublayer.....	68
5.4.1	Services.....	68
5.4.2	Synchronization burst format.....	68
5.4.2.1	General	68
5.4.2.2	Fixed and variable data fields.....	69
5.4.2.3	Fixed data field format.....	69
5.4.2.4	Variable data field format	72
5.4.2.5	Synchronization burst request	72
5.4.2.6	Link management burst.....	72
5.4.3	Control (CTRL) parameter formats	73
5.4.3.1	Encoding	73
5.4.3.2	VDL Mode 4 parameter identification	73
5.4.3.3	Ground-initiated modification parameters	74
5.4.3.4	Ground-initiated information parameters	75
5.4.4	LME procedures	78
5.4.4.1	Synchronization burst procedures	78
5.4.4.2	Peer entity contact table (PECT).....	79
5.4.4.3	Network entry protocol specifications	80
5.4.5	Additional material for ADS-B applications	81
5.4.5.1	Information field formats	81
5.4.5.2	ADS-B request format.....	81
5.5	Additional requirements for ground stations	81
5.5.1	System timing requirements	81
5.5.1.1	Maintenance of Primary time	81
5.5.2	Ground station interface requirements.....	82
5.5.2.1	Ground station coordination.....	82
5.5.2.2	Network timing requirements.....	82
5.5.2.3	Application interface requirements	82
5.5.2.4	Transmission control requirements	82
5.5.2.5	Superframe block reservation rebroadcast procedures.....	83
5.5.2.6	Fixed transmission parameters	83
5.5.2.7	Protection of fixed access protocol transmissions by ground quarantine	83
5.5.2.8	Protection of fixed access protocol transmissions by use of appropriate reservation protocols.....	83
5.5.2.9	Restriction of autotune reservations	84

5.5.2.10	Transmission time for autotune reservations.....	84
5.5.2.11	Reporting of channel usage.....	84
5.6	Definitions for compact position reporting.....	84
5.6.1	Introduction.....	84
5.6.2	Parameter symbols, data types, constants and variables.....	84
5.6.2.1	Parameter symbols.....	84
5.6.2.2	Data types.....	85
5.6.2.3	Constants.....	85
5.6.2.4	Variables.....	85
5.6.2.5	Functions.....	86
5.6.2.6	Patch constants.....	87
5.6.3	Fixed data field position encoding.....	89
5.6.3.1	General.....	89
5.6.3.2	Input parameters.....	89
5.6.3.3	Calculations.....	89
5.6.4	Fixed data field position local decoding.....	89
5.6.4.1	General.....	89
5.6.4.2	Input parameters.....	90
5.6.4.3	Calculations.....	90
5.6.5	Fixed data field position global decoding.....	91
5.6.5.1	General.....	91
5.6.5.2	Input parameters.....	91
5.6.5.3	Transition level straddling.....	91
5.6.5.4	Calculations.....	92
5.6.6	Position report processing.....	92
5.6.6.1	Services.....	92
5.6.6.2	Position report parameters.....	92
5.6.6.3	Position report processing procedures.....	93
6	General design requirements.....	95
6.1	Controls and indicators.....	95
6.2	Operation of controls.....	95
6.3	Warm up.....	95
6.4	Effects of tests.....	95
6.5	Software management.....	96
6.6	Recovery from failure.....	96
6.6.1	Failure of the VDL equipment.....	96
6.7	Monitoring of proper operation.....	96
7	Protocol test procedures.....	96
7.1	General.....	96
7.1.1	Input voltage.....	96
7.1.2	Power input frequency.....	96
7.1.3	Adjustment of equipment.....	97
7.1.4	Equipment configuration.....	97
7.1.5	Test equipment.....	97
7.1.6	Test equipment precautions.....	97
7.1.7	Ambient conditions.....	97
7.1.8	Connected loads.....	97
7.1.9	Warm-up period.....	97
7.2	Required test rig.....	97
7.3	Protocol test-suite description methodology.....	100
7.4	Detailed protocol test procedures.....	100
7.4.1	Test-suite overview.....	100
7.4.2	Declarations.....	104
7.4.3	Constraints.....	105
7.4.3.1	Abbreviations.....	105
7.4.3.1.1	Subfield mnemonics.....	105
7.4.3.1.2	Special characters used in the subfield definitions.....	106
7.4.3.1.3	Station addresses and positions.....	106
7.4.3.1.4	Tables of values for use in CPR test cases.....	108
7.4.3.1.5	Tables of values for use in content checking test cases.....	118

7.4.3.1.6	VDL4 burst formats.....	121
7.4.3.2	Test cases	138
7.4.3.2.1	Test case macros.....	139
7.4.3.2.2	Test case descriptions.....	141
Annex A (informative):	Cross reference matrix.....	307
Annex B (informative):	Description of ISO/IEC 9646 Test Methodology.....	322
B.1	Overview of the structure of the ISO/IEC 9646 Test-Suites.....	322
B.2	Test case description	322
B.3	Queue action.....	324
B.4	Repeat construct	324
B.5	Macro definitions	325
B.6	Test case naming	325
Annex C (informative):	Bibliography.....	326
History		331

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 842-2 V1.3.1:2006

<https://standards.iteh.ai/catalog/standards/sist/6211f3c7-7e8c-4cdd-b842-fc8a3635a400/sist-en-301-842-2-v1-3-1-2006>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document is part 2 of a multi-part deliverable covering the VHF air-ground Data Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment, as identified below:

Part 1: "General description and physical layer";

Part 2: "Data link layer";

Part 3: "Additional broadcast aspects";

Part 4: "Point-to-point functions".

STANDARD PREVIEW
(standards.iteh.ai)

The present document is accompanied by an equivalent airborne standard, EN 302 842 Parts 1 to 4, covering the VHF air-ground Data Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for airborne equipment.

National transposition dates	
Date of adoption of this EN:	6 August 2004
Date of latest announcement of this EN (doa):	30 November 2004
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 May 2005
Date of withdrawal of any conflicting National Standard (dow):	31 May 2005

Introduction

The present document states the technical specifications for Very High Frequency (VHF) Digital Link (VDL) Mode 4 ground stations for air-ground communications operating in the VHF band (117,975 MHz to 136,975 MHz), using Gaussian-filtered Frequency Shift Keying (GFSK) Modulation with 25 kHz channel spacing. Optionally, the ground stations may tune between 112,000 MHz to 117,975 MHz.

The present document may be used to produce tests for the assessment of the performance of the equipment. The performance of the equipment submitted for type testing should be representative of the performance of the corresponding production model.

The present document has been written on the assumption that:

- the type test measurements will be performed only once, in an accredited test laboratory and the measurements accepted by the various authorities in order to grant type approval;
- if equipment available on the market is required to be checked it will be tested in accordance with the methods of measurement specified in the present document or a documented alternative approved by the certifying authority;
- Equipment comply with EN 301 489-22 [2] and EN 301 842-1 [4].

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 842-2 V1.3.1:2006](https://standards.iteh.ai/catalog/standards/sist/6211f3c7-7e8c-4cdd-b842-fc8a3635a400/sist-en-301-842-2-v1-3-1-2006)

<https://standards.iteh.ai/catalog/standards/sist/6211f3c7-7e8c-4cdd-b842-fc8a3635a400/sist-en-301-842-2-v1-3-1-2006>

1 Scope

The present document states part 2 of the minimum performance requirements for VHF Datalink Mode 4 (VDL Mode 4) ground station equipment intended to be used for air-ground data communications, operating in the VHF band (117,975 MHz to 136,975 MHz and optionally 112,000 MHz to 117,975 MHz) allocated to the aeronautical mobile service. The equipment is also intended to be interoperable with mobile equipment supporting air-air data communications. It is designed to ensure that equipment certified to it will be compatible with the relevant ICAO VHF Digital Link (VDL) Standards and Recommended Practices (SARPs) and VDL Mode 4 Technical Manual (TM) [1].

Manufacturers should note that all or part of the frequency band 108,000 MHz to 117,975 MHz might become available for aeronautical communications.

The present document applies to Gaussian-filtered Frequency Shift Keying (GFSK) systems, with channel separations of 25 kHz intended for air-ground communications. The scope of the present document is limited to ground base stations.

The VDL system provides data communication exchanges between aircraft and ground based systems supporting surveillance and communication applications. The supported modes of communication include:

- broadcast and point-to-point communication;
- broadcast services including Automatic Dependent Surveillance - Broadcast (ADS-B), Traffic Information Service – Broadcast (TIS-B) and Flight Information Service - Broadcast (FIS-B) capabilities;
- air-air and ground-air services;
- operation without ground infrastructure.

VDL Mode 4 is designed to be an Air/Ground subsystem of the Aeronautical Telecommunication Network (ATN) [8] using the AM(R)S band and it is organized according to the Open Systems Interconnection (OSI) model (defined by ISO). It provides reliable sub network services to the ATN system. Other networks can also be supported but these have not been focussed on in the present document.

The present document specifies functional specifications of VHF communication ground station equipment intended to be used for air-ground and air-air data communications. The present document is derived from the standards and specifications in:

- VDL Mode 4 standards produced under the auspices of the International Civil Aviation Organization (ICAO) [1].
- Other relevant standards as defined in clause 2.

It is envisaged that manufacturers may provide equipment supporting:

- broadcast services only;
- point-to-point services only;
- both broadcast and point-to-point services.

EN 301 842-1 [4] deals with tests of the physical layer. The present document defines the core link layer requirements for the VDL Mode 4 ground station necessary to support all types of equipment. This includes a simple position broadcast functionality.

The present document deals with tests of the link layer sufficient to support core link layer functionality, and it also includes requirements and tests sufficient to recognize and respond to transmissions associated with point-to-point communication. The present document does not address requirements for the full ADS-B message set, or for other broadcast applications that can be supported by the VDL Mode 4 equipment. These are covered by EN 301 842-3 [9]. Detailed requirements for point-to-point communication are beyond the scope of the present document, but can be found in EN 301 842-4 [10]. EN 301 842-4 [10] also include the interface to the Aeronautical Telecommunication Network (ATN) as defined in ATN SARPs [8].

As the measured values of equipment performance may be a function of the method of measurement, standard test conditions and methods of test are recommended in the present document.

The present document is organized as follows:

- references, definitions, abbreviations and symbols are provided in clauses 2 and 3;
- clause 4 describes the VDL Mode 4 ground station link layer;
- clause 5 performance specifications for the VDL Mode 4 ground station and ground station co-ordination;
- clause 6 provides general design requirements;
- clause 7 provides protocol tests for core link layer functions;
- a document history is contained in clause 8;
- clause A provides a detailed cross-reference to the relevant requirements contained in reference [1];
- annex B provides a description of the ISO/IEC 9646 [7] Test Methodology.

Note that the system can support a very wide range of functions. It is not practical to provide specific tests for all aspects of its functionality. The approach used is to provide detailed tests for the core link layer functionality and to provide tests of those remaining requirements which, if wrongly implemented, could cause a deterioration in the service offered by other VDL Mode 4 stations. Therefore:

- a detailed set of protocol tests are provided for the core link layer functionality necessary to support broadcast functions;
- a detailed test of position encoding and decoding is provided because of the importance of position in the management of the VDL Mode 4 link specifically and the need to support ADS-B applications in general.

Mandating and Recommendation Phrases

- SIST EN 301 842-2 V1.3.1:2006
<https://standards.iteh.ai/catalog/standards/sist/6211f3c7-7e8c-4cdd-b842-f8a3635a400/sist-en-301-842-2-v1-3-1-2006>
- a) "Shall":
 the use of the word "Shall" indicates a mandated criterion; i.e. compliance with the particular procedure or specification is mandatory and no alternative may be applied.
- b) "Should":
 the use of the word "Should" (and phrases such as "It is recommended that...", etc.) indicates that though the procedure or criterion is regarded as the preferred option, alternative procedures, specifications or criteria may be applied, provided that the manufacturer, installer or tester can provide information or data to adequately support and justify the alternative.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

- [1] "Annex 10 to the Convention on International Civil Aviation", International Civil Aviation Organization, 2004.

- [2] ETSI EN 301 489-22: "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 22: Specific conditions for ground based VHF aeronautical mobile and fixed radio equipment".
- [3] ISO/IEC 13239 (2002): "Information technology - Telecommunications and information exchange between systems - High-level Data Link Control (HDLC) procedures".
- [4] ETSI EN 301 842-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); VHF air-ground Data Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment; Part 1: General description and physical layer".
- [5] ISO/IEC 7498-1 (1994): "Information technology - Open Systems Interconnection - Basic Reference Model: The Basic Model".
- [6] ISO/IEC 10731 (1994): "Information technology - Open Systems Interconnection - Basic Reference Model - Conventions for the definition of OSI services".
- [7] ISO/IEC 9646 (all parts): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework".
- [8] ICAO Doc 9705 - AN/956 (Edition 3 - 2002): "Manual of Technical Provisions for the Aeronautical Telecommunication Network (ATN)".

NOTE: See http://www.icao.int/icao/en/cd_pub_list.htm.

- [9] ETSI EN 301 842-3: "Electromagnetic compatibility and Radio spectrum Matters (ERM); VHF air-ground Data Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment; Part 3: Additional Broadcast aspects".
- [10] ETSI EN 301 842-4: "Electromagnetic compatibility and Radio spectrum Matters (ERM); VHF air-ground Data Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment; Part 4: Point-to-point functions".
- [11] Eurocontrol ESARR 6 (2003): "Software in ATM Systems".
- [12] ETSI EN 300 676: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Ground-based VHF hand-held, mobile and fixed radio transmitters, receivers and transceivers for the VHF aeronautical mobile service using amplitude modulation; Technical characteristics and methods of measurement".

3 Definitions and abbreviations

3.1 Definitions

3.1.1 Basic reference model definitions

The present document is based on the concepts developed in the open systems interconnect basic reference model. For the purposes of the present document the terms and definitions given in ISO/IEC 7498-1 [5] applies for:

- layer;
- sublayer;
- entity;
- service;
- physical layer;
- data link layer.

3.1.2 Service conventions definitions

For the purposes of the present document, the terms and definitions given in ISO/IEC 10731 [6] apply for:

- service provider;
- request;
- indication;
- confirm.

3.1.3 General definitions

For the purposes of the present document, the terms and definitions given in EN 301 842-1 [4] clause 3.1.3 and the following apply:

Aeronautical Mobile Service (AMS): mobile service between aeronautical stations and aircraft stations, or between aircraft stations, in which survival craft stations may participate

Aeronautical Telecommunications Network (ATN): internetwork architecture that allows ground, air/ground, and aircraft data sub networks to interoperate by adopting common interface services and protocols based on the International Organization for Standardization Open Systems Interconnection Reference Model

aircraft address: unique combination of 24 bits available for assignment to an aircraft for the purpose of air-ground communications, navigation and surveillance

NOTE: An aircraft may choose not to use this unique address and can use instead a non-unique address.

Automatic Dependent Surveillance-Broadcast (ADS-B): surveillance application transmitting parameters, such as position, track, ground speed and time via a broadcast mode data link for use by any air and/or ground users requiring it

NOTE: ADS-B is a surveillance service based on aircraft self-determination of position/velocity/time and automatic, periodic, broadcast of this information along with auxiliary data such as aircraft identity (ID), intent information and communications control parameters, etc. ADS-B is intended to support multiple high-level applications and associated services such as cockpit display of traffic information, traffic alert and collision avoidance functionality, enhanced traffic management in the air and on the ground, search and rescue support and others.

autotune: procedure by which a VDL Mode 4 ground station may direct a mobile VDL Mode 4 station to transmit on a specified frequency, and with certain characteristics, by sending an uplink burst containing an autotune reservation

burst: VHF Digital Link (VDL) specific services burst is composed of a sequence of source address, burst ID, information, slot reservation, and Cyclic Redundancy Code (CRC) fields, bracketed by opening and closing flag sequences

NOTE: The start of a burst may occur only at quantized time intervals and this constraint allows the propagation delay between the transmission and reception to be derived.

burst length: number of slots across which the VDL Mode 4 burst is transmitted

CTRL DLPDU: basic unit of transmission of the LME and VME

current slot: slot in which a received transmission begins

Data Link Entity (DLE): protocol state machine capable of setting up and managing a single data link connection

Data Link Protocol Data Unit (DLPDU): general burst format used by the Data Link Service (DLS) sublayer

Data Link Service (DLS) sublayer: resides above the VDL Mode 4 Specific Services (VSS) and the MAC sublayers

NOTE: The Data Link Service (DLS) manages the transmit queue, creates and destroys Data Link Entities (DLEs) for connection-oriented communications, provides facilities for the Link Management Entity (LME) to manage the DLS, and provides facilities for connection-less communications.