



SLOVENSKI STANDARD
SIST EN 300 392-2 V2.4.2:2006

01-april-2006

Prizemni snopovni radio (TETRA) – Govor in podatki (V+D) – 2. del: Radijski vmesnik (AI)

Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 392-2 V2.4.2:2006](https://standards.iteh.ai/catalog/standards/sist/641fb712-ab0c-4d11-8aa0-1e14d63c12b5/sist-en-300-392-2-v2-4-2-2006)

Ta slovenski standard je istoveten z: **EN 300 392-2 Version 2.4.2**

ICS:

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	---------------------------------	-----------------------------------

SIST EN 300 392-2 V2.4.2:2006 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 392-2 V2.4.2:2006

<https://standards.iteh.ai/catalog/standards/sist/641fb712-ab0c-4d11-8aa0-fe14db5ef2b5/sist-en-300-392-2-v2-4-2-2006>

ETSI EN 300 392-2 V2.4.2 (2004-02)

European Standard (Telecommunications series)

Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 392-2 V2.4.2:2006](https://standards.iteh.ai/catalog/standards/sist/641fb712-ab0c-4d11-8aa0-fe14db5ef2b5/sist-en-300-392-2-v2-4-2-2006)

<https://standards.iteh.ai/catalog/standards/sist/641fb712-ab0c-4d11-8aa0-fe14db5ef2b5/sist-en-300-392-2-v2-4-2-2006>



Reference

REN/TETRA-03097

Keywords

radio, TETRA, V+D**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 392-2 V2.4.2:2006

<https://standards.iteh.ai/catalog/standards/sist/641fb712-ab0c-4d11-8aa0-fe14db5ef21b/etsi-en-300-392-v2-4-2-2006>
Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.org

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2004.
All rights reserved.

DECT™, **PLUGTESTS™** and **UMTS™** are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	29
Foreword.....	29
1 Scope	31
2 References	32
3 Definitions and abbreviations.....	34
3.1 Definitions	34
3.2 Abbreviations	39
4 Radio aspects.....	42
4.1 Introduction	42
4.2 Set of logical channels.....	42
4.3 Reference configuration	42
4.4 Error control schemes.....	43
4.5 Multiple access and time slot structure.....	43
4.5.1 Hyperframes, multiframe and frames.....	44
4.5.2 Time slots and bursts	44
4.5.3 Mapping of logical channels onto physical channels.....	45
4.6 Coding, interleaving and scrambling.....	45
4.7 Modulation	45
4.8 Transmission and reception.....	45
4.9 Other radio-related functions.....	45
4.10 Performance	46
4.11 TETRA modes of operation	46
4.11.1 Transmission modes	46
4.11.1.1 D-CT mode	46
4.11.1.2 D-CTT mode.....	46
4.11.1.3 D-MCCTT mode.....	46
4.11.1.4 U-MST mode	46
4.11.2 Control modes.....	47
4.11.2.1 NCM	47
4.11.2.2 MC mode	47
5 Modulation	47
5.1 Introduction	47
5.2 Modulation type	47
5.3 Modulation rate	47
5.4 Modulation symbol definition.....	47
5.5 Modulated signal definition.....	48
5.6 Modulation filter definition.....	49
5.7 Modulation block diagram	49
6 Radio transmission and reception.....	49
6.1 Introduction	49
6.2 Frequency bands and channel arrangement.....	49
6.3 Reference test planes	50
6.4 Transmitter characteristics.....	50
6.4.1 Output power	50
6.4.1.1 Base Station (BS).....	51
6.4.1.2 Mobile Station (MS)	51
6.4.2 Unwanted conducted emissions.....	51
6.4.2.1 Definitions.....	51
6.4.2.2 Unwanted emissions close to the carrier	52
6.4.2.2.1 Emission during the useful part of the burst.....	52
6.4.2.2.2 Emission during the switching transients	53
6.4.2.3 Unwanted emissions far from the carrier	53
6.4.2.4 Unwanted emissions during the CLCH and BLCH	54

6.4.2.5	Unwanted emissions in the non-transmit state	54
6.4.3	Unwanted radiated emissions	54
6.4.4	RF tolerance.....	54
6.4.5	RF Output power time mask	54
6.4.5.1	BS.....	55
6.4.5.2	MS.....	55
6.4.6	Transmitter intermodulation attenuation.....	55
6.4.6.1	Definition	55
6.4.6.2	BS.....	56
6.4.6.3	MS.....	56
6.4.7	Intra-BS intermodulation requirements	56
6.5	Receiver characteristics	56
6.5.1	Blocking characteristics	56
6.5.1.1	Definition	56
6.5.1.2	Specification.....	57
6.5.2	Spurious response rejection	57
6.5.2.1	Definition	57
6.5.2.2	Specification.....	57
6.5.3	Intermodulation response rejection.....	58
6.5.3.1	Definition	58
6.5.3.2	Specification.....	58
6.5.4	Unwanted conducted emissions	58
6.5.4.1	Definition	58
6.5.4.2	Specification.....	58
6.5.5	Unwanted radiated emissions	58
6.6	Transmitter/receiver performance	58
6.6.1	Modulation accuracy.....	59
6.6.1.1	Ideal case.....	59
6.6.1.2	Vector error magnitude requirement at symbol time	59
6.6.2	Receiver performance	60
6.6.2.1	Nominal error rates	60
6.6.2.2	Dynamic reference sensitivity performance	61
6.6.2.2.1	BS receiver performance	61
6.6.2.2.2	MS receiver performance	61
6.6.2.3	Receiver performance at reference interference ratios	62
6.6.2.3.1	BS receiver performance	62
6.6.2.3.2	MS receiver performance	63
6.6.2.4	Static reference sensitivity performance	63
6.6.2.4.1	BS receiver performance	63
6.6.2.4.2	MS receiver performance	64
6.6.2.5	MS receiver performance for synchronization burst acquisition.....	64
6.6.3	Propagation conditions	64
6.6.3.1	Propagation conditions - introduction	64
6.6.3.2	Tap-gain process types.....	65
6.6.3.3	Propagation models.....	65
7	Radio sub-system synchronization	66
7.1	Introduction	66
7.2	General description of synchronization system.....	66
7.3	Timebase counters	67
7.3.1	Timing counters	67
7.3.2	Values of the counters.....	67
7.4	Timing of transmitted signals.....	67
7.5	BS requirements for synchronization	68
7.6	MS requirements for synchronization	68
8	Channel coding and scrambling	68
8.1	Introduction	68
8.2	General	69
8.2.1	Interfaces in the error control structure.....	69
8.2.2	Notation	70
8.2.3	Definition of error control codes.....	70

8.2.3.1	16-state Rate-Compatible Punctured Convolutional (RCPC) codes	70
8.2.3.1.1	Encoding by the 16-state mother code of rate $\frac{1}{4}$	70
8.2.3.1.2	Puncturing of the mother code.....	71
8.2.3.1.3	Puncturing scheme of the RCPC code of rate $\frac{2}{3}$	71
8.2.3.1.4	Puncturing scheme of the RCPC code of rate $\frac{1}{3}$	71
8.2.3.1.5	Puncturing scheme of the RCPC code of rate $\frac{292}{432}$	71
8.2.3.1.6	Puncturing scheme of the RCPC code of rate $\frac{148}{432}$	71
8.2.3.2	Shortened (30,14) Reed-Muller (RM) code	72
8.2.3.3	$(K_I + 16, K_I)$ block code	72
8.2.4	Definition of interleaving schemes	73
8.2.4.1	Block interleaving	73
8.2.4.2	Interleaving over N blocks	73
8.2.5	Definition of scrambling	73
8.2.5.1	Scrambling method	73
8.2.5.2	Scrambling sequence.....	73
8.3	Error control schemes.....	74
8.3.1	Access Assignment Channel (AACH).....	75
8.3.2	Broadcast Synchronization Channel (BSCH)	75
8.3.3	Traffic channels in circuit switched mode	76
8.3.3.1	Traffic CHannel, net rate = 4,8 kbit/s (TCH/4,8).....	76
8.3.3.2	Traffic CHannel, net rate = 2,4 kbit/s (TCH/2,4).....	77
8.3.3.3	Traffic CHannel, net rate = 7,2 kbit/s (TCH/7,2).....	77
8.3.3.4	Speech Traffic Channel, full slot (TCH/S).....	78
8.3.3.5	Speech Traffic Channel, half slot (TCH/S)	78
8.3.4	Signalling channels for signalling and packet mode data	78
8.3.4.1	Signalling CHannel for mapping onto Half-bursts on the Downlink (SCH/HD), Broadcast Network CHannel (BNCH), and STealing CHannel (STCH)	78
8.3.4.2	Signalling CHannel for mapping onto Half-bursts on the Uplink (SCH/HU).....	79
8.3.4.3	Signalling CHannel for mapping onto Full bursts (SCH/F).....	79
9	Channel multiplexing for V+D.....	80
9.1	Introduction	80
9.2	Logical channels.....	80
9.2.1	Logical channels hierarchy.....	80
9.2.2	Traffic channels	80
9.2.3	Control CHannels (CCH).....	80
9.2.3.1	General	80
9.2.3.2	BCCH.....	81
9.2.3.3	LCH.....	81
9.2.3.4	SCH.....	81
9.2.3.5	AACH	81
9.2.3.6	STCH	81
9.3	The physical resource	82
9.3.1	General.....	82
9.3.2	RF channels	82
9.3.3	Timeslots	83
9.3.4	TDMA frame	83
9.3.5	Timeslot numbering	83
9.3.6	Subslot	83
9.3.7	Multiframe	83
9.3.8	Hyperframe	83
9.3.9	Frame alignment	83
9.4	Physical channels	83
9.4.1	General.....	83
9.4.2	Types of physical channels	84
9.4.2.1	CP channel	84
9.4.2.2	TP channel.....	84
9.4.2.3	UP channel	84
9.4.3	Bursts	84
9.4.3.1	General	84
9.4.3.2	Modulation symbol numbering	84
9.4.3.3	Modulation bit numbering.....	85

9.4.3.4	Burst timing.....	85
9.4.4	Type of bursts	85
9.4.4.1	General	85
9.4.4.2	Modulation bits allocation.....	87
9.4.4.2.1	Control uplink Burst (CB).....	87
9.4.4.2.2	Linearization uplink Burst (LB).....	87
9.4.4.2.3	Linearization downlink burst.....	87
9.4.4.2.4	Normal Uplink Burst (NUB).....	88
9.4.4.2.5	Normal continuous downlink burst	88
9.4.4.2.6	Synchronization continuous downlink burst.....	88
9.4.4.2.7	Normal discontinuous downlink burst.....	89
9.4.4.2.8	Synchronization discontinuous downlink burst.....	89
9.4.4.3	Burst fields	89
9.4.4.3.1	Frequency correction field.....	89
9.4.4.3.2	Normal training sequence.....	90
9.4.4.3.3	Extended training sequence.....	90
9.4.4.3.4	Synchronization training sequence.....	90
9.4.4.3.5	Tail bits.....	90
9.4.4.3.6	Phase adjustment bits	91
9.4.5	Transmission modes	91
9.4.5.1	BS continuous transmission	91
9.4.5.2	BS timesharing transmission.....	92
9.4.5.3	MS multiple slot transmission.....	92
9.5	Mapping of logical channels into physical channels	93
9.5.1	General mapping of logical channels.....	93
9.5.2	Mapping of BCCH and CLCH	94
9.5.3	Mapping of SCH.....	95
9.5.4	Mapping of TCH and STCH.....	95
9.5.5	Mapping of AACCH	95
9.6	Monitoring pattern for transmitting MSs.....	95
9.7	BS timesharing transmission	96
9.7.1	Carrier sharing	96
9.7.2	MCCH sharing.....	96
9.8	Modes of control	96
9.8.1	NCM.....	96
9.8.2	MCM	97
10	Radio subsystem link control	97
10.1	Introduction	97
10.2	RF power control.....	98
10.3	Radio link measurements	98
10.3.1	Received signal strength	98
10.3.1.1	Sample duration for signal strength measurement	98
10.3.2	Signal quality	98
10.3.3	Round-trip MS-BS path delay	98
11	Call Control (CC) service description	98
11.1	Introduction	98
11.2	Services offered.....	98
11.3	CC service	99
11.3.1	CC primitives exchanged through the TNCC-SAP	99
11.3.2	Service primitives at the TNCC-SAP	99
11.3.3	Primitive description.....	100
11.3.3.1	TNCC-ALERT primitive	100
11.3.3.2	TNCC-COMplete primitive	101
11.3.3.3	TNCC-DTMF primitive	101
11.3.3.4	TNCC-MODIFY primitive	102
11.3.3.5	TNCC-NOTIFY primitive	102
11.3.3.6	TNCC-PROCEED primitive.....	103
11.3.3.7	TNCC-RELEASE primitive.....	103
11.3.3.8	TNCC-SETUP primitive	103
11.3.3.9	TNCC-TX primitive.....	104

11.3.4	Parameter description	105
11.4	States for CC SAP	112
12	Supplementary Service (SS) service description.....	113
12.1	Introduction	113
12.2	Services offered.....	113
12.3	SS service	113
12.3.1	Primitives exchanged through TNSS-SAP	113
12.3.2	Parameter description	113
13	Short Data Service (SDS) service description.....	114
13.1	Introduction	114
13.2	Services offered.....	114
13.3	SDS	114
13.3.1	SDS primitives exchanged through the TNSDS-SAP	114
13.3.2	Service primitives at the TNSDS-SAP	115
13.3.2.1	TNSDS-STATUS primitive	115
13.3.2.2	TNSDS-REPORT primitive.....	116
13.3.2.3	TNSDS-UNITDATA primitive.....	116
13.3.2.4	TNSDS-CANCEL primitive	117
13.3.3	Parameter description	117
13.3.4	State description.....	119
13.3.4.1	NULL state.....	119
13.3.4.2	SHORT DATA INITIATED state	119
13.3.5	Service state diagram for the TNSDS-SAP	120
14	CMCE protocol	120
14.1	Introduction	120
14.2	Overview of CMCE.....	120
14.2.1	Communication routes of the CMCE model.....	121
14.2.2	Protocol structure and protocol stack.....	122
14.2.3	Addressing rules	124
14.2.4	CC, SS and SDS sub-entities	124
14.2.4.1	CC sub-entity	124
14.2.4.2	SS sub-entity	125
14.2.4.3	SDS sub-entity	125
14.2.5	PC sub-entity	125
14.2.6	Internal routes	126
14.2.7	Intra-CMCE primitive summary.....	128
14.2.7.1	Down link CC PDU parameters	128
14.2.7.2	Uplink CC PDU parameters.....	128
14.2.7.3	Downlink SS PDU parameters.....	129
14.2.7.4	Uplink SS PDU parameters.....	129
14.2.7.5	Down link SDS PDU parameters	129
14.2.7.6	Uplink SDS PDU parameters.....	129
14.2.7.7	CMCE management primitives.....	129
14.2.7.7.0	ACTIVITY request.....	129
14.2.7.7.1	BREAK indication.....	129
14.2.7.7.1a	BUSY indication	129
14.2.7.7.2	CANCEL request.....	130
14.2.7.7.3	CLOSE indication	130
14.2.7.7.4	CONFIGURE indication	130
14.2.7.7.5	CONFIGURE request.....	130
14.2.7.7.6	IDENTITIES request.....	130
14.2.7.7.6a	IDLE indication	130
14.2.7.7.6b	INFO indication.....	131
14.2.7.7.7	OPEN indication.....	131
14.2.7.7.8	REOPEN indication.....	131
14.2.7.7.9	REPORT indication.....	131
14.2.7.7.10	RESUME indication	131
14.3	Overview of services required by the CMCE.....	131
14.4	CMCE protocol states	131
14.4.1	States for PC	132

14.4.1.1	CLOSED	132
14.4.1.2	OPEN	132
14.4.2	States for CC	133
14.4.2.1	IDLE	135
14.4.2.2	MO-CALL-SETUP	135
14.4.2.3	MT-CALL-SETUP	135
14.4.2.4	CALL ACTIVE	136
14.4.2.5	CALL DISCONNECT	136
14.4.2.6	WAIT	136
14.4.3	States for SS	136
14.4.4	States for SDS	137
14.5	Procedures	137
14.5.1	Individual CC procedures	137
14.5.1.1	Call set-up procedures	138
14.5.1.1.1	Incoming call	139
14.5.1.1.2	Outgoing call	140
14.5.1.1.3	Colliding calls	141
14.5.1.1.4	Unsuccessful call set-up	142
14.5.1.1.5	Call rejection	142
14.5.1.2	Call maintenance procedures	142
14.5.1.2.1	Transmission control procedures	143
14.5.1.2.2	Call status information procedures	147
14.5.1.2.3	Call modification procedures	147
14.5.1.2.4	Call restoration procedures	149
14.5.1.2.5	DTMF procedures	151
14.5.1.2.6	Calls to and from external subscribers	152
14.5.1.3	Call disconnection procedures	153
14.5.1.3.1	User initiated disconnection	153
14.5.1.3.2	Network initiated disconnection	154
14.5.1.3.3	Reception of disconnection request	154
14.5.1.3.4	Expiry of timers	154
14.5.1.3.5	Colliding disconnection	155
14.5.1.4	U-Plane switching	155
14.5.1.4.1	End of call set-up phase	155
14.5.1.4.2	During call maintenance phase	156
14.5.1.4.3	Call disconnection phase	156
14.5.2	Group CC procedures	156
14.5.2.1	Call set-up procedures	157
14.5.2.1.1	Incoming call	158
14.5.2.1.2	Outgoing call	159
14.5.2.1.3	Colliding calls	160
14.5.2.1.4	Unsuccessful call set-up	160
14.5.2.1.5	Call rejection	160
14.5.2.2	Call maintenance procedures	161
14.5.2.2.1	Transmission control procedures	161
14.5.2.2.2	Call status information procedures	165
14.5.2.2.3	Call modification procedures	165
14.5.2.2.4	Call restoration procedures	167
14.5.2.2.5	DTMF procedures	169
14.5.2.2.6	Temporary address handling procedures	169
14.5.2.2.7	Calls to and from external subscribers	170
14.5.2.3	Call disconnection procedures	170
14.5.2.3.1	User initiated disconnection	171
14.5.2.3.2	Network initiated disconnection	171
14.5.2.3.3	Reception of disconnection request	172
14.5.2.3.4	Colliding disconnection	172
14.5.2.3.5	Expiry of timers	172
14.5.2.4	U-Plane switching	173
14.5.2.4.1	End of call set-up phase	173
14.5.2.4.2	During call maintenance phase	173
14.5.2.4.3	Call disconnection phase	174
14.5.2.5	Void	174

14.5.2.6	Acknowledged group call procedures	174
14.5.2.7	Call ownership	175
14.5.3	Traffic channel assignment procedures.....	176
14.5.3.1	SwMI related procedures	176
14.5.3.2	MS related procedures.....	177
14.5.3.2.1	General procedures	177
14.5.3.2.2	Procedures for acceptance of individually-addressed channel allocation.....	178
14.5.3.2.3	Procedures for acceptance of group-addressed channel allocation.....	178
14.5.4	SS procedures	180
14.5.5	SDS procedures	180
14.5.5.1	Incoming short data message	180
14.5.5.2	Outgoing short data messages	180
14.5.6	PC procedures.....	181
14.5.6.1	Access to the communication resources.....	181
14.5.6.2	Access priority handling	181
14.5.6.2.1	Cancel.....	182
14.5.6.3	CMCE PDU exchange	182
14.5.6.3.1	Choice of layer 2 service	182
14.5.6.4	Control information exchange.....	182
14.5.6.5	PC protocol error conditions	183
14.5.6.5.1	PDU type error	183
14.5.6.5.2	Invalid call identifier	183
14.5.6.5.3	MS busy.....	183
14.5.7	Subscriber class	183
14.5.8	Activity handling	183
14.6	Protocol timers	184
14.7	PDU descriptions.....	185
14.7.1	PDU description tables - downlink.....	185
14.7.1.1	D-ALERT.....	185
14.7.1.2	D-CALL PROCEEDING.....	186
14.7.1.3	D-CALL RESTORE	186
14.7.1.4	D-CONNECT.....	187
14.7.1.5	D-CONNECT ACKNOWLEDGE.....	187
14.7.1.6	D-DISCONNECT	188
14.7.1.7	D-FACILITY	188
14.7.1.8	D-INFO	188
14.7.1.9	D-RELEASE.....	189
14.7.1.10	D-SDS-DATA.....	189
14.7.1.11	D-STATUS	190
14.7.1.12	D-SETUP	190
14.7.1.13	D-TX CEASED.....	191
14.7.1.14	D-TX CONTINUE.....	191
14.7.1.15	D-TX GRANTED	192
14.7.1.16	D-TX INTERRUPT	192
14.7.1.17	D-TX WAIT.....	193
14.7.2	PDU description tables - uplink.....	193
14.7.2.1	U-ALERT.....	193
14.7.2.2	U-CALL RESTORE	194
14.7.2.3	U-CONNECT.....	194
14.7.2.4	U-DISCONNECT	195
14.7.2.5	U-FACILITY	195
14.7.2.6	U-INFO	195
14.7.2.7	U-STATUS	196
14.7.2.8	U-SDS-DATA.....	196
14.7.2.9	U-RELEASE.....	197
14.7.2.10	U-SETUP	198
14.7.2.11	U-TX CEASED.....	198
14.7.2.12	U-TX DEMAND.....	199
14.7.3	PDU description tables - downlink and uplink	199
14.7.3.1	General rules for function not supported.....	199
14.7.3.2	CMCE FUNCTION NOT SUPPORTED	199
14.8	Information elements coding.....	200

14.8.1	Area Selection.....	200
14.8.2	Basic service information	201
14.8.3	Call identifier	201
14.8.3a	Call identifier present.....	201
14.8.4	Call ownership	201
14.8.5	Called party type identifier	202
14.8.6	Called party SNA.....	202
14.8.7	Called party extension	202
14.8.8	Called party SSI	202
14.8.9	Calling party type identifier.....	202
14.8.10	Calling party extension	203
14.8.11	Calling party SSI.....	203
14.8.12	Call priority.....	203
14.8.13	Call status	204
14.8.14	Call queued	204
14.8.15	Continue.....	204
14.8.16	Call time-out	205
14.8.17	Call time-out, set-up phase	205
14.8.17a	Circuit mode type	206
14.8.17b	CLIR control	206
14.8.17c	Communication type.....	206
14.8.18	Disconnect cause	207
14.8.18a	DM-MS address.....	207
14.8.19	DTMF	207
14.8.19a	DTMF digit.....	208
14.8.19b	DTMF type	208
14.8.20	External subscriber number	209
14.8.21	Encryption control	209
14.8.21a	Encryption flag	209
14.8.22	Facility	210
14.8.23	Hook method selection	210
14.8.24	Length indicator.....	210
14.8.25	New call identifier.....	210
14.8.26	Modify	210
14.8.27	Notification indicator.....	211
14.8.27a	Other party type identifier.....	211
14.8.27b	Other party SNA.....	211
14.8.27c	Other party extension.....	211
14.8.27d	Other party SSI	211
14.8.28	PDU type	212
14.8.29	Poll request	212
14.8.30	Poll response.....	212
14.8.31	Poll response addresses.....	213
14.8.32	Poll response number.....	213
14.8.33	Poll response percentage.....	213
14.8.34	Pre-coded status	214
14.8.35	Proprietary	214
14.8.36	Request to transmit/send data	214
14.8.37	Reset call time-out timer (T310).....	214
14.8.38	Short data type identifier.....	215
14.8.39	Simplex/duplex selection.....	215
14.8.39a	Slots per frame.....	215
14.8.40	Speech service	215
14.8.41	Temporary address.....	215
14.8.42	Transmission grant.....	216
14.8.43	Transmission request permission.....	216
14.8.44	Transmitting party type identifier	216
14.8.45	Transmitting party extension	216
14.8.46	Transmitting party SSI.....	217
14.8.47	TX demand priority	217
14.8.48	Type 3 element identifier	217
14.8.49	User defined data-1	217

14.8.50	User defined data-2	218
14.8.51	User defined data-3	218
14.8.52	User defined data-4	218
15	Mobility Management (MM) service description	218
15.1	Introduction	218
15.2	Services offered	218
15.3	Primitive description	219
15.3.1	Service state model for the MS	219
15.3.2	Service primitives at the TNMM-SAP, MS/LS side	220
15.3.3	Primitive description	220
15.3.3.1	TNMM-ATTACH DETACH GROUP IDENTITY primitive	220
15.3.3.2	TNMM-DEREGISTRATION primitive	221
15.3.3.3	TNMM-DISABLING primitive	221
15.3.3.4	TNMM-ENABLING primitive	221
15.3.3.5	TNMM-ENERGY SAVING primitive	221
15.3.3.6	TNMM-REPORT primitive	222
15.3.3.7	TNMM-REGISTRATION primitive	222
15.3.3.8	TNMM-SERVICE primitive	223
15.3.3.9	TNMM-STATUS primitive	223
15.3.4	Parameters description	223
15.3.5	State description for the MS	227
15.3.5.1	Not updated	227
15.3.5.2	Wait updating	227
15.3.5.3	Updated	227
15.3.5.4	Temporary disabled	227
15.3.5.5	Permanently disabled	228
15.3.6	Service state diagram for the TNMM-SAP	228
16	MM protocol	231
16.1	Introduction	231
16.2	MM procedures	232
16.2.1	General	232
16.2.2	Services provided by the protocol	232
16.2.3	Underlying services assumed by the protocol	233
16.2.4	Services assumed from the local environment	233
16.3	Protocol functions	233
16.3.1	Activation and control of underlying MLE Service	235
16.3.1.1	Activation procedure	235
16.3.1.2	Deactivation procedure	235
16.3.1.3	Maintenance procedures	236
16.3.1.3.1	Report and cancel handling	236
16.3.1.3.2	Stealing permission and stealing repeats flag handling	236
16.3.1.3.3	Busy handling	236
16.3.1.3.4	Activity handling	236
16.4	Registration procedure	236
16.4.1	MLE initiated registration procedure	237
16.4.1.1	Normal registration	237
16.4.1.2	Forward registration	242
16.4.2	User application initiated registration procedure	244
16.4.3	Infrastructure initiated registration procedure	248
16.4.4	Colliding registrations	250
16.4.5	Expiry of timer T351	250
16.4.6	Expiry of LA timers	250
16.4.7	Lifetime of ASSI/(V)ASSI	251
16.4.7.1	ASSI/(V)ASSI validity at migration	251
16.4.7.2	ASSI/(V)ASSI validity by MS initiative	251
16.4.7.3	ASSI/(V)ASSI validity at registration rejection	251
16.4.8	Temporary registration	251
16.4.9	Subscriber class procedures	252
16.4.10	Frequency band capability procedures	252
16.4.11	Air to ground reporting procedure	253

16.5	Enable and disable procedures	253
16.6	De-registration procedure	254
16.6.1	Trunking mode de-registration	254
16.6.2	Direct mode related de-registration	254
16.7	Energy economy	255
16.7.1	Energy economy mode procedure	255
16.7.2	Procedures for requesting Direct Mode dual watch operation	256
16.7.2.1	Introduction	256
16.7.2.2	MS requesting to start, modify or resume dual watch mode	257
16.7.2.3	MS terminating dual watch mode	258
16.7.2.4	SwMI modifying or terminating dual watch mode	259
16.7.2.5	Changing between modes	259
16.7.2.6	General dual watch procedures	260
16.7.2.7	Idle dual watch without informing SwMI	260
16.7.3	Expiry of timer T352	261
16.8	Attachment/detachment of group identities and group reporting procedures	261
16.8.1	Infrastructure initiated attachment/detachment of group identities procedure	262
16.8.2	MS initiated attachment/detachment of group identities procedure	263
16.8.3	SwMI initiated group report procedure	264
16.8.4	MS initiated group report procedure	265
16.8.5	Expiry of timer T353	266
16.8.6	Colliding requests for group attachment/detachment and group reporting	266
16.8.7	Group Identity Address Type (GIAT) usage in group identity downlink/uplink	266
16.8.8	PDU or function not supported	267
16.9	MM PDU structures and contents	268
16.9.1	MM PDU general description	268
16.9.2	MM PDU description tables - downlink	268
16.9.2.1	D-ATTACH/DETACH GROUP IDENTITY	268
16.9.2.2	D-ATTACH/DETACH GROUP IDENTITY ACKNOWLEDGEMENT	268
16.9.2.3	Void	269
16.9.2.4	Void	269
16.9.2.5	D-MM STATUS	269
16.9.2.5.1	D-MM STATUS generic structure	269
16.9.2.5.2	D-CHANGE OF ENERGY SAVING MODE REQUEST	269
16.9.2.5.3	D-CHANGE OF ENERGY SAVING MODE RESPONSE	270
16.9.2.5.4	D-DUAL WATCH MODE RESPONSE	270
16.9.2.5.5	D-TERMINATING DUAL WATCH MODE RESPONSE	271
16.9.2.5.6	D-CHANGE OF DUAL WATCH MODE REQUEST	271
16.9.2.5.7	Direct mode gateway related D-MM STATUS	272
16.9.2.5.8	D-MS FREQUENCY BANDS REQUEST	272
16.9.2.5.9	DISTANCE REPORTING REQUEST	272
16.9.2.6	Void	272
16.9.2.7	D-LOCATION UPDATE ACCEPT	273
16.9.2.8	D-LOCATION UPDATE COMMAND	273
16.9.2.9	D-LOCATION UPDATE REJECT	273
16.9.2.10	D-LOCATION UPDATE PROCEEDING	274
16.9.3	MM PDU descriptions - uplink	274
16.9.3.1	U-ATTACH/DETACH GROUP IDENTITY	274
16.9.3.2	U-ATTACH/DETACH GROUP IDENTITY ACKNOWLEDGEMENT	275
16.9.3.3	U-ITSI DETACH	275
16.9.3.4	U-LOCATION UPDATE DEMAND	275
16.9.3.5	U-MM STATUS	276
16.9.3.5.1	U-MM STATUS generic construction	276
16.9.3.5.2	U-CHANGE OF ENERGY SAVING MODE REQUEST	276
16.9.3.5.3	U-CHANGE OF ENERGY SAVING MODE RESPONSE	277
16.9.3.5.4	U-DUAL WATCH MODE REQUEST	277
16.9.3.5.5	U-TERMINATING DUAL WATCH MODE REQUEST	278
16.9.3.5.6	U-CHANGE OF DUAL WATCH MODE RESPONSE	278
16.9.3.5.7	U-START OF DIRECT MODE OPERATION	279
16.9.3.5.8	Direct mode gateway related U-MM STATUS	279
16.9.3.5.9	U-MS FREQUENCY BANDS INFORMATION	279
16.9.4	PDU description tables - downlink and uplink	280

16.9.4.1	MM FUNCTION NOT SUPPORTED	280
16.10	MM information elements coding	280
16.10.1	Address extension	280
16.10.2	Cipher control	281
16.10.3	Cipher parameters	281
16.10.4	Void	281
16.10.5	Class of MS	281
16.10.6	Class of usage	282
16.10.7	Disabling type	282
16.10.7a	Default group attachment lifetime	283
16.10.7b	Distance reporting timer	283
16.10.7c	Distance reporting validity	283
16.10.8	Distribution on 18th frame	283
16.10.8a	DMO carrier	284
16.10.8b	Dual watch mode	284
16.10.9	Energy saving mode	285
16.10.10	Energy saving information	285
16.10.11	Frame Number	285
16.10.11a	Frequency band definition	286
16.10.12	Group identity accept/reject	286
16.10.13	Group identity acknowledgement request	286
16.10.14	Group identity acknowledgement type	286
16.10.15	Group identity address type	287
16.10.16	Group identity attachment lifetime	287
16.10.17	Group identity attach/detach mode	287
16.10.18	Group identity attach/detach type identifier	287
16.10.19	Group identity attachment	288
16.10.20	Group identity detachment downlink	288
16.10.21	Group identity detachment uplink	288
16.10.22	Group identity downlink	289
16.10.23	Group identity location accept	289
16.10.24	Group identity location demand	289
16.10.25	Void	289
16.10.26	Group identity report	290
16.10.27	Group identity uplink	290
16.10.27a	Group report response	290
16.10.28	Group Short Subscriber Identity (GSSI)	290
16.10.29	KSG number	291
16.10.30	LA	291
16.10.31	LACC	291
16.10.32	LANC	291
16.10.33	LA timer	291
16.10.34	LA information	292
16.10.34a	Length of the copied PDU	292
16.10.35	Location update type	292
16.10.35a	Location update accept type	293
16.10.36	Mobile Country Code (MCC)	293
16.10.37	Mobile Network Code (MNC)	293
16.10.37a	Mode change information	293
16.10.37b	MS operating with type 2 repeater	294
16.10.38	Multiframe Number (MN)	294
16.10.38a	Not-supported PDU type	294
16.10.38b	Number of frequency band definitions	294
16.10.39	PDU type	295
16.10.40	New registered area	295
16.10.41	Proprietary	295
16.10.41a	Reason for dual watch change by SwMI	296
16.10.42	Reject cause	296
16.10.43	Request to append LA	297
16.10.43a	Re-send interval	297
16.10.43b	Result of dual watch request	297
16.10.44	SSI	297