



SLOVENSKI STANDARD
SIST EN 300 392-12-6 V1.2.1:2006
01-april-2006

Df]nYa b]`gbcdcj b]`fUX]c`fH9HF5ŁĘ; c j cf]b`dcXUh_].fU Ź8 ŁĘ%&"XY.Ł8cdc`b]bY
ghcf]hj Ygħċdb`Y' ŁE* "dcXXY.Ł?]WĘ_][U'YcXcVf]`X]gdY Yf`fV 58Ł

Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-part 6: Call Authorized by Dispatcher (CAD)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: [SIST EN 300 392-12-6 V1.2.1:2006
https://standards.iteh.ai/catalog/standards/sist/e14c50fd-d332-4338-bb62-e2f0a54fb839/sist-en-300-392-12-6-v1-2-1-2006](https://standards.iteh.ai/catalog/standards/sist/e14c50fd-d332-4338-bb62-e2f0a54fb839/sist-en-300-392-12-6-v1-2-1-2006)

ICS:

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	------------------------------------	--------------------------------------

SIST EN 300 392-12-6 V1.2.1:2006 en

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST EN 300 392-12-6 V1.2.1:2006

<https://standards.iteh.ai/catalog/standards/sist/e14c50fd-d332-4338-bb62-e2f0a54fb839/sist-en-300-392-12-6-v1-2-1-2006>

ETSI EN 300 392-12-6 V1.2.1 (2004-01)

European Standard (Telecommunications series)

**Terrestrial Trunked Radio (TETRA);
Voice plus Data (V+D);
Part 12: Supplementary services stage 3;
Sub-part 6: Call Authorized by Dispatcher (CAD)**

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST EN 300 392-12-6 V1.2.1:2006

<https://standards.iteh.ai/catalog/standards/sist/e14c50fd-d332-4338-bb62-e2f0a54fb839/sist-en-300-392-12-6-v1-2-1-2006>



Reference

REN/TETRA-03100

Keywords

TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse 06 N° 7303/88

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 392-12-6 V1.2.1:2006](#)

<https://standards.iteh.ai/catalog/standards/sist/e14c50fd-d332-4338-bb62-e2f0a54fb839> **Important notice**

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:
editor@etsi.org

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2004.
All rights reserved.

DECT™, PLUGTESTS™ and UMTS™ are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	5
Foreword.....	5
1 Scope	7
2 References	7
3 Definitions and abbreviations.....	8
3.1 Definitions	8
3.2 Abbreviations	8
4 SS-CAD overview	8
4.1 Functional entities and communication routes	8
4.2 Protocol structure and protocol stack	9
5 SS-CAD service description.....	9
5.1 General	9
5.2 SS-CAD services offered over the TNSS-SAP	9
5.2.1 ACCEPT response	10
5.2.2 ACCEPTED indication	10
5.2.3 ACTIVATE indication	10
5.2.4 ACTIVATE request.....	10
5.2.5 CANCEL indication	10
5.2.6 DEACTIVATE indication.....	11
5.2.7 DEACTIVATE request.....	11
5.2.8 DEFINE indication	11
5.2.9 DEFINE request.....	12
5.2.10 DIVERT response.....	12
5.2.11 DIVERTED indication	12
5.2.12 INTERCEPTED indication.....	12
5.2.13 INTERROGATE indication.....	13
5.2.14 INTERROGATE request.....	13
5.2.15 REJECTED indication	13
5.2.16 REJECT response	14
5.2.17 REQUEST indication	14
5.3 Parameter description	14
6 SS-CAD protocol description.....	16
6.1 PDU descriptions.....	16
6.1.1 ACCEPT PDU	16
6.1.2 ACCEPTED PDU.....	17
6.1.3 ACTIVATE PDU	17
6.1.4 ACTIVATE ACK PDU	17
6.1.5 CANCEL PDU	18
6.1.6 DEACTIVATE PDU	18
6.1.7 DEACTIVATE ACK PDU	19
6.1.8 DEFINE PDU	20
6.1.9 DEFINE ACK PDU.....	20
6.1.10 DIVERT PDU.....	21
6.1.11 DIVERTED PDU	21
6.1.12 INTERCEPTED PDU.....	22
6.1.13 INTERROGATE PDU	22
6.1.14 INTERROGATE ACK PDU	23
6.1.15 PROFILE and PROFILE ACK information elements	24
6.1.16 REJECT PDU	24
6.1.17 REJECTED PDU.....	25
6.1.18 REQUEST PDU	25
6.2 Information element coding	26
6.2.1 Activation failure reason.....	26

6.2.2	Activation result.....	27
6.2.3	Activation type.....	27
6.2.4	Basic service restriction - called party	27
6.2.5	Basic service restriction - calling party.....	27
6.2.6	CAD PDU type element	28
6.2.7	Deactivation rejection reason.....	28
6.2.8	Deactivation result	28
6.2.9	Definition failure reason	29
6.2.10	Definition result	29
6.2.11	Dispatcher address type	29
6.2.12	Interception cause	30
6.2.13	Interception type	30
6.2.14	Interrogation failure reason.....	30
6.2.15	Interrogation result.....	30
6.2.16	Multiple user mask.....	30
6.2.17	Range type	30
6.2.18	Rejection cause	30
6.2.19	Restricted basic service	31
6.2.20	Restricted destination address type	31
6.2.21	Restricted destination external subscriber number	31
6.2.22	Restricted parties	31
6.2.23	Restricted source address type	31
6.2.24	Restricted user address type.....	31
6.2.25	Type of restriction change	32
6.3	SS-CAD protocol states.....	32
6.4	Protocol states for FE1	32
6.4.1	Protocol states for FE2.....	34
6.4.2	Protocol states for FE3.....	38
6.4.3	Protocol states for FE7.....	40
6.5	Procedures	42
6.5.1	General routing of SS information	42
6.5.2	Procedures for FE1	42
6.5.3	Procedures for FE2.....	43
6.5.3.1	CAD invocation procedures.....	43
6.5.3.2	Call authorization	43
6.5.3.3	Activation/deactivation procedures.....	44
6.5.3.4	Definition procedure	44
6.5.3.5	Interrogation procedure	44
6.5.4	Procedures for FE3	44
6.5.5	Procedures for FE7	45
6.5.5.1	Normal operation of FE7	45
6.5.5.2	Calling user A disconnects during interception.....	45
6.5.5.3	Activation/deactivation/definition/interrogation requests from the dispatcher	45
	Annex A (informative): Change requests.....	46
	History	47

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Project Terrestrial Trunked Radio (TETRA).

The present document is part 12, sub-part 6 of a multi-part deliverable covering the Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D), as identified below:

EN 300 392-1: "General network design";

EN 300 392-2: "Air Interface (AI)";

EN 300 392-3: "Interworking at the Inter-System Interface (ISI)";
**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

EN 300 392-5: "Peripheral Equipment Interface (PEI)";

EN 300 392-7: "Security", <http://standards.iteh.ai/catalog/standards/sist/e14c50fd-d332-4338-bb62-e2f0a54fb839/sist-en-300-392-12-6-v1-2-1-2006>

EN 300 392-9: "General requirements for supplementary services";

EN 300 392-10: "Supplementary services stage 1";

EN 300 392-11: "Supplementary services stage 2";

EN 300 392-12: "Supplementary services stage 3";

EN 300 392-12-1: "Call Identification (CI)";

ETS 300 392-12-2: "Call Report (CR)";

EN 300 392-12-3: "Talking Party Identification (TPI)";

EN 300 392-12-4: "Call Forwarding (CF)";

ETS 300 392-12-5: "List Search Call (LSC)";

EN 300 392-12-6: "Call Authorized by Dispatcher (CAD)";

ETS 300 392-12-7: "Short Number Addressing (SNA)";

EN 300 392-12-8: "Area Selection (AS)";

ETS 300 392-12-9: "Access Priority (AP)";

EN 300 392-12-10: "Priority Call (PC)";

ETS 300 392-12-11: "Call Waiting (CW)";

EN 300 392-12-12: "Call Hold (HOLD)";

ETS 300 392-12-13: "Call Completion to Busy Subscriber (CCBS)";
 EN 300 392-12-14: "Late Entry (LE)";
 ETS 300 392-12-16: "Pre-emptive Priority Call (PPC)";
 EN 300 392-12-17: "Include Call (IC)";
 EN 300 392-12-18: "Barring of Outgoing Calls (BOC)";
 EN 300 392-12-19: "Barring of Incoming Calls (BIC)";
 ETS 300 392-12-20: "Discreet Listening (DL)";
 EN 300 392-12-21: "Ambience Listening (AL)";
 EN 300 392-12-22: "Dynamic Group Number Assignment (DGNA)";
 ETS 300 392-12-23: "Call Completion on No Reply (CCNR)";
 ETS 300 392-12-24: "Call Retention (CRT)";
 ETS 300 392-13: "SDL model of the Air Interface (AI)";
 ETS 300 392-14: "Protocol Implementation Conformance Statement (PICS) proforma specification";
 TS 100 392-15: "TETRA frequency bands, duplex spacing and channel numbering";
 TS 100 392-16: "Network Performance Metrics";
 TS 100 392-17: "TETRA V+D and DMO Release 1.1 specifications".

iTEh STANDARD PREVIEW (standards.iteh.ai)

National transposition dates	
Date of adoption of this EN:	SIST EN 300 392-12-6 V1.2.1:2006
Date of latest announcement of this EN (doa):	19 December 2003 e2f0a54fb839/sist-en-300-392-12-6-v1-2-1-2006
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 March 2004
Date of withdrawal of any conflicting National Standard (dow):	30 September 2004

1 Scope

The present document defines the stage 3 specifications of the Supplementary Service Call Authorized by Dispatcher (SS-CAD) for the Terrestrial Trunked RAdio (TETRA) as provided by European operators. Stage 3 defines the signalling system protocols needed to implement the service described in stage 1 and stage 2. The stage 1 and stage 2 aspects are detailed in EN 300 392 10-6 [2] and EN 300 392-11-6 [3] respectively. Aspects relating to all supplementary services are detailed in EN 300 392-9 [6].

Charging principles and the Man-Machine Interface (MMI) are outside the scope of the present document.

The SS-CAD ensures that predefined TETRA calls do not proceed without first being authorized by a dispatcher.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

(standards.iteh.ai)

- [1] ITU-T Recommendation Z.100: "Specification and Description Language (SDL)".
- [2] ETSI EN 300 392-10-6: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 10: Supplementary services stage 1; Sub-part 6: Call Authorized by Dispatcher (CAD)".
SIST EN 300 392-12-6 V1.2.1:2006
https://standards.iteh.ai/catalog/standards/etsi/14c50fb-4322-4338-bf62-e2f0a54fb839/sist-en-300-392-12-6-v1-2-1-2006
- [3] ETSI EN 300 392-11-6: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 11: Supplementary services stage 2; Sub-part 6: Call Authorized by Dispatcher (CAD)".
- [4] ETSI EN 300 392-1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 10: Supplementary services stage 1; Sub-part 1: Call Identification (CI)".
- [5] ETSI EN 300 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
- [6] ETSI EN 300 392-9: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 9: General requirements for supplementary services".
- [7] ETSI EN 300 392-3-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 2: Additional Network Feature Individual Call (ANF-ISIIC)".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

authorized user: user who can make service definition

NOTE: The authorized user can also activate/deactivate and interrogate the service.

dispatcher: user to whom the request for authorization shall be directed to. This user is also able to activate/deactivate SS-CAD for other users (individuals and groups) within his responsibility area and interrogate the activation status for these users.

restricted user: user whose calls are forced to be authorized by a dispatcher before the call can proceed. The restricted user can be either the calling user (A) or the called user (B) or both.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CAD	Call Authorized by Dispatcher
CC	Call Control
CMCE	Circuit Mode Control Entity
FE	Functional Entity
GTSI	Group TETRA Subscriber Identity
ISI	Inter-System Interface
ITSI	Individual TETRA Subscriber Identity
LS	Line Station SIST EN 300 392-12-6 V1.2.1:2006
MMI	Man Machine Interface Machine Interface
MS	Mobile Station e2f0a54fb839/sist-en-300-392-12-6-v1-2-1-2006
PDU	Protocol Data Unit
SAP	Service Access Point
SDL	Specification and Description Language
SNA	Short Number Address
SS	Supplementary Service

NOTE: The abbreviation SS is only used when referring to a specific supplementary service.

SSI	Short Subscriber Identity
SwMI	Switching and Management Infrastructure
TETRA	Terrestrial Trunked RAdio
TSI	TETRA Subscriber Identity
V+D	Voice plus Data

4 SS-CAD overview

4.1 Functional entities and communication routes

The functional model for SS-CAD consists of Functional Entities FE1 to FE5 as defined in EN 300 392-11-6 [3], clause 4.1.

These functional entities can, for one call, be located in different TETRA systems, refer to EN 300 392-11-6 [3], clause 4.

4.2 Protocol structure and protocol stack

SS-CAD PDUs shall be routed as specified in EN 300 392-9 [6] (e.g. at the air interface in facility information elements for the call related SS-CAD PDUs and in U/D-FACILITY PDUs for the call unrelated SS-CAD PDUs, and using ANF-ISISS for conveying SS-CAD PDUs over the ISI). In addition some specific SS-CAD information elements have been included in the definition of some ANF-ISIIC and ANF-ISIGC PDUs. The present document is normative for the protocol architecture and user application Service Access Points (SAPs) within the MS/LS, but gives an informative description of the protocol within the SwMI.

5 SS-CAD service description

5.1 General

This clause describes the CAD specific services offered by the Circuit Mode Control Entity (CMCE) at the Supplementary Services Service Access Point (TNSS-SAP) of the TETRA Voice plus Data (V+D) layer 3 service boundary. The SS-CAD service access point may be used in conformance testing as a normative boundary in TETRA Mobile Stations (MSs) and TETRA Line Stations (LSs).

NOTE 1: As the present document only deals with the SS-CAD all service primitives has been shown without a TNSS-CAD-prefix e.g. TNSS-CAD-ACTIVATE request is shortened to ACTIVATE request.

NOTE 2: User application is the user of the supplementary service.

5.2 SS-CAD services offered over the TNSS-SAP *(standards.iteh.ai)*

The SS-CAD service primitives at the restricted user MS/LS (FE1) TNSS-SAP shall be:

- a) ACCEPTED indication; [SIST EN 300 392-12-6 V1.2.1:2006](#)
- b) DIVERTED indication; <https://standards.iteh.ai/catalog/standards/sist/e14c50fd-d332-4338-bb62-e2f0a54fb839/sist-en-300-392-12-6-v1-2-1-2006>
- c) REJECTED indication;
- d) INTERCEPTED indication.

The SS-CAD service primitives specific at the authorized user MS/LS (FE3) TNSS-SAP shall be:

- a) DEFINE request;
- b) DEFINE indication.

The SS-CAD service primitives at the authorized user MS/LS (FE3) and dispatcher (FE7) TNSS-SAP shall be:

- a) ACTIVATE request;
- b) ACTIVATE indication;
- c) DEACTIVATE request;
- d) DEACTIVATE indication;
- e) INTERROGATE request;
- f) INTERROGATE indication.

The SS-CAD service primitives specific at the dispatcher (FE7) TNSS-SAP shall be:

- a) ACCEPT response;
- b) CANCEL indication;
- c) DIVERT response;
- d) REJECT response;
- e) REQUEST indication.

NOTE: Following service primitives assume that a call identifier or equivalent information is exchanged implicitly or explicitly with the primitive, when the primitive is related to a call.

5.2.1 ACCEPT response

The user application shall offer an ACCEPT response to the dispatching user MS/LS (FE7) to indicate that the call has been authorized. The only parameter for this primitive is an optional Access priority.

5.2.2 ACCEPTED indication

The calling user MS/LS (FE1) shall offer an ACCEPTED indication to the user application to inform that the call authorization is successfully completed. There are no parameters for this primitive.

5.2.3 ACTIVATE indication

iTeh STANDARD PREVIEW
The authorized or dispatching user MS/LS (FE3 or FE7) shall offer an ACTIVATE indication to the user application to inform an activation of call authorization. (standards.iteh.ai)

Parameters for the primitive ACTIVATE indication shall be as defined in table 1.

standards.iteh.ai
Table 1: Parameters for the primitive ACTIVATE indication

Parameter	Indication
Activation result	M
Restricted user TETRA identity (ies)	M (see note)
NOTE: It is optional to support more than one identities.	

5.2.4 ACTIVATE request

The user application shall offer an ACTIVATE request to the authorized or dispatching user MS/LS (FE3 or FE7) to request an activation of call authorization.

Parameters for the primitive ACTIVATE request shall be as defined in table 2.

Table 2: Parameters for the primitive ACTIVATE request

Parameter	Request
Access priority	O
Restricted user TETRA identity (ies)	M (see note)
Intercepting dispatcher identity (ies)	O
NOTE: It is optional to support more than one identities.	

5.2.5 CANCEL indication

The dispatching user MS/LS (FE7) shall offer a CANCEL indication to the user application to indicate that the restricted user no longer expects a call authorization. There are no parameters for this primitive.

5.2.6 DEACTIVATE indication

The authorized or dispatching user MS/LS (FE3 or FE7) shall offer a DEACTIVATE indication to the user application to inform a deactivation of call authorization.

Parameters for the primitive DEACTIVATE indication shall be as defined in table 3.

Table 3: Parameters for the primitive DEACTIVATE indication

Parameter	Indication
Deactivation result	M
Restricted user TETRA identity (ies)	M (see note)
NOTE: It is optional to support more than one identities.	

5.2.7 DEACTIVATE request

The user application shall offer a DEACTIVATE request to the authorized or dispatching user MS/LS (FE3 or FE7) to request a deactivation of call authorization.

Parameters for the primitive DEACTIVATE request shall be as defined in table 4.

Table 4: Parameters for the primitive DEACTIVATE request

Parameter	Request
Access priority	O
Restricted user TETRA identity	M (see note)
NOTE: It is optional to support more than one identities.	

(standards.iteh.ai)

5.2.8 DEFINE indication

SIST EN 300 392-12-6 V1.2.1:2006

The authorized user MS/LS (FE3) shall offer a DEFINE indication to the user application to indicate a result of the call authorization definition request.

Parameters for the primitive DEFINE indication shall be as defined in table 5.

Table 5: Parameters for the primitive DEFINE indication

Parameter	Indication
Definition result	M
Restricted user TETRA identity	M (see note)
NOTE: It is optional to support more than one identities.	