

SLOVENSKI STANDARD SIST EN 20286-2:2000

01-december-2000

ISO system of limits and fits - Part 2: Tables of standard tolerance grades and limit deviations for holes and shafts (ISO 286-2:1988)

ISO system of limits and fits - Part 2: Tables of standard tolerance grades and limit deviations for holes and shafts (ISO 286-2:1988)

ISO-System für Grenzabmaße und Passungen - Teil 2: Tabellen der Grundtoleranzgrade und Grenzabmaße für Bohrungen und Wellen (ISO 286-2:1988)

(standards.iteh.ai)
Systeme ISO de tolérances et d'ajustements - Partie 2: Tables des degrés de tolérance normalisés et des écarts limites des alésages et des arbres (ISO 286-2:1988)

https://standards.iteh.ai/catalog/standards/sist/05a3a80a-d4bd-43c3-a9de-

Ta slovenski standard je istoveten z: EN 20286-2-2000

ICS:

17.040.10 Tolerance in ujemi Limits and fits

SIST EN 20286-2:2000 en

SIST EN 20286-2:2000

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 20286-2:2000

https://standards.iteh.ai/catalog/standards/sist/05a3a80a-d4bd-43c3-a9de-ff321ba58268/sist-en-20286-2-2000

EUROPEAN STANDARD

EN 20286-2:1993

NORME EUROPÉENNE

EUROPÄISCHE NORM

April 1993

UDC 621.713.1/.2:621.824

Descriptors:

Machine components, reaming, shafts: rotating, dimensional tolerances, standard tolerances, dimensional deviations, fundamental tolerances

English version

ISO system of limits and fits - Part 2: Tables of standard tolerance grades and limit deviations for holes and shafts (ISO 286-2:1988)

Système ISO de tolérances et d'ajustèments - DARD PRE ISO-Systèm für Grenzabmaße und Passungen - Teil Partie 2: Tables des degrés de tolérance normalisés et des écarts limites des alésages et des arbres (ISO 286-2:1988)

Standards.iteh.al (ISO 286-2:1988)

SIST EN 20286-2:2000

https://standards.iteh.ai/catalog/standards/sist/05a3a80a-d4bd-43c3-a9de-ff321ba58268/sist-en-20286-2-2000

This European Standard was approved by CEN on 1993-04-15. CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

The European Standards exist in three official versions (English, French, German)— A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CEN

European Committee for Standardization Comité Européen de Normalisation Europäisches Komitee für Normung

Central Secretariat: rue de Stassart, 36 B-1050 Brussels

Page 2 EN 20286-2:1993

Foreword

In 1991, the International Standard ISO 286-2:1988 "ISO system of limits and fits - Part 2: Tabels of standard tolerance grades and limit deviations for holes and shafts" was submitted to the CEN Primary Questionnaire procedure.

Following the positive result of the CEN/CS Proposal, ISO 286-2:1988 was submitted to the Formal Vote.

The result of the Formal Vote was positive.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 1993, and conflicting national standards shall be withdrawn at the latest by October 1993.

According to the CEN/CENELEC Internal Regulations, the following countries are bound to implement this European Standard: Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, United Kingdom.

Endorsement notice

The text of the International Standard ISO 286-2:1988 was approved by CEN as a European Standard without any modification.

(standards.iteh.ai)

NOTE: The European references to international publications are given in annex ZA (normative).

https://standards.iteh.ai/catalog/standards/sist/05a3a80a-d4bd-43c3-a9de-ff321ba58268/sist-en-20286-2-2000

Page 3 EN 20286-2:1993

Annex ZA (normative) Normative references to international publications with their relevant European publications

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies (including amendments).

Publication	<u>Title</u>	EN/HD
ISO 286-1	ISO system of limits and fits - Part 1: Bases of tolerances, deviations and fits	EN 20286-1
ISO 1829	Selection of tolerance zones for general iTpurposes I ANDARD PREVII (standards.iteh.ai)	EW

<u>SIST EN 20286-2:2000</u> https://standards.iteh.ai/catalog/standards/sist/05a3a80a-d4bd-43c3-a9de-ff321ba58268/sist-en-20286-2-2000 SIST EN 20286-2:2000

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 20286-2:2000

https://standards.iteh.ai/catalog/standards/sist/05a3a80a-d4bd-43c3-a9de-ff321ba58268/sist-en-20286-2-2000

INTERNATIONAL STANDARD

ISO 286-2

1988-06-01



INTERNATIONAL ORGANIZATION FOR STANDARDIZATION ORGANISATION INTERNATIONALE DE NORMALISATION МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ

ISO system of limits and fits -

Part 2:

Tables of standard tolerance grades and limit deviations for holes and shafts, STANDARD PREVIEW

Système ISO de tolérances et d'ajustements —

Partie 2: Tables des degrés de tolérance normalisés et des écarts limites des alésages et des arbres https://standards.iteh.ai/catalog/standards/sist/05a3a80a-d4bd-43c3-a9deff321ba58268/sist-en-20286-2-2000

Reference number ISO 286-2:1988 (E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

This part of ISO 286 has been prepared by ISO/TC 3, *Limits and fits*, and, together with ISO 286-1, completes the revision of ISO/R 286, *ISO system of limits and fits*. ISO/R 286 was first published in 1962 and subsequently confirmed in November 1964; it was based on ISA Bulletin 25 first published in 1940.

The major changes incorporated in this part of ISO 286 are as follows:

- a) The presentation of the information has been modified so that ISO 286 can be used directly in both the design office and the workshop. This has been achieved by separating the material dealing with the bases of the system, and the calculated values of standard tolerances and fundamental deviations, from the tables giving specific limits of the most commonly used tolerances and deviations.
- b) The new symbols js and JS replace the former symbols j_s and J_s (i.e. s and S are no longer placed as subscripts) to facilitate the use of the symbols on equipment with limited character sets, e.g. computer graphics. The letters "s" and "S" stand for "symmetrical deviation".

 SIST EN 20286-2:2000
- c) Limit deviations have been included for basic sizes from 500 to 3 150 mm as d4bd-43c3-a9de-standard requirements (these were previously included on an experimental basis only).
- d) Limit deviations have been extended for holes H and JS, for shafts h and js, by including tolerance grades IT17 and IT18 in all basic sizes, and, for experimental purposes only, by including tolerance grades IT1 to IT5 in basic sizes over 500 mm up to 3 150 mm.
- e) Limit deviations have been extended for some tolerance classes used in fine mechanisms and horology, in basic sizes up to 50 mm.
- f) Inch values have been deleted.
- g) The principles, terminology and symbols have been aligned with those required by contemporary technology.

Users should note that all International Standards undergo revision from time to time and that any reference made herein to any other International Standard implies its latest edition, unless otherwise stated.

© International Organization for Standardization, 1988 ●

Printed in Switzerland

Contents	Page
0 Introduction	1
1 Scope	1
2 Field of application	1
3 References	2
4 Standard tolerances	2
5 Limit deviations for holes	2
iTeh S6 Limit deviations for shafts R. F. V. I.E. W	2
(Stablingraphy ds.iteh.ai)	3
Notes on the presentation of tables 2 to 32	7
https://standards.iteh.ai/catalog/standards/sist/05a3a80a-d4bd-43c3-a9de- Tables 210 32 / Sist-en-20286-2-2000 8 t	
Annex — Graphical review of tolerance zones of holes and shafts	39

SIST EN 20286-2:2000

iTen This page intentionally left blank (VIEW (standards.iteh.ai)

SIST EN 20286-2:2000 https://standards.iteh.ai/catalog/standards/sist/05a3a80a-d4bd-43c3-a9deff321ba58268/sist-en-20286-2-2000

ISO system of limits and fits —

Part 2:

Tables of standard tolerance grades and limit deviations for holes and shafts

iTeh STANDARD PREVIEW

0 Introduction

The need for limits and fits for machined workpieces was 20286 ei (for shafts) (see figure 1). brought about mainly by the inherent inaccuracy of manufac dards/sist/05a3a80a-d4bd-43c3-a9deturing methods, coupled with the fact that "exactness" of size 1. NOTE — In the tables of limit deviations, the values for the upper that function could be satisfied, it was found sufficient to manufacture a given workpiece so that its size lay within two permissible limits, i.e. a tolerance, this being the variation in size acceptable in manufacture.

Similarly, where a specific fit condition is required between mating workpieces, it is necessary to ascribe an allowance, either positive or negative, to the basic size to achieve the required clearance or interference, i.e. a "deviation".

With developments in industry and international trade, it became necessary to develop formal systems of limits and fits. firstly at the industrial level, then at the national level and later at the international level.

This International Standard therefore gives the internationally accepted system of limits and fits.

A general graphical representation of the relationship between the respective tolerance classes and their deviations is given in the annex.

Scope

This part of ISO 286 gives values of the limit deviations for commonly used tolerance classes (zones) for holes and shafts calculated from the information given in ISO 286-1. This part of

(standards.iteh.ai) ISO 286 covers values for the upper deviations ES (for holes) and and es (for shafts), and the lower deviations EI (for holes) and

deviation ES or es are shown above the values for the lower deviation EI or ei except for tolerance class JS and js which is symmetrical about the zero line.


Field of application

The ISO system of limits and fits provides a system of tolerances and deviations suitable for plain workpieces.

It should be noted that the general term "hole" or "shaft" used in this International Standard can be taken as referring to the space contained by (or containing) the two parallel faces (or tangent planes) of any workpiece, such as the width of a slot or the thickness of a key (see also ISO 286-1). Similarly, the term "commonly used holes and shafts" shall be interpreted as providing a very wide choice of limit deviations suitable for a wide variety of requirements.

For further information on terminology, symbols, bases of the system, etc., see ISO 286-1.

Notes on the presentation of tables 2 to 32 are given on page 7.



https://standaFig.ucen.lai/catalogera.and.dower.deviations.bd-43c3-a9de-ff321ba58268/sist-en-20286-2-2000

3 References

NOTE — See also clause 7.

ISO 286-1, ISO system of limits and fits — Part 1: Bases of tolerances, deviations and fits.

ISO 1829, Selection of tolerance zones for general purposes.

4 Standard tolerances

The values of standard tolerance grades IT1 to IT18 inclusive are given in table 1.

For information on the bases of the system and its application, see ISO 286-1; for values of standard tolerances IT0 and IT01, see ISO 286-1, annex A, table 5.

5 Limit deviations for holes

A synoptic representation of the tolerance classes for holes, given in this part of ISO 286, is shown in figures 2 and 3.

Attention is drawn to the fact that the tolerance classes shown in figures 2 and 3, and their limit deviations, given in tables 2 to 16, are not intended to give detailed directives on the selection of tolerance classes for any purpose. Recommendations for the selection of tolerance classes are given in ISO 1829.

NOTE — Some tolerance classes are only provided for a restricted range of basic size steps. For further information, see note 1 on page 7.

6 Limit deviations for shafts

A synoptic representation of the tolerance classes for shafts, given in this part of ISO 286, is shown in figures 4 and 5.

Attention is drawn to the fact that the tolerance classes shown in figures 4 and 5, and their limit deviations, given in tables 17 to 32, are not intended to give detailed directives on the selection of tolerance classes for any purpose. Recommendations for the selection of tolerance classes are given in ISO 1829.

NOTE — Some tolerance classes are only provided for a restricted range of basic size steps. For further information, see note 1 on page 7.

7 Bibliography

The following International Standards on tolerancing and tolerance systems will be useful with regard to the application of this part of ISO 286:

ISO 406, Technical drawings — Linear and angular tolerancing — Indications on drawings.

ISO 1101, Technical drawings — Geometrical tolerancing — Tolerancing of form, orientation, location and run-out — Generalities, definitions, symbols, indications on drawings.

ISO/R 1938, ISO system of limits and fits — Inspection of plain workpieces. 1)

ISO 2692, Technical drawings — Geometrical tolerancing — Maximum material principle.

ISO 2768-1, General tolerances for dimensions without tolerance indications — Part 1: Tolerances for linear and angular dimensions. 2

ISO 5166, System of cone fits for cones from C=1:3 to 1:500, lengths from 6 to 630 mm and diameters up to 500 mm.

ISO 8015, Technical drawings — Fundamental tolerancing principle.

ISO 8062, Castings - System of dimensional tolerances.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 20286-2:2000</u> https://standards.iteh.ai/catalog/standards/sist/05a3a80a-d4bd-43c3-a9de-ff321ba58268/sist-en-20286-2-2000

¹⁾ At present under revision.

²⁾ At present at the stage of draft. (Revision, in part, of ISO 2768: 1973.)

Table 1 - Numerical values of standard tolerance grades IT for basic sizes up to 3 150 mm $^{1)}$

NOTE — This table, taken from ISO 286-1, has been included in this part of ISO 286 to facilitate understanding and use of the system.

Racio	size	Standard tolerance grades																	
1	m	IT1 ²⁾	IT2 ²⁾	IT3 ²⁾	IT4 ²⁾	IT5 ²⁾	IT6	IT7	IT8	IT9	IT10	IT11	IT12	IT13	IT14 ³⁾	IT15 ³⁾	IT16 ³⁾	IT17 ³⁾	IT18 ³⁾
Above	Up to and in-									Tole	erances	; ;							
	cluding	μm mm																	
_	33)	0,8	1,2	2	3	4	6	10	14	25	40	60	0,1	0,14	0,25	0,4	0,6	1	1,4
3	6	1	1,5	2,5	4	5	8	12	18	30	48	75	0,12	0,18	0,3	0,48	0,75	1,2	1,8
6	10	1	1,5	2,5	4	6	9	15	22	36	58	90	0,15	0,22	0,36	0,58	0,9	1,5	2,2
10	18	1,2	2	3	5	8	11	18	27	43	70	110	0,18	0,27	0,43	0,7	1,1	1,8	2,7
18	30	1,5	2,5	4	6	9	13	21	33	52	84	130	0,21	0,33	0,52	0,84	1,3	2,1	3,3
30	50	1,5	2,5	4	7	11	16	25	39	62	100	160	0,25	0,39	0,62	1	1,6	2,5	3,9
50	80	2	3	5	8	13	19	30	46	74	120	190	0,3	0,46	0,74	1,2	1,9	3	4,6
80	120	2,5	4	6	10	15	22	35	54	87	140	220	0,35	0,54	0,87	1,4	2,2	3,5	5,4
120	180	3,5	5	8	12	18	25	40	63	100	160	250	0,4	0,63	1	1,6	2,5	4	6,3
180	250	4,5	7	10	14	20	29	46	72	115	185	290	0,46	0,72	1,15	1,85	2,9	4,6	7,2
250	315	6	8	12	16	23	32	52	81	130	210	320	0,52	0,81	1,3	2,1	3,2	5,2	8,1
315	400	7	9	13	18	25	36	57	89	140	230	360	0,57	0,89	1,4	2,3	3,6	5,7	8,9
400	500	8	10	15	20	27	40	63	97	155	250	400	0,63	0,97	1,55	2,5	4	6,3	9,7
500	630 ²⁾	9	11	16	22	32	44	70	110	175	280	440	0,7	1,1	1,75	2,8	4,4	7	11
630	8002)	10	13	18	25	e 36	50 /	80	125	200	320	500	/0,8 ₹	1,25	2	3,2	5	8	12,5
800	10002)	11	15	21	28	40	56	90	140	230	360	560	0,9	1,4	2,3	3,6	5,6	9	14
1000	12502)	13	18	24	33	47	66	105	465	260	420	660	1,05	1,65	2,6	4,2	6,6	10,5	16,5
1250	16002)	15	21	29	39	55	78	125	195	310	500	780	1,25	1,95	3,1	5	7,8	12,5	19,5
1600	20002)	18	25	35	46	65	92	SIST	E230	2 370 2	2600	920	1,5	2,3	3,7	6	9,2	15	23
2000	2500 ²⁾	22	30	41 ht	ps://sta 55	ndards 78	iteh ai	catalog	280 la	rds/sis	⁷⁰ 503a	89100	bd-43	:3 _{2,8} 9d	4,4	7	11	17,5	28
2500	3150 ²⁾	26	36	50	68	96	135	ba582 210	68/sist- 330	cn-20 2 540	86-2-2 860	1350	2,1	3,3	5,4	8,6	13,5	21	33

¹⁾ Values for standard tolerance grades IT01 and IT0 for basic sizes less than or equal to 500 mm are given in ISO 286-1, annex A, table 5.

²⁾ Values for standard tolerance grades IT1 to IT5 (incl.) for basic sizes over 500 mm are included for experimental use.

³⁾ Standard tolerance grades IT14 to IT18 (incl.) shall not be used for basic sizes less than or equal to 1 mm.

2	3		4		5		H16 H17 H18	JS16 JS17 JS18	8		9	10	11	12	13	14		15	16
							H14 H15	JS14 JS15											
A13 B13 C13	D13						H13	JS13											
A11 B11 C11 A12 B12 C12	D11						H11 H12	JS11 JS12			N11							Z11 ZA11	ZB11 ZC1
A10 B10 C10	CD10 D10		EF10	F10	FG10		H10	JS10	K10		0 N10	P10	R10	S10	U10	i	Y10	Z10 ZA10	ZB10 ZC10
A9 B9 C9	CD9 D9	E9	EF9	F9	FG9	G9	H9	JS9	K9	M9		P9	R9	S9	18 U8	V8 X8	78 Y9	Z8 ZA8 Z9 ZA9	ZB8 ZC8 ZB9 ZC9
B8 C8	CD7 D7	E7 E8	EF7 EF8	F7 F8	FG7 FG8	G7 G8	H7 H8	JS7 JS8	J7 K7 J8 K8	M7		P7 P8	R7 R8	S7 S8	T7 U7 T8 U8	V7 X7	Y7 Y8	Z7 ZA7 Z8 ZA8	ZB7 ZC7 ZB8 ZC8
	CD6 D6	E6	EF6	F6	FG6	G6	Н6	JS6	J6 K6	Me		P6	R6	S6	T6 ∪6	V6 X6		Z6 ZA6	
		E5	EF5	F5	FG5	G5	H5	JS5	K5	M5		P5	R5	S5	T5 U5	V5 X5			
			EF3	F3 F4	FG3 FG4	G3 G4	H3 H4	JS3 JS4	K3 K4	M3 M4		P3	R3 R4	S3 S4					
							H1 H2	JS1 JS2											

Figure 2 — Synoptic representation of tolerance classes for holes for basic sizes less than or equal to 500 mm

D6 E6 P	F6 F7 F8	ch ST. (get G7 G8 adards.iteh.a ff32	_	JS2 JS3 JS4 JS5 JS7 JS8 JS9 Stays 10 ds 8/JS11-en JS12 JS13 JS14 JS15 JS16 JS17 JS18	D Pl .itch .r 6-2:2000 s/sist/05a3: -20286-2-	M6 N6 N7 N7 M8 N8 N9 a80a-d4bd-2000	P6 P7 P8 P9 43 C3 - 8	R6 R7 R8	\$6 \$7 \$8	T6 U6 T7 U7 T8 U8
3	4	5	6	7	8	9	10	11	12	13

 NOTE — The tolerance classes in the frame are given for experimental use.

Figure 3 - Synoptic representation of tolerance classes for holes for basic sizes greater than 500 mm and less than or equal to 3 150 mm