

IEC 62368-1
(First edition – 2010)

Audio/video, information and communication technology equipment –

Part 1: Safety requirements

CORRIGENDUM 1

0.7.2 Models for electrically-caused fire

Replace, in the last paragraph, the penultimate sentence, as follows:

When the gas is at its spontaneous ignition temperature, the gas will ignite by itself.

2 Normative references

Delete the reference to publication “IEC/TS 61202-1”.

Table 5 – Electrical energy source limits for d.c. and low frequency a.c. voltages

Replace, in the last sentence of the table, the publication reference number, by the following:

IEC/TS 61201

5.3.6.2 Contact requirements

Replace, item a), by the following:

- a) pass an electric strength test in accordance with 5.4.11.1 at a test voltage (d.c. or peak a.c.) that is equal to the test voltage for **basic insulation** in Table 32 corresponding to the **peak working voltage**; or

5.4.2.5.1 Mains transient voltages

Replace, item c), by the following:

- c) For circuits supplied from a d.c. **mains**, b)1), b)2) or b)3) shall be applied.

Table 18 – Minimum clearances up to 2 000 m above sea level, inhomogeneous field distribution (for steady-state voltages, temporary overvoltages and recurring peak voltages)

Replace the entire existing table by the following:

Peak working voltage V peak or d.c. up to and including	Basic insulation or supplementary insulation mm			Reinforced insulation mm		
	Pollution degree			Pollution degree		
	1 ^a	2	3	1 ^a	2	3
330	0,01	0,2	0,8	0,04	0,6	1,5
400	0,02			0,074		
500	0,04			0,13		
600	0,06			0,234		
800	0,13			0,76		
1 000	0,26	0,26		0,76	0,76	
1 200	0,42			1,19		
1 500	0,76			1,8		1,8
2 000	1,27			2,8		
2 500	1,8			3,8		
3 000	2,4			6,2		
4 000	3,8			7,9		
5 000	6,7			11		
6 000	7,9			11		
8 000	11,0			19		
10 000	15,2			26,8		
12 000	19			32,56		
15 000	25			42		
20 000	34			59,4		
25 000	44			77		
30 000	55			95,4		
40 000	77			131		
50 000	100			175		
60 000	120			219		
80 000	175			307		
100 000	230			395		

The values in the above table are derived from IEC 60664-1:2007, Table F.7a.
Linear interpolation may be used between the nearest two points, the calculated minimum clearances being rounded up to the next higher 0,1 mm increment or the value in the next row below whichever is lower.

^a The values for **Pollution degree** 1 may be used if a sample complies with the tests of 5.4.8.

5.4.2.8 Minimum clearances based on electric strength test

Replace, in the first two paragraphs, "Table 20" by "Table 21".