



Edition 2.0 2014-12

# INTERNATIONAL STANDARD

Fibre optic interconnecting devices and passive components – Performance standard – Part 031-3: Non-connectorized single-mode 1×N and 2×N non-wavelength-

selective branching devices for Category U – Uncontrolled environment

IEC 61753-031-3:2014

https://standards.iteh.ai/catalog/standards/iec/efa96cc9-1d94-4483-b352-8d5338ebed69/iec-61753-031-3-2014





## THIS PUBLICATION IS COPYRIGHT PROTECTED

## Copyright © 2014 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office	Tel.: +41 22 919 02 11
3, rue de Varembé	Fax: +41 22 919 03 00
CH-1211 Geneva 20	info@iec.ch
Switzerland	www.iec.ch

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

#### IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

#### IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

#### Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### IEC Glossary - std.iec.ch/glossary

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

#### IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

## IEC 61753-031-3:2014

https://standards.iteh.ai/catalog/standards/iec/efa96cc9-1d94-4483-b352-8d5338ebed69/iec-61753-031-3-2014





Edition 2.0 2014-12

# INTERNATIONAL STANDARD

Fibre optic interconnecting devices and passive components – Performance standard – Part 031-3: Non-connectorized single-mode 1×N and 2×N non-wavelength-selective branching devices for Category U – Uncontrolled environment

IEC 61753-031-3:2014

https://standards.iteh.ai/catalog/standards/iec/efa96cc9-1d94-4483-b352-8d5338ebed69/iec-61753-031-3-2014

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

ICS 33.180.10

ISBN 978-2-8322-1819-8

R

Warning! Make sure that you obtained this publication from an authorized distributor.

## CONTENTS

FOF	REWC	)RD	3
1	Scop	e	5
2	Norn	native references	5
3	Test		6
4	Test	report	7
5	Perf	ormance requirements	7
5	5.1	Dimensions	7
5	5.2	Sample size	7
-	5.3	Test details and requirements	
Ann	ex A	(normative) A and U requirements of 1 $\times$ N and 2 $\times$ N NWBDs	15
	<b>\</b> .1	Attenuation and uniformity requirements of 1 $\times$ N and 2 $\times$ N NWBDs calculated by the equations of Tests No.1 and 2	15
A	A.2	Minimum requirements at room temperature of attenuation values for	40
۸nn	ov B	balanced bidirectional 1 $\times$ N and 2 $\times$ N NWBD(normative) Sample size	
		bhy	
	• •	-	
Tab	le 1 –	Test details and requirements	8
NW	BD ha	A.1 – Attenuation and uniformity requirements of balanced bidirectional aving the most common port configurations for Class A, with the underlying as specified in the Tests 1 and 2 of Table 1	15
NW	BD ha	A.2 – Attenuation and uniformity requirements of balanced bidirectional aving the most common port configurations for Class B, with the underlying as specified in the Tests 1 and 2 of Table 1	16
the	most	A.3 – Attenuation requirements of $1 \times 2$ and $2 \times 2$ unbalanced NWBD having common port configurations, with the underlying formula as specified in Test $1$	
Tab Clas	leau / ss A b	A.4 – Minimum requirements at room temperature of attenuation values for alanced bidirectional NWBD	17
		A.5 – Minimum requirements at room temperature of attenuation values for palanced bidirectional NWBD	17
Tab	le B.1	- Sample size for each test	18

INTERNATIONAL ELECTROTECHNICAL COMMISSION

## FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS – PERFORMANCE STANDARD –

## Part 031-3: Non-connectorized single-mode 1×N and 2×N non-wavelength-selective branching devices for Category U – Uncontrolled environment

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in

https://stauthe latter ch.ai/catalog/standar

- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61753-031-3 has been prepared by subcommittee 86B: Fibre optic interconnecting devices and passive components, of IEC technical committee 86: Fibre optics.

This second edition of IEC 61753-031-3 cancels and replaces the first edition published in 2009 and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

 a) an updated and extended scope to reflect an introduction of two attenuation and uniformity performance classes for balanced NWBD instead of branching device technologies on the market;

- b) an updated list of normative references;
- c) a more simplified introduction to the two types of spectral bands;
- d) Clause 5, Performance requirements, has been updated and extended to reflect the introduction of two attenuation and uniformity performance classes for balanced NWBD;
- e) simplified test items to exclude tests for damp heat (steady state) and impact for performance requirements;
- f) Annexe A has been changed to introduce the calculated and minimum requirements for attenuation and uniformity;
- g) Annex B has been updated to reflect revised performance requirements.

The text of this standard is based on the following documents:

FDIS	Report on voting
86B/3792/FDIS	86B/3824/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 61753 consists of the following parts, under the general title *Fibre optic interconnecting devices and passive components – Performance standard.* 

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,

<u>IEC 61753-031-3:2014</u>

https://earreplaced by a revised edition, or fa96cc9-1d94-4483-b352-8d5338ebed69/iec-61753-031-3-2014

• amended.

A bilingual version of this publication may be issued at a later date.

## FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS – PERFORMANCE STANDARD –

## Part 031-3: Non-connectorized single-mode 1×N and 2×N non-wavelength-selective branching devices for Category U – Uncontrolled environment

#### 1 Scope

This part of IEC 61753 contains the minimum initial tests and measurement requirements and severities which a non-wavelength selective branching device (NWBD) should satisfy in order to be categorized as meeting the requirements of this standard.

The requirements cover balanced bidirectional non-connectorized single-mode  $1 \times N$  and  $2 \times N$  non-wavelength-selective branching devices for use in an IEC category U environment (N is the number of branching ports), especially but not exclusively used for PON application. For balanced NWBD two attenuation and uniformity performance classes are considered: class A (premium class) which meets more restrictive requirements (i.e. for extended reach PON application) and class B (standard class) for standard application (i.e. for normal reach PON application).

The requirements also cover unbalanced, bidirectional, non-connectorized, single-mode, non-wavelength-selective branching devices; however, the specifications of unbalanced branching devices are limited to  $1 \times 2$  and  $2 \times 2$  devices because they are the most commonly used.

## 2 Normative references <u>IEC 61753-031-3:2014</u>

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60793-2-50:2012, Optical fibres – Part 2-50: Product specifications – Sectional specification for class B single-mode fibres

IEC 61300-2-1, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-1: Tests – Vibration (sinusoidal)

IEC 61300-2-4, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-4: Tests – Fibre/cable retention

IEC 61300-2-5, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-5: Tests – Torsion

IEC 61300-2-9, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-9: Tests – Shock

IEC 61300-2-14, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-14: Tests – High optical power

IEC 61300-2-17, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-17: Tests – Cold

IEC 61300-2-18, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-18: Tests – Dry heat – High temperature endurance

IEC 61300-2-22, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-22: Tests – Change of temperature

IEC 61300-2-42, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-42: Tests – Static side load for connectors

IEC 61300-2-44, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-44: Tests – Flexing of the strain relief of fibre optic devices

IEC 61300-2-46, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-46: Tests – Damp heat, cyclic

IEC 61300-3-2:2009, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-2: Examination and measurements – Polarization dependent loss in a single-mode fibre optic device

IEC 61300-3-3:2009, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-3: Examinations and measurements – Active monitoring of changes in attenuation and return loss

IEC 61300-3-6:2009, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-6: Examinations and measurements – Return loss

IEC 61300-3-7:2009, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-7: Examinations and measurements – Wavelength dependence of attenuation and return loss of single mode components

IEC 61300-3-20, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-20: Examinations and measurements – Directivity of fibre optic branching devices

IEC 61300-3-28, Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-28: Examinations and measurements – Transient loss

#### 3 Test

All test methods are selected within the IEC 61300 series.

The samples for tests shall be terminated onto single-mode fibres according to category B1.1, B1.3, or B.6 of IEC 60793-2-50:2012 in either coated fibres (primary and secondary) or reinforced cable format.

All tests shall be carried out to validate performance over one of the spectral bands listed below:

- 1) Spectral bands I:
  - 1 260 nm to 1 360 nm
  - 1 480 nm to 1 625 nm

- 2) Spectral bands II:
  - 1 260 nm to 1 360 nm
  - 1 480 nm to 1 660 nm

#### 4 Test report

Fully documented test reports and supporting evidence shall be prepared and be available for inspection as evidence that the tests have been carried out and complied with.

- 7 -

#### 5 **Performance requirements**

#### 5.1 Dimensions

Dimensions shall comply with those given in appropriate manufacturer's drawings.

#### 5.2 Sample size

Sample sizes for the tests are defined in Annex B.

#### 5.3 Test details and requirements

Performance requirements and details are specified in Table 1.

All optical performances are given only for non-connectorized NWBD. During the environmental tests where monitoring of the NWBD is needed, all ports of the device shall be monitored.

In Annex A some numerical values of attenuation and uniformity requirements of test numbers 1 and 2 for the most commonly used NWBD are shown in Tables A.1, A.2 and A.3.

#### EC 61753-031-3:2014

In Tables A.4 and A.5 the minimum attenuation requirements at room temperature are described by way of equations on the top of column, with the calculated values of the most commonly used NWBD listed below.

S	2 m	Unpolarized	The wavelength of the source shall be longer than the cut-off wavelength of the fibre source the fibre ≤ ± 0,05 dB The measurement should be performed with all combination of input/output ports See Tables A.1, A.2 and A.3 for example						≥ 2 m	≥ 2 m Unpolarized The wavelength of the source shall be longer than the cut-off wavelength of the fibre ≤ ± 0,05 dB ≤ ± 0,05 dB						with all combination of input/output ports	See Tables A.1 and A.2 for example
Details	Launch patchcord length ≥ 2 m	Source type	Launch conditions	<u></u>	<u></u>	Uncertaintv		<u> </u>	Launch patchcord length	Source type	Launch conditions	<u>,                                    </u>	<u> </u>	Uncertainty		, , , , , , , , , , , , , , , , , , , ,	
		2 × N	В	$\leq$ 0,7 + 3,5log <sub>2</sub> N (dB)	$\leq$ 0,7 + 3,6log <sub>2</sub> N (dB)					2 x N	В	$\leq$ 0,5 + 0,4log <sub>2</sub> N (dB)	$\leq$ 0,5 + 0,5log <sub>2</sub> N (dB)				
		< 2	A	$\leq$ 0,7 + 3,4log <sub>2</sub> N (dB)	$\leq$ 0,7 + 3,5log <sub>2</sub> N (dB)	ttj I	ssociated with one port		it: n en		lo P P	$\leq 0,4+0,4\log_2 N (dB)$	$\leq 0,4+0,5log_2N$ (dB)	ls ite ie	eh w	.ai	)
Requirements		Z	В	$\leq 0,5 + 3,4 \log_2 N$ (dB)	$\leq 0,5 + 3,5log_2N$ (dB)		<ul> <li>22 – 10,5log<sub>10</sub>P (dB)</li> <li>22 – 10,5log<sub>10</sub>P (dB)</li> <li>where P is the nominal percentage of power associated with one port</li> </ul>		153 nlog hed	- <u>03</u> /sta 59/i	<u>1-3</u> nda ec-	$\leq$ 0,2 + 0,3log <sub>2</sub> N (dB)	$\leq$ 0,2 + 0,4log <sub>2</sub> N (dB)	/efa9 031	96cc -3-2	9-1 <b>d</b> 2014	94-
		1 × N	А	$\leq$ 0,5 + 3,3log <sub>2</sub> N (dB)	$\leq$ 0,5 + 3,4log_2N (dB)		≤ 22 – 10,5log <sub>10</sub> P (dB) where <i>P</i> is the nominal			1 × 1	А	$\leq$ 0,1 + 0,3log <sub>2</sub> N (dB)	$\leq$ 0,1 + 0,4log <sub>2</sub> N (dB)				
	Balanced NWBD	Configuration	Performance class	Spectral band I	Spectral band II	Unbalanced NWBD	Spectral band I Spectral band I		Balanced NWBD	Configuration	Performance Class	Spectral band I	Spectral band II				
Tests	Attenuation (A)	(Insertion loss)	IEC 61300-3- 7-2000	(Method A)					Uniformity (U)	IEC 61300-3-	/:zuug (Method A)						
No.	٢								2								

(1 of 7)
requirements
details and
Table 1 – Test c