







THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Email: inmail@iec.ch Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Catalogue of IEC publications: <u>www.iec.ch/searchpub</u>

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications

IEC Just Published: www.iec.ch/online_news/ivstpub Stay up to date on all new IEC publications. Just Published details wice a month all new publications released. Available on-line and also by email.

Electropedia: <u>www.electropedia.org</u>

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

• Customer Service Centre: <u>neww.iec.ch/webstore/custserv</u> If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

https:

S:// Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00

Email: csc@iec.ch

39c5-4887-9506-0caa50550360/iec-61784-5-3-2010



Edition 2.0 2010-07



CONTENTS

FO	REWORD	5
INT	FRODUCTION	7
1	Scope	8
2	Normative references	8
3	Terms, definitions and abbreviated terms	8
4	CPF 3: Overview of installation profiles	8
5	Installation profile conventions	9
6	Conformance to installation profiles	
	nex A (normative) CP 3/1 (PROFIBUS) specific installation profile	
An	nex B (normative) CP 3/2 (PROFIBUS) specific installation profile	43
	nex C (normative) CP 3/3, CP 3/4, CP 3/5, CP 3/6 (PROFINET) specific installation	77
Bib	oliography	. 103
Fig	jure 1 – Standards relationships	7
net	ure A.1 – Recommended combination of shielding and earthing for CP 3/1 works with RS 485-IS	24
Fig	jure A.2 – Sub-D connector pin numberings (front view)	29
Fig	jure A.3 – 5-pin M-12 female socket	30
Fig	ure A.4 – 5 pins M-12 male plug for CP 3/1	31
Fig	ure A.5 – Test circuit A - resistance measurement of data line B and shield	36
Fig	ure A.6 – Test circuit B resistance measurement of data line A and shield	37
	ure A.7 – Test circuit C, resistance measurement of data line A, data line B, and eld	37
Fig	ure A.8 – Test circuit Q - resistance measurement between data line A and B	4-383-201
Fig	jure A.9 – Resistance measurement without 9-pin Sub-D plug	38
Fig	jure A.10 – Loop core resistance (cable type A)	39
Fig	jure A.11 – Action and resolution tree for measurement 1 (RS 485 and RS 485-IS)	40
Fig	jure A.12 – Action and resolution tree for measurement 2 (RS 485 and RS 485-IS)	41
Fig	ure A.13 – Action and resolution tree for measurement 3 (RS 485 and RS 485-IS)	41
Fig	ure B.1 – Connection of CP 3/1 networks	46
Fig	jure B.2 – Typical fieldbus architecture	48
Fig	ure B.3 – Fieldbus with stations supplied by auxiliary power sources	49
Fig	jure B.4 – Fieldbus model	51
Fig	ure B.5 – Current modulation (Manchester II code)	52
Fig	jure B.6 – Tree topology	53
Fig	jure B.7 – Bus topology	54
Fig	ure B.8 – Combination of the tree topology and the bus topology	54
Fig	jure B.9 – Fieldbus extension	55
Fig	ure B.10 – Recommended combination of shielding and earthing	67
Fig	ure B.11 – Ideal combination of shielding and earthing	69
Fig	ure B.12 – Capacitive earthing	70
Fig	ure B.13 – Galvanic isolated field device	71

Figure B.14 – Pin assignment of the male and female connectors IEC 60947-5-2 (A- coding)	74
Figure C.1 – End-to-end link without interconnections	
Figure C.2 – Assembled end-to-end link	
Figure C.3 – Connectionless optical fibre link	
Figure C.4 – Assembled optical fibre link	
Figure C.5 – Shielded connectors for CP 3/3, CP 3/4, CP 3/5 and CP 3/6 fieldbus networks	
Figure C.6 – Pin-assignment for a straight cable	
Table A.1 – Excerpt of MICE definition	13
Table A.2 – Basic network characteristics for balanced cabling not based on Ethernet (ISO/IEC 8802-3)	15
	15
Table A.4 – Information relevant to copper cable: fixed cables	17
Table A.5 – Information relevant to optical fibre cables	18
Table A.6 – Connectors for copper cabling CPs not based on Ethernet	19
Table A.7 – Optical fibre connecting hardware	
Table A.8 – Relationship between FOC and fibre types (CP 8/1)	
Table A.9 – Parameters for balanced cables	
Table A.10 – Parameters for silica optical fibre cables	27
Table A.11 – Parameters for POF optical fibre cables	
Table A.12 – Parameters for hard clad silica optical fibre cables	
Table A.13 – Use of 9 pin Sub-D connector pins (RS 485)	
Table A.14 – Use of 9 pin Sub-D connector pins (RS 485-IS)	30
Table A.15 – Use of M12 connector pins (RS 485)	
Table A.16 - Use of M12 connector pins (RS 485-IS)	32
Table A.17 – Maximum fibre channel attenuation for CP 3/1 (PROFIBUS)	42
Table B.1 - Valid parameter range of the FISCO model for use as EEx ib IIC / IIB	50
Table B.2 - Valid parameter range of the FISCO model for use as EEx ia IIC	50
Table B.3 – Power supply operational values)	56
Table B.4 – Line lengths which can be achieved	56
Table B.5 – Limit values for distortion, reflection and signal delay	57
Table B.6 – Recommended maximum cable lengths including spurs	
Table B.7 – Recommended length of the spurs	57
Table B.8 – Maximum length of the splices	58
Table B.9 – Information relevant to copper cable: fixed cables	59
Table B.10 – Safety limit values for the fieldbus cable	60
Table B.11 – Connectors for copper cabling CPs not based on Ethernet	
Table B.12 – Mixing devices from different categories	
Table B.13 – Electrical characteristics of fieldbus interfaces	
Table B.14 – Recommended data sheet specifications for CP 3/2 devices	
Table B.15 – Parameters for balanced cables	
Table B.16 – Contact assignments for the external connector for harsh industrial	
environments	74

Table C.1 – General transmission media selection information	79
Table C.2 – Network characteristics for balanced cabling based on Ethernet (ISO/IEC 8802-3)	80
Table C.3 – Network characteristics for optical fibre cabling	80
Table C.4 – Information relevant to copper cable: CP 3/3, CP 3/4, CP 3/5 and CP 3/6 type A fixed cables	82
Table C.5 – Information relevant to copper cable: CP 3/3, CP 3/4, CP 3/5 and CP 3/6 type B flexible cables	82
Table C.6 – Information relevant to copper cable: CP 3/3, CP 3/4, CP 3/5 and CP 3/6 type C special cables	83
Table C.7 – Information relevant to optical fibre cables	83
Table C.8 – Requirements for plastic and hard clad silica optical fibre cables	84
Table C.9 – Requirements for glass multimode optical fibre cables	85
Table C.10 – Requirements for glass singlemode optical fibre cables	86
Table C.11 – Information relevant to hybrid cables (application type B)	87
Table C.12 – Information relevant to hybrid cables (application type Cy	87
Table C.13 – Connectors for balanced cabling CPs based on Ethernet	88
Table C.14 – Optical fibre connecting hardware	89
Table C.15 – Relationship between FOC and fibre types (CP/3/3, CP 3/4, CP 3/5, CP3/6)	89
Table C.16 – Typical fibre channels common for industrial applications.	92
Table C.17 – Parameters for balanced cables	95
Table C.18 – Parameters for silica optical fibre cables	96
Table C.19 – Parameters for PQF optical fibre cables	96
Table C.20 - Parameters for hard clad silica optical fibre cables	96
Table C.21 - Colour coding for CP 3/3, CP 3/4, CP 3/5 and CP 3/6 connectors	97
Table C.22 – Maximum fibre channel attenuation for CP 3/3, CP 3/4, CP 3/5 and icc-6178 CP 3/6 (PROFINET)	4-5-3-2 . 101

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INDUSTRIAL COMMUNICATION NETWORKS – PROFILES –

Part 5-3: Installation of fieldbuses – Installation profiles for CPF 3

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for Standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international user and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies. 3-3:2010

https://6) All users should ensure that they have the latest edition of this publication 6-0caa50550360/iec-61784-5-3-2010

- 7) No liability shall attach to NEC or its directors, employees, servants or agents including individual experts and members of its technical committees and NEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61784-5-3 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This second edition cancels and replaces the first edition published in 2007. This edition constitutes a technical revision.

This edition includes the technical changes of the corrigendum for the first edition in 2008 and an addition concerning transmission performance measurement (see Annex C.6.3.2.1.2).

This standard is to be used in conjunction with IEC 61918:2010.

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/602/FDIS	65C/616/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61784-5 series, published under the general title *Industrial communication networks – Profiles – Installation of fieldbuses*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.jec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

https

INTRODUCTION

This International Standard is one of a series produced to facilitate the use of communication networks in industrial control systems.

IEC 61918:2010 provides the common requirements for the installation of communication networks in industrial control systems. This installation profile standard provides the installation profiles of the communication profiles (CP) of a specific communication profile family (CPF) by stating which requirements of IEC 61918 fully apply and, where necessary, by supplementing, modifying, or replacing the other requirements (see Figure 1).

For general background on fieldbuses, their profiles, and relationship between the installation profiles specified in this standard, see IEC/TR 61158-1.

Each CP installation profile is specified in a separate annex of this standard. Each annex is structured exactly as the reference standard IEC 61918 for the benefit of the persons representing the roles in the fieldbus installation process as defined in IEC 61918 (planner, installer, verification personnel, validation personnel, maintenance personnel, administration personnel). By reading the installation profile in conjunction with IEC 61918, these persons immediately know which requirements are common for the installation of all CPs and which are modified or replaced. The conventions used to draft this standard are defined in Clause 5.

The provision of the installation profiles in one standard for each CPF (for example IEC 61784-5-3 for CPF 3), allows readers to work with standards of a convenient size.



Figure 1 – Standards relationships

INDUSTRIAL COMMUNICATION NETWORKS – PROFILES –

Part 5-3: Installation of fieldbuses – Installation profiles for CPF 3

1 Scope

This part of IEC 61784 specifies the installation profiles for CPF 3 (PROFIBUS/RROFINET)¹.

The installation profiles are specified in the annexes. These annexes are read in conjunction with IEC 61918:2010.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61918:2010, Industrial communication networks – Installation of communication networks in industrial premises

The normative references of IEC 61918:2010, Clause 2, apply. For profile specific normative references, see Clause(s) A.2, B,2 and C.2.

3 Terms, definitions and abbreviated terms

For the purposes of this document, the terms, definitions and abbreviated terms of 2010 IEC 61918:2010, Clause 3, apply. For profile specific terms, definitions and abbreviated terms see Clause(s) A.3, B.3 and C.3.

4 CPF 3: Overview of installation profiles

CPF 3 consists of six communication profiles as specified in IEC 61784-1 and IEC 61784-2.

The installation requirements for CP 3/1 (PROFIBUS with physical layer according to RS 485, RS 485-IS, and fibre) are specified in Annex A.

The installation requirements for CP 3/2 (PROFIBUS with physical layer according to MBP, MBP-IS, MBP-LP) are specified in Annex B.

The installation requirements for CP 3/3, CP 3/4, CP 3/5, and CP 3/6 (PROFINET) are specified in Annex C.

PROFIBUS and PROFINET are trade names of the non-profit organization PROFIBUS Nutzerorganisation e.V. (PNO). This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trade names holder or any of its products. Compliance to this profile does not require use of the trade names. Use of the trade names PROFIBUS and PROFINET requires permission of the trade name holder.

61784-5-3 © IEC:2010(E)

5 Installation profile conventions

The numbering of the clauses and subclauses in the annexes of this standard corresponds to the numbering of IEC 61918 main clauses and subclauses.

The annex clauses and subclauses of this standard supplement, modify, or replace the respective clauses and subclauses in IEC 61918.

Where there is no corresponding subclause of IEC 61918 in the normative annexes in this standard, the subclause of IEC 61918 applies without modification.

The annex heading letter represents the installation profile assigned in Clause 4. The annex (sub)clause numbering following the annex letter shall represent the corresponding (sub)clause numbering of IEC 61918.

EXAMPLE "Annex B.4.4" in IEC 61784-5-3 means that CP 3/2 specifies the Subclause 4.4 of IEC 61918,

All main clauses of IEC 61918 are cited and apply in full unless otherwise stated in each normative installation profile annex.

If all subclauses of a (sub)clause are omitted, then the corresponding IEC 61918 (sub)clause applies.

If in a (sub)clause it is written "Not applicable", then the corresponding IEC 61918 (sub)clause does not apply.

If in a (sub)clause it is written "Addition", then the corresponding IEC 61918 (sub)clause applies with the additions written in the profile.

If in a (sub)clause it is written "*Replacement*", then the text provided in the profile replaces the text of the corresponding IEC 61918 (sub)clause.

NOTE A replacement can also comprise additions 17 1-5-3:20

If in a (sub)clause it is written "Modification", then the corresponding IEC 61918 (sub)clause applies with the modifications written in the profile.

If all (sub)clauses of a (sub)clause are omitted but in this (sub)clause it is written "(Sub)clause x has addition" (or "replacement", or "modification") or "(Sub)clause is not applicable.", then (sub)clause x becomes valid as declared and all the other corresponding IEC 61918 (sub)clauses apply.

6 Conformance to installation profiles

Each installation profile within this standard includes part of IEC 61918:2010. It may also include defined additional specifications.

A statement of compliance to an installation profile of this standard shall be stated² as either

Compliance to IEC 61784-5-3:2010³ for CP 3/m <name> or

Compliance to IEC 61784-5-3 (Ed.2.0) for CP 3/m <name>

where the name within the angle brackets < > is optional and the angle brackets are not to be included. The m within CP 3/m shall be replaced by the profile number 1 to 6.

² In accordance with ISO/IEC Directives

³ The date should not be used when the edition number is used.

NOTE The name may be the name of the profile, for example PROFIBUS or PROFINET.

If the name is a trade name then the permission of the trade name holder shall be required.

- 10 -

Product standards shall not include any conformity assessment aspects (including quality management provisions), neither normative nor informative, other than provisions for product testing (evaluation and examination).

iTex Sxn (axos (https://standards.iteh.ati) D cover- Preview https://standards.iteh.ati controls/vice265833-3965-4887-9506-0eaa50550360/jee-61784-5-3-2010

Annex A

(normative)

CP 3/1 (PROFIBUS) specific installation profile

A.1 Installation profile scope

Addition:

This standard specifies the installation profile for Communication Profile CP 3/1 (PROFIBUS with a physical layer according to RS 485, RS 485-IS, and fibre). The CP 3/1 is specified in IEC 61784-1.

A.2 Normative references

Addition:

IEC 60079-11:2006, Explosive Athmospheres – Part 11: Equipment protection by intrinsic safety "I"

IEC 60512-6-3, Connectors for electronic equipment – Tests and measurements – Part 6-3: Dynamic stress tests; Test 6c: Shock

IEC 60512-6-4, Connectors for electronic equipment – Tests and measurements – Part 6-4: Dynamic stress tests; Test 6d: Vibration (sinusoidal)

IEC 61508 (all parts), Functional safety of electrical/electronic/programmable electronic safety-related systems

ANSI TIA/EIA-485 A Electrical Characteristics of Generators and Receivers for Use in Balanced Digital Multipoint Systems

A.3 Installation profile terms, definitions, and abbreviated terms

Terms and definitions A.3.1

Addition:

6.1 hazard potential source of harm

NOTE The term includes danger to persons arising within a short time scale (for example fire and explosion) and also those that have a long term effect on a person's health (for example release of a toxic substance).

[IEC 61508-4:2010⁴, 3.1.2]

6.2

intrinsic safety "i"

type of protection based on the restriction of electrical energy within apparatus and of interconnecting wiring exposed to the potentially explosive atmosphere to a level below that which can cause ignition by either sparking or heating effects

⁴ To be published.

[IEC 60079-11:2006, 3.1.1]

NOTE No single device or wiring is intrinsically safe by itself (except for battery-operated self-contained apparatus such as portable pagers, transceivers, gas detectors, etc., which are specifically designed as intrinsically safe self-contained devices) but is intrinsically safe only when employed as part of a properly designed intrinsically safe system.

A.3.2 Abbreviated terms

Addition:

MAU	Medium attachment unit
PELV	Protective Extra Low Voltage
PNO	PROFIBUS Nutzer Organisation (a non profit user organisation)
RS 485	MAU according to ANSI TIA/EIA-485-A
RS 485-IS	MAU according to ANSI TIA/EIA-485-A and applicable to IS
SELV	Safety Extra Low Voltage
TN-S	Coded type of system earthing according to IEC 60364-1, 312.2

A.3.3 Conventions for installation profiles

Not applicable.

A.4 Installation planning

A.4.1 Introduction

Subclause 4.1.2 has addition:

Generic cabling in accordance with ISO/IEC 24702 is not suitable for the cabling of CP 3/1 networks.

CP 3/1 networks only can be connected to the generic cabling via converter/adapter as specified in IEC 61918:2010, 4.1.2

A.4.2 Planning requirements

A.4.2.1 Safety

Subclause 4.2.1.3 has addition:

NOTE Each and every device on CP 3/1 networks (standard and safety) should provide a test certificate issued by PROFIBUS International (more information available by <www.profibus.com>) based on IEC 61158 or at least provide a corresponding manufacturers declaration stating compliance with CP 3/1 specification.

Each and every safety device shall comply with IEC 61508 series and other related standards if applicable.

The 24V power supplies in use shall be one-error proof and provide SELV/PELV only. National regulations shall be considered.

EXAMPLE In the United States of America the power supplies provide a current limitation of 8A according to UL508C.

No spurs or branch lines are permitted in a CP 3/1 network for safety applications.

Effective cable shielding especially after bending the cable or after changing connectors shall be ensured. In case of doubt, a more flexible and robust cable type should be used.