

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Industrial communication networks – Fieldbus specifications –
Part 4-12: Data-link layer protocol specification – Type 12 elements

Réseaux de communication industriels – Specifications de bus de terrain –
Partie 4-12: Spécification du protocole de couche de liaison de données –
Eléments de Type 12

<https://standards.itech.ai/ctn/ing/standards/icc/c00ce225-c2e6-4a61-a86d-a230954d2303/iec-61158-4-12-2010>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Useful links:

IEC publications search - www.iec.ch/searchpub

The advanced search enables you to find IEC publications by a variety of criteria (reference number, text, technical committee,...).

It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available on-line and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary (IEV) on-line.

Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Liens utiles:

Recherche de publications CEI - www.iec.ch/searchpub

La recherche avancée vous permet de trouver des publications CEI en utilisant différents critères (numéro de référence, texte, comité d'études,...).

Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

Just Published CEI - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications de la CEI. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électriques et électroniques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (VEI) en ligne.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.



IEC 61158-4-12

Edition 2.0 2010-08

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Industrial communication networks – Fieldbus specifications –
Part 4-12: Data-link layer protocol specification – Type 12 elements

Réseaux de communication industriels – Specifications de bus de terrain –
Partie 4-12: Spécification du protocole de couche de liaison de données –
Eléments de Type 12

<https://standards.itech.ai/ctc/ing/standards/iec/c00ce225-c2e6-4a61-a86d-a230954d2303/iec-61158-4-12-2010>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX XG

ICS 25.04.40; 35.100.20; 35.110

ISBN 978-2-88912-942-3

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	7
INTRODUCTION.....	9
1 Scope.....	10
1.1 General	10
1.2 Specifications	10
1.3 Procedures.....	10
1.4 Applicability.....	10
1.5 Conformance.....	10
2 Normative references	11
3 Terms, definitions, symbols and abbreviations.....	11
3.1 Reference model terms and definitions.....	11
3.2 Service convention terms and definitions.....	12
3.3 Common terms and definitions	13
3.4 Additional Type 12 definitions.....	13
3.5 Common symbols and abbreviations	16
3.6 Additional Type 12 symbols and abbreviations.....	17
3.7 Conventions	18
4 Overview of the DL-protocol	23
4.1 Operating principle	23
4.2 Topology	23
4.3 Frame processing principles	23
4.4 Data-link layer overview	24
4.5 Error detection overview	25
4.6 Node reference model	25
4.7 Operation overview	26
5 Frame structure.....	27
5.1 Frame coding principles	27
5.2 Data types and encoding rules	27
5.3 DLRDU structure	29
5.4 Type 12 DLPDU structure.....	32
5.5 Network variable structure	48
5.6 Type 12 mailbox structure	48
6 Attributes.....	50
6.1 Management	50
6.2 Statistics	66
6.3 Watchdogs	69
6.4 Slave information interface	72
6.5 Media independent interface (MII)	77
6.6 Fieldbus memory management unit (FMMU).....	80
6.7 Sync manager	83
6.8 Distributed clock.....	89
7 DL-user memory.....	93
7.1 Overview	93
7.2 Mailbox access type	94
7.3 Buffered access type	97

8	Type 12: FDL protocol state machines.....	99
8.1	Overview of slave DL state machines	99
8.2	State machine description	99
Annex A (informative)	Type 12: Additional specifications on DL-Protocol state machines	107
Bibliography.....	141	
Figure 1 – Type description example	19	
Figure 2 – Common structure of specific fields.....	20	
Figure 3 – Frame structure.....	24	
Figure 4 – Mapping of data in a frame.....	25	
Figure 5 – Slave node reference model.....	26	
Figure 6 – Type 12 PDUs embedded in Ethernet frame.....	27	
Figure 7 – Type 12 PDUs embedded in UDP/IP	27	
Figure 8 – DL information type description	51	
Figure 9 – Address type description.....	53	
Figure 10 – DL control type description.....	55	
Figure 11 – DL status type description.....	57	
Figure 12 – Successful write sequence to DL-user control register	59	
Figure 13 – Successful read sequence to the DL-user status register	60	
Figure 14 – RX error counter type description.....	67	
Figure 15 – Lost link counter type description	68	
Figure 16 – Additional counter type description.....	69	
Figure 17 – Sync configuration type description	70	
Figure 18 – Watchdog divider type description.....	70	
Figure 19 – Sync manager watchdog type description	71	
Figure 20 – Sync manager watchdog status type description	71	
Figure 21 – Watchdog counter type description.....	72	
Figure 22 – Slave information interface access type description	72	
Figure 23 – Slave information interface control/status type description	74	
Figure 24 – Slave information interface address type description	76	
Figure 25 – Slave information interface data type description	77	
Figure 26 – MII control/status type description	78	
Figure 27 – MII address type description	79	
Figure 28 – MII data type description	80	
Figure 29 – FMMU mapping example	80	
Figure 30 – FMMU entity type description	81	
Figure 31 – SyncM mailbox interaction.....	84	
Figure 32 – SyncM buffer allocation	84	
Figure 33 – SyncM buffer interaction	85	
Figure 34 – Handling of write/read toggle with read mailbox	85	
Figure 35 – Sync manager channel type description	87	
Figure 36 – Distributed clock local time parameter type description	91	
Figure 37 – Successful write sequence to mailbox	94	

Figure 38 – Bad write sequence to mailbox	95
Figure 39 – Successful read sequence to mailbox	95
Figure 40 – Bad read sequence to mailbox	96
Figure 41 – Successful write sequence to buffer	97
Figure 42 – Successful read sequence to buffer	98
Figure 43 – Structuring of the protocol machines of an slave	99
Figure 44 – Slave information interface read operation	101
Figure 45 – Slave information interface write operation	102
Figure 46 – Slave information interface reload operation	103
Figure 47 – Distributed clock	105
Figure 48 – Delay measurement sequence	106
Table 1 – PDU element description example	19
Table 2 – Example attribute description	20
Table 3 – State machine description elements	21
Table 4 – Description of state machine elements	22
Table 5 – Conventions used in state machines	22
Table 6 – Transfer Syntax for bit sequences	28
Table 7 – Transfer syntax for data type Unsignedn	28
Table 8 – Transfer syntax for data type Integern	29
Table 9 – Type 12 frame inside an Ethernet frame	30
Table 10 – Type 12 frame inside an UDP PDU	30
Table 11 – Type 12 frame structure containing Type 12 PDUs	31
Table 12 – Type 12 frame structure containing network variables	31
Table 13 – Type 12 frame structure containing mailbox	32
Table 14 – Auto increment physical read (APRD)	32
Table 15 – Configured address physical read (FPRD)	33
Table 16 – Broadcast read (BRD)	34
Table 17 – Logical read (LRD)	35
Table 18 – Auto Increment physical write (APWR)	37
Table 19 – Configured address physical write (FPWR)	38
Table 20 – Broadcast write (BWR)	39
Table 21 – Logical write (LWR)	40
Table 22 – Auto increment physical read write (APRW)	41
Table 23 – Configured address physical read write (FPRW)	42
Table 24 – Broadcast read write (BRW)	43
Table 25 – Logical read write (LRW)	44
Table 26 – Auto increment physical read multiple write (ARMW)	46
Table 27 – Configured address physical read multiple write (FRMW)	47
Table 28 – Network variable	48
Table 29 – Mailbox	49
Table 30 – Error Reply Service Data	49
Table 31 – DL information	52

Table 32 – Configured station address	54
Table 33 – DL control	55
Table 34 – DL status	58
Table 35 – DLS-user specific registers	60
Table 36 – DLS-user event	62
Table 37 – DLS-user event mask	64
Table 38 – External event	65
Table 39 – External event mask	66
Table 40 – RX error counter	67
Table 41 – Lost link counter	68
Table 42 – Additional counter	69
Table 43 – Watchdog divider	70
Table 44 – DLS-user watchdog	70
Table 45 – Sync manager channel watchdog	71
Table 46 – Sync manager watchdog Status	71
Table 47 – Watchdog counter	72
Table 48 – Slave information interface access	72
Table 49 – Slave information interface control/status	75
Table 50 – Actual slave information interface address	76
Table 51 – Actual slave information interface data	77
Table 52 – MII control/status	78
Table 53 – Actual MII address	79
Table 54 – Actual MII data	80
Table 55 – Fieldbus memory management unit (FMMU) entity	82
Table 56 – Fieldbus memory management unit (FMMU)	83
Table 57 – Sync manager channel	87
Table 58 – Sync manager Structure	89
Table 59 – Distributed clock local time parameter	92
Table 60 – Distributed clock DLS-user parameter	93
Table A.1 – Primitives issued by DHSM to PSM	107
Table A.2 – Primitives issued by PSM to DHSM	107
Table A.3 – Parameters used with primitives exchanged between DHSM and PSM	107
Table A.4 – Identifier for the octets of a Ethernet frame	108
Table A.5 – DHSM state table	110
Table A.6 – DHSM function table	125
Table A.7 – Primitives issued by SYSM to DHSM	125
Table A.8 – Primitives issued by DHSM to SYSM	126
Table A.9 – Primitives issued by DL-User to SYSM	126
Table A.10 – Primitives issued by SYSM to DL-User	126
Table A.11 – Parameters used with primitives exchanged between SYSM and DHSM	126
Table A.12 – SYSM state table	128
Table A.13 – SYSM function table	137
Table A.14 – Primitives issued by RMSM to SYSM	137

Table A.15 – Primitives issued by SYSM to RMSM	138
Table A.16 – Parameters used with primitives exchanged between RMSM and SYSM	138
Table A.17 – RMSM state table.....	139
Table A.18 – RMSM function table.....	140



<https://standards.iteh.ai/ct/ing/standards/iec/c00ce225-c2e6-4a61-a86d-a230954d2303/iec-61158-4-12-2010>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL COMMUNICATION NETWORKS –
FIELDBUS SPECIFICATIONS –****Part 4-12: Data-link layer protocol specification –
Type 12 elements****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

International Standard IEC 61158-4-12 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This second edition cancels and replaces the first edition published in 2007. This edition constitutes a technical revision.

The main changes with respect to the previous edition are listed below:

- bug fixes and
- editorial improvements.

This bilingual version (2012-05) corresponds to the monolingual English version published in 2010-08.

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/605/FDIS	65C/619/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The French version has not been voted upon.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

A list of all the parts of the IEC 61158 series, published under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

NOTE The revision of this standard will be synchronized with the other parts of the IEC 61158 series.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC/TR 61158-1.

The data-link protocol provides the data-link service by making use of the services available from the physical layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer data-link entities (DLEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- a) as a guide for implementors and designers;
- b) for use in the testing and procurement of equipment;
- c) as part of an agreement for the admittance of systems into the open systems environment;
- d) as a refinement to the understanding of time-critical communications within OSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

NOTE Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in Type combinations as specified explicitly in the profile parts. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of patents concerning Type 12 elements and possibly other types given as follows:

EP 1 590 927 B1	[BE] Koppler für ein Netzwerk mit Ringtopologie und ein auf Ethernet basierten Netzwerk
EP 1 789 857 B1	[BE] Datenübertragungsverfahren und automatisierungssystem zum Einsatz eines solchen Datenübertragungsverfahrens
DE 102007017835.4	[BE] Paketvermittlungsvorrichtung und lokales Kommunikationsnetz mit einer solchen Paketvermittlungsvorrichtung
EP 1 456 722 B1	[BE] Datenübertragungsverfahren, serielles Bussystem und Anschalteinheit für einen passiven Busteilnehmer

IEC takes no position concerning the evidence, validity and scope of these patent rights.

The holder of these patent rights has assured the IEC that he/she is willing to negotiate licences either free of charge or under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of these patent rights is registered with IEC. Information may be obtained from:

[BE]: Beckhoff Automation GmbH
Eiserstraße 5
33415 Verl,
Germany

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

ISO (www.iso.org/patents) and IEC (http://www.iec.ch/tctools/patent_decl.htm) maintain on-line data bases of patents relevant to their standards. Users are encouraged to consult the data bases for the most up to date information concerning patents.

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 4-12: Data-link layer protocol specification – Type 12 elements

1 Scope

1.1 General

The data-link layer provides basic time-critical messaging communications between devices in an automation environment.

This protocol provides communication opportunities to all participating data-link entities

- a) in a synchronously-starting cyclic manner, and
- b) in a cyclic or acyclic asynchronous manner, as requested each cycle by each of those data-link entities.

Thus this protocol can be characterized as one which provides cyclic and acyclic access asynchronously but with a synchronous restart of each cycle.

1.2 Specifications (<https://standards.iteh.ai>)

This standard specifies

- a) procedures for the transfer of data and control information from one data-link user entity to one or more user entity;
- b) the structure of the DLPDUs used for the transfer of data and control information by the protocol of this standard, and their representation as physical interface data units.

1.3 Procedures

The procedures are defined in terms of

- a) the interactions between DL-entities (DLEs) through the exchange of DLPDUs;
- b) the interactions between a DL-service (DLS) provider and a DLS-user in the same system through the exchange of DLS primitives;
- c) the interactions between a DLS-provider and the MAC services of ISO/IEC 8802-3.

1.4 Applicability

These procedures are applicable to instances of communication between systems which support time-critical communications services within the data-link layer of the OSI reference model, and which require the ability to interconnect in an open systems interconnection environment.

Profiles provide a simple multi-attribute means of summarizing an implementation's capabilities, and thus its applicability to various time-critical communications needs.

1.5 Conformance

This standard also specifies conformance requirements for systems implementing these procedures. This part of this standard does not contain tests to demonstrate compliance with such requirements.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61158-2:2010¹, *Industrial communication networks – Fieldbus specifications – Part 2: Physical layer specification and service definition*

IEC 61158-3-12, *Industrial communication networks – Fieldbus specifications – Part 3-12: Data-link layer service definition – Type 12 elements*

IEC 61588, *Precision clock synchronization protocol for networked measurement and control system*

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model*

ISO/IEC 7498-3, *Information technology – Open Systems Interconnection – Basic Reference Model: Naming and addressing*

ISO/IEC 8802-3:2000, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications*

ISO/IEC 9899, *Programming Languages – C*

ISO/IEC 10731, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*

<https://standards.iteh.ai>
Document Preview
IEC 61158-4-12:2010
IEEE 802.1Q, *IEEE Standard for Local and metropolitan Area Networks – Virtual Bridged Local Area Networks*, available at <<http://www.ieee.org>>

IETF RFC 768, *User Datagram Protocol (UDP)*, available at <<http://www.ietf.org>>

IETF RFC 791, *Internet protocol DARPA internet program protocol specification*, available at <<http://www.ietf.org>>

3 Terms, definitions, symbols and abbreviations

For the purposes of this document, the following terms, definitions, symbols and abbreviations apply.

3.1 Reference model terms and definitions

This standard is based in part on the concepts developed in ISO/IEC 7498-1 and ISO/IEC 7498-3, and makes use of the following terms defined therein.

3.1.1 DL-duplex-transmission

[ISO/IEC 7498-1]

3.1.2 DL-protocol

[ISO/IEC 7498-1]

¹ To be published

3.1.3 DL-protocol-data-unit	[ISO/IEC 7498-1]
3.1.4 (N)-entity DL-entity Ph-entity	[ISO/IEC 7498-1]
3.1.5 (N)-interface-data-unit DL-service-data-unit (N=2) Ph-interface-data-unit (N=1)	[ISO/IEC 7498-1]
3.1.6 (N)-layer DL-layer (N=2) Ph-layer (N=1)	[ISO/IEC 7498-1]
3.1.7 (N)-service DL-service (N=2) Ph-service (N=1)	[ISO/IEC 7498-1]
3.1.8 (N)-service-access-point DL-service-access-point (N=2) Ph-service-access-point (N=1)	[ISO/IEC 7498-1]
3.1.9 (N)-service-access-point-address DL-service-access-point-address (N=2) Ph-service-access-point-address (N=1)	[ISO/IEC 7498-1]
3.1.10 peer-entities	[ISO/IEC 7498-1]
3.1.11 Ph-interface-data	[ISO/IEC 7498-1]
3.1.12 primitive name	[ISO/IEC 7498-3]
3.1.13 reassembling	[ISO/IEC 7498-1]
3.1.14 recombining	[ISO/IEC 7498-1]
3.1.15 reset	[ISO/IEC 7498-1]
3.1.16 routing	[ISO/IEC 7498-1]
3.1.17 segmenting	[ISO/IEC 7498-1]
3.1.18 sequencing	[ISO/IEC 7498-1]
3.1.19 splitting	[ISO/IEC 7498-1]
3.1.20 systems-management	[ISO/IEC 7498-1]

3.2 Service convention terms and definitions

This standard also makes use of the following terms defined in ISO/IEC 10731 as they apply to the data-link layer:

- 3.2.1 asymmetrical service**
- 3.2.2 confirm (primitive); requestor.deliver (primitive)**
- 3.2.3 deliver (primitive)**
- 3.2.4 DL-service-primitive; primitive**
- 3.2.5 DL-service-provider**