

Edition 2.0 2010-08

INTERNATIONAL STANDARD



https://standards.iteh.a

<u>118-6-9:2010</u> 105dd-43c5-42bc-8db6-72fcc64ea6d7/iec-61158-6-9-2010



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Email: inmail@iec.ch Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Catalogue of IEC publications: <u>www.iec.ch/searchpub</u>

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications

IEC Just Published: www.iec.ch/online_news/ivstpub Stay up to date on all new IEC publications. Just Published details wice a month all new publications released. Available on-line and also by email.

Electropedia: <u>www.electropedia.org</u>

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

Customer Service Centre: <u>nww.iec.ch/webstore/custServ</u>
If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service
Centre FAQ or contact us:

https:

ps://Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00

Email: csc@iec.ch

d-43c5-42bc-8db6-72fcc64ea6d7/iec-61158-6-9-2010



Edition 2.0 2010-08

INTERNATIONAL STANDARD

Industrial communication networks - Fieldbus specifications -Part 6-9: Application layer protocol specification - Type 9 elements

https://standards.iteh.ai/

<u>8-6-9.2010</u> dd-43c5-42bc-8db6-72fcc64ea6d7/iec-61158-6-9-2010

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

ICS 25.04.40; 35.100.70; 35.110

ISBN 978-2-88912-127-4

CONTENTS

| 1 S | соре | 8 |
|-------|--|----|
| 1 | .1 General | 8 |
| 1 | .2 Specifications | 8 |
| 1 | .3 Conformance | 9 |
| 2 N | ormative references | 9 |
| 3 Т | erms, definitions, symbols, abbreviations and conventions | 9 |
| 3 | .1 Terms and definitions from other ISO/IEC standards | 9 |
| 3 | | |
| 3 | .3 Abbreviations and symbols | |
| 3 | .4 Conventions | |
| 3 | .5 Conventions used in state machines | 15 |
| 4 A | bstract syntax | 16 |
| 4 | .1 FAL-AR PDU abstract syntax | |
| 4 | .2 Abstract syntax of PDUBody | |
| 4 | .3 Type definitions for ASEs | 22 |
| 4 | .4 Abstract syntax of data types | 27 |
| 5 T | ransfer syntax | |
| 5 | .1.1 General | |
| 5 | .1.2 Coding rules | 28 |
| 5 | .1.3 Structure of the identification information | 29 |
| 6 S | tructure of FAL protocol state machines | |
| 7 A | P-Context state machines | 40 |
| 7 | .1 VCR PM structure | |
| | .2 VCR PM state machine | |
| 8 F | AL service protocol machine (FSPM) | |
| | .1 General | |
| | .2 FSPM state tables | |
| 8 | .3 Functions used by FSPM | |
| 8 | .4 Parameters of FSPM/ARPM primitives | |
| 9 A | pplication relationship protocol machines (ARPMs) | 55 |
| 9 | .1 AREP mapping to data-link layer | |
| | .2 Application relationship protocol machines (ARPMs) | |
| | .3 AREP state machine primitive definitions | |
| 9 | .4 AREP state machine functions | |
| 10 D | LL mapping protocol machine (DMPM) | 84 |
| | 0.1 DMPM States | |
| | 0.2 DMPM state table | |
| | 0.3 Primitives exchanged between data-link layer and DMPM | |
| | 0.4 Functions used by DMPM | |
| | graphy | |
| | | |
| Figur | e 1 – Insertion of identification information in the FMS PDU | |

| Figure 3 – Coding with identification | 30 |
|--|----------|
| Figure 4 – Coding without identification | 30 |
| Figure 5 – Representation of the value true | |
| Figure 6 – Representation of the value false | 31 |
| Figure 7 – Coding of data of data type Integer16 | |
| Figure 8 – Coding of data of data type Unsigned16 | |
| Figure 9 – Coding of data of data type Floating Point | 32 |
| Figure 10 – Coding of data of data type Visible String | 33 |
| Figure 11 – Coding of data of data type Octet String | 33 |
| Figure 12 – Coding of data of type Date | 34 |
| Figure 13 – Coding of data of data type Time-of-day | 35 |
| Figure 14 – Coding of data of data type Time-difference | 35 |
| Figure 15 – Coding of data of data type Bit String | |
| Figure 16 – Coding of data of data type Time-value | 36 |
| Figure 17 – Coding of data of user data definitions with identifier | 37 |
| Figure 18 – Coding of data of user data definitions without identifier | |
| Figure 19 – Coding of ID info for a SEQUENCE | 37 |
| Figure 20 – Relationships among protocol machines and adjacent layers | 39 |
| Figure 21 – Relationships among protocol machines and adjacent layers | 40 |
| Figure 22 – VCR state machine | 41 |
| Figure 23 – State transition diagram of FSPM | 52 |
| Figure 24 - State transition diagram of the QUU ARPM | 66 |
| Figure 25 – State transition diagram of QUB ARPM | 68 |
| Figure 26 - State transition diagram of the BNU ARPM 10. | 76 |
| Figure 27 - State transition diagram of DMPMdd.43.5.42ho.8dh6.72foc64co6d7/icc.61158 | -849-201 |
| | |
| Table 1 – Conventions used for state machines | |
| Table 2 – Coding for Date type | |
| Table 3 – AP-VCR state machine transactions | |
| Table 4 - Primitives issued by FAL-User to VCR PM | |
| Table 5 – Primitives issued by VCR PM to FAL-User | |
| Table 6 – Primitives Issued by VCR PM to FSPM | |
| Table 7 – Primitives issued by FSPM to VCR PM | |
| Table 8 – FSPM state table – sender transactions | |
| Table 9 – FSPM state table – receiver transactions | |
| Table 10 – Function SelectArep() | |
| Table 11 – Parameters used with primitives exchanged between FSPM and ARPM | |
| Table 12 – QUU ARPM states | |
| Table 13 – QUU ARPM state table – sender transactions | |
| Table 14 – QUU ARPM state table – receiver transactions | |
| Table 15 – QUB ARPM states | |
| Table 16 – QUB ARPM state table – sender transactions | |
| Table 17 – QUB ARPM state table – receiver transactions | 70 |

| Table 18 – BNU ARPM states | 76 | | | |
|--|----|--|--|--|
| Table 19 – BNU ARPM state table – sender transactions | | | | |
| Table 20 – BNU ARPM state table – receiver transactions | | | | |
| Table 21 – Primitives issued from ARPM to DMPM81 | | | | |
| Table 22 – Primitives issued by DMPM to ARPM | | | | |
| Table 23 – Parameters used with primitives exchanged between ARPM and DMPM82 | | | | |
| Table 24 – Function GetArepId()8 | 83 | | | |
| Table 25 – Function BuildFAS-PDU | 83 | | | |
| Table 26 – Function FAS_Pdu_Type8 | | | | |
| Table 27 – Function AbortIdentifier | 83 | | | |
| Table 28 – Function AbortReason | 83 | | | |
| Table 29 – Function AbortDetail | 84 | | | |
| Table 30 – DMPM state descriptions | 84 | | | |
| Table 31 – DMPM state table – sender transactions | | | | |
| Table 32 – DMPM state table – receiver transactions | | | | |
| Table 33 – Primitives exchanged between data-link layer and DMPM | | | | |
| Table 34 – Function PickArep | 94 | | | |
| Table 35 – Function FindAREP | 95 | | | |
| Table 36 – Function LocateQubArep | 95 | | | |
| Table 37 – Function SetIdentifier() | 95 | | | |
| Curlen Preview | | | | |

https://standards.iteh.ai

idd-43c5-42bc-8db6-72fcc64ea6d7/iec-61158-6-9-2010

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS -

Part 6-9: Application layer protocol specification – Type 9 elements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The 🔊 💫 to f IEC is 🗽 promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and nongovernmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any
- services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

NOTE 1 Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in Type combinations as specified explicitly in the profile parts. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

International Standard IEC 61158-6-9 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This second edition cancels and replaces the first edition published in 2007. This edition constitutes a technical revision.

The main change with respect to the previous edition is listed below:

• Correction of Table 32.

The text of this standard is based on the following documents:

| FDIS | Report on voting |
|--------------|------------------|
| 65C/607/FDIS | 65C/621/RVD |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61158 series, published under the general title *Industrial* communication networks – Fieldbus specifications, can be found on the IEC web site.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be:

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

NOTE 2 The revision of this standard will be synchronized with the other parts of the IEC 61158 series.

https://standards.iteh.au

dd-43c5-42bc-8db6-72fcc64ea6d7/iec-61158-6-9-2010

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the "three-layer" fieldbus reference model described in IEC/TR 61158-1.

The application protocol provides the application service by making use of the services available from the data-link or other immediately lower layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer application entities (AEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- as a guide for implementors and designers;
- for use in the testing and procurement of equipment;
- as part of an agreement for the admittance of systems into the open systems environment;
- as a refinement to the understanding of time-critical compunications within OSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

https://standards.iteh.au

1-43c5-42bc-8db6-72fcc64ea6d7/iec-61158-6-9-2010

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 6-9: Application layer protocol specification – Type 9 elements

1 Scope

1.1 General

The Fieldbus Application Layer (FAL) provides user programs with a means to access the fieldbus communication environment. In this respect, the FAL can be viewed as a "window between corresponding application programs."

This standard provides common elements for basic time-critical and non-time-critical messaging communications between application programs in an automation environment and material specific to type 9 fieldbus. The term "time-critical" is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This standard defines in an abstract way the externally visible behavior provided by the Type 9 fieldbus Application Layer in terms of

- a) the abstract syntax defining the application layer protocol data units conveyed between communicating application entities.
- b) the transfer syntax defining the application layer protocol data units conveyed between communicating application entities,
- c) the application context state machine defining the application service behavior visible between communicating application entities; and
- d) the application relationship state machines defining the communication behavior visible between communicating application entities; and.

The purpose of this standard is to define the protocol provided to

- 1) define the wire-representation of the service primitives defined in IEC 61158-5-5, and
- 2) define the externally visible behavior associated with their transfer.

This standard specifies the protocol of the Type 9 IEC fieldbus application layer, in conformance with the OSI Basic Reference Model (ISO/IEC 7498) and the OSI Application Layer Structure (ISO/IEC 9545).

1.2 Specifications

The principal objective of this standard is to specify the syntax and behavior of the application layer protocol that conveys the application layer services defined in IEC 61158-5-9.

A secondary objective is to provide migration paths from previously-existing industrial communications protocols. It is this latter objective which gives rise to the diversity of protocols standardized in IEC 61158-6.

61158-6-9 © IEC:2010(E)

1.3 Conformance

This standard does not specify individual implementations or products, nor does it constrain the implementations of application layer entities within industrial automation systems. Conformance is achieved through implementation of this application layer protocol specification.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60559, Binary floating-point arithmetic for microprocessor systems

IEC 61158-3-1, Industrial communication networks – Fieldbus specifications – Part 3-1: Datalink layer service definition – Type 1 elements

IEC 61158-4-1, Industrial communication networks – Fieldbus specifications – Part 4-1: Datalink layer protocol specification – Type 1 elements

IEC 61158-5-5, Industrial communication networks - Fieldbus specifications – Part 5-5: Application layer service definition – Type 5 elements

IEC 61158-5-9, Industrial communication networks - Fieldbus specifications – Part 5-9: Application layer service definition – Type 9 elements

ISO/IEC 7498-1, Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model

ISO/IEC 8824-1, Information technology Abstract Syntax Notation One (ASN.1):

ISO/IEC 8825-1, Information technology -- ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)

ISO/IEC 9545, Information technology – Open Systems Interconnection – Application Layer structure

ISO/IEC 10731, Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services

3 Terms, definitions, symbols, abbreviations and conventions

For the purposes of this document, the following terms and definitions apply.

3.1 Terms and definitions from other ISO/IEC standards

3.1.1 Terms and definitions from ISO/IEC 7498-1

- a) abstract syntax
- b) application entity
- c) application process
- d) application protocol data unit
- e) application service element
- f) application entity invocation

- application process invocation
- g) application process invoch) application transaction
- i) presentation context
- j) real open system
- k) transfer syntax

3.1.2 Terms and definitions from ISO/IEC 9545

- a) application-association
- b) application-context
- c) application context name
- d) application-entity-invocation
- e) application-entity-type
- f) application-process-invocation
- g) application-process-type
- h) application-service-element
- i) application control service element

3.1.3 Terms and definitions from ISO/IEC 8824-1

- a) object identifier
- b) type
- c) value
- d) simple type
- e) structured type
- f) component type
- g) tag
- h) Boolean type
- i) true
- j) false
- k) integer type
- bitstring type
- m) octetstring type
- n) null type
- o) sequence type
- p) sequence of type
- q) choice type
 - tagged type
- s) any type
- t) module

r)

u) production

3.1.4 Terms and definitions from ISO/IEC 8825-1

- a) encoding (of a data value)
- b) data value
- c) identifier octets (the singular form is used in this standard)
- d) length octet(s) (both singular and plural forms are used in this standard)
- e) contents octets

3.2 IEC/TR 61158-1 terms

The following IEC/TR 61158-1 terms apply.

3.2.1 application

function or data structure for which data is consumed or produced

3.2.2 application layer interoperability

capability of application entities to perform coordinated and cooperative operations using the services of the FAL

61158-6-9 © IEC:2010(E) - 11 -

3.2.3 application object

object class that manages and provides the run time exchange of messages across the network and within the network device

NOTE: Multiple types of application object classes may be defined

3.2.4 application process

part of a distributed application on a network, which is located on one device and unambiguously addressed

3.2.5 application process identifier

distinguishes multiple application processes used in a device

3.2.6 application process object

component of an application process that is identifiable and accessible through an FAL application relationship. Application process object definitions are composed of a set of values for the attributes of their class (see the definition for Application Process Object Class Definition). Application process object definitions may be accessed remotely using the services of the FAL Object Management ASE. FAL Object Management services can be used to load or update object definitions, to read object definitions, and to dynamically create and delete application objects and their corresponding definitions

3.2.7 application process object class

a class of application process objects defined in terms of the set of their network-accessible attributes and services

3.2.8 application relationship

http

cooperative association between two or more application-entity-invocations for the purpose of exchange of information and coordination of their joint operation. This relationship is activated either by the exchange of application-protocol-data-units or as a result of preconfiguration activities

3.2.9 application relationship application service element

application-service-element that provides the exclusive means for establishing and terminating all application relationships

3.2.10 application relationship endpoint

context and behavior of an application relationship as seen and maintained by one of the application processes involved in the application relationship. Each application process involved in the application relationship maintains its own application relationship endpoint

3.2.11 attribute

description of an externally visible characteristic or feature of an object. The attributes of an object contain information about variable portions of an object. Typically, they provide status information or govern the operation of an object. Attributes may also affect the behaviour of an object. Attributes are divided into class attributes and instance attributes

3.2.12 behaviour

indication of how the object responds to particular events. Its description includes the relationship between attribute values and services

3.2.13 class

a set of objects, all of which represent the same kind of system component. A class is a generalisation of the object; a template for defining variables and methods. All objects in a class are identical in form and behaviour, but usually contain different data in their attributes

3.2.14 class attributes

an attribute that is shared by all objects within the same class

3.2.15 class code

a unique identifier assigned to each object class

3.2.16 class specific service

a service defined by a particular object class to perform a required function which is not performed by a common service. A class specific object is unique to the object class which defines it

3.2.17 client

(a) an object which uses the services of another (server) object to perform a task

(b) an initiator of a message to which a server reacts, such as the role of an AR endpoint in which it issues confirmed service request APRUs to a single AR endpoint acting as a server

3.2.18 conveyance path

unidirectional flow of APDUs across an application relationship

3.2.19 cyclic

https://term/used/to/describe events which repeat in a regular and repetitive manner6d7/iec-61158-6-9-2010

3.2.20 dedicated AR

AR used directly by the FAL User. On Dedicated ARs, only the FAL Header and the user data are transferred

3.2.21 device

a physical hardware connection to the link. A device may contain more than one node

3.2.22 device profile

a collection of device dependent information and functionality providing consistency between similar devices of the same device type

3.2.23 dynamic AR

AR that requires the use of the AR establishment procedures to place it into an established state

3.2.24 endpoint

one of the communicating entities involved in a connection