IEC 60079-2

Edition 6.0 2014-07
REDLINE VERSION

INTERNATIONAL STANDARD

colour inside

Explosive atmospheres –
Part 2: Equipment protection by pressurized enclosure "p"

IEC 60079-2:2014-07 RLV(en)

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue
The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,…). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org
The world's leading online dictionary of electronic and electrical terms containing 21 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary
67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC 60079-2

Edition 6.0 2014-07
REDLINE VERSION

INTERNATIONAL STANDARD

colour inside

Explosive atmospheres –
Part 2: Equipment protection by pressurized enclosure "p"

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.260.20

ISBN 978-2-8322-1775-7

CONTENTS

FOREWORD 7
INTRODUCTION 16
1 Scope 17
2 Normative references 17
3 Terms and definitions 18
4 Protection ~~types~~ levels 21
5 Constructional requirements for pressurized enclosures 24
5.1 Enclosure 24
5.2 Materials 24
5.3 Doors and covers 24
5.3.1 Group I pressurized enclosures 24
5.3.2 Group I pressurized enclosures with static pressurization 24
5.3.3 Group II and Group III pressurized enclosures 24
5.3.4 Group II and Group III pressurized enclosures with static pressurization 25
5.3.5 ~~Type px~~ Group II and Group III Level of Protection “pxb” 25
5.3.6 ~~Marking for Group I or~~ Group II and Group III Door and Cover warning 25
5.4 Mechanical strength 25
5.5 Group I and Group II Apertures, partitions, compartments and internal components 25
5.6 Apertures for Static Pressurization 26
5.7 Insulating materials for Group I equipment 26
5.8 Sealing 26
5.9 Spark and particle barriers 26
5.10 Cells and batteries 25
6 Temperature limits 27
6.1 General 27
6.2 For ~~type px or type py~~ Level of Protection “pxb” or Level of Protection “pyb” 27
6.3 For ~~type pz~~ Level of Protection “pzc” 28
7 Safety provisions and safety devices (except for static pressurization) 28
7.1 Suitability of safety devices for hazardous area 28
7.2 Integrity of safety devices 28
7.3 Provider of safety devices 29
7.4 Pressurization System evaluated as associated equipment 29
7.4.1 Pressurization systems for Level of Protection ”pzc”. 29
7.4.2 Pressurization systems for Level of Protection ”pyb”. 29
7.4.3 Pressurization systems for Level of Protection ”pxb”. 29
7.5 Sequence diagram for ~~type px~~ Level of Protection “pxb” 30
7.6 Ratings for safety devices 30
7.7 Group I and Group II – Purging automated for ~~type px~~ Level of Protection “pxb” 30
7.8 Group I or Group II – Purging criteria 30
7.9 Group III – Cleaning 31
7.10 Requirements when a minimum flow rate required 31
7.11 Safety devices to detect minimum overpressure 31
7.12 Value of minimum overpressure 32
7.13 Pressurizing multiple enclosures 32

7.14 Safety devices on doors and covers 33
7.15 ~~Protection types~~ Equipment that may remain energized 33
7.16 ~~Protection types~~ Equipment permitted within ~~type py~~ Level of Protection "pyb" 33
8 Safety provisions and safety devices for static pressurization 33
8.1 Suitability of safety devices for hazardous area 33
8.2 Protective gas 34
8.3 Internal sources of release 34
8.4 Group I and Group II – Filling procedure 34
8.5 Group III – Filling Procedure 34
8.6 Safety devices 34
8.7 ~~Protection types~~ Equipment that may remain energized 34
8.8 Overpressure 34
9 Supply of protective gas 34
9.1 Backup supply 34
9.2 Independent supplies 35
9.3 Type of gas 35
9.4 Temperature 35
10 Pressurized equipment with an internal source of release 35
11 Release conditions 35
11.1 No release 35
11.2 Limited release of a gas or vapour 36
11.3 Limited release of a liquid 36
12 Design requirements for the containment system 36
12.1 General design requirements 36
12.2 Infallible containment system 37
12.3 Containment system with a limited release 37
13 Protective gas and pressurizing techniques when there is an internal source of release 38
13.1 General 38
13.2 Pressurization with leakage compensation 38
13.2.1 No release 38
13.2.2 Limited release of a gas or liquid 38
13.3 Pressurization with dilution 39
13.3.1 General 39
13.3.2 No release 39
13.3.3 Limited release of a gas or vapour 39
13.3.4 Limited release of a liquid 39
14 Ignition-capable ~~apparatus~~ equipment 39
15 Internal hot surfaces 40
16 Type verification and tests 40
16.1 Determining the maximum overpressure rating 40
16.2 Maximum overpressure test 40
16.3 Leakage test 41
16.3.1 Other than static pressurization 41
16.3.2 Static pressurization 41

16.4 Purging test for pressurized enclosures with no internal source of release~~(pressurization technique may be leakage compensation or continuous flow)~~ and filling procedure test for static pressurization 41
16.4.1 General 41
16.4.2 Pressurized enclosure where the protective gas is air 41
16.4.3 Pressurized enclosure where the protective gas is inert 41
16.4.4 Pressurized enclosure where the protective gas may be either air or an inert gas with a density equal to air ±10 % 42
16.4.5 Filling procedure test for a pressurized enclosure protected by static pressurization 42
16.5 Purging and dilution tests for a pressurized enclosure with an internal source of release 42
16.5.1 Test gas 42
16.5.2 Pressurized enclosure where the flammable substance has less than 2 % (V/V) oxygen and the protective gas is inert 42
16.5.3 Pressurized enclosure with pressurization by continuous flow, containment system with less than 21 % (V/V) oxygen and the protective gas is inert 42
16.5.4 Pressurized enclosure where the flammable substance is not a liquid, pressurization by continuous flow and the protective gas is air 43
16.6 Verification of minimum overpressure 44
16.7 Tests for an infallible containment system 44
16.7.1 Overpressure test 44
16.7.2 Infallibility test 44
16.8 Overpressure test for a containment system with a limited release 45
17 Routine tests 45
17.1 Functional test 45
17.2 Leakage test 45
17.3 Tests for an infallible containment system 45
17.4 Test for a containment system with a limited release 45
18 Marking 46
18.1 ~~Warnings~~ General 46
18.2 Identifying as pressurized 46
18.3 Supplementary marking 46
18.4 Internal source of release 46
18.5 Static pressurization 47
18.6 Pressurization systems 47
18.7 Warnings required in other clauses 47
18.8 Overpressure limited by user 48
18.9 Inert gas 48
19 Instructions 48

Annex A (normative) Purging and dilution tests 49
A.1 Geneal 49
A.2 Criteria for compliance where the protective gas is inert 49
A.3 Criteria for compliance where the protective gas is inert 49
Annex B (informative) Examples of functional sequence diagram 50
Annex C (informative) Examples of the changes in pressure in ducts and enclosures 52
Annex D (informative) Information to be provided to the user 57
D.1 General 57

D.2 Ducting of protective gas 57
D.2.1 Location of inlet 57
D.2.2 Ducting between pressurized enclosure and inlet 57
D.2.3 Outlets for protective gas 57
D.2.4 Additional purge time to account for ducting 58
D.2.5 Temperature of protective gas at the inlet 58
D.3 Power for protective gas supply 58
D.4 Static pressurization 58
D.5 Enclosures with a containment system 58
D.6 Enclosure maximum overpressure 58
Annex E (normative) Classification of the type of release within enclosures 59
E.1 General 59
E.2 No normal release, no abnormal release 59
E.3 No normal release, limited abnormal release 59
E.4 Limited normal release 59
Annex F (informative) Examples for the use of the dilution area concept 60
~~Annex G (normative) Infallibility test for containment system ....60~~
Annex G (normative) Internal Cells and Batteries for Level of Protection “pxb” and Level of Protection “pyb” 67
G.1 General Requirements 67
G.1.1 General 67
G.1.2 Accepted Electrochemical Systems 67
G.1.3 Secondary cells and secondary batteries 67
G.1.4 Mechanical Protection 67
G.2 Electrical Protection by energy limiting circuits 68
G.2.1 Assessing as energy limited 68
G.2.2 Protective Components 68
G.2.3 Preventing excessive gas pressure 68
G.3 Additional requirements for Primary batteries 69
G.3.1 Prevention of reverse charging. 69
G.3.2 Prevention of accidental charging of primary batteries 69
G.4 Additional requirements for secondary batteries 70
G.4.1 Charging of secondary batteries inside the pressurized housing 70
G.5 Specific requirements for Inherently Safe (IhS) cells and batteries 70
G.6 Equipment located inside a pressurized enclosure connected to a battery which is also located inside the pressurized enclosure and not disconnected in the event of loss of pressurization 71
G.6.1 General 71
G.6.2 Circuit Isolation 71
G.6.3 Intrinsically safe battery or inherently safe battery used with “Ex” equipment 71
G.6.4 Intrinsically Safe or Inherently Safe battery with non-"Ex" equipment. 71
G.7 Supplementary marking and constructional requirements for pressurized enclosures containing one or more cells or batteries 73
G.7.1 General 73
G.7.2 Battery removal warning 73
G.7.3 Batteries requiring routine maintenance 73
G.8 Type tests 73
G.8.1 Voltage 73

G.8.2 Short circuit test for an Inherently Safe Cell or Battery 73
G.8.3 Full load test for other than Inherently safe batteries 73
~~Annex H (informative) Introduction of an alternative risk assessment method encompassing "equipment protection levels" for Ex equipment ..... 61~~
Annex H (normative) Internal Cells and Batteries for Level of Protection "pzc" 74
H.1 General Requirements 74
H.1.1 General 74
H.1.2 Accepted Electrochemical Systems 74
H.1.3 Secondary cells and secondary batteries 74
H.1.4 Mechanical Protection 74
H.2 Equipment located inside a pressurized enclosure connected to a battery which is also located inside the pressurized enclosure and is not disconnected when power is removed from the enclosure. 75
H.3 Supplementary marking and constructional requirements for pressurized enclosures containing one or more cells or batteries 75
H.3.1 General 75
H.3.2 Battery removal warning 75
H.3.3 Batteries requiring routine maintenance 75

Bibliography 76

Figure B.1 – State diagram of a leakage-compensation purge control system 50
Figure C.1 – Protective gas outlet 53
Figure C.2 – Pressurized enclosures with leakage compensation, enclosures without moving parts 54
Figure C.3 – Pressurized enclosures with leakage compensation, rotating electrical machine with an internal cooling fan 55
Figure C.4 – Pressurized enclosure with a leakage compensation, rotating electrical machine with an external cooling fan 56
Figure F.1 – Diagram showing the use of the dilution area concept to simplify the purge and dilution test requirements 60
Figure F.2 – Diagram showing the use of the infallible containment system concept to simplify the purging and dilution requirements around IC~~A~~E 61
Figure F.3 – Diagram showing the use of internal partitions around the potential source of release to simplify the purging and dilution requirements around IC~~A~~E located outside the partitions 61
Figure G.1 – Reverse charging protection 69
Figure G.2 – Accidental charging protection 69

Table 1 – Determination of protection ~~type~~ level 22
Table 2 – Design criteria based upon ~~type~~ level of protection 23
Table 3 – Safety devices based upon ~~protection type~~ Level of Protection 28
Table 4 – Protective gas requirements for a pressurized enclosure with a containment system 38
Table 5 – Equipment Protection ~~types~~ Levels permitted within the dilution area based upon the Level of Protection of the pressurized enclosure 39
Table 6 – Text of warning markings 47
Table B.1 – Truth table of a leakage-compensation purge control system 50

INTERNATIONAL ELECTROTECHNICAL COMMISSION

EXPLOSIVE ATMOSPHERES –

Part 2: Equipment protection by pressurized enclosure "p"

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

International Standard IEC 60079-2 has been prepared by technical committee 31: Explosive atmospheres.

This sixth edition cancels and replaces the fifth edition published in 2007. This sixth edition cancels and replaces the first edition of IEC 61241-4 published in 2001. This sixth edition constitutes a technical revision.

The significance of changes between IEC 60079-2, Edition 6.0, 2014 and IEC 60079-2, Edition 5.0, 2007 are as listed below:

		Type		
Changes	**Clause**	**Minor and Editorial Changes**	**Extension**	**Major Technical Changes**
Scope Expanded to include combustible dust	1		X	
Protective Gas Replaced “apparatus” with “equipment”	3			
Protective Gas Revised to show that purging is not required for explosive dust atmospheres	3.16	X		
Level of Protection “pxb” Term and definitions revised to reflect EPL and level of protection	3.21	X		
Level of Protection “pyb” Term and definitions revised to reflect EPL and level of protection	3.22	X		
Level of Protection “pzc” Term and definitions revised to reflect EPL and level of protection	3.23	X		
Lower Flammable Limit Term and definition revised to agree with 60079-0	3.26	X		
Upper Flammable Limit Term and definition revised to agree with 60079-0	3.27	X		
Table 1 – Determination of protection level Revised to use EPL terminology	Table 1	X		
Table 2 – Design Criteria based upon level of protection Revised to use EPL terminology	Table 2	X		
Enclosure Requirements relaxed for specific designs	5.1		X	
Group II and Group III pressurized enclosures Text revised to use EPL terminology	5.3.3	X		
Group II and Group III Level of Protection “pxb” Added that warning also applies for explosive dust atmospheres	5.3.5		X	
Group II and Group III door and cover warning Added that warning also applies for explosive dust atmospheres	5.3.6		X	
Group II and Group III door and cover warning Revised warning from atmosphere “may be present” to “is present”	5.3.6	X		

		Type		
Changes	**Clause**	**Minor and Editorial Changes**	**Extension**	**Major Technical Changes**
Mechanical Strength Removed reference to 60079-0 by clause number for “X” condition	5.4	X		
Spark and particle barriers Removed reference to 60079-0 by clause number for “X” condition	5.9	X		
Cells and batteries Added requirements for cells and batteries	5.10			C1
For Level of Protection “pxb” or Level of Protection “pyb” Revised Table to use terminology consistent with EPLs	6.2	X		
Suitability of safety devices for hazardous area Word “explosion” changed to “ignition” to reflect UFL/LFL terms	7.1	X		
Integrity of safety devices Added requirement for detecting fan failure	7.2			C2
Table 3 – Safety devices based upon Level of Protection Revised column labels to use Level of Protection terminology	Table 3	X		
Provider of safety devices Remove reference to 60079-0 by clause number for “X” condition	7.3	X		
Pressurization System evaluated as associated equipment Added requirements for pressurization systems	7.4			C3
Sequence diagram for Level of Protection “pxb” Revised text to use Level of Protection terminology	7.5	X		
Group I and Group II purging automated for Level of Protection “pxb” Revised text to use Level of Protection terminology	7.7	X		
Group I and Group II purging automated for Level of Protection “pxb” Added text specifying that for “pxb”, control must be automated	7.7			C4
Group I or Group II – purging criteria Revised text to use Level of Protection terminology	7.8	X		
Group III – cleaning Added text for cleaning enclosures used in explosive dust atmospheres	7.9		X	
Safety devices to detect minimum overpressure Add word “minimum” to clause title to be consistent with text	7.11	X		
Safety devices to detect minimum overpressure Revised text to use Level of Protection terminology	7.11 d)	X		
Value of minimum overpressure Added word “minimum” to clause title to be consistent with text	7.12	X		
Value of minimum overpressure Revised text to use Level of Protection terminology	7.12	X		
Value of minimum overpressure Added text to reflect a note in Annex C	7.12		X	
Pressurizing multiple enclosures Revised text to use Level of Protection terminology	7.13	X		

		Type		
Changes	**Clause**	**Minor and Editorial Changes**	**Extension**	**Major Technical Changes**
Safety devices on doors and covers Revised text to use Level of Protection terminology	7.14	X		
Equipment that may remain energized Revised text to use EPL and level of protection terminology	7.15	X		
Equipment permitted within Level of Protection “pyb” Revised text to use EPL and level of protection terminology	7.16	X		
Group I and Group II Filling procedure Allow filling in a hazardous location if tested as non-hazardous	8.4		X	
Group III Filling Procedure Added static pressurization filling procedure for combustible dust	8.5		X	
Safety devices Revised text to use Level of Protection terminology	8.6	X		
Equipment that may remain energized Revised text to use EPL terminology	8.7	X		
Overpressure Removed reference to 60079-0 by clause number	8.8	X		
Backup supply Added requirements for a backup supply of protective gas	9.1			C5
Independent supplies Provided requirements for independence of pressurization	9.2		X	C6
Release Conditions Removed reference to 60079-0 by clause number for “X” condition	11.1.2	X		
Containment system with a limited release Removed reference to 60079-0 by clause number for “X” condition	12.3	X		
13.3.3 Limited release of a gas or vapour Revised text to reflect UFL/LFL terms	13.3.3	X		
Ignition-capable equipment Revised text to use Level of Protection terminology	14	X		
Type verification and tests Edition 5 clauses 16.1 to 16.7 moved to Edition 6 clauses 16.2 to 16.8	16	X		
Determining the maximum overpressure rating Added requirements to determine maximum overpressure	16.1			C7
Maximum overpressure test Moved Maximum overpressure test to 16.2	16.2			C7
Leakage test Clarify the acceptance criteria for the test	16.3.2		X	
Tests for an infallible containment system Clarify the rating used for the test	16.7.1			C8
Tests for an infallible containment system Modified test for infallible containment	16.7.2			C9

		Type		
Changes	**Clause**	**Minor and Editorial Changes**	**Extension**	**Major Technical Changes**
Edition 5 – Verifying ability of the pressurized enclosure to limit internal pressure Eliminated test	16.8			C7
Functional test Clarified that applies only to safety devices provided with enclosures	17.1	X		
Tests for an infallible containment system Waived helium leak tests for liquid systems	17.3		X	
Supplementary marking Allowed continued use of type of protection marking	18.3			
Pressurization systems Clarified use of Ex [p] and [Ex p] marking	18.6	X		
Warnings required in other clauses Added table number	18.7	X		
Warnings required in other clauses Added warning from 7.9	18.7		X	
Warnings required in other clauses Added warnings from Annex G and Annex H	18.7			C1
Instructions Added requirements for Group III	19		X	
Edition 5 Annex G – Infallibility test for containment system Deleted and replaced	Annex G	X		
Edition 5 Annex H – Introduction of an alternative risk assessment method encompassing “equipment protection levels” Deleted and replaced	Annex H	X		
Annex G – Internal Cells and Batteries for Level of Protection “pxb” and Level of Protection “pyb” Added requirements for cells and Batteries			X	
Annex H – Internal Cells and Batteries for Level of Protection “pzc” Added requirements for cells and Batteries			X	

Explanations:

A) Definitions

Minor and editorial changes clarification decrease of technical requirements minor technical change editorial corrections

These are changes which modify requirements in an editorial or a minor technical way. They include changes of the wording to clarify technical requirements without any technical change, or a reduction in level of existing requirement.

Extension addition of technical options

These are changes which add new or modify existing technical requirements, in a way that new options are given, but without increasing requirements for equipment that was fully compliant with the previous standard. Therefore, these will not have to be considered for products in conformity with the preceding edition. 5.

Major technical changes addition of technical requirements increase of technical requirements

These are changes to technical requirements (addition, increase of the level or removal) made in a way that a product in conformity with the preceding edition will not always be able to fulfill the requirements given in the later edition. These changes have to be considered for products in conformity with the preceding edition. For these changes additional information is provided in clause B) below

B) Information about the background of 'Major Technical Changes'

C1 – Added annexes with requirements for using cells and batteries.

C2 – Added requirement that fan failure cannot be based upon loss of power to the fan.

C3 – Added requirements for equipment evaluated as a pressurization system to provide uniformity in the testing of such equipment.

C4 – Although, in Edition 5, the title of clause 7.6 stated automated purging, the word automated was not in the requirement. It is intended that all "pxb" equipment have an automated purging system to prevent energizing of ignition capable circuits until the purge cycle has been properly completed. This requires verifying that the flow is at least the minimum required for the purge time as well as verifying that the minimum overpressure exists within the enclosure.

C5 – If a backup supply of protective gas is provided, then both the primary and the backup supply needs to be capable of maintaining the required pressurization.

C6 – If a pressurized enclosure is used within a larger pressurized enclosure the protective gas supplies need to be independent.

C7 – The previous text in 16.1 of Edition 5, assumed that the enclosures had a maximum overpressure rating, but this is rarely the case. Some test houses relied upon the test in 16.8 to determine the maximum overpressure. Various methods were used to simulate regulator failure such as removing the regulator, but this also removed the orifices that would limit the flow. Based upon test house experience, the danger of flying fragments from the enclosure is acceptably small as either the enclosure or the gaskets will deform to relieve the internal pressure. A decision was taken to eliminate the overpressure test based upon the failed regulator. In addition, the definition of maximum overpressure is now based upon the value obtained when the pressurized enclosure is operated within its ratings. This maximum overpressure will generally occur when the equipment is in rapid purge mode with the maximum rated pressure applied to the inlet of the regulator. The Edition 5 text of 16.1 was modified and moved to 16.2.

C8 – The term overpressure in most cases implies operation outside of the normal ratings. Text was clarified to use the term "maximum operating pressure" rather than maximum internal overpressure. Test was 16.6.1 in Edition 5.

C9 – The test was modified to use helium leak detection rather than rely on maintaining a vacuum since this would depend upon the capability of the vacuum system. Test was 16.6.2 in Edition 5.

The significance of changes between IEC 60079-2, Edition 6.0, 2014 and IEC 61241-4, Edition 5.0, 2007 are as listed below:

		Type		
Changes	**Clause in 61241-4**	**Minor and Editorial Changes**	**Extension**	**Major Technical Changes**
Removed type of protection "pD". Included in 3.20, 3.21 and 3.22	3.1		X	
Definition of pressurization now accommodates both gas and dust	3.3		X	
Definition of protective gas now accommodates both gas and dust	3.4		X	
Removed definition for an enclosure. Defined in IEC 60079-0	3.5	X		
Removed note in definition for pressurized enclosure.	3.6	X		