

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Maritime navigation and radiocommunication equipment and systems –
Digital interfaces –
Part 3: Serial data instrument network**

**Matériels et systèmes de navigation et de radiocommunication maritimes –
Interfaces numériques –
Partie 3: Réseau par liaison de données série d'instruments**





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC online collection - oc.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online, and once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -

webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC online collection - oc.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 000 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.



IEC 61162-3

Edition 1.1 2010-11
CONSOLIDATED VERSION

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Maritime navigation and radiocommunication equipment and systems –
Digital interfaces –
Part 3: Serial data instrument network**

**Matériels et systèmes de navigation et de radiocommunication maritimes –
Interfaces numériques –
Partie 3: Réseau par liaison de données série d'instruments**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 47.020.70

ISBN 978-2-8322-1004-5

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[IEC 61162-3:2008+AMD1:2010 CSV](https://standards.iteh.ai/catalog/standards/sist/61802f3c-f34a-43c0-b80e-32f3d27294ed/iec-61162-3-2008amd1-2010-csv)

<https://standards.iteh.ai/catalog/standards/sist/61802f3c-f34a-43c0-b80e-32f3d27294ed/iec-61162-3-2008amd1-2010-csv>

REDLINE VERSION

VERSION REDLINE



**Maritime navigation and radiocommunication equipment and systems –
Digital interfaces –
Part 3: Serial data instrument network**

**Matériels et systèmes de navigation et de radiocommunication maritimes –
Interfaces numériques –
Partie 3: Réseau par liaison de données série d'instruments**

CONTENTS

FOREWORD 3

INTRODUCTION 5

INTRODUCTION to Amendment 1 5

1 Scope 6

2 Normative references 6

3 Terms, definitions and conventions 7

 3.1 Terms and definitions 7

 3.2 Conventions 10

4 Physical layer 10

 4.1 CAN transceiver 10

 4.2 Environmental 10

 4.3 Radio frequency interference 10

 4.3.1 Unwanted electromagnetic emissions 10

 4.3.2 Immunity to electromagnetic environment 10

 4.4 Cables 10

 4.5 Interface power 11

 4.6 Network power source 11

5 Data link layer 11

6 Network layer 11

7 Network management 11

 7.1 Address configuration method 11

 7.2 Address retention 11

8 Application layer 11

 8.1 Parameter groups 11

 8.1.1 Parameter group priority 11

 8.1.2 Parameter group broadcast rate 12

9 Test criteria 12

10 Application notes 12

11 Manufacturer's documentation 12

Annex A (informative) System integration 13

Bibliography 17

Figure A.1 – Example of configuration 15

Figure A.2 – Example of configuration 15

Table A.1 – Test characteristics 14

STANDARD PREVIEW

(standards.iteh.ai)

IEC 61162-3:2008+AMD1:2010 CSV

[https://standards.iteh.ai/catalog/standards/sist/61802f3c-b4a-43c0-b80e-](https://standards.iteh.ai/catalog/standards/sist/61802f3c-b4a-43c0-b80e-32f3d27294ed/iec-61162-3-2008amd1-2010-csv)

[32f3d27294ed/iec-61162-3-2008amd1-2010-csv](https://standards.iteh.ai/catalog/standards/sist/61802f3c-b4a-43c0-b80e-32f3d27294ed/iec-61162-3-2008amd1-2010-csv)

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARITIME NAVIGATION AND RADIOCOMMUNICATION
EQUIPMENT AND SYSTEMS –
DIGITAL INTERFACES –**

Part 3: Serial data instrument network

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 61162-3 edition 1.1 contains the first edition (2008-05) [documents 80/496/CDV and 80/526/RVC] and its amendment 1 (2010-06) [documents 80/580/CDV and 80/594/RVC].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

International Standard IEC 61162-3 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61162 series, under the general title *Maritime navigation and radiocommunication equipment and systems – Digital interfaces*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

ITEH STANDARD PREVIEW
(standards.iteh.ai)

[IEC 61162-3:2008+AMD1:2010 CSV](https://standards.iteh.ai/catalog/standards/sist/61802f3c-f34a-43c0-b80e-32f3d27294ed/iec-61162-3-2008amd1-2010-csv)

<https://standards.iteh.ai/catalog/standards/sist/61802f3c-f34a-43c0-b80e-32f3d27294ed/iec-61162-3-2008amd1-2010-csv>

INTRODUCTION

This part of IEC 61162 has been developed by the IEC technical committee 80 working group 6, to meet the requirement for a versatile and economic means of connecting a wide range of marine navigation and radiocommunications equipment aboard SOLAS vessels. The National Marine Electronics Association's Standard Committee has developed the NMEA 2000®¹ standard. The NMEA² 2000 Standard provides for capabilities across all classes of vessels. The development of NMEA 2000 began in 1994 and was completed in 1999. More than a dozen manufacturers worldwide conducted a two-year beta test. The finalised NMEA 2000 standard version 1.000 was published in 2001. IEC and NMEA have worked together since 1999 to ensure that the NMEA 2000 standard fully supports SOLAS applications. NMEA 2000 version 1.200 was published in 2004, with expanded support for redundant messaging and for equipments such as AIS.

The need for an improved standard, compared with IEC 61162-1 and IEC 61162-2, has arisen due to the increased complexity of the latest equipment and systems. This requires multiple links between equipment and greatly improved communication speed.

The parts 400 of the IEC 61162 series have already been issued and cater for the most complex systems to be found on board a ship.

This new part 3 of IEC 61162 adopts the controller area network (CAN) technology, already well established for many industrial systems. This permits a versatile system to be established with the minimum of effort and reasonable cost. The equipment types supported and the sentence data content developed for IEC 61162-1 has been retained.

IEC 61162-3 describes a low cost, moderate capacity, bi-directional multi-transmitter/multi-receiver instrument network to interconnect marine electronic equipment. The connectors and cables used are compatible with industrial bus systems for instance DeviceNet^{TM3} and Profibus^{TM4}.

IEC 61162-3 provides for the application of NMEA 2000 aboard SOLAS vessels. Exceptions, additions and specific requirements for implementation upon SOLAS vessels are contained in this document.

INTRODUCTION to Amendment 1

The amendment updates the normative reference for NMEA 2000 Appendix B to a later version which includes five new sentences: PGN # 129807 - AIS Class B Group Assignment, PGN # 129809 - AIS Class B "CS" Static Report Part A, PGN # 129810 - AIS Class B, PGN # 129039 - AIS Class B Position Report, and PGN # 129040 - AIS Class B Extended Position Report.

¹ NMEA 2000® is the registered trademark of the National Marine Electronics Association, Inc. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trademark holder or any of its products. Compliance to this profile does not require use of the trade name. Use of the trade name requires permission of the trade holder.

² NMEA is the registered trademark of the National Marine Electronics Association, Inc. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trademark holder or any of its products. Compliance to this profile does not require use of the trade name. Use of the trade name requires permission of the trade holder.

³ DeviceNetTM is the registered trademark of the Open DeviceNet Vendor Association, Inc. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trademark holder or any of its products. Compliance to this profile does not require use of the trade name. Use of the trade name requires permission of the trade holder.

⁴ ProfibusTM is the registered trademark of PROFIBUS International. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trademark holder or any of its products. Compliance to this profile does not require use of the trade name. Use of the trade name requires permission of the trade holder.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – DIGITAL INTERFACES –

Part 3: Serial data instrument network

1 Scope

This part of IEC 61162 is based upon the NMEA 2000 standard. The NMEA 2000 standard contains the requirements for the minimum implementation of a serial-data communications network to interconnect marine electronic equipment onboard vessels. Equipment designed to this standard will have the ability to share data, including commands and status, with other compatible equipment over a single signalling channel.

Data messages are transmitted as a series of data frames, each with robust error check confirmed frame delivery and guaranteed latency times. As the actual data content of a data frame is at best 50 % of the transmitted bits, this standard is primarily intended to support relatively brief data messages, which may be periodic, transmitted as needed, or on-demand by use of query commands. Typical data includes discrete parameters such as position latitude and longitude, GPS status values, steering commands to autopilots, finite parameter lists such as waypoints, and moderately sized blocks of data such as electronic chart database updates. This standard is not necessarily intended to support high-bandwidth applications such as radar, electronic chart or other video data, or other intensive database or file transfer applications.

This standard defines all of the pertinent layers of the International Standards Organisation Open Systems Interconnect (ISO/OSI) model, from the application layer to the physical layer, necessary to implement the required IEC 61162-3 network functionality.

This standard defines data formats, network protocol, and the minimum physical layer necessary for devices to interface. SOLAS applications shall employ redundant designs (for instance dual networks, redundant network interface circuits) to reduce the impact of single point failures. The NMEA 2000 standard provides the fundamental tools and methods to support redundant equipment, buses and messaging. Specific shipboard installation designs are beyond the scope of this standard, however some guidance is given in Annex A.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

ISO 11783 (all parts), *Tractors and machinery for agriculture and forestry – Serial control and communications data network*

ISO 11783-3, *Tractors and machinery for agriculture and forestry – Serial control and communications data network – Part 3: Data link layer*

ISO 11783-5:2001, *Tractors and machinery for agriculture and forestry – Serial control and communications data network – Part 5 Network management (including its corrigendum 1 (2002))*

NMEA 2000 Main document, Version 1.200: October 2004, *Serial-Data Networking Of Marine Electronic Devices*⁵

NMEA 2000, Appendix A, Version 1.200: October 2004, *Serial-Data Networking Of Marine Electronic Devices – Application Layer (Parameter Group Definitions)*

NMEA 2000, Appendix B, Version ~~1.210: September 2006~~ 1.300: May 2009, *Serial-Data Networking Of Marine Electronic Devices – Data Base*

NMEA 2000, Appendix C, Version 1.200: October 2004, *Serial-Data Networking Of Marine Electronic Devices – Certification Criteria and Test Methods*

NMEA 2000, Appendix D, Version 1.200: October 2004, *Serial-Data Networking Of Marine Electronic Devices – Application Notes*

IMO 1974, *International Convention for the Safety of Life at Sea (SOLAS), as amended – Chapter V – Safety of navigation*

3 Terms, definitions and conventions

ITeH STANDARD PREVIEW

3.1 Terms and definitions (standards.iteh.ai)

For the purposes of this document, the following definitions apply.

[IEC 61162-3:2008+AMD1:2010 CSV](https://standards.iteh.ai/catalog/standards/sist/61802f3c-f34a-43c0-b80e-32f3d27294ed/iec-61162-3-2008amd1-2010-csv)

3.1.1 bit

<https://standards.iteh.ai/catalog/standards/sist/61802f3c-f34a-43c0-b80e-32f3d27294ed/iec-61162-3-2008amd1-2010-csv>

the smallest element of information on the communication channel

NOTE Bits are grouped into bit fields of one or more bits. A bit is of constant time duration set by the signalling rate specified in this standard and has one of two logical values, dominant or recessive. When dominant and recessive levels are impressed on the communications channel at the same time the resulting level is dominant.

3.1.2 bridge

device that joins two network segments using the same network protocol and address space

NOTE Data rate and physical media may differ on the two sides of a bridge. A bridge may perform message filtering.

3.1.3 byte

eight bits

3.1.4 Controller area network (CAN) frame

series of bits transmitted on the communications channel

NOTE CAN frames convey the following types of information:

- data frame. Carries data from a transmitter to the receivers.
- error frame. Transmitted by a unit detecting a bus error.
- overload frame. Transmitted to provide a delay between preceding and succeeding data frames.

⁵ Available from National Marine Electronics Association (USA), www.nmea.org.

The CAN data frame has defined start of frame and end of frame bit fields and is separated from preceding fields by an interframe space. CAN error and overload frames, when used, are appended directly to the preceding frame without an interframe space.

3.1.5

class 1 devices

refers to devices that have a single level A or level B network interface connection

3.1.6

class 2 devices

describes devices that have two level A or two level B network interface connections

NOTE Class 2 devices are intended for use on dual redundant bus systems. In addition to providing either level A or level B capabilities, class 2 devices provide a means to identify messages that are received from redundant buses as being the same or different.

3.1.7

default operation

operation or settings that exist when standard equipment is first shipped from the manufacturer

3.1.8

device

a product or equipment which, through a node, is connected to an IEC 61162-3 network

3.1.9

gateway

device that joins a network to another network or system

iTeh STANDARD PREVIEW
(standards.itoh.ai)

3.1.10

interframe space

bit field that separates data frames from preceding frames

[IEC 61162-3:2008+AMD1:2010 CSV](https://standards.itoh.ai/catalog/standards/sist/61802f3c-f34a-43c0-b80e-34a219000000/iec-61162-3-2008-amd1-2010-csv)

<https://standards.itoh.ai/catalog/standards/sist/61802f3c-f34a-43c0-b80e-34a219000000/iec-61162-3-2008-amd1-2010-csv>

3.1.11

level A devices

support the ISO transport layer and the complete set of network management parameter groups

3.1.12

level B devices

support address claim, ISO request PGN, and the product information parameter group

3.1.13

listen only device

device on the network that receives messages but does not participate in bus activity

NOTE This device cannot send any frames on the network (data, error, or acknowledge).

3.1.14

load equivalency number

a node's power rating reported in units of network load

3.1.15

message

consists of one or more data frames, as specified in this standard, that contain the parameter group information to be communicated from a network address

NOTE A message contains the message priority code, parameter group number, destination network address, source network address, and data fields. The destination network address may be a specific address or global.

3.1.16

network address

identifier of a functional entity on the network

3.1.17

network load

one network load is a unit of measure defined as 50 mA

NOTE This is used to determine loading of network.

3.1.18

node

a physical connection to the network

NOTE A node may have more than one network address, see virtual nodes.

3.1.19

node power

power supplied from the network

3.1.20

parameter group (PG)

set of associated variables, commands, status, or other information to be transmitted on the network

iTeh STANDARD PREVIEW

3.1.21

parameter group number (PGN)

an 8-bit or 16-bit number that identifies each parameter group

<http://standards.iteh.ai/catalog/standards/sist/618022bc-27ae-4300-b00c-44d122222222/iec-61162-3-2008-amd1-2010>

NOTE The parameter group number (PGN) is analogous to the three-character sentence formatter in IEC 61162-1. By definition, parameter groups identified by 16-bit parameter group numbers are broadcast to all addresses on the network. Parameter groups identified by 8-bit parameter group numbers may be used to direct data for use by a specific address.

3.1.22

receiver

recipient of a message if the bus is not idle and the device is not a transmitter

3.1.23

router

device that joins two network segments with the same network protocol

NOTE On each side of a router address space, data rate and physical media may differ.

3.1.24

transmitter

originator of a message

NOTE The unit remains a transmitter until it loses arbitration or until the bus becomes idle.

3.1.25

virtual nodes

functional entities within a device that share a physical connection to the network

NOTE Each virtual node within a device has a unique address on the network.

3.2 Conventions

3.2.1

may

In this document “may” when relating to network requirements applies to alternatives and optional items that are allowed in a network. An implementation that does not include an alternative shall be prepared to tolerate another implementation that does.

3.2.2

shall

In this document “shall” when relating to network requirements signifies items that are required in a network.

3.2.3

shall not

In this document “shall not” when relating to network requirements signifies items that are prohibited in a network.

3.2.4

should

In this document “should” when relating to network requirements signifies a recommendation that, if followed, could ease development or improve the operation of the network in some manner.

4 Physical layer

iTeh STANDARD PREVIEW
(standards.iteh.ai)

The physical layer of this standard is as described in the NMEA 2000 Main document.

4.1 CAN transceiver

[IEC 61162-3:2008+AMD1:2010 CSV](https://standards.iteh.ai/catalog/standards/sist/61802f3c-b34a-43c0-b80e-32f3d27294ed/iec-61162-3-2008-amd1-2010-csv)

[https://standards.iteh.ai/catalog/standards/sist/61802f3c-b34a-43c0-b80e-](https://standards.iteh.ai/catalog/standards/sist/61802f3c-b34a-43c0-b80e-32f3d27294ed/iec-61162-3-2008-amd1-2010-csv)

[32f3d27294ed/iec-61162-3-2008-amd1-2010-csv](https://standards.iteh.ai/catalog/standards/sist/61802f3c-b34a-43c0-b80e-32f3d27294ed/iec-61162-3-2008-amd1-2010-csv)

Devices shall utilize CAN transceivers that include a “transmit dominant timeout” timer circuit (babbling idiot protection).

4.2 Environmental

Components and circuits shall be designed to meet the durability and resistance to environmental conditions of IEC 60945, Clause 8. The requirements of 8.8 (rain and spray) apply only to those network components actually intended to be exposed to rain and/or spray.

4.3 Radio frequency interference

4.3.1 Unwanted electromagnetic emissions

Components and circuits shall be designed to meet the unwanted electromagnetic emission requirements of IEC 60945, Clause 9.

4.3.2 Immunity to electromagnetic environment

Components and circuits shall be designed to meet the Immunity to electromagnetic environment conditions of IEC 60945, Clause 10.

4.4 Cables

Network cables shall meet the electrical and minimum physical characteristics specified in the NMEA 2000 Main document.

4.5 Interface power

A class 2 IEC device load equivalency number shall represent the larger power rating of the two network connections, if different.

4.6 Network power source

The network shall have an independent power source for each bus.

5 Data link layer

The data link layer of this standard is defined in ISO 11783-3 with additional requirements specified in the NMEA 2000 Main Document, Section 3.0.

6 Network layer

The network layer is defined in the NMEA 2000 Main Document, Section 4.0.

7 Network management

Network management is defined in ISO 11783-5 with additional requirements specified in the NMEA 2000 Main Document, Section 8.0.

7.1 Address configuration method

Devices shall provide a method (not specified in this standard) to configure a preferred address. A device being configured in this manner shall not transmit data on the bus until completing the address claim process. This capability is only provided for use during initial shipboard installation and configuration, not during normal operations of networks. Reconfiguring the preferred address shall override the retained address.

7.2 Address retention

Devices shall retain the last successfully claimed address as the preferred address for use on the next power up.

8 Application layer

The application layer (messaging) supported by this standard consists of the parameter group structure and the parameter group number contents. The structure is defined in the NMEA 2000, Appendix A and the contents are defined by the NMEA 2000, Appendix B.

8.1 Parameter groups

Parameter groups contain predefined default values for message priority and broadcast rates. The predefined default values provide a level of expectation and consistency of operations. Though the predefined values are intended to meet the needs of the majority of shipboard network configurations, it is recognized that some installations or equipment standards may require different values for optimum performance. Methods to adjust these values to suit specific installations are provided.

8.1.1 Parameter group priority

Any change to the default parameter group priority values shall be retained, using means such as non-volatile memory.