

INTERNATIONAL STANDARD



Information technology – UPnP device architecture –
Part 16-1: Low Power Device Control Protocol – Low Power Architecture
(standards.iteh.ai)

ISO/IEC 29341-16-1:2011

<https://standards.iteh.ai/catalog/standards/sist/0af74e64-5d79-4cc7-a1dd-63bc194f59df/iso-iec-29341-16-1-2011>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2011 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/customerservice

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00



ISO/IEC 29341-16-1

Edition 1.0 2011-08

INTERNATIONAL STANDARD



Information technology – UPnP device architecture –
Part 16-1: Low Power Device Control Protocol – Low Power Architecture
STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 29341-16-1:2011

<https://standards.iteh.ai/catalog/standards/sist/0af74e64-5d79-4cc7-a1dd-63bc194f59df/iso-iec-29341-16-1-2011>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE



ICS 35.200

ISBN 978-2-88912-645-3

CONTENTS

Glossary.....	3
1 Introduction	4
2 UPnP Low Power Feature Overview	4
2.1 The Need for UPnP Low Power	4
2.2 System Power States.....	4
2.3 UPnP Low Power Network Elements	5
2.4 Overarching Use Cases	6
2.4.1 UPnP Low Power Solution - Without Proxy	6
2.4.2 UPnP Low Power Solution – With Basic Power Management Proxy	7
2.5 Low Level Use Cases	8
2.5.1 Use Case 1 – Device Waking PC without Use of Proxy	9
2.5.2 Use Case 2 – Node Going to Sleep	10
2.5.3 Use Case 3 – Device Entering System.....	11
2.5.4 Use case 4 – Device leaving system.....	12
2.5.5 Use Case 5 – Node Changing IP Address.....	13
2.5.6 Use Case 6 – Device Waking PC – Using proxy.....	14
3 Theory of Operation.....	15
3.1 Impact on UPnP Device Architecture 1.0 and 1.1.....	15
3.2 UPnP Low Power Requirements.....	15
3.2.1 Low Power Requirements and Compatibility with Legacy Control Points.....	16
3.2.2 Low Power Requirements Supported By Low Power Aware Control Point.....	16
3.2.3 UPnP Low Power states	17
3.2.4 New SSDP headers	21
3.2.5 Bearer Dependent Wake Up Mechanism.....	22
3.2.6 UPnP Low Power Devices	22
3.2.7 UPnP Power Management Proxy	24
3.2.8 UPnP Low Power Aware Control Point.....	26
3.3 Architecture Sequence Diagrams	26
3.3.1 Scenarios Without proxy	26
3.3.2 Scenarios with Basic Power Management Proxy	33
4 UPnP Low Power Service Protocol.....	36
5 UPnP Low Power Proxy Service Protocol	36
6 Use of UPnP Low Power Feature by Applications	36
6.1 Digital Media Adapter / Player.....	36
6.2 Mobile / Handheld.....	36
7 References.....	37
Figure 1 — UPnP Low Power solution without Proxy.....	6
Figure 2 — UPnP Low Power Solution with Basic Proxy.....	7
Figure 3 — Device waking PC without use of proxy	9
Figure 4 — Node going to sleep	10
Figure 5 — Device Entering System	11

Figure 6 — Device Leaving System	12
Figure 7 — Node Changing IP Address	13
Figure 8 — Device waking PC – using Proxy	14
Figure 9 — UPnP Low Power states	19
Figure 10 — Basic functionality between autonomous wake up low power device in <i>Transparent Sleep</i> and <i>Deep Sleep Online</i> , Legacy and Low Power Aware Control Points without Proxy	27
Figure 11 — Basic functionality between controlled wake up sleep device in <i>Transparent Sleep</i> and <i>Deep Sleep Offline</i> , Legacy and Low Power Aware Control points without Proxy	28
Figure 12 — Wake up functionality between autonomous wake up device and Low Power Aware Control points without Proxy	29
Figure 13 — Basic functionality between controlled wake up device in <i>Transparent Sleep</i> and <i>Deep Sleep Offline</i> , Legacy and Low Power Aware Control Points without Proxy	31
Figure 14 — Interaction of a Low Power UPnP device with a Basic Power Management Proxy, a Low Power Aware Control Point and a Legacy Control Point	33
Figure 15 — Low Power Aware Control Point waking up a device from <i>Deep Sleep Offline</i> State	35
Table 1 — Low Power requirements supported by Legacy Control Point and Low Power Aware Control Point	15
Table 2 — UPnP Low Power States	18
Table 3 — State Machine Transition Description	21
Table 4 — SSDP UPnP Low Power Extension Headers	22
Table 5 — UPnP Low Power Device Requirements	23
Table 6 — UPnP Basic Power Management Proxy Requirements	24

INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

Part 16-1: Low Power Device Control Protocol – Low Power Architecture

FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 10) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 29341-16-1 was prepared by UPnP Forum Steering committee¹, was adopted, under the fast track procedure, by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Information technology – UPnP device architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

¹ UPnP Forum Steering committee, UPnP Forum, 3855 SW 153rd Drive, Beaverton, Oregon 97006 USA. See also "Introduction".

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 29341-16-1:2011](https://standards.iteh.ai/catalog/standards/sist/0af74e64-5d79-4cc7-a1dd-63bc194f59df/iso-iec-29341-16-1-2011)

<https://standards.iteh.ai/catalog/standards/sist/0af74e64-5d79-4cc7-a1dd-63bc194f59df/iso-iec-29341-16-1-2011>

Glossary

ACPI

Advanced Configuration and Power Interface

AP

Access Point: Any entity that has station functionality and provides access to the distribution services (Ethernet network), via the wireless medium for associated stations

AV

Audio / Video

BOOTID

BOOTID is a part of the SSDP:Alive header defined in UPnP Device Architecture 1.1 and is defined as a number that is increased each time device sends an initial announcement

BPMPX

Basic Power Management Proxy

BTH

Bluetooth

CP

Control Point

DHCP

Dynamic Host Configuration Protocol

DMA

Digital Media Adapter

DMP

Digital Media Player

[ISO/IEC 29341-16-1:2011](https://standards.iteh.ai/catalog/standards/sist/0af74e64-5d79-4cc7-a1dd-63bc194f59df/iso-iec-29341-16-1-2011)

<https://standards.iteh.ai/catalog/standards/sist/0af74e64-5d79-4cc7-a1dd-63bc194f59df/iso-iec-29341-16-1-2011>

IP

Internet Protocol

LPACP

Low Power Aware Control Point

NIC

Network Interface Card

OSPM

Operating System-directed Power Management

PAN

Personal Area Network

PC

Personal Computer

PM

Power Management

PM Service

UPnP Based Power Management Service

SSDP

Simple Service Discovery Protocol

Standby period

Time interval SoftAP monitors traffic for no activity before going to standby mode.

UDN

Unique Device Number

UI

User Interface

UUID

Universally Unique Identifier

UPnP

Universal Plug and Play

WoLAN

Wake On LAN

WoWLAN

Wake on Wireless LAN

1 Introduction

The UPnP Low Power architecture allows devices implementing power saving modes to conserve energy. The purpose of this document is to define an architecture that will address the issue of reporting and tracking power states of nodes in a network. The UPnP Low Power solution is designed to enable nodes in the network to report and track the Low Power states of other nodes in the network. Additionally, for nodes that support wake up capabilities, this architecture addresses methods to wake up those nodes when required. The objective of the UPnP Low Power solution is to allow UPnP devices to conserve energy and still be discoverable by UPnP Control Points. The UPnP Control Point will be aware of the UPnP devices and services implemented on a Low Power device even when the Low Power device is in a power savings mode.

This architecture document defines two UPnP services that comprise the UPnP Low Power framework:

- Low Power device service
- Basic Power Management Proxy service

The Low Power device service allows UPnP devices to transition to low power states and still be part of the UPnP network. The Basic Power Management Proxy service can optionally represent the sleeping UPnP devices in the network and is capable of certain limited functions to support the discovery of Low Power devices that are in a power saving mode. The introduction of Low Power into the UPnP architecture will help align UPnP with emerging energy regulation requirements.

2 UPnP Low Power Feature Overview**2.1 The Need for UPnP Low Power**

Platforms and devices must be able to run in an energy efficient manner. It is important that these platforms and devices intelligently transition between system power levels to reduce system power consumption, heat and noise. It is equally important that these systems be able to return to normal running power state with limited impact to the responsiveness of the overall system. For example, on PC platforms, in the state known as System Standby (G1, S3), video and hard drive subsystems, and the fan are powered down. In mobile platforms, where power consumption is a primary consideration, standby mode allows extended battery life. On desktop platforms, especially in residential environments, system noise is often a significant issue. Power Management reduces noise by transitioning desktops platforms to a power saving mode when not in use.

2.2 System Power States

A system can have many power states. The Advanced Configuration and Power Interface (ACPI) specification was developed to establish industry common interfaces; enabling robust operating system (OS) directed motherboard device configuration and Power Management of

devices. ACPI is the key element in Operating System-directed configuration and Power Management (OSPM). For more details, please refer [ACPI].

UPnP Power states are defined in Table 2 in clause 3.2.3. A Low Power device controls its internal power state and UPnP Low Power implementation advertises the power state of the Low Power device to other UPnP devices in the network. The UPnP Low Power implementation abstracts the internal power state of Low Power device and represents the internal power state as one of the Low Power defined power states in Table 2.

2.3 UPnP Low Power Network Elements

A typical set of power managed networked devices may be a PC, laptop, printer, networked CE devices or a handheld. Each node on the network that supports UPnP Low Power runs the UPnP Control Point (CP) and/or UPnP Low Power service. Some nodes may act as a Proxy, if they wish to represent other UPnP Low Power devices in power savings mode.

- **UPnP Low Power Aware Control Point:** A device or a UPnP control point that can monitor the sleep state of other nodes in the network. It can also monitor the entry and exit of nodes from the network. It may store/cache this information. A UPnP Low Power Aware Control Point can wake up a device from a sleep state or request the device to go into a low power state.
- **UPnP Low Power Device:** A UPnP device informs the UPnP network about change in power state of the node. It also informs the UPnP networked devices about its entry into and exit from the network. A UPnP Low Power device can be classified into the following categories:
 - a) **Sleep-autonomous device:** A device that can go to sleep autonomously using internal timers.
 - b) **Sleep-controlled device:** A device that can go to a sleep state on receiving an external control message.
 - c) **Wake up-autonomous devices:** A device that wakes up autonomously using internal timers.
 - d) **Wake up-controlled devices:** A device that requires an external interaction, such as control message, to wake up.
- **UPnP Basic Power Management Proxy:** This node will act on behalf of sleeping devices and make sure that the devices are discoverable if they are in low power state. This node will also store methods for waking the UPnP Low Power devices.

2.4 Overarching Use Cases

The following use cases illustrate the use and need for UPnP Low Power solution.

2.4.1 UPnP Low Power Solution - Without Proxy




Figure 1 — UPnP Low Power solution without Proxy

- The PC advertises that it is transitioning to a low power state. The transition information is recorded by the DMA.
- The PC completes the transition to a low power state.
- Richard wants to watch a movie on his TV. The movie is stored on the PC, which is in low power state (power saving mode). The DMA knows that the movie is on the PC (set up was performed earlier). The DMA wakes up the PC based on the Power management information it received from the PC. The DMA displays a user friendly message. Richard observes a “Waking up PC ... please wait” message on his TV, while the DMA wakes the PC.
- The TV displays a UI showing content selections on the PC. Using the UI, Richard browses the servers and selects the movie he wants to watch.
- The PC streams the movie to the TV via the DMA. Richard watches his movie.

The additional information below will help define the use case better.

- Information regarding the wake up procedure of the PC needs to be communicated to the DMA before it can wake up the PC. This information may contain wake up patterns (if present).
- A Wake on Wireless LAN solution will be required if the PC needs to be woken up using a wireless link. A Wake on Wireless LAN solution is vendor specific mechanism and not defined by the UPnP Low Power solution.

h) After the TV is turned off, the PC automatically enters a low power state when not in use.

2.4.2 UPnP Low Power Solution – With Basic Power Management Proxy




Figure 2 — UPnP Low Power Solution with Basic Proxy

- a) The PC advertises that it is transitioning to a low power state. The transition information is recorded by the DMA. The Basic Power Management Proxy implemented on the DMA, knows the current power state of the PC.
- b) The PC completes the transition to a low power state.
- c) John wants to watch a movie on his Mobile but the PC with the movie is in a low power state. The Mobile is aware that the movie is on the PC. However, the Mobile has been out of the house and is unaware of the current wake up settings of the PC. When the Mobile comes back into the network, it requests for all sleeping devices from the Basic Power Management Proxy (DMA).
- d) The Basic Power Management Proxy Service on the DMA sends the Sleep state and wake up information of the PC to the Mobile.
- e) A Local UI displayed on the Mobile shows a list of media servers including the ones in low power state that are discoverable because of the presence of UPnP Basic Power Management Proxy Service. John selects media server with the movie. The Mobile wakes up the PC. John observes a “Waking up PC ... please wait” message on Mobile.
- f) The PC wakes up and John browses the server contents and selects the movie he wants to watch.
- g) The PC streams the movie and John watches it on his Mobile/PDA.

Certain assumptions have been made in the above mentioned use case. They are:

- h) The PC is configured to support UPnP Low Power functionality.
- i) The Home Network is set up and functioning. The devices are connected via this Home Network.
- j) These devices support UPnP Low Power states to fulfill energy saving requirements.
- k) The PC supports ability to enter and exit low power states (i.e. sleep / hibernation).
- l) Requirements of what needs to be in place:

- 1) Devices have to be discoverable and eventually available at all times but still be able to minimize their energy consumption.
- 2) Media server in devices with limited resources, such as mobile phones must be available in the background and not interfere with everyday phone use. They must also be available for accepting incoming file sharing requests.

The additional information below will help define the use case better.

- m) Information regarding the wake up procedure of the PC is communicated to a proxy before it can propagate the wake up information to the mobile/PDA to wake up the PC.
- n) In this scenario, the PC conveyed the wake up information to the DMA prior to entering the sleep state. The DMA was able to act as a proxy and wake up the PC.

2.5 Low Level Use Cases

The following subclause describes the use cases that may arise in a network. The overarching use cases mentioned above is broken down into smaller use cases that define specific uses.

In all the diagrams below, the initial request is shown as an orange colored arrow.

The response is shown as a purple colored arrow.

Any information being sent out that does not require response are shown in blue. For example

- a) A new device enters a system and announces its entry.
- b) An existing device exits from the system and announces its exit.
- c) An existing device changes its IP address.