

INTERNATIONAL  
STANDARD

ISO/IEC  
10777

First edition  
1991-09-15

---

---

**Information technology — 3,81 mm wide  
magnetic tape cartridge for information  
interchange — Helical scan recording —  
DDS format**

**iTeh STANDARD PREVIEW**

*Technologies de l'information — Cartouche de bande magnétique de 3,81 mm de  
large pour l'échange d'information — Enregistrement par balayage en spirale —  
Format DDS*

[ISO/IEC 10777:1991](https://standards.iso.org/iso-iec-10777-1991)

<https://standards.iteh.ai/catalog/standards/sist/d73be6da-cb8d-4c5e-bb35-55b10e00b454/iso-iec-10777-1991>



Reference number  
ISO/IEC 10777 : 1991 (E)

Contents

	Page
<b>Section 1 - General</b>	<b>1</b>
1 Scope	1
2 Conformance	1
2.1 Magnetic tape cartridge	1
2.2 Generating system	1
2.3 Receiving system	1
3 Normative references	2
4 Definitions	2
4.1 Absolute Frame Number (AFN)	2
4.2 automatic track finding (ATF)	2
4.3 Area ID	2
4.4 Average Signal Amplitude	2
4.5 azimuth	2
4.6 back surface	2
4.7 byte	2
4.8 cartridge	2
4.9 Channel bit	2
4.10 Data Format ID	2
4.11 Early Warning Point (EWP)	2
4.12 End of Data (EOD)	2
4.13 Error Correcting Code (ECC)	2
4.14 flux transition position	2
4.15 flux transition spacing	2
4.16 frame	2
4.17 housekeeping frame	2
4.18 Logical Beginning of Tape (LBOT)	3
4.19 magnetic tape	3
4.20 Master Standard Amplitude Calibration Tape	3

© ISO/IEC 1991

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

4.21	Master Standard Reference Tape	3
4.22	Optimum Recording Field	3
4.23	Partition boundary	3
4.24	Physical Beginning of Tape (PBOT)	3
4.25	Physical End of Tape (PEOT)	3
4.26	physical recording density	3
4.27	pre-recording condition	3
4.28	record	3
4.29	Reference Recording Field	3
4.30	Secondary Standard Amplitude Calibration Tape	3
4.31	Secondary Standard Reference Tape	3
4.32	separator	3
4.33	Standard Reference Amplitude	4
4.34	Tape Reference Edge	4
4.35	Test Recording Current	4
4.36	track	4
4.37	Virtual End of Tape (VEOT)	4
5	Environment and safety	4
5.1	Testing environment	4
5.2	Operating environment	4
5.3	Storage environment	4
5.4	Transportation	5
5.5	Safety	5
5.6	Flammability	5
Section 2 - Requirements for the case		5
6	Dimensional and mechanical characteristics of the case	5
6.1	General	5
6.2	Overall dimensions (figures 6 and 7)	6
6.3	Loading grip (figure 6)	6
6.4	Holding areas (figure 6)	6
6.5	Notches of the lid (figures 5 and 8)	6
6.6	Lid dimensions (figures 6 to 8)	7
6.7	Optical detection of the Beginning and End of Tape (figures 9 and 12)	7
6.8	Bottom side (figures 10 and 11)	8
6.8.1	Locking mechanism of the slider	8
6.8.2	Access holes	9
6.8.3	Recognition, Sub-datums, and Write-inhibit Holes	9
6.8.4	Datum Holes	11
6.8.5	Access room for tape guides	11
6.8.6	Holes for accessing the hubs	12
6.8.7	Internal structure of the lower half (figure 12)	12
6.8.8	Light path (figure 12)	13
6.8.9	Support Areas (figure 13)	13
6.8.10	Datum Areas (figure 13)	14

6.8.11	Relationship between Support and Datum Areas and Reference Plane Z (figure 14)	14
6.9	Hubs (figures 15, 16)	14
6.10	Leader and trailer attachment	15
6.11	Interface between the hubs and the drive spindles (figure 17)	15
6.12	Opening of the lid (figure 18)	15
6.13	Release of the hub locking mechanism (figures 19, 20)	15
6.14	Label areas (figure 21, 22)	16
<b>Section 3 - Requirements for the unrecorded tape</b>		<b>27</b>
7	<b>Mechanical, physical and dimensional characteristics of the tape</b>	<b>27</b>
7.1	Materials	27
7.2	Tape length	27
7.2.1	Length of magnetic tape	27
7.2.2	Length of leader and trailer tapes	27
7.3	Tape width	27
7.4	Discontinuities	27
7.5	Total thickness	27
7.6	Longitudinal curvature	27
7.7	Cupping	27
7.8	Coating adhesion	28
7.9	Layer-to-layer adhesion	28
7.10	Tensile strength	29
7.10.1	Breaking strength	29
7.10.2	Yield strength	29
7.11	Residual elongation	29
7.12	Electrical resistance of coated surfaces	29
7.13	Light transmittance of the tape	30
8	<b>Magnetic recording characteristics</b>	<b>30</b>
8.1	Optimum Recording Field	31
8.2	Signal amplitude	31
8.3	Resolution	31
8.4	Overwrite	31
8.4.1	Physical recording densities of 750,6 ftpmm and 3002 ftpmm	31
8.4.2	Physical recording densities of 83,4 ftpmm and 1001 ftpmm	32
8.5	Ease of erasure	32
8.6	Tape quality	32
8.6.1	Missing pulses	32
8.6.2	Missing pulse zone	32
8.7	Signal-to-noise ratio (S/N) characteristic	32

Section 4 - Requirements for an interchanged tape	33
9 Format	33
9.1 General	33
9.2 Basic Groups	33
9.2.1 Group Information Table	34
9.2.2 Block Access Table	37
9.3 Sub-Groups	39
9.3.1 G1 Sub-Group	39
9.3.2 G2 Sub-Group - Randomizing	40
9.3.3 G3 Sub-Group	40
9.3.4 G4 Sub-Group	42
9.3.5 Main Data Block	46
9.4 Sub Data Area	48
9.4.1 Pack Item No. 1	48
9.4.2 Pack Item No. 2	49
9.4.3 Pack Item No. 3	50
9.4.4 Pack Item No. 4	51
9.4.5 Pack Item No. 5	53
9.4.6 Pack Item No. 6	54
9.4.7 Pack Item No. 7	55
9.4.8 Pack Item No. 8	56
9.4.9 Sub Data Block	56
10 Method of recording	61
10.1 Physical recording density	61
10.2 Long-term average bit cell length	61
10.3 Short-term average bit cell length	61
10.4 Rate of change	61
10.5 Bit shift	61
10.6 Read signal amplitude	61
10.7 Maximum recorded levels	61
11 Track geometry	61
11.1 Track configuration	61
11.2 Average track pitch	62
11.3 Variations of the track pitch	62
11.4 Track width	62
11.5 Track angle	63
11.6 Track edge linearity	63
11.7 Track length	63
11.8 Ideal tape centreline	63
11.9 Azimuth angles	63
12 Recording of blocks on the tape	63
12.1 Recorded Main Data Block	63

12.2	Recorded Sub Data Block	63
12.3	Margin Blocks, Preamble Blocks and Postamble Blocks	63
12.4	Spacer Blocks	63
13	Format of a track	64
13.1	Track capacity	64
13.2	Positioning accuracy	64
13.3	Tracking scheme	64
14	Layout of a Single Data Space tape	67
14.1	Device Area	67
14.2	Reference Area	68
14.3	Position Tolerance Band No. 1	68
14.4	System Area	68
	14.4.1 System Preamble	68
	14.4.2 System Log	68
	14.4.3 System Postamble	68
	14.4.4 Position Tolerance Band No. 2	68
	14.4.5 Vendor Group Preamble	68
14.5	Data Area	68
	14.5.1 Vendor Group	69
	14.5.2 Recorded Data Group	69
	14.5.3 ECC3	69
	14.5.4 Multiple recorded instances	70
	14.5.5 Repeated frames	70
	14.5.6 Appending and overwriting	71
14.6	EOD Area	72
14.7	Post-EOD Area	73
14.8	Early Warning Point - EWP	73
14.9	Initialization	73
15	Layout of a Partitioned tape	73
15.1	Overall magnetic tape layout	74
	15.1.1 Device Area	74
	15.1.2 Partition 1	74
	15.1.3 Partition 0	75
15.2	Area ID	76
15.3	System Area Pack Items No. 3 and No. 4	76
15.4	Empty Partition	76
15.5	Initialization of Partitioned Tapes	76
16	Housekeeping frames	76
16.1	Amble Frames	77
16.2	System Log Frames	77
16.3	Tape Management Frames	77

## Annexes

Annex A - Measurement of the light transmittance of the prisms	79
Annex B - Recognition Holes	81
Annex C - Means to open the lid	82
Annex D - Measurement of light transmittance of tape and leaders	83
Annex E - Measurement of Signal-to-Noise Ratio	86
Annex F - Method for determining the nominal and the maximum allowable recorded levels	87
Annex G - Representation of 8-bit bytes by 10-bit patterns	88
Annex H - Measurement of bit shift	94
Annex J - Recommendations for transportation	97
Annex K - Method of measuring track edge linearity	98
Annex L - Read-After-Write	99
Annex M - Example of the content of a Basic Group No. 0	100

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 10777:1991](https://standards.iteh.ai/catalog/standards/sist/d73be6da-cb8d-4c5e-bb35-55b10e00b454/iso-iec-10777-1991)

<https://standards.iteh.ai/catalog/standards/sist/d73be6da-cb8d-4c5e-bb35-55b10e00b454/iso-iec-10777-1991>

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 10777 was prepared by the European Computer Manufacturers Association (as Standard ECMA-139) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

ISO/IEC 10777:1991

Annexes A, D to H and K form an integral part of this International Standard. Annexes B, C, J, L and M are for information only.

## Patents

During the preparation of the ECMA standard, information was gathered on patents upon which application of the standard might depend. Relevant patents were identified as belonging to Hewlett Packard Limited and the Sony Corporation. However, neither ECMA, nor ISO/IEC can give authoritative or comprehensive information about evidence, validity or scope of patent and like rights. The patent holders have stated that licences will be granted under reasonable and non-discriminatory terms. Communications on this subject should be addressed to

Hewlett Packard Limited  
Computer Peripherals Bristol  
Filton road  
Stoke Gifford  
Bristol BS12 6Q2  
United Kingdom

Sony Corporation  
Licensing and Trademark Division  
6-7-35 Kitashinagawa  
Shinagawa-ku  
Tokyo 141  
Japan



## **Introduction**

This International Standard specifies the characteristics of a 3,81 mm wide magnetic tape cartridge to enable interchangeability of such cartridges. The format used is known as Digital Data Storage (DDS).

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 10777:1991](https://standards.iteh.ai/catalog/standards/sist/d73be6da-cb8d-4c5e-bb35-55b10e00b454/iso-iec-10777-1991)

<https://standards.iteh.ai/catalog/standards/sist/d73be6da-cb8d-4c5e-bb35-55b10e00b454/iso-iec-10777-1991>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO/IEC 10777:1991

<https://standards.iteh.ai/catalog/standards/sist/d73be6da-cb8d-4c5e-bb35-55b10e00b454/iso-iec-10777-1991>

# Information technology - 3,81 mm wide magnetic tape cartridge for information interchange - Helical scan recording - DDS format

## Section 1 - General

### 1 Scope

This International Standard specifies the physical and magnetic characteristics of such cartridges. It also specifies the quality of the recorded signal, the format and the recording method, thereby allowing data interchange by means of such magnetic tape cartridges.

### 2 Conformance

#### 2.1 Magnetic tape cartridge

A tape cartridge shall be in conformance with this International Standard if it meets all mandatory requirements specified herein. A recorded tape shall be either a Single Data Space Tape or a Partitioned Tape.

#### 2.2 Generating system

A system generating a magnetic tape cartridge for interchange shall be entitled to claim conformance with this International Standard if all recordings on the tape meet the mandatory requirements of this International Standard, and if either or both methods of appending and overwriting are implemented.

In addition a claim of conformance shall state which of the following optional features are implemented and which are not:

- the performing of a Read-After-Write check and the recording of any necessary repeated frames,
- the recording of multiple representations of the same Basic Group,
- the generation of ECC3 Frames.

#### 2.3 Receiving system

A system receiving a magnetic tape cartridge for interchange shall be entitled to claim conformance with this International Standard if it is able to handle any recording made on the tape according to this International Standard. In particular it shall be able:

- to recognize repeated frames and to make available to the user data and separator marks from only one of these frames,
- to recognize multiple representations of the same Basic Group and to make available to the user data and separator marks from only one of these representations,
- to update the System Log(s) if the Write-inhibit Hole state so permits,
- to recognize an ECC3 frame, and ignore it if the option specified below is not implemented.

In addition a claim of conformance shall state whether or not the system is capable of using ECC3 check bytes in a process of error correction.

### 3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO R/527:1966, *Plastics - Determination of tensile properties.*

ISO 1302:1978, *Technical Drawings - Method of indicating Surface Texture on Drawings.*

IEC 950:1988, *Safety of Information Technology Equipment (ITE).*

### 4 Definitions

For the purpose of this International Standard, the following definitions apply.

- 4.1 **Absolute Frame Number (AFN)** : A sequence number, encoded in the frame.
- 4.2 **automatic track finding (ATF)** : The method by which tracking is achieved.
- 4.3 **Area ID** : An identifier defining the area of the tape and specifying the types of frame written.
- 4.4 **Average Signal Amplitude** : The average peak-to-peak value of the output signal from the read head at the fundamental frequency of the specified physical recording density over a minimum of 7,8 mm of track, exclusive of missing pulses.
- 4.5 **azimuth** : The angular deviation, in degrees, minutes and seconds of arc, made by the mean flux transition line with the line normal to the centreline of the recorded track.
- 4.6 **back surface** : The surface of the tape opposite to the magnetic coating which is used to record data.
- 4.7 **byte** : An ordered set of bits acted upon as a unit.
- 4.8 **cartridge** : A case containing magnetic tape stored on twin hubs.
- 4.9 **Channel bit** : A bit after 8-10 transformation.
- 4.10 **Data Format ID** : An identifier specifying which data format is being used on the tape.
- 4.11 **Early Warning Point (EWP)** : A point along the length of the tape at which warning is given of the approach, in the forward direction of tape motion, of the partition boundary or of the Physical End of Tape.
- 4.12 **End of Data (EOD)** : The point on the tape at the end of the group which contains the last user data.
- 4.13 **Error Correcting Code (ECC)** : A mathematical algorithm yielding check bytes used for the detection and correction of errors.
- 4.14 **flux transition position** : That point which exhibits maximum free-space flux density normal to the tape surface.
- 4.15 **flux transition spacing** : The distance along a track between successive flux transitions.
- 4.16 **frame** : A pair of adjacent tracks with azimuths of opposite polarity, in which the track with the positive azimuth precedes that with the negative azimuth.
- 4.17 **Housekeeping Frame** : A frame which contains no user data and which is identified as such by the values in the data fields therein.

- 4.18 Logical Beginning of Tape (LBOT) :** The point along the length of the tape where a recording of data for interchange commences.
- 4.19 magnetic tape :** A tape which will accept and retain the magnetic signals intended for input, output and storage purposes on computers and associated equipment.
- 4.20 Master Standard Amplitude Calibration Tape :** A pre-recorded tape on which the standard signal amplitudes have been recorded in the tracks of positive azimuth, 23,0  $\mu\text{m}$  wide, at nominal track pitch, on an AC-erased tape.

NOTE 1 - The tape includes recordings made at 83,4 ftpmm, 333,6 ftpmm, 500,4 ftpmm, 1001 ftpmm and 1501 ftpmm.

NOTE 2 - The Master Standard Amplitude Calibration Tape has been established by Sony Corporation.

- 4.21 Master Standard Reference Tape :** A tape selected as the standard for Reference Recording Field, Signal Amplitude, Resolution, Overwrite and Signal-to-Noise Ratio.

NOTE 3 - The Master Standard Reference Tape has been established by Sony Corporation.

- 4.22 Optimum Recording Field :** In the plot of Average Signal Amplitude against the recording field at the physical recording density of 3002 ftpmm, the field that causes the maximum Average Signal Amplitude.

- 4.23 Partition boundary :** The point along the length of a magnetic tape at which Partition 1 ends and Partition 0 commences.

- 4.24 Physical Beginning of Tape (PBOT) :** The point where the leader tape is joined to the magnetic tape.

- 4.25 Physical End of Tape (PEOT) :** The point where the trailer tape is joined to the magnetic tape.

- 4.26 physical recording density :** The number of recorded flux transitions per unit length of track, expressed in flux transitions per millimetre (ftpmm).

- 4.27 pre-recording condition :** The recording levels above which a tape intended for interchange shall not previously have been recorded.

- 4.28 record :** Related data treated as a unit of information.

- 4.29 Reference Recording Field :** The Optimum Recording Field of the Master Standard Reference Tape.

- 4.30 Secondary Standard Amplitude Calibration Tape :** A tape pre-recorded as defined for the Master Standard Amplitude Calibration Tape; the outputs are known and stated in relation to those of the Master Standard Amplitude Calibration Tape.

NOTE 4 - Secondary Standard Amplitude Calibration Tapes can be ordered from Sony Corporation, Audio Device Business Department, Component Marketing Group, 4-10-18, Takanawa, Minato-ku, Tokyo 108, Japan, under Part Number TY-7000G until the year 2000. It is intended that these be used for calibrating tertiary reference tapes for use in routine calibration.

- 4.31 Secondary Standard Reference Tape :** A tape the performance of which is known and stated in relation to that of the Master Standard Reference Tape.

NOTE 5 - Secondary Standard Reference Tapes can be ordered from Sony Corporation, Major Customer Division, Magnetic Products Group, 6-7-35, Kitashinagawa, Shinagawa-ku, Tokyo 141, Japan, under Part Number RSD 1079 until the year 2000. It is intended that these be used for calibrating tertiary reference tapes for use in routine calibration.

- 4.32 Separator :** A record containing no user data, which is used to separate data.

- 4.33 **Standard Reference Amplitude** : The Average Signal Amplitude from the tracks of positive azimuth of the Master Standard Amplitude Calibration Tape at a specified physical recording density.
- 4.34 **Tape Reference Edge** : The bottom edge of the tape when viewing the recording side of the tape, with the PEOT to the observer's right.
- 4.35 **Test Recording Current** : The current that produces the Reference Recording Field.
- 4.36 **track** : A diagonally positioned area on the tape along which a series of magnetic signals may be recorded.
- 4.37 **Virtual End of Tape (VEOT)** : The point along the length of the magnetic tape within Partition 1 which defines the end of the part of Partition 1 which is usable for recording data for interchange.

**5 Environment and safety**

Unless otherwise stated, the conditions specified below refer to the ambient conditions of the air immediately surrounding the cartridge.

**5.1 Testing environment**

Unless otherwise stated tests and measurements made on the tape cartridge to check the requirements of this International Standard shall be carried out under the following conditions:

Temperature : 23 °C ± 2 °C

Relative Humidity : 40 % to 60 %

Conditioning period before testing : 24 hours

ITeH STANDARD PREVIEW  
(standards.iteh.ai)

**5.2 Operating environment**

ISO/IEC 10777:1991

Cartridges used for data interchange shall be capable of operating under the following conditions:

Temperature : 5 °C to 45 °C

Relative Humidity : 20 % to 80 %

Wet Bulb Temperature : 26 °C max.

There shall be no deposit of moisture on or in the cartridge.

Conditioning before operating:

If a cartridge has been exposed during storage and/or transportation to a condition outside the above values, before use the cartridge shall be conditioned in the operating environment for a time at least equal to the period during which it has been out of the operating environment, up to a maximum of 24 hours.

NOTE 6 - Rapid variations of temperature should be avoided.

**5.3 Storage environment**

For long-term or archival storage of cartridges the following conditions shall be observed:

Temperature : 5 °C to 32 °C

Relative Humidity : 20 % to 60 %

Wet Bulb Temperature : 26 °C max.

The stray magnetic field at any point on the tape shall not exceed 4000 A/m. There shall be no deposit of moisture on or in the cartridge.

#### 5.4 Transportation

Recommended limits for the environment to which a cartridge may be subjected during transportation, and the precautions to be taken to minimize the possibility of damage, are provided in annex J.

#### 5.5 Safety

The cartridge and its components shall satisfy the requirements of IEC 950.

#### 5.6 Flammability

The cartridge and its components shall be made from materials, which if ignited from a match flame, do not continue to burn in a still carbon dioxide atmosphere.

## Section 2 - Requirements for the case

### 6 Dimensional and mechanical characteristics of the case

#### 6.1 General

The case of the cartridge shall comprise:

- an upper half,
- a lower half,
- a slider movably mounted on the lower half,
- a lid pivotally mounted on the upper half.

In the drawings, using third angle projection, an embodiment of the cartridge is shown as an example.

- <https://standards.iteh.ai/catalog/standards/sist/d73be6da-cb8d-4c5e-bb35-55b10e00b454/iso-iec-10777-1991>
- ISO/IEC 10777:1991
- Figure 1 is a perspective view of the cartridge seen from top.
- Figure 2 is a perspective view of the cartridge seen from bottom.
- Figure 3 is a partial view of the rear side.
- Figure 4 is a schematic view showing the Reference Planes X, Y and Z.
- Figure 5 shows the front side.
- Figure 6 shows the top side with the lid in closed position.
- Figure 7 shows the left side.
- Figure 8 shows the top side with the lid in open position.
- Figure 9 shows the left side with the lid in open position.
- Figure 10 shows the bottom side with the lid and the slider in closed position.
- Figure 11 shows the bottom side with the lid and the slider in open position.
- Figure 12 is a view from the top of the inside of the lower half with the upper half removed.
- Figure 13 is a view of the bottom half with the lid and the slider in open position.
- Figure 14 is a view of the left side with the lid and the slider in open position.
- Figure 15 is a top view of a hub.