



Edition 6.0 2016-10 REDLINE VERSION

INTERNATIONAL STANDARD



Safety of machinery - Electrical equipment of machines -

Part 1: General requirements (https://standards.iteh.ai)





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2016 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office Tel.: +41 22 919 02 11 3, rue de Varembé Fax: +41 22 919 03 00

CH-1211 Geneva 20 info@iec.ch Switzerland www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

IEC 60204-1:2016

https://standards.iteh.ai/catalog/standards/iec/ce9c4b09-1552-4cae-a57f-b1652e9052ea/iec-60204-1-2016





Edition 6.0 2016-10 REDLINE VERSION

INTERNATIONAL STANDARD



Safety of machinery – Electrical equipment of machines –
Part 1: General requirements

Document Preview

IEC 60204-1:2016

https://standards.iteh.ai/catalog/standards/iec/ce9c4h09-1552-4cae-a57f-b1652e9052ea/iec-60204-1-2016

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 13.110; 29.020 ISBN 978-2-8322-3696-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

F	OREW	ORD	10
I	NTROD	UCTION	13
	1 Sco	pe	15
2	2 Nori	mative references	16
	3 Terr	ns, definitions and abbreviated terms	19
`	3.1	Terms and definitions	
	3.2	Abbreviated terms	
		eral requirements	
	4.1	General	
	4.1	Selection of equipment	
	4.2.	• •	
I	4.2.		20
		Switchgear	30
1	4.3	Electrical supply	30
	4.3.	1 General	30
	4.3.	2 AC supplies	30
	4.3.		
	4.3.	4 Special supply systems	31
	4.4	Physical environment and operating conditions	
	4.4.		
	4.4.		
	4.4.		
	4.4.	,	
	4.4.	<u>1EC 00204-1.2010</u>	
	://sta4.4		
	4.4.	3	
	4.4.	- '	
	4.5	Transportation and storage	
ı	4.6 4.7	Provisions for handling	
,		ming supply conductor terminations and devices for disconnecting and	
•		ching off	33
	5.1	Incoming supply conductor terminations	
	5.2	Terminal for connection to of the external protective earthing system	
		conductor	34
	5.3	Supply disconnecting (isolating) device	34
	5.3.	1 General	34
	5.3.	2 Type	35
	5.3.	Requirements	35
	5.3.	1 3	
	5.3.	•	37
	5.4	Devices for switching off removal of power for prevention of unexpected start-up	
	5.5	Devices for-disconnecting isolating electrical equipment	38
•	5.6	Protection against unauthorized, inadvertent and/or mistaken connection	
(6 Prot	ection against electric shock	39

	6.1	General	39	
	6.2	Basic protection-against direct contact		
	6.2.1	General	39	•
	6.2.2	Protection by enclosures	40	
	6.2.3	Protection by insulation of live parts	41	
	6.2.4	Protection against residual voltages	41	
	6.2.5	,		
	6.2.6	, ,		
	6.3	Fault protection-against direct contact	42	
	6.3.1	General		
	6.3.2	Prevention of the occurrence of a touch voltage	42	
	6.3.3	Protection by automatic disconnection of supply	42	
	6.4	Protection by the use of PELV		
	6.4.1	General requirements		
	6.4.2			
7	Prote	ection of equipment	44	
	7.1	General	44	
	7.2	Overcurrent protection	45	
	7.2.1	General	45	
	7.2.2			
	7.2.3	Power circuits	45	
	7.2.4	Control circuits	45	
	7.2.5	Socket outlets and their associated conductors	46	
	7.2.6	Lighting circuits	46	
	7.2.7	Transformers	46	
	7.2.8	Location of overcurrent protective devices	46	
	7.2.9	<u>110 0020 i 112010</u>		
	sta7.2.1	0 Rating and setting of overcurrent protective devices	.447	
	7.3	Protection of motors against overheating	47	
	7.3.1	General	47	
	7.3.2	!		
	7.3.3	Over-temperature protection	48	
	7.3.4	Current limiting protection		
	7.4	Protection against abnormal temperature protection	48	
	7.5	Protection against the effects of supply interruption or voltage reduction and subsequent restoration	48	
	7.6	Motor overspeed protection	49	
	7.7	Additional earth fault/residual current protection	49	
	7.8	Phase sequence protection	49	١
	7.9	Protection against overvoltages due to lightning and to switching surges	49	
	7.10	Short-circuit current rating	50	
8	Equip	potential bonding	50	•
	8.1	General	50	
	8.2	Protective bonding circuit	53	
	8.2.1	General		
	8.2.2			
	8.2.3			
	8.2.4			
	8.2.4	· · · · · · · · · · · · · · · · · · ·		1

	0.2		Parts that need not to be connected to the protective bonding circuit	
'	8.2	.5	Mobile machines	56
	8.2	.6	Additional protective bonding requirements for electrical equipment having earth leakage currents higher than 10 mA a.c. or d.c.	56
	8.3	Мє	easures to limit restrict the effects of high leakage current	57
ı	8.4	Fu	nctional bonding	57
	9 Co	ntrol	circuits and control functions	58
	9.1	Co	ontrol circuits	58
	9.1	.1	Control circuit supply	58
	9.1	.2	Control circuit voltages	
	9.1	.3	Protection	
	9.2	Со	ontrol functions	58
- [9.2	2.1	Start functions General	58
- 1	9.2	2.2	Categories of stop functions	59
	9.2	2.3	Operation	
- [9.2	<u>'</u> .4	Cableless control system (CCS)	63
	9.2	<u>!-6</u>	Other control functions	
I	9.3	Pr	otective interlocks	66
	9.3	3.1	Reclosing or resetting of an interlocking safeguard	66
	9.3	3.2	Exceeding operating limits	
	9.3	3.3	Operation of auxiliary functions	
	9.3	3.4	Interlocks between different operations and for contrary motions	
	9.3	3.5	Reverse current braking	
	9.3	3.6	Suspension of safety functions and/or protective measures	
	9.4	Co	ontrol functions in the event of failure	
	9.4	l.1	General requirements	67
	9.4	.2	Measures to minimize risk in the event of failure	
http	s://stand	a3ds.it	Protection against maloperation due to earth faults, voltage interruptions and loss of circuit continuity malfunction of control circuits)204-1-20 570
'	10 Op	erato	r interface and machine-mounted control devices	77
	10.1	Ge	eneral	77
-	10.	.1.1	General-device requirements	77
- 1		.1.2	Location and mounting	77
	10.	.1.3	Protection	77
	10.	.1.4	Position sensors	77
	10.	.1.5	Portable and pendant control stations	78
	10.2	Pu	sh-buttons Actuators	
1	10.	.2.1	Colours	78
	10.	.2.2	Markings	79
	10.3	Inc	dicator lights and displays	80
	10.	.3.1	General	
	10.	.3.2	Colours	81
	10.	.3.3	Flashing lights and displays	
	10.4	IIΙι	ıminated push-buttons	
	10.5		tary control devices	
	10.6		art devices	
	10.7	En	nergency stop devices	82
	10.	.7.1	Location of emergency stop devices	
	10.	.7.2	Types of emergency stop device	

10.7.3 	iolour of actuators	
	ocal Operation of the supply disconnecting device to effect emergency top	82
	gency switching off devices	
	ocation of emergency switching off devices	
	ypes of emergency switching off device	
	Colour of actuators	
	ocal operation of the supply disconnecting device to effect emergency witching off	83
10.9 Enabl	ing control device	83
11 Controlgear	: location, mounting, and enclosures	84
11.1 Gener	al requirements	84
11.2 Locati	on and mounting	84
11.2.1 A	ccessibility and maintenance	84
	hysical separation or grouping	
	leating effects	
11.3 Degre	es of protection	85
11.4 Enclos	sures, doors and openings	86
11.5 Acces	s to- controlgear electrical equipment	87
12 Conductors	and cables	87
12.1 Gener	al requirements Tah. Standards	87
	uctors	
	tion(httms://standards.iteh.ai)	
	nt-carrying capacity in normal service	
	uctor and cable voltage drop	
	le cables	
	Seneral	
	lechanical ratinglechanical rating	
	Current-carrying capacity of cables wound on drums	
	uctor wires, conductor bars and slip-ring assemblies	
	asic protection against direct contact	
	rotective conductors- circuit	
	rotective conductor current collectors	
	Removable current collectors with a disconnector function	
	learances in air	
	reepage distances	
	Conductor system sectioning	
12.7.8 C	Construction and installation of conductor wire, conductor bar systems and slip-ring assemblies	
	tices	
	ections and routing	
	Seneral requirements	
	Conductor and cable runs	
	conductors of different circuits	
	C circuits - Electromagnetic effects (prevention of eddy currents)	
13.1.5 C	Connection between pick-up and pick-up converter of an inductive ower supply system	
•	fication of conductors	
	Seneral requirements	
10.2.1	, on or ar 1 oquil on 1011.0	

	13.2.2	Identification of the protective conductor / protective bonding conductor	96
•	13.2.3	Identification of the neutral conductor	97
	13.2.4	Identification by colour	97
	13.3 V	/iring inside enclosures	98
	13.4 V	/iring outside enclosures	98
	13.4.1	General requirements	98
	13.4.2	External ducts	98
	13.4.3	Connection to moving elements of the machine	
	13.4.4	Interconnection of devices on the machine	
	13.4.5	Plug/socket combinations	
	13.4.6	Dismantling for shipment	
	13.4.7	Additional conductors	
		ucts, connection boxes and other boxes	
	13.5.1	General requirements	
ī	13.5.2	•	
1	13.5.2	Rigid metal conduit and fittings	
	13.5.3	Flexible metal conduit and fittings	
	13.5.4	Flexible non-metallic conduit and fittings	
	13.5.5	Cable trunking systems	
	13.5.6	Machine compartments and cable trunking systems	
	13.5.7	Connection boxes and other boxes	
	13.5.8	Motor connection boxes	
		motors and associated equipment	
		General requirements	
		lotor enclosures	
		lotor dimensions	
		lotor mounting and compartments	
		riteria for motor selection	
		rotective devices for mechanical brakes	
ı		eries Socket-outlets and lighting	
		ocket-outlets for accessories	
		ocal lighting of the machine and of the equipment	
	15.2.1 15.2.2	General	
	_	Supply	
	15.2.3 15.2.4	Protection	
		Fittings	
		g, warning signs and reference designations	
		eneral	
		/arning signs	
	16.2.1	Electric shock hazard	
	16.2.2	Hot surfaces hazard	
1		unctional identification	
		larking of enclosures of electrical equipment	
		deference designations	
		cal documentation	
		eneral	
		nformation to be provided related to the electrical equipment	
	17.3 —₽	equirements applicable to all documentation	

17.4—Installation documents	
17.5 Overview diagrams and function diagrams	
17.6 Circuit diagrams	
17.7 Operating manual	
17.8 Maintenance manual	
17.9 Parts list	
18 Verification	112
18.1 General	112
18.2 Verification of conditions for protection by automatic disconnection of supply	113
18.2.1 General	113
18.2.2 Test methods in TN-systems	
18.2.2 Test 1 – Verification of the continuity of the protective bonding circuit	114
18.2.3 Test 2 – Fault loop impedance verification and suitability of the	
associated overcurrent protective device	
18.2.4 Application of the test methods for TN-systems	
18.3 Insulation resistance tests	
18.4 Voltage tests	
18.5 Protection against residual voltages	
18.6 Functional tests	
18.7 Retesting	118
Annex A (normative) Protection against indirect contact in TN-systems Fault protection by automatic disconnection of supply	110
A.1 Fault protection for machines supplied from TN-systems	
A.1.1 General	
A.1.2 Conditions for protection by automatic disconnection of the supply by	119
overcurrent protective devices	120
A.1.3 Condition for protection by reducing the touch voltage below 50 V	
A.1.4 Verification of conditions for protection by automatic disconnection of	
ps://standards.itel_the_supplystandards/iec/ce9c4b09-1552-4cae-a57f-b1652e9052ea/iec-6020	
A.2 Fault protection for machines supplied from TT-systems	
A.2.1 Connection to earth	
A.2.2 Fault protection for TT systems	124
A.2.3 Verification of protection by automatic disconnection of supply using a residual current protective device	126
A.2.4 Measurement of the fault loop impedance (Z_S)	126
Annex B (informative) Enquiry form for the electrical equipment of machines	128
Annex C (informative) Examples of machines covered by this part of IEC 60204	132
Annex D (informative) Current-carrying capacity and overcurrent protection of	
conductors and cables in the electrical equipment of machines	134
D.1 General	134
D.2 General operating conditions	134
D.2.1 Ambient air temperature	134
D.2.2 Methods of installation	134
D.2.3 Grouping	136
D.2.4 Classification of conductors	137
D.3 Co-ordination between conductors and protective devices providing overload protection	137
D.4 Overcurrent protection of conductors	
D.5 Effect of harmonic currents on balanced three-phase systems	
Annex E (informative) Explanation of emergency operation functions	140

Annex G (informative) Comparison of typical conductor cross-sectional areas	143
Annex H (informative) Measures to reduce the effects of electromagnetic influences	145
H.1 Definitions	145
H.1.1 apparatus	145
H.1.2 fixed installation	145
H.2 General	
H.3 Mitigation of electromagnetic interference (EMI)	
H.3.1 General	
H.3.2 Measures to reduce EMI	
H.4 Separation and segregation of cables	
H.5 Power supply of a machine by parallel sourcesH.6 Supply impedance where a Power Drive System (PDS) is used	
Annex I (informative) Documentation / Information	
Bibliography	
ndex	
maex	
igure 1 – Block diagram of a typical machine	14
igure 2 – Disconnector isolator	
igure 3 - Method a)	
igure 3 – Disconnecting circuit breaker	
igure 4 – Method b)	
igure 4 – Example of equipotential bonding for electrical equipment of a machine	
igure 5 – Symbol IEC 60417-5019: Protective earth	
IEC 00204-1:2010	
Figure 6 – Symbol IEC 60417-5020: Frame or chassis	
Figure 7 – Method a) Earthed control circuit fed by a transformer	
rigure 8 – Method b1) Non-earthed control circuit fed by transformer	
Figure 9 – Method b2) Non-earthed control circuit fed by transformer	72
igure 10 – Method b3) Non-earthed control circuit fed by transformer	73
Figure 11 – Method c) Control circuits fed by transformer with an earthed centre-tap vinding	74
igure 12 – Method d1a) Control circuit without transformer connected between a hase and the neutral of an earthed supply system	7
igure 13 – Method d1b) Control circuit without transformer connected between two shases of an earthed supply system	7
Figure 14 – Method d2a) Control circuit without transformer connected between phase and neutral of a non-earthed supply system	76
phases of a non-earthed supply system	
Phases of a non-earthed supply system Figure 16 – Symbol IEC 60417-5019	97
Figure 15 – Method d2b) control circuit without transformer connected between two chases of a non-earthed supply system Figure 16 – Symbol IEC 60417-5019 Figure 17 – Symbol IEC 60417-5021	
ohases of a non-earthed supply system Figure 16 – Symbol IEC 60417-5019	10

Figure A.1 – Typical arrangement for fault loop impedance ($Z_{\rm S}$) measurement in T systems	
Figure A.2 – Typical arrangement for fault loop impedance (Z_S) measurement for power drive system circuits in TN systems	123
Figure A.3 – Typical arrangement for fault loop impedance ($Z_{\rm S}$) measurement in T systems	
Figure A.4 – Typical arrangement for fault loop impedance (Z_s) measurement for power drive system circuits in TT systems	127
Figure D.1 – Methods of conductor and cable installation independent of number conductors/cables	
Figure D.2 – Parameters of conductors and protective devices	137
Figure H.1 – By-pass conductor for screen reinforcement	146
Figure H.2 – Examples of vertical separation and segregation	148
Figure H.3 – Examples of horizontal separation and segregation	148
Figure H.4 – Cable arrangements in metal cable trays	149
Figure H.5 – Connections between metal cable trays or cable trunking systems	149
Figure H.6 – Interruption of metal cable trays at fire barriers	150
Table 1 – Minimum cross-sectional area of the external copper protective conductor	ors34
Table 2 - Colour-coding for push-button actuators and their meanings	
Table 2 – Symbols for push-buttons actuators (Power)	
Table 3 – Symbols for actuators (Machine operation)	80
Table 4 – Colours for indicator lights and their meanings with respect to the condit of the machine	
Table 5 – Minimum cross-sectional areas of copper conductors	88
Table 6 – Examples of current-carrying capacity (I_Z) of PVC insulated copper conductors or cables under steady-state conditions in an ambient air temperature (I_Z) of FVC for different methods of installation	
Table 7 – Derating factors for cables wound on drums	92
Table 8 – Minimum permitted bending radii for the forced guiding of flexible cables	99
Table 9 – Application of the test methods for TN-systems	115
Table 10 – Examples of maximum cable lengths from each protective devices to it their loads for TN-systems	
Table A.1 – Maximum disconnecting times for TN systems	120
Table A.2 – Maximum disconnecting time for TT-systems	126
Table D.1 – Correction factors	134
Table D.2 – Derating factors from for I_Z for grouping	136
Table D.3 – Derating factors—from for I _Z for multicore cables up to 10 mm ²	
Table D.4 – Classification of conductors	
Table D.5 – Maximum allowable conductor temperatures under normal and short-circuit conditions	138
Table F.1 – Application options	
Table G.1 – Comparison of conductor sizes	
Table H.1 – Minimum separation distances using metallic containment as illustrate Figure H.2	ed in
Table I.1 – Documentation / Information that can be applicable	151

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SAFETY OF MACHINERY – ELECTRICAL EQUIPMENT OF MACHINES –

Part 1: General requirements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication. 10 10 50 50 60 60 2 29 0
 - 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
 - 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
 - 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

International Standard IEC 60204-1 has been prepared by IEC technical committee 44: Safety of machinery – Electrotechnical aspects.

This sixth edition cancels and replaces the fifth edition published in 2005. It constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) added requirements to address applications involving power drive systems (PDS);
- b) revised electromagnetic compatibility (EMC) requirements;
- c) clarified overcurrent protection requirements;
- d) requirements for determination of the short circuit current rating of the electrical equipment;
- e) revised protective bonding requirements and terminology;
- f) reorganization and revision to Clause 9, including requirements pertaining to safe torque off of PDS, emergency stop, and control circuit protection;
- g) revised symbols for actuators of control devices;
- h) revised technical documentation requirements;
- i) general updating to current special national conditions, normative standards, and bibliographical references.

The text of this standard is based on the following documents:

TUDS FDISSUALITY	Report on voting
44/765/FDIS	44/771/RVD
DUCUIIICII	

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table. $\underline{\mathbb{IEC}\ 60204-12016}$

187/8tandards.iterra/catalog/standards/ec/ce/c4009-1332-4cae-a3/1-01032e9032ea/ec-00204-

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 60204 series, published under the general title *Safety of machinery – Electrical equipment of machines*, can be found on the IEC website.

The following differing practices of a less permanent nature exist in the countries indicated below.

- 4.3.1: The voltage characteristics of electricity supplied by public distribution systems in Europe are given in EN 50160:2010.
- 5.1: Exception is not allowed (USA).
- 5.1: TN-C systems are not permitted in low-voltage installations in buildings (Norway).
- 5.2: Terminals for the connection of the protective earthing conductors may be identified by the colour green, the letters "G" or "GR" or "GRD" or "GND", or the word "ground" or "grounding", or with the graphical symbol IEC 60417-5019:2006-08 or any combination (USA).
- 6.3.3 b), 13.4.5 b), 18.2.1: TT power systems are not allowed (USA).
- 6.3.3, 18.2, Annex A: TN systems are not used. TT systems are the national standard (Japan).
- 6.3.3 b): The use of residual current protective devices with a rated residual operating current not exceeding 1 A is mandatory in TT systems as a means for fault protection by automatic disconnection of supply (Italy).

- 7.2.3: Disconnection of the neutral conductor is mandatory in a TN-S system (France and Norway).
- 7.2.3: Third paragraph: distribution of a neutral conductor with an IT system is not allowed (USA and Norway).
- 7.10: For evaluation of short circuit ratings the requirements of UL 508A Supplement SB, may be used (USA).
- 8.2.2: See IEC 60364-5-54:2011, Annex E List of notes concerning certain countries.
- 9.1.2: Maximum nominal AC control circuit voltage is 120 V (USA).
- 12.2: Only stranded conductors are allowed on machines, except for 0,2 mm² solid conductors within enclosures (USA).
- 12.2: The smallest power circuit conductor allowed on machines is 0,82 mm² (AWG 18) in multiconductor cables or in enclosures (USA).
- Table 5: Cross-sectional area is specified in NFPA 79 using American Wire Gauge (AWG) (USA). See Annex G.
- 13.2.2: For the protective conductor, the colour identification GREEN (with or without YELLOW stripes) is used as equivalent to the bicolour combination GREEN-AND-YELLOW (USA and Canada).
- 13.2.3: The colour identification WHITE or GREY is used for earthed neutral conductors instead of the colour identification BLUE (USA and Canada).
- 15.2.2: First paragraph: Maximum value between conductors 150 V (USA).
- 15.2.2: Second paragraph, 5th bullet: The full load current rating of lighting circuits does not exceed 15 A (USA).
- 16.4: Nameplate marking requirements (USA).
- A.2.2.2: The permissible maximum value of $R_{\rm A}$ is regulated (e.g. when $\rm U_o \ge 300V$, $R_{\rm A}$ shall be less than 10 Ω , when $\rm U_o < 300~V$, $\rm R_A$ shall be less than 100 Ω , $\rm U_o$ is the nominal AC line to earth voltage in volts (V) (Japan).
- A.2.2.2: The maximum permissible value of R_A is 83 Ω (Netherlands).

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- · reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.