
AUUd`cj]U!`?cbglfi _VYUfifi dU]b`nU Hvj UbY`Uglbcgh`!) "XY.`BU flcj Ub]`hU_]`nU
fifi dYžbU flcj UbY`bUdYfcgh]`]b`Xc`c UbY`Uglbcgh]`fIGC`%&&%) !).&\$\$, Ł

Small craft - Hull construction and scantlings - Part 5: Design pressures for monohulls,
design stresses, scantlings determination (ISO 12215-5:2008)

Kleine Wasserfahrzeuge - Rumpfbauweise und Dimensionierung - Teil 5:
Entwurfsdrücke, Entwurfsspannungen und Ermittlung der Dimensionierung (ISO 12215-
5:2008)

(standards.iteh.ai)

Petits navires - Construction de la coque et échantillonnage - Partie 5: Pressions de
conception pour monocoques, contraintes de conception, détermination de
l'échantillonnage (ISO 12215-5:2008)

Ta slovenski standard je istoveten z: EN ISO 12215-5:2008

ICS:

47.020.10	Ladijski trupi in njihovi konstrukcijski elementi	Hulls and their structure elements
47.080	[] ã	Small craft

SIST EN ISO 12215-5:2008**en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN ISO 12215-5:2008

<https://standards.iteh.ai/catalog/standards/sist/e7c53a32-fa3e-4b06-b532-5304b452c5a0/sist-en-iso-12215-5-2008>

ICS 47.020.10; 47.080

English Version

Small craft - Hull construction and scantlings - Part 5: Design pressures for monohulls, design stresses, scantlings determination (ISO 12215-5:2008)

Petits navires - Construction de la coque et échantillonnage
- Partie 5: Pressions de conception pour monocoques, contraintes de conception, détermination de l'échantillonnage (ISO 12215-5:2008)

Kleine Wasserfahrzeuge - Rumpfbauweise und Dimensionierung - Teil 5: Entwurfsdrücke für Einrumpffahrzeuge, Entwurfsspannungen, Ermittlung der Dimensionierung (ISO 12215-5:2008)

This European Standard was approved by CEN on 28 December 2007.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

Page

Foreword.....	3
Annex ZA (informative) Relationship between this International Standard and the Essential Requirements of EU Directive 94/25/EC as amended by Directive 2003/44/EC	4

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN ISO 12215-5:2008](https://standards.iteh.ai/catalog/standards/sist/e7c53a32-fa3e-4b06-b532-5304b452c5a0/sist-en-iso-12215-5-2008)

<https://standards.iteh.ai/catalog/standards/sist/e7c53a32-fa3e-4b06-b532-5304b452c5a0/sist-en-iso-12215-5-2008>

Foreword

This document (EN ISO 12215-5:2008) has been prepared by Technical Committee ISO/TC 188 "Small craft" in collaboration with Technical Committee CEN/SS T01 "Shipbuilding and maritime structures" the secretariat of which is held by CMC.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2008, and conflicting national standards shall be withdrawn at the latest by October 2008.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EC Directive(s).

For relationship with EC Directive, see informative Annex ZA, which is an integral part of this document.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

Endorsement notice

<https://standards.iteh.ai/catalog/standards/sist/e7c53a32-fa3e-4b06-b532-6304b453e5a9/sist-en-iso-12215-5-2008>

The text of ISO 12215-5:2008 has been approved by CEN as a EN ISO 12215-5:2008 without any modification.

**Annex ZA
(informative)**

Relationship between this International Standard and the Essential Requirements of EU Directive 94/25/EC as amended by Directive 2003/44/EC

This International Standard has been prepared under a mandate given to CEN by the European Commission to provide one means of conforming to Essential Requirements of the New Approach Directive 94/25/EC as amended by Directive 2003/44/EC.

Once this standard is cited in the Official Journal of the European Communities under that Directive and has been implemented as a national standard in at least one Member State, compliance with the normative clauses of this standard given in Table ZA.1 confers, within the limits of the scope of this standard, a presumption of conformity with the corresponding Essential Requirements of that Directive and associated EFTA regulations.

Table ZA.1 — Correspondence between this International Standard and Directive 94/25/EC as amended by Directive 2003/44/EC

Clause(s)/sub-clause(s) of this International Standard	Essential requirements (ERs) of EU Directive 94/25/EC as amended by Directive 2003/44/EC	Qualifying remarks/Notes
All clauses	Annex I, Part A, Clause 3.1, Structure	The standard provides requirements for scantling determination for monohull craft constructed from fibre reinforced plastics, aluminium or steel alloys, glued wood (laminated) or similar suitable materials.

WARNING — Other requirements and other EU Directives may be applicable to the products falling within the scope of this standard.

**Small craft — Hull construction
and scantlings —**

Part 5:

**Design pressures for monohulls, design
stresses, scantlings determination**

iTeh STANDARD PREVIEW

(standard not for sale)

Petits navires — Construction de la coque et échantillonnage —

*Partie 5: Pressions de conception pour monocoques, contraintes de
conception, détermination de l'échantillonnage*

SIST EN ISO 12215-5:2008

<https://standards.iteh.ai/catalog/standards/sist/e7c53a32-fa3e-4b06-b532-5304b452c5a0/sist-en-iso-12215-5-2008>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN ISO 12215-5:2008](https://standards.iteh.ai/catalog/standards/sist/e7c53a32-fa3e-4b06-b532-5304b452c5a0/sist-en-iso-12215-5-2008)

<https://standards.iteh.ai/catalog/standards/sist/e7c53a32-fa3e-4b06-b532-5304b452c5a0/sist-en-iso-12215-5-2008>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	2
4 Symbols	4
5 General.....	6
6 Dimensions, data and areas	7
6.1 Dimensions and data.....	7
6.2 Areas	7
7 Pressure adjusting factors	9
7.1 General.....	9
7.2 Design category factor k_{DC}	9
7.3 Dynamic load factor n_{CG}	9
7.4 Longitudinal pressure distribution factor k_L	10
7.5 Area pressure reduction factor k_{AR}	11
7.6 Hull side pressure reduction factor k_Z	12
7.7 Superstructure and deckhouse pressure reduction factor k_{SUP}	13
7.8 Light and stable sailing craft pressure correcting factor for slamming k_{SLS}	13
8 Design pressures	14
8.1 Motor craft design pressure	14
8.2 Sailing craft design pressure	16
8.3 Watertight bulkheads and integral tank boundaries design pressure.....	16
8.4 Design pressures for structural components where k_{AR} would be $\leq 0,25$	18
9 Dimensions of panels and stiffeners	19
9.1 Dimensions of plating panels.....	19
9.2 Dimensions of stiffeners	23
10 Plating — Scantling equations	25
10.1 Thickness adjustment factors for plating	25
10.2 FRP single-skin plating	28
10.3 Metal plating — Aluminium alloy and steel.....	29
10.4 Laminated wood or plywood single-skin plating	30
10.5 FRP sandwich plating.....	31
10.6 Single-skin plating minimum thickness	35
11 Stiffening members requirements	36
11.1 General.....	36
11.2 Properties adjustment factors for stiffeners.....	37
11.3 Design stresses for stiffeners	37
11.4 Requirements for stiffeners made with similar materials.....	38
11.5 Requirements for stiffeners made with dissimilar materials	39
11.6 Effective plating	40
11.7 Overall dimensions of stiffeners	41
11.8 Structural bulkheads	43
11.9 Structural support for sailing craft ballast keel	44

12	Owner's manual.....	44
12.1	General.....	44
12.2	Normal mode of operation	44
12.3	Possibility of outer skin damage.....	44
Annex A	(normative) Simplified method for scantling determination	45
Annex B	(normative) Drop test for boats of < 6 m.....	49
Annex C	(normative) FRP laminates properties and calculations	52
Annex D	(normative) Sandwich mechanical core properties and sandwich calculation.....	63
Annex E	(normative) Wood laminate properties and wood calculations	69
Annex F	(normative) Mechanical properties of metals.....	78
Annex G	(normative) Geometric properties of stiffeners	80
Annex H	(normative) Laminate stack analysis	97
Bibliography	108

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN ISO 12215-5:2008](https://standards.iteh.ai/catalog/standards/sist/e7c53a32-fa3e-4b06-b532-5304b452c5a0/sist-en-iso-12215-5-2008)
<https://standards.iteh.ai/catalog/standards/sist/e7c53a32-fa3e-4b06-b532-5304b452c5a0/sist-en-iso-12215-5-2008>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12215-5 was prepared by Technical Committee ISO/TC 188, *Small craft*.

ISO 12215 consists of the following parts, under the general title *Small craft — Hull construction and scantlings*:

- Part 1: Materials: Thermosetting resins, glass fibre reinforcement, reference laminate
- Part 2: Materials: Core materials for sandwich construction, embedded materials
- Part 3: Materials: Steel, aluminium alloys, wood, other materials
- Part 4: Workshop and manufacturing
- Part 5: Design pressures for monohulls, design stresses, scantlings determination
- Part 6: Structural arrangements and details
- Part 7: Scantling determination of multihulls
- Part 8: Rudders
- Part 9: Sailing boats — Appendages and rig attachment

Introduction

The reason underlying the preparation of this part of ISO 12215 is that standards and recommended practices for loads on the hull and the dimensioning of small craft differ considerably from one to another, thus limiting the general worldwide acceptability of boat scantlings. This part of ISO 12215 has been set towards the lower boundary of the range of current practice.

The objective of this part of ISO 12215 is to achieve an overall structural strength that ensures the watertight and weathertight integrity of the craft. It is intended to be a tool to assess the scantlings of a craft against lower bound practice and it is not intended to be a structural design procedure

The scantling requirements are based principally on providing adequate local strength. Serviceability issues such as deflection under normal operating loads, global strength and its connected shell and deck stability are not addressed. The criteria contained within may need to be supplemented by additional considerations deemed necessary by the designer of the structure.

The mechanical property data supplied as default values make no explicit allowance for deterioration in service nor provide any guarantee that these values can be obtained for any particular craft. The responsibility for the decision to use this part of ISO 12215 as part of the design procedure rests solely with the designer and/or manufacturer.

The design pressures given in this part of ISO 12215 are only used with the given equations.

Considering future development in technology and boat types and small craft currently outside the scope of this part of ISO 12215, provided methods supported by appropriate technology exist, consideration may be given to their use provided equivalent support for this part of ISO 12215 is achieved.

The dimensioning according to this part of ISO 12215 is regarded as reflecting current practice, provided the craft is correctly handled in the sense of good seamanship and operated at a speed appropriate to the prevailing sea state.

Important notice:

- 1) ISO/TC 188/WG 18 believes that this part of ISO 12215 is the best that can be achieved at the time of publication. It has therefore decided to publish this document as an ISO Standard. It is anticipated that wider usage may reveal a number of issues that require modification. It is for this reason that WG 18 has asked for a revision of the document at the same time as its publication. This revision agreement will enable the group to amend this part of ISO 12215 quickly should this prove necessary.
- 2) In furtherance of this, this part of ISO 12215 needs to be applied with a critical mind, and users are invited to report to the TC secretariat, or national standardization body, any items that are considered to require correction, together with supporting evidence, be that theoretical or based on satisfactory, long-term service experience with actual boats operating in the appropriate design category sea states.

Small craft — Hull construction and scantlings —

Part 5:

Design pressures for monohulls, design stresses, scantlings determination

1 Scope

This part of ISO 12215 applies to the determination of design pressures and stresses, and to the determination of the scantlings, including internal structural members of monohull small craft constructed from fibre-reinforced plastics, aluminium or steel alloys, glued wood or other suitable boat building material, with a length of hull, L_H , in accordance with ISO 8666, between 2,5 m and 24 m. It only applies to boats in the intact condition.

It only applies to craft with a maximum speed ≤ 50 knots in m_{LDC} conditions.

The assessment shall generally include all parts of the craft that are assumed watertight or weathertight when assessing stability, freeboard and buoyancy in accordance with ISO 12217 and are essential to the safety of the craft and of persons on board.

For the complete scantlings of the craft, this part of ISO 12215 is used in conjunction with Part 6, for details, Part 7 for multihulls, Part 8 for rudders and Part 9 for appendages and rig attachment.

The scantling determination of windows, portlights, deadlights, hatches and doors, is in accordance with ISO 12216. The structure supporting these elements is in accordance with this part of ISO 12215.

NOTE 1 Scantlings derived from this part of ISO 12215 are primarily intended to apply to recreational craft including recreational charter vessels and may not be suitable for performance racing craft.

NOTE 2 This part of ISO 12215 is based on the assumption that scantlings are governed solely by local loads.

NOTE 3 The scantling requirements of this part of ISO 12215 are considered to correspond to the minimum strength requirements of motor and sailing craft which are operated in a safe and responsible manner, having due cognisance of the prevailing conditions.

Pressures and stresses are normally expressed in pascals, kilopascals or megapascals. For the purposes of a better understanding for the users of this part of ISO 12215, the pressures are expressed in kilonewtons per square metre ($1\text{ kN/m}^2 = 1\text{ kPa}$) and stresses or elastic moduli are expressed in newtons per square millimetre ($1\text{ N/mm}^2 = 1\text{ MPa}$).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 178, *Plastics — Determination of flexural properties*

ISO 527-1, *Plastics — Determination of tensile properties — Part 1: General principles*

ISO 12215-5:2008(E)

ISO 527-2, *Plastics — Determination of tensile properties — Part 2: Test conditions for moulding and extrusion plastics*

ISO 844, *Rigid cellular plastics — Determination of compression properties*

ISO 845, *Cellular plastics and rubbers — Determination of apparent density*

ISO 1922, *Rigid cellular plastics — Determination of shear strength*

ISO 8666:2002, *Small craft — Principal data*

ISO 12215-3, *Small craft — Hull construction and scantlings — Part 3: Materials: Steel, aluminium alloys, wood, other materials*

ISO 12215-6, *Small craft — Hull construction and scantlings — Part 6: Structural arrangements and details*

ISO 12215-7, *Small craft — Hull construction and scantlings — Part 7: Scantling determination of multihulls*

ISO 12215-9, *Small craft — Hull construction and scantlings — Part 9: Sailing boats — Appendages and rig attachment*

ISO 12216, *Small craft — Windows, portlights, hatches, deadlights and doors — Strength and watertightness requirements*

ISO 12217 (all parts), *Small craft — Stability and buoyancy assessment and categorization*

ASTM C393, *Standard Test Method for Flexural Properties of Sandwich Constructions*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

3 Terms and definitions

SIST EN ISO 12215-5:2008

<https://standards.iteh.ai/catalog/standards/sist/e7c53a32-fa3e-4b06-b532->

For the purposes of this document, the following terms and definitions apply:

3.1

design categories

sea and wind conditions for which a boat is assessed by this part of ISO 12215 to be suitable, provided the craft is correctly handled in the sense of good seamanship and operated at a speed appropriate to the prevailing sea state

3.1.1

design category A (“ocean”)

category of boats considered suitable to operate in seas with significant wave heights above 4 m and wind speeds in excess of Beaufort Force 8, but excluding abnormal conditions, e.g. hurricanes

NOTE For the application of this part of ISO 12215, the calculation wave height is 7 m.

3.1.2

design category B (“offshore”)

category of boats considered suitable to operate in seas with significant wave heights up to 4 m and winds of Beaufort Force 8 or less

3.1.3

design category C (“inshore”)

category of boats considered suitable to operate in seas with significant wave heights up to 2 m and a typical steady wind force of Beaufort Force 6 or less

3.1.4**design category D (“sheltered waters”)**

category of boats considered suitable to operate in waters with significant wave heights up to and including 0,3 m with occasional waves of 0,5 m height, for example from passing vessels, and a typical steady wind force of Beaufort Force 4 or less

3.2**loaded displacement mass**

m_{LDC}

mass of the craft, including all appendages, when in the fully loaded ready-for-use condition as defined in ISO 8666

3.3**sailing craft**

craft for which the primary means of propulsion is wind power, having $A_S > 0,07(m_{LDC})^{2/3}$ where A_S is the total profile area of all sails that may be set at one time when sailing close hauled, as defined in ISO 8666 and expressed in square metres

NOTE In the rest of this part of ISO 12215, non-sailing craft are considered as motor craft.

3.4**second moment of area**

I

for a homogeneous material, it is the sum of the component areas multiplied by the square of the distance from centre of area of each component area to the neutral axis, plus the second moment of area of each component area about an axis passing through its own centroid, and is expressed in centimetres to the fourth or millimetres to the fourth

NOTE The second moment of area is also referred to in other documentation as the moment of inertia and for brevity as “second moment” within this part of ISO 12215.

[SIST EN ISO 12215-5:2008](https://standards.iteh.ai/catalog/standards/sist/e7c53a32-fa3e-4b06-b532-5304b452c5a0/sist-en-iso-12215-5-2008)

3.5**section modulus**

SM

for a homogeneous material, it is the second moment of area divided by the distance to any point from the neutral axis at which the stress is to be calculated and is expressed in cubic centimetres or cubic millimetres

NOTE The minimum section modulus is calculated to the furthest point from the neutral axis.

3.6**displacement craft**

craft whose maximum speed in flat water and m_{LDC} conditions, declared by its manufacturer, is such that

$$\frac{V}{\sqrt{L_{WL}}} < 5$$

3.7**displacement mode**

mode of running of a craft in the sea such that its mass is mainly supported by buoyancy forces

NOTE This is the case if the actual speed in a seaway and m_{LDC} conditions is such that its speed:length ratio makes the craft behave as a displacement craft.

3.8**planing craft**

craft whose maximum speed in flat water and m_{LDC} conditions, declared by its manufacturer, is such that

$$\frac{V}{\sqrt{L_{WL}}} \geq 5$$

NOTE This speed:length ratio limit has been arbitrarily set up in this part of ISO 12215, but it may vary from one boat to another according to hull shape and other parameters.