

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Low-voltage fuses – Part 2: Supplementary requirements for fuses for use by authorized persons (fuses mainly for industrial application) – Examples of standardized systems of fuses A to K

STANDARD PREVIEW
<https://standards.iteh.ai/catalog/standards/sist/7667c665-69f9-4d84-a043-f0793f08b05a/iec-60269-2-2013>

Fusibles basse tension –

Partie 2: Exigences supplémentaires pour les fusibles destinés à être utilisés par des personnes habilitées (fusibles pour usages essentiellement industriels) – Exemples de systèmes de fusibles normalisés A à K



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2013 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.
If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.
Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Useful links:

IEC publications search - www.iec.ch/searchpub

The advanced search enables you to find IEC publications by a variety of criteria (reference number, text, technical committee,...).

It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available on-line and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary (IEV) on-line.

Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Liens utiles:

Recherche de publications CEI - www.iec.ch/searchpub

La recherche avancée vous permet de trouver des publications CEI en utilisant différents critères (numéro de référence, texte, comité d'études,...).

Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

Just Published CEI - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications de la CEI. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (VEI) en ligne.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Low-voltage fuses – Supplementary requirements for fuses for use by authorized persons (fuses mainly for industrial application) – Examples of standardized systems of fuses A to K

IEC 60269-2:2013

<https://standards.iteh.ai/catalog/standards/sist/7667c665-69f9-4d84-a043-f0793f08b05a/iec-60269-2-2013>

Fusibles basse tension –

Partie 2: Exigences supplémentaires pour les fusibles destinés à être utilisés par des personnes habilitées (fusibles pour usages essentiellement industriels) – Exemples de systèmes de fusibles normalisés A à K

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE **XH**
CODE PRIX

ICS 29.120.50

ISBN 978-2-8322-0898-4

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	16
INTRODUCTION.....	18
1 General scope.....	19
1.1 Scope.....	19
1.2 Normative references	20
Fuse system A – Fuses with fuse-links with blade contacts (NH fuse system)	21
1 General	21
1.1 Scope.....	21
2 Terms and definitions	21
3 Conditions for operation in service.....	22
4 Classification.....	22
5 Characteristics of fuses	22
5.2 Rated voltage	22
5.3.1 Rated current of the fuse-link.....	22
5.3.2 Rated current of the fuse-holder	22
5.5 Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	22
5.6 Limits of time-current characteristics	22
5.6.1 Time-current characteristics, time-current zones and overload curves	22
5.6.2 Conventional times and currents.....	22
5.6.3 Gates	23
5.7.2 Rated breaking capacity	23
6 Markings	23
6.1 Markings of fuse-holders	23
6.2 Markings of fuse-links.....	24
7 Standard conditions for construction.....	24
7.1 Mechanical design.....	24
7.1.2 Connections, including terminals	24
7.1.3 Fuse-contacts.....	25
7.1.6 Construction of fuse-bases	25
7.1.7 Construction of a fuse-link	25
7.2 Insulating properties and suitability for insulation	26
7.7 I^2t characteristics	26
7.8 Overcurrent discrimination of fuse-links	27
7.9 Protection against electric shock	27
8 Tests	28
8.1.4 Arrangement of the fuse and dimensions	28
8.1.6 Testing of fuse-holders	28
8.2.4 Acceptability of test results.....	29
8.2.5 Resistance to tracking	29
8.3 Verification of temperature rise and power dissipation	29
8.3.1 Arrangement of the fuse	29
8.3.2 Measurement of the temperature rise	29
8.5.5 Test method	30

8.5.8	Acceptability of test results	31
8.7.4	Verification of overcurrent discrimination	31
8.9	Verification of resistance to heat	32
8.9.1	Fuse-base	33
8.9.2	Fuse-links with gripping-lugs of moulded material or of metal fixed in moulded material	33
8.10	Verification of non-deterioration of contacts	34
8.10.1	Arrangement of the fuse	34
8.10.2	Test method	36
8.10.3	Acceptability of test results	37
8.11	Mechanical and miscellaneous tests	39
FIGURES	42
Annex AA (informative)	Special test for cable overload protection	61
AA.1	Arrangement of the fuse	61
AA.2	Test method and acceptability of test results	61
Fuse system B – Fuses with striker fuse-links with blade contacts (NH fuse system)	62
1	General	62
1.1	Scope	62
2	Terms and definitions	62
3	Conditions for operation in service	62
4	Classification	62
5	Characteristics of fuses	62
5.2	Rated voltage	62
5.3.1	Rated current of the fuse-link	63
5.3.2	Rated current of the fuse-holder	63
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	63
5.6	Limits of time-current characteristics	63
5.7.2	Rated breaking capacity	63
6	Markings	63
7	Standard conditions for construction	63
7.1	Mechanical design	63
7.1.2	Connections, including terminals	63
7.1.3	Fuse-contacts	63
7.1.7	Construction of a fuse-link	64
7.2	Insulating properties and suitability for insulation	64
7.7	I^2t characteristics	64
7.8	Overcurrent discrimination of "gG" fuse-links	64
7.9	Protection against electric shock	64
8	Tests	64
8.1.6	Testing of fuse-holders	64
8.3	Verification of temperature rise and power dissipation	64
8.7.4	Verification of overcurrent discrimination	65
8.9	Verification of resistance to heat	65
8.9.1	Fuse-base	65

FIGURES	67
Fuse system C – Fuse-rails (NH fuse system)	74
1 General.....	74
1.1 Scope.....	74
2 Terms and definitions.....	74
3 Conditions for operation in service.....	74
4 Classification.....	74
5 Characteristics of fuses.....	74
5.2 Rated voltage.....	74
5.3.2 Rated current.....	74
5.5.1 Rated acceptable power dissipation.....	74
6 Markings.....	75
7 Standard conditions for construction.....	75
7.1 Mechanical design.....	75
7.1.2 Connections, including terminals.....	75
7.2 Insulating properties.....	75
8 Tests.....	75
8.1.6 Testing of fuse-holders.....	75
8.3 Verification of temperature rise and power dissipation.....	76
8.3.1 Arrangement of the fuse.....	76
8.9 Verification of resistance to heat.....	77
8.9.1 Fuse-base.....	77
8.10 Verification of non-deterioration of contacts.....	77
8.10.1 Arrangement of the fuse.....	77
FIGURES	79

Fuse system D – Fuse-bases for busbar mounting (40 mm system) (NH fuse system)	84
1 General.....	84
1.1 Scope.....	84
2 Terms and definitions.....	84
3 Conditions for operation in service.....	84
4 Classification.....	84
5 Characteristics of fuses.....	84
5.2 Rated voltage.....	84
5.3.2 Rated current.....	85
5.5.2 Rated acceptable power dissipation of tandem fuse-bases.....	85
6 Markings.....	85
7 Standard conditions for construction.....	85
7.1 Mechanical design.....	85
7.1.2 Connections, including terminals.....	85
7.1.5 Construction of a fuse-base for busbar mounting.....	86
7.2 Insulating properties and suitability for insulation.....	86
8 Tests.....	86

8.3	Verification of temperature rise and power dissipation	86
8.3.1	Arrangement of the fuse	86
8.9.1	Fuse-base	87
8.10	Verification of non-deterioration of contacts	87
8.10.1	Arrangement of the fuse	87
8.10.2	Test method	88
8.11	Mechanical and miscellaneous tests	88
FIGURES	89

Fuse system E – Fuses with fuse-links for bolted connections (BS bolted fuse system)	96
1	General	96
1.1	Scope	96
2	Terms and definitions	96
3	Conditions for operation in service	96
4	Classification	96
5	Characteristics of fuses	96
5.3.1	Rated current of the fuse-link	96
5.3.2	Rated current of the fuse-holder	96
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	97
5.6	Limits of time-current characteristics	97
5.6.1	Time-current characteristics, time-current zones and overload curves	97
5.6.2	Conventional times and currents	97
5.6.3	Gates	97
5.7.2	Rated breaking capacity	97
6	Markings	97
6.1	Markings of fuse-holders	98
6.2	Markings of fuse-links	98
7	Standard conditions for construction	98
7.1	Mechanical design	98
7.1.2	Connections including terminals	98
7.2	Insulating properties and suitability for insulation	98
7.9	Protection against electric shock	98
8	Tests	98
8.3	Verification of temperature rise and power dissipation	98
8.3.1	Arrangement of the fuse	98
8.3.3	Measurement of the power dissipation of the fuse-link	98
8.4	Verification of operation	99
8.4.1	Arrangement of the fuse	99
8.5	Verification of breaking capacity	99
8.5.1	Arrangement of the fuse	99
8.5.8	Acceptability of test results	99
8.9	Verification of resistance to heat	99
8.10	Verification of non-deterioration of contacts	99
8.10.1	Arrangement of the fuse	99
8.10.2	Test method	99

8.10.3	Acceptability of the results.....	100
8.11	Mechanical and miscellaneous tests.....	100
FIGURES	101

Fuse system F – Fuses with fuse-links having cylindrical contact caps (NF cylindrical fuse system)..... 110

1	General.....	110
1.1	Scope.....	110
2	Terms and definitions.....	110
3	Conditions for operation in service.....	110
4	Classification.....	110
5	Characteristics of fuses.....	110
5.2	Rated voltage.....	110
5.3.1	Rated current of the fuse-link.....	111
5.3.2	Rated current of the fuse-holder.....	111
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder.....	111
5.6	Limits of time-current characteristics.....	112
5.6.1	Time-current characteristics, time-current zones and overload curves.....	112
5.6.2	Conventional times and currents.....	112
5.6.3	Gates.....	113
5.7.2	Rated breaking capacity.....	113
6	Markings.....	113
6.1	Markings of fuse-holders.....	113
6.2	Markings of fuse-links.....	114
7	Standard conditions for construction.....	114
7.1	Mechanical design.....	114
7.1.2	Connections including terminals.....	114
7.2	Insulating properties and suitability for insulation.....	114
7.7	I^2t characteristics.....	115
7.8	Overcurrent discrimination of "gG" fuse-links.....	115
7.9	Protection against electric shock.....	115
8	Tests.....	115
8.1.6	Testing of fuse-holders.....	116
8.3.1	Arrangement of the fuse.....	116
8.7.4	Verification of overcurrent discrimination.....	118
8.9	Verification of resistance to heat.....	119
8.10	Verification of non-deterioration of contacts.....	119
8.10.1	Arrangement of the fuse.....	119
8.10.2	Test method.....	119
8.10.3	Acceptability of test results.....	120
FIGURES	121

Fuse system G – Fuses with fuse-links with offset blade contacts (BS clip-in fuse system)..... 125

1	General.....	125
1.1	Scope.....	125

2	Terms and definitions	125
3	Conditions for operation in service	125
4	Classification	125
5	Characteristics of fuses	125
5.2	Rated voltage	126
5.3.1	Rated current of the fuse-link	126
5.3.2	Rated current of the fuse-holder	126
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	126
5.6.1	Time-current characteristics, time-current zones	126
5.6.2	Conventional times and currents	126
5.6.3	Gates	126
5.7.2	Rated breaking capacity	127
6	Markings	127
6.1	Markings of fuse-holders	127
6.2	Markings of fuse-links	127
7	Standard conditions for construction	127
7.1	Mechanical design	127
7.1.2	Connections including terminals	127
7.2	Insulating properties and suitability for insulation	128
7.7	I^2t characteristics	128
7.9	Protection against electric shock	128
8	Tests	128
8.3.3	Measurement of the power dissipation of the fuse-link	128
8.4.1	Arrangement of the fuse	129
8.5.1	Arrangement of the fuse	129
8.7.4	Verification of overcurrent discrimination	129
8.9	Verification of resistance to heat	129
8.10	Verification of non-deterioration of contacts	129
8.10.1	Arrangement of the fuse	129
8.10.2	Test method	130
8.10.3	Acceptability of test results	130
8.11	Mechanical and miscellaneous tests	130
FIGURES		131
Fuse system H – Fuses with fuse-links having "gD" and "gN" characteristics (class J, class T, and class L time delay and non time delay fuse types)		
1	General	136
1.1	Scope	136
2	Terms and definitions	136
3	Conditions for operation in service	136
4	Classification	136
5	Characteristics of fuses	136
5.2	Rated voltage	136
5.3.1	Rated current of the fuse-link	137
5.3.2	Rated current of the fuse-holder	137

5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	137
5.6	Limits of the time-current characteristics	137
5.6.1	Time-current characteristics, time-current zones	137
5.6.2	Conventional times and currents.....	137
5.6.3	Gates	137
5.7.2	Rated breaking capacity	138
6	Markings	138
6.1	Markings of fuse-holders	138
6.2	Markings of fuse-links.....	138
7	Standard conditions for construction.....	138
7.1	Mechanical design.....	138
7.2	Insulating properties and suitability for insulation	138
7.5	Breaking capacity.....	138
7.6	Cut-off current characteristics.....	139
7.7	I^2t characteristics	139
7.8	Overcurrent discrimination.....	140
7.9	Protection against electric shock	140
8	Tests	140
8.3	Verification of temperature rise and power dissipation	140
8.3.1	Arrangement of the fuse	140
8.4	Verification of operation	141
8.4.1	Arrangement of the fuse	141
8.5.4	Recovery voltage.....	142
8.6	Verification of cut-off current characteristics	142
8.7	Verification of I^2t characteristics and overcurrent discrimination.....	143
8.9	Verification of resistance to heat	143
8.10	Verification of non-deterioration of contacts.....	143
8.10.1	Arrangement of the fuse	143
8.10.2	Test method	144
8.10.3	Acceptability of test results.....	144
8.11	Mechanical and miscellaneous tests.....	144
8.11.2	Miscellaneous tests	144
FIGURES	145
Fuse system I – gU fuse-links with wedge tightening contacts	158
1	General	158
1.1	Scope.....	158
2	Terms and definitions	158
3	Conditions for operation in service.....	159
3.9	Discrimination of fuse-links.....	159
4	Classification.....	159
5	Characteristics of fuses	159
5.2	Rated voltage	159
5.3.1	Rated current of the fuse-link.....	159
5.5	Rated power dissipation of a fuse-link	159
5.6.1	Time-current characteristics, time-current zones	159

5.6.2	Conventional times and currents.....	160
5.6.3	Gates	160
5.7.2	Rated breaking capacity	160
5.8	Cut-off current and I^2t characteristics.....	160
6	Markings	160
6.1	Markings of fuse-holders	160
6.2	Markings of fuse-links.....	160
7	Standard conditions for construction.....	160
7.1	Mechanical design.....	160
7.2	Insulating properties and suitability for insulation	160
7.5	Breaking capacity.....	160
7.7	I^2t characteristics.....	161
7.8	Overcurrent discrimination of the fuse-links	161
8	Tests.....	161
8.1.1	Kind of tests	161
8.3.1	Arrangement of the fuse	161
8.3.3	Measurement of the power dissipation of the fuse-link.....	162
8.4.1	Arrangement of the fuse	162
8.5.1	Arrangement of the fuse	162
8.5.2	Characteristics of the test circuit.....	162
8.5.5	Test method	162
8.5.8	Acceptability of test results.....	162
8.7.3	Verification of compliance for fuse-links at 0,01 s	163
8.9	Verification of resistance to heat	163
8.11	Mechanical and miscellaneous tests.....	163
FIGURES	164

Fuse system J – Fuses with fuse-links having "gD class CC" and "gN class CC" characteristics (class CC time delay and non-time delay fuse types)	172
1	General	172
1.1	Scope.....	172
2	Terms and definitions	172
3	Conditions for operation in service.....	172
4	Classification.....	172
5	Characteristics of fuses	172
5.2	Rated voltage	172
5.3.1	Rated current of the fuse-link.....	173
5.3.2	Rated current of the fuse-holder	173
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	173
5.6	Limits of the time-current characteristics	173
5.6.1	Time-current characteristics, time-current zones	173
5.6.2	Conventional times and currents.....	173
5.6.3	Gates	173
5.7.2	Rated breaking capacity	173
6	Markings	174
6.1	Markings of fuse-holders	174

6.2	Markings of fuse-links.....	174
7	Standard conditions for construction.....	174
7.1	Mechanical design.....	174
7.2	Insulating properties and suitability for insulation	174
7.5	Breaking capacity.....	174
7.6	Cut-off current characteristics.....	174
7.7	I^2t characteristics.....	174
7.8	Overcurrent discrimination.....	175
7.9	Protection against electric shock	175
8	Tests.....	175
8.3	Verification of temperature rise and power dissipation	175
8.3.1	Arrangement of the fuse	175
8.4	Verification of operation	176
8.4.1	Arrangement of the fuse	176
8.5.4	Recovery voltage.....	176
8.6	Verification of cut-off current characteristics.....	176
8.7	Verification of I^2t characteristics and overcurrent discrimination.....	177
8.9	Verification of resistance to heat	178
8.10	Verification of non-deterioration of contacts.....	178
8.10.1	Arrangement of the fuse.....	178
8.10.2	Test method	178
8.10.3	Acceptability of test results.....	178
8.11	Mechanical and miscellaneous tests.....	178
8.11.2	Miscellaneous tests	179
FIGURES	https://standards.iteh.ai/catalog/standards/sist/7667c665-69f9-4d84-a043-f0793f08b05a/iec-60269-2-2013	180

Fuse system K – gK fuse-links with blade contacts for bolted connections – High current fuse-link ratings from 1 250 A up to 4 800A (Master fuse-links)		
		189
1	General.....	189
1.1	Scope.....	189
2	Terms and definitions	189
3	Conditions for operation in service.....	189
3.9	Discrimination of fuse-links.....	189
4	Classification.....	189
5	Characteristics of fuses	189
5.2	Rated voltage	190
5.3.1	Rated current of the fuse-link.....	190
5.3.2	Rated current of the fuse-holder	190
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	190
5.6	Limits of the time-current characteristics	190
5.6.1	Time-current characteristics, time-current zones	190
5.6.2	Conventional times and currents.....	191
5.6.3	Gates	191
5.7.2	Rated breaking capacity	191
6	Markings	191
6.2	Markings of fuse-links.....	192

7	Standard conditions for construction.....	192
7.1	Mechanical design.....	192
7.1.3	Fuse-contacts.....	192
7.6	Cut-off current characteristics.....	192
7.7	I^2t characteristics.....	192
7.8	Over-current selectivity of “gK” fuse-links.....	192
7.9	Protection against electric shock.....	192
8	Tests.....	193
8.3	Verification of temperature rise and power dissipation.....	193
8.3.1	Arrangement of the fuse.....	193
8.4.1	Arrangement of the fuse.....	193
8.6	Verification of cut-off current characteristics.....	193
8.7	Verification of I^2t characteristics and over-current selectivity.....	194
8.9	Verification of resistance to heat.....	195
8.10	Verification of non-deterioration of contacts.....	195
8.10.1	Arrangement of the fuse.....	195
8.10.2	Test method.....	195
8.10.3	Acceptability of test results.....	195
	FIGURES	196
	Bibliography.....	203
	Figure 101 – Fuse-links with blade contacts (1 of 3).....	42
	Figure 102 – Fuse-bases for fuse-links with blade contacts (1 of 3).....	45
	Figure 103 – Replacement handle.....	48
	Figure 104 – Time-current zones for “gG” fuse-links (1 of 5).....	49
	Figure 105 – Dummy fuse-link according to 8.3.4.1, 8.9.1 and 8.10.....	54
	Figure 106 – Measuring points according to 8.3.4 of IEC 60269-1, 8.3.4.1, 8.3.4.2 and 8.10.2 of fuse system A.....	55
	Figure 107 – Test knife according to 8.5.5.1.2.....	55
	Figure 108 – Example of a measuring device for determining the withdrawal forces according to 8.9.1 and 8.11.1.2.....	56
	Figure 109 – Facility for verifying the mechanical strength of gripping-lugs (see 8.11.1.8).....	57
	Figure 110 – Measuring points according to 8.10.2.....	58
	Figure 111 – Reference fuse-base.....	59
	Figure 112 – Design mark for isolated gripping-lugs.....	60
	Figure 201 – Fuse-links with blade contacts with striker (1 of 4).....	67
	Figure 202 – Fuse-bases for fuse-links with blade contacts with striker (1 of 3).....	71
	Figure 301 – Fuse-rails for fuse-links with blade contacts (1 of 3).....	79
	Figure 302 – Test arrangement for fuse-rails (1 of 2).....	82
	Figure 401 – Busbar mounting bases, 1 pole.....	89
	Figure 402 – Busbar mounting bases, 3 pole.....	90
	Figure 403 – Busbar mounting base, size 00, 2 × 3 pole (tandem fuse-base).....	91
	Figure 404 – Test arrangement for single-pole and triple-pole fuse-bases for busbar-mounting according to 8.3.1.....	92

iTech STANDARD PREVIEW

(standards.iteh.ai)

IEC 60269-2:2013

<https://standards.iteh.ai/catalog/standards/sist/7667c665-69f9-4d84-a043-10795108b05a/iec-60269-2-2013>

Figure 405 – Test arrangement for two single-pole and six single-pole fuse-bases in tandem arrangement for busbar-mounting according to 8.3.1	93
Figure 406 – Test arrangement for the verification of the peak withstand current	94
Figure 407 – Dummy fuse-link	95
Figure 501 – Fuse-links for bolted connection – Sizes A, B, C and D (1 of 2)	101
Figure 502 – Typical fuse-holder (1 of 2).....	103
Figure 503 – Time-current zones for "gG" fuse-link	105
Figure 504 – Time-current zones for "gG" fuse-link	106
Figure 505 – Power dissipation test rig	107
Figure 506 – Breaking capacity test rig for fuse-links for bolted connection (1 of 2)	108
Figure 601 – Fuse-links with cylindrical caps	121
Figure 602 – Fuse-links with cylindrical contact caps with striker – Additional dimensions for sizes 14 × 51 and 22 × 58 only	122
Figure 603 – Base for fuse-links with cylindrical caps (1 of 2)	123
Figure 701 – Fuse-links having offset blade contacts, sizes E1, F1, F2 and F3	131
Figure 702 – Typical fuse-holder.....	132
Figure 703 – Time-current zones for "gG" fuse-links	133
Figure 704 – Time-current zones for "gG" fuse-links	134
Figure 705 – Power dissipation test rig	135
Figure 801 – Class J fuse-links (1 A to 600 A)	145
Figure 802 – Class L fuse-links (700 A to 6 000 A)	146
Figure 803 – Fuse-base and contacts for class J fuse-links 1 A to 600 A	147
Figure 804 – Fuse-base and contacts for class L fuse-links 700 A to 6 000 A	148
Figure 805 – Class T fuse-links (1 A to 1 200 A)	149
Figure 806 – Fuse-base and contacts for class T fuse-links 1 A to 1 200 A	150
Figure 807 – Temperature test arrangement	151
Figure 808 – Time-current zones for "gN" fuse-links	152
Figure 809 – Time-current zones for "gN" fuse-links	153
Figure 810 – Time-current zones for "gN" fuse-links	154
Figure 811 – Time-current zones for "gD" fuse-links	155
Figure 812 – Time-current zones for "gD" fuse-links	156
Figure 813 – Time-current zones for "gD" fuse-links	157
Figure 901 – Time-current zones for current ratings 100 A, 200 A, 355 A and 630 A.....	164
Figure 902 – Time-current zones for current ratings 160 A and 315 A	165
Figure 903 – Time-current zones for current ratings 250 A and 500 A	166
Figure 904 – Time-current zones for current ratings 200 A and 400 A	167
Figure 905 – Dimensions for fuse-links with L type and U type tags	168
Figure 906 – Power dissipation test rig	169
Figure 907 – Breaking capacity test rig (1 of 2)	170
Figure 1001 – Class CC fuse-links (1 A to 30 A)	180
Figure 1002 – Fuse-base and contacts for class CC fuse-links 1 A to 30 A	180
Figure 1003 – Class CC dummy fuse-link dimensions	181
Figure 1004 – Temperature test arrangement	182

IPEC STANDARD PREVIEW
(standards.iteh.ai)

IEC 60269-2:2013

base and contacts for class L fuse-links 700 A to 6 000 A

f0793f08b05a/iec-60269-2-2013

Figure 1005 – Time-current zones for class CC “gN” fuses	183
Figure 1006 – Time-current zones for class CC “gN” fuses	184
Figure 1007 – Time-current zones for class CC “gN” fuses	185
Figure 1008 – Time-current zones for class CC “gD” fuses	186
Figure 1009 – Time-current zones for class CC “gD” fuses	187
Figure 1010 – Time-current zones for class CC “gD” fuses	188
Figure 1101 – “gK” fuse-links (1 of 2).....	196
Figure 1102 – Connecting dimensions for “gK” fuse-links (1 of 3).....	198
Figure 1103 – Dummy fuse-link.....	200
Figure 1104 – Time-current zones for “gK” fuse system K (1 of 2).....	201
Table 101 – Conventional time and current for “gG” fuse-links with rated current lower than 16 A.....	23
Table 102 – Gates for specified pre-arcing and operating times of “gG” fuse-links	23
Table 103 – Minimum rated breaking capacities.....	23
Table 104 – Marking of fuse-links	24
Table 105 – Minimum cross-sectional ranges of unprepared conductors	25
Table 106 – Pre-arcing and operating I^2t values at 0,01 s for “gG” fuse-links	26
Table 107 – Maximum operating I^2t values for “aM” fuse-links	27
Table 108 – Pre-arcing I^2t values for discrimination of gG fuse-links	27
Table 109 – Survey of tests on fuse-holders and number of fuse-holders to be tested	28
Table 110 – Rated impulse withstand voltage.....	28
Table 111 – Torque to be applied to the terminal screws.....	29
Table 112 – Test currents	30
Table 113 – Test currents and I^2t limits for discrimination test.....	32
Table 114 – Torques to be applied when no values are given by the manufacturer	35
Table 115 – Cross-sectional area of aluminium conductors for tests corresponding to 8.10	35
Table 116 – Test sequence for direct terminal clamps.....	37
Table 117 – Permissible changes of the resistance.....	38
Table 118 – Force to withdraw the fuse-link from the fuse-base contacts	39
Table 201 – Position and force of the striker	64
Table 301 – Minimum cross-sectional ranges of unprepared conductors for fuse-rails.....	75
Table 302 – Survey of complete tests on fuse-rails and number of fuse-rails to be tested	76
Table 401 – Minimum cross-sectional ranges of unprepared conductors for fuse-bases for busbar mounting	85
Table 402 – Torques to be applied to contact making screws.....	86
Table 403 – Test currents	87
Table 404 – Force to withdraw the fuse-link from the fuse-base contacts	88
Table 501 – Conventional time and current for “gG” fuse-links	97
Table 502 – Gates for specified pre-arcing times of “gG” fuse-links	97
Table 601 – Maximum rated current of fuse-links with cylindrical caps	111
Table 602 – Maximum rated current of fuse-holders.....	111