

SLOVENSKI STANDARD SIST ISO 11052:1997

01-maj-1997

Pšenična moka durum in pšenični zdrob durum - Določanje vsebnosti rumenega pigmenta

Durum wheat flour and semolina -- Determination of yellow pigment content

Farines et semoules de blé dur -- Détermination de la teneur en pigments jaunes (standards.iteh.ai)

Ta slovenski standard je istoveten z: ISO 11052:1994

https://standards.iteh.ai/catalog/standards/sist/84f1733a-aaa5-4d7e-8c79-

1856cf8d11c2/sist-iso-11052-1997

ICS:

67.060 Žita, stročnice in proizvodi iz Cereals, pulses and derived

njih products

SIST ISO 11052:1997 en

SIST ISO 11052:1997

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 11052:1997

 $https://standards.iteh.ai/catalog/standards/sist/8\overline{4}f1733a-aaa5-4d7e-8c79-1856cf8d11c2/sist-iso-11052-1997$

SIST ISO 11052:1997

INTERNATIONAL STANDARD

ISO 11052

> First edition 1994-09-01

Durum wheat flour and semolina — Determination of yellow pigment content

iTeh STANDARD PREVIEW
Farines et semoules de blé dur — Détermination de la teneur en pigments
(saunes dards.iteh.ai)

<u>SIST ISO 11052:1997</u> https://standards.iteh.ai/catalog/standards/sist/84f1733a-aaa5-4d7e-8c79-1856cf8d11c2/sist-iso-11052-1997



ISO 11052:1994(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75% of the member bodies casting VIEW a vote.

(standards.iteh.ai)

International Standard ISO 11052 was prepared by Technical Committee ISO/TC 34, Agricultural food products, Subcommittee SC 4.5 Cereals and pulses.

https://standards.iteh.ai/catalog/standards/sist/84f1733a-aaa5-4d7e-8c79-

Annexes A and B of this International Standard are for information only.

© ISO 1994

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Durum wheat flour and semolina — Determination of vellow pigment content

Scope

This International Standard specifies a method for determination of the yellow pigment content in durum wheat flour and semolina (Triticum durum L.).

2 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions s 5.1 Water-saturated n-butanol of this International Standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 712:1985, Cereals and cereal products — Determination of moisture content (Routine reference method).

Definition

For the purposes of this International Standard, the following definition applies.

3.1 yellow pigment content: An essential quality factor of raw materials for the production of pasta, defined as the content of extractable carotenoids of the endosperm.

It is expressed as milligrams of β -carotene in 100 g of dry matter.

Principle

Extraction of the carotenoids at room temperature with water-saturated *n*-butanol. Then photometric evaluation of the optical density of the clear filtrate against β -carotene standard solutions.

Reagents

Use only reagents of recognized analytical grade and distilled or demineralized water or water of at least equivalent purity.

Prepare a solution of n-butanol and water in proportions 6:2 (V/V) and shake vigorously. Use the clear upper layer after separation of the phases.

5.2 Diethyl ether

5.3 Synthetic β -carotene, crystalline, finely crushed.

Apparatus

Usual laboratory apparatus and, in particular, the following.

- **6.1 Grinder**, having the following properties:
- constructed of a material that does not absorb water;
- easy to clean;
- of minimal dead space;
- capable of grinding rapidly and uniformly without heating, and avoiding as far as possible contact of the sample with the outside air.
- **6.2** Spectrometer, capable of operating at a wavelength of 440 nm.

ISO 11052:1994(E) © ISO

- **6.3 Erlenmeyer flasks**, of capacity 200 ml, preferably of brown glass, with ground glass stoppers.
- **6.4 Erlenmeyer flasks**, of capacity 100 ml.
- **6.5 Volumetric flasks**, of capacity 10 ml, narrownecked, with ground glass stoppers.
- **6.6 Volumetric flasks**, of capacities 100 ml and 250 ml, with ground glass stoppers.
- 6.7 Pipettes, of capacities 20 ml and 25 ml.
- **6.8 Watch glass** or **Petri dish**, as cover for the funnel (6.10).
- 6.9 Filter paper, hard, fluted.
- 6.10 Funnel.
- **6.11 Analytical balance**, capable of weighing to an accuracy of 0,001 g.

water-saturated *n*-butanol (5.1) to give a homogeneous suspension. Shake gently in the stoppered flask several times during the first hour. Allow the suspension to stand overnight (16 h to 18 h) at room temperature.

NOTE 2 If no brown glass flasks are available, protect the stoppered flask from light.

The next morning, shake the contents again, then filter **completely** through the fluted filter paper (6.9) into a 100 ml Erlenmeyer flask (6.4). To avoid solvent loss by evaporation, place the funnel (6.10) on the flask and cover it with a watch glass or Petri dish (6.8).

10.2 Determination

Measure the optical density of the clear filtrate at 440 nm as absorbance, using the spectrometer (6.2).

Use unfiltered water-saturated *n*-butanol for setting-up the instrument and for the blank determinations. Read the corresponding β-carotene content from the calibration curve (10.4).

7 Sampling

(standard 10.3 terreparation of standard solution of the istruly representative and has not been damping β -carotene

which is truly representative and has not been dam ISO 11052:1997
aged or changed during transport or storage and catalog/standarth/ast 00 miles mark/volumetric flask (6.6), weigh, to

Sampling is not part of the method specified in this International Standard. A recommended sampling method is given in ISO 2170.

8 Preparation of test sample

Flour or semolina with a particle size smaller than 0,5 mm can be used as such. Grind semolina with a particle size greater than 0,5 mm, using the grinder (6.1).

NOTE 1 A comparative study has demonstrated that a particle size under 0,5 mm is appropriate.

9 Determination of moisture content

Determine the moisture content of the test sample in accordance with ISO 712.

10 Determination of yellow pigment

10.1 Preparation of extract

In a 200 ml Erlenmeyer flask (6.3), weigh, to the nearest 0,001 g, 10 g of the test sample, ground if necessary (see clause 8). Disperse it in 50 ml of

ndarh as 100 ml one-mark volumetric flask (6.6), weigh, to sist-within 0,0017g, exactly 0,025 g of β-carotene. Dissolve it in diethyl ether (5.2). Make up to the mark with diethyl ether and mix carefully. Take, using a pipette (6.7), 20 ml of this homogeneous solution (= 5 mg of β-carotene) and place in a 250 ml one-mark volumetric flask (6.6). Make up to the mark with water-saturated n-butanol (5.1) and mix carefully. Then take, using the pipette, 25 ml of this solution and place in a 100 ml one-mark volumetric flask (6.6). Make up to the mark with the water-saturated n-butanol and mix carefully.

This is the standard solution. It has the following concentration:

1 ml = 0,005 mg = 5 μ g β -carotene.

10.4 Preparation of calibration curve

Prepare suitable dilutions of the standard solution (10.3) with water-saturated *n*-butanol in calibrated 10 ml volumetric flasks (6.5) (e.g. from 0,5 ml to 3 ml of standard solution in 10 ml).

Measure the absorbance A, of each dilution and establish a calibration curve (β -carotene in 10 ml of solution as a function of absorbance).

11 Calculation

The yellow pigment content, w_p , expressed as milligrams of β -carotene in 100 g of dry matter, is equal to

$$w_{\mathsf{P}} = \frac{5a}{100 - H}$$

where

- is the β -carotene content corresponding to the 10 ml extract (equivalent to 2 g of the test sample), in milligrams;
- is the moisture content of the test sample, Η expressed as a percentage by mass.

Precision 12

Results of an interlaboratory test are given in annex A.

12.1 Accuracy

Since β -carotene is used for calibration but is not \mathbb{R} present, or is only a minor constituent of the grain endosperm pigments, the resulting values may devi-dis.iteh.all ate by up to 5 % from the true value. However, as xanthophyl (lutein) is not readily available for pali-11052:199 quoted result obtained. bration, this error is unavoidable and is of minor condards/sis sequence. 1856cf8d11c2/sist-iso-1

Repeatability 12.2

For a yellow pigment content within the range of 0,651 mg/100 g to 0,754 mg/100 g, the absolute difference between two single test results, obtained using the same method on identical test material in the same laboratory by the same operator using the same equipment within a short interval of time, should not be greater than 0,03 mg/100 g.

Reproducibility 12.3

For a yellow pigment content within the range of 0,651 mg/100 g to 0,754 mg/100 g, the absolute difference between two single test results, obtained using the same method on identical test material in different laboratories with different operators using different equipment, should not be greater than 0,3 mg/100 g.

13 **Test report**

The test report shall specify

 the method in accordance with which sampling was carried out, if known,

the method used,

- the test result(s) obtained, and
- if the repeatability has been checked, the final

It shall also mention all operating details not specified in this International Standard, or regarded as optional, together with details of any incidents which may have influenced the test result(s).

The test report shall include all information necessary for the complete identification of the sample.

Annex A

(informative)

Results of interlaboratory test

An interlaboratory test, carried out by the International Association for Cereal Science and Technology (ICC) in 1989, in which seven laboratories participated, each

of which carried out four determinations on each sample, gave the statistical results (evaluated in accordance with ISO 5725) shown in table A.1.

Table A.1

Sample	I		111	IV	V	VI
Number of laboratories retained after eliminating outliers	7	7	7	7	7	7
Mean content, mg/100 g d.m. ¹⁾	0,754	0,731	0,697	0,699	0,658	0,651
Standard deviation of repeatability S_r , mg/100 g d.m.	0,007 28	0,007 21	0,010 8	0,005 68	0,006 05	0,007 36
Coefficient of variation of repeatability, %	0.96 (Star	idards.	iteh.ai)	0,81	0,92	1,13
Repeatability, 2,83 S _r , mg/100 g d.m.	0,020	0,020	0,031	0,016	0,017	0,021
Standard deviation of reproducibility//star S_r , mg/100 g d.m.	0,082 0	alog/stgy/lagds/ 8d11c2/sist-iso		^{1a5} 0,698 6°79	0,105 6	0,088 0
Coefficient of variation of reproducibility, %	10,83	11,53	13,84	14,24	16,05	13,52
Reproducibility, 2,83 S_r , mg/100 g d.m.	0,233	0,238	0,273	0,282	0,299	0,249
1) d.m. = dry matter						