



Edition 1.0 2016-06

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Thyristor valves for high voltage direct current (HVDC) power transmission – Part 2: Terminology (standards.iteh.ai)

Valves à thyristors pour le transport d'énergie en courant continu à haute tension (CCHT) https://standards.iteh.ai/catalog/standards/sist/dc269acf-5038-437e-a734-Partie 2: Terminologie 722f1599ba5b/iec-60700-2-2016





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2016 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office	Tel.: +41 22 919 02 11
3, rue de Varembé	Fax: +41 22 919 03 00
CH-1211 Geneva 20	info@iec.ch
Switzerland	www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a converse of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20/000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 15 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

65 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.





Edition 1.0 2016-06

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Thyristor valves for high soltage direct current (HVDC) power transmission – Part 2: Terminology (standards.iteh.ai)

Valves à thyristors pour le transp<u>ort d'épergie</u> en courant continu à haute tension (CCHT)_{https://standards.iteh.ai/catalog/standards/sist/dc269acf-5038-437e-a734-Partie 2: Terminologie 722f1599ba5b/iec-60700-2-2016}

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 29.200

ISBN 978-2-8322-3474-7

Warning! Make sure that you obtained this publication from an authorized distributor. Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

 Registered trademark of the International Electrotechnical Commission Marque déposée de la Commission Electrotechnique Internationale

CONTENTS

FOREWORD	3	
1 Scope	5	
2 Normative references	5	
3 Symbols and abbreviations	5	
3.1 General	5	
3.2 List of letter symbols	5	
3.3 List of abbreviations		
4 General terms related to converter circuits	6	
5 Converter performance	6	
6 Thyristor valve design	6	
7 Thyristor valve performance	11	
8 Thyristor valve voltages, currents and other parameters		
9 Thyristor valve control	15	
10 Thyristor valve protection	16	
Bibliography	22	
Figure 1 – Example of a converter unit NDARD PREVIEW	17	
Figure 2 – Commutation process at rectifier and inverter modes of operation	18	
Figure 2 – Commutation process at rectifier and inverter modes of operation		
Figure 4 – Typical valve voltage waveforms60700-2:2016		
Figure 5 – An example of thyristor valve composition 722t1599ba5b/iec-60700-2-2016	21	

INTERNATIONAL ELECTROTECHNICAL COMMISSION

THYRISTOR VALVES FOR HIGH VOLTAGE DIRECT CURRENT (HVDC) POWER TRANSMISSION –

Part 2: Terminology

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user. (Standards.iten.al)
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter. https://standards.iteh.ai/catalog/standards/sist/dc269acf-5038-437e-a734-
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60700-2 has been prepared by subcommittee 22F: Power electronics for electrical transmission and distribution systems, of IEC technical committee 22: Power electronic systems and equipment.

The text of this standard is based on the following documents:

CDV	Report on voting
22F/373/CDV	22F/395A/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 60700 series, published under the general title *Thyristor valves for high voltage direct current (HVDC) power transmission*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

The contents of the corrigendum of June 2017 have been included in this copy.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>IEC 60700-2:2016</u> https://standards.iteh.ai/catalog/standards/sist/dc269acf-5038-437e-a734-722f1599ba5b/iec-60700-2-2016

THYRISTOR VALVES FOR HIGH VOLTAGE DIRECT CURRENT (HVDC) POWER TRANSMISSION -

Part 2: Terminology

1 Scope

This part of IEC 60700 defines terms for thyristor valves for high-voltage direct current (HVDC) power transmission with line commutated converters most commonly based on three-phase bridge connections for the conversion from AC to DC and vice versa.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60027(all parts), Letter symbols to be used in electrical technology

IEC 60633, Terminology for high-voltage direct current (HVDC) transmission (standards.iten.al)

3 Symbols and abbreviations IEC 60700-2:2016

https://standards.iteh.ai/catalog/standards/sist/dc269acf-5038-437e-a734-722f1599ba5b/iec-60700-2-2016

The lists in 3.2 and 3.3 cover only the most frequently used symbols. The lists of symbols of the IEC 60027 series and IEC 60633 apply.

3.2 List of letter symbols

- α (trigger/firing) delay angle
- β (trigger/firing) advance angle
- μ commutation overlap angle
- γ extinction angle

General

3.1

3.3 List of abbreviations

The following abbreviations are always in capital letters and without dots:

- ETT electrically triggered thyristor
- LTT light triggered thyristor
- TCU thyristor control unit
- HVDC high-voltage direct current
- VBE valve base electronics
- MVU multiple valve (unit)
- BOD breakover diode

4 General terms related to converter circuits

4.1

converter arm

part of a bridge connecting two points of different potentials within a bridge, for example between an AC terminal and a DC terminal

Note 1 to entry: The main function of a converter arm is conversion.

4.2

converter bridge

equipment used to implement the bridge converter connection, if used

SEE: Figure 1

Note 1 to entry: The term "bridge" may be used to describe either the circuit connection or the equipment implementing that circuit.

[SOURCE: IEC 60633: 2015, 6.2, modified – The expression "and the by-pass arm" has been deleted from the definition.]

4.3

converter unit

indivisible operative unit comprising all equipment between the point of common coupling on the AC side and the point of common coupling on the DC side, essentially one or more converter bridges, together with one or more converter transformers, converter unit control equipment, essential protective and switching devices and auxiliaries, if any, used for conversion **(Standards.iten.al)**

SEE: Figure 1

IEC 60700-2:2016

https://standards.itch.ai/catalog/standards/sist/dc269acf-5038-437e-a734-Note 1 to entry: If a converter unit comprises two converter bridges with a phase displacement of 30 degrees, then the converter unit forms a 12-pulse unit.

5 Converter performance

5.1

forward direction

conducting direction

direction of current through a valve, when current flows from the anode terminal to the cathode terminal

5.2

reverse direction

non-conducting direction

direction of current through a valve, when current flows from the cathode terminal to the anode terminal

6 Thyristor valve design

6.1

thyristor

bi-stable semiconductor device comprising three or more junctions which can be switched from the off-state to the on-state

Note 1 to entry: Devices having only three layers but having switching characteristics similar to those of fourlayers devices may also be called thyristors.

Note 2 to entry: The term "thyristor" is used as a generic term to cover the whole range of PNPN type devices. It may be used by itself for any member of the thyristor family when such use does not result in ambiguity or

misunderstanding. In particular, the term "thyristor" is widely used for reverse blocking triode thyristor, formerly called "silicon controlled rectifier".

Note 3 to entry: Thyristors may either be electrically triggered thyristor (ETT) or light triggered thyristor (LTT).

6.2

electrically triggered thyristor

ETT

thyristor triggered by applying electrical pulses to the thyristor gate

Note 1 to entry: This note applies to the French language only.

6.3 light triggered thyristor

LŤT

thyristor triggered by applying light pulses to a photosensitive area within the thyristor gate area

Note 1 to entry: This note applies to the French language only.

6.4

damping circuit

snubber circuit

circuit (usually consisting of a series connected resistor and capacitor) connected in parallel to a thyristor to reduce the amplitude of the extinction overshoot voltage

6.4.1

damping capacitor

iTeh STANDARD PREVIEW

(standards.iteh.ai)

snubber capacitor (Standards.iten.al) capacitor connected in parallel to a thyristor (usually in series with a resistor) to reduce the amplitude of the extinction overshoot voltage)700-22016

> https://standards.iteh.ai/catalog/standards/sist/dc269acf-5038-437e-a734-722f1599ba5b/iec-60700-2-2016

6.4.2

damping resistor snubber resistor

resistor connected in parallel to a thyristor (in series with a capacitor) to limit the amplitude of discharge current of the snubber capacitor after thyristor turn-on

6.5

DC grading resistor

resistor connected in parallel to the thyristor to equalize DC voltage unbalance caused by tolerances of thyristor blocking currents

Note 1 to entry: In some designs, DC grading resistor also acts as high voltage arm of the voltage divider for monitoring voltage across the thyristor level.

6.6

heat sink

separable cooling element, usually through which a heat transfer agent flows, that contributes to the dissipation of the heat produced within the thyristors and other components, if any, in the valve

6.7

thyristor control unit

TCU

electronic unit at thyristor level potential used to trigger, protect and monitor the thyristor

Note 1 to entry: Some other terms are used for this unit: thyristor electronics (TE), thyristor firing and monitoring unit (TFM) or (thyristor) gating unit.

Note 2 to entry: In some designs, a thyristor voltage monitoring unit (TVM) is used which performs monitoring functions only.

Note 3 to entry: This note applies to the French language only.

6.8 thyristor stack thyristor clamped assembly

mechanical arrangement of more than one thyristor, stacked in an alternating series with heat sinks and clamped within an insulating mechanical support unit

Note 1 to entry: The clamping force is usually exerted by a disk spring arrangement.

6.9

single valve unit

single structure comprising only one valve

[SOURCE: IEC 60633:2015, 6.3.1]

6.10 multiple valve unit MVU single structure comprising more than one valve

EXAMPLE Double valves, quadrivalves and octovalves with two, four and eight series-connected valves respectively.

Note 1 to entry: This note applies to the French language only.

[SOURCE: IEC 60633:2015, 6:3.2] ANDARD PREVIEW

6.11

thyristor valve

complete operative controllable valve device assembly, normally conducting in only one direction (the forward direction), which can stude to stude

(standards.iteh.ai)

SEE: Figure 5

6.12

valve thyristor level

part of a valve comprising a thyristor, or thyristors connected in parallel, together with their immediate auxiliaries, and reactor, if any

[SOURCE: IEC 60633:2015, 6.9]

6.13

valve section

electrical assembly, comprising a number of thyristors and other components, which exhibits prorated electrical properties of a complete valve

Note 1 to entry: This term is mainly used to define a test object for valve testing purposes.

[SOURCE: IEC 60633:2015, 6.8]

6.14

redundant thyristor levels

maximum number of thyristor levels in a thyristor valve that may be short-circuited externally or internally during service without affecting the safe operation of the thyristor valve as demonstrated by type tests, and which if and when exceeded, would require shutdown of the valve to replace the failed thyristors or acceptance of increased risk of failures

6 1 5

valve reactor

reactor contained within the valve and connected directly in series with one or more thyristor levels to control d*i*/d*t* at turn-on and d*u*/d*t* in the off-state

Note 1 to entry: di/dt is rate of rise of on-state current.

Note 2 to entry: du/dt is rate of rise of off-state voltage.

6.16

valve section capacitor

capacitor connected across two or more thyristor levels and at least one valve reactor, for the purpose of ensuring voltage sharing in fast transient conditions (for example lightning and steep-front impulse)

Note 1 to entry: Term "grading capacitor" is also used.

6.17

fast grading circuit surge distribution circuit

capacitor, or resistor-capacitor circuit with a time constant of less than 5 µs, connected directly across each thyristor level (or across the thyristor level plus level reactor) for the purpose of ensuring voltage sharing in fast transient conditions (for example lightning and steep-front impulse)

6.18 iTeh STANDARD PREVIEW fast grading capacitor surge distribution capacitor (standards.iteh.ai) capacitive part of the fast grading circuit

IEC 60700-2:2016

fast grading resistor 722f1599ba5b/iec-60700-2-2016 surge distribution resistor

resistive part (if any) of the fast grading circuit

6.20

valve electronics

electronic circuits at valve potential(s) which perform control and protection functions for one or more valve levels

6.21 valve base electronics VBE

electronic unit, at earth potential, providing the electrical to optical conversion between the converter control system and the valves

Note 1 to entry: This note applies to the French language only.

[SOURCE: IEC 60633:2015, 6.12]

6.22 trigger system firing system means to provide firing pulses to the thyristors at high potential

Note 1 to entry: In case of electrically triggered thyristor (ETT) valves, the trigger circuit consists of light emitting devices in the VBE, the fibre optics which transmit the trigger pulses to the individual thyristor levels and the electrical circuits on the TCUs which convert the optical pulses to electrical trigger pulses applied to the thyristors. In light triggered thyristor (LTT) valves, the optical trigger pulses may be split to the individual thyristors directly inside the valve using a multimode star coupler.

6.23

recovery protection circuit

electronic circuit or device to protect the thyristor against excessive positive rate of voltage change during the recovery period by measuring the du/dt rate and firing the thyristor in case a limit value is exceeded

Note 1 to entry: The recovery protection circuit may be implemented at the thyristor control unit or as a separate unit per valve section.

Note 2 to entry: The recovery protection function may also be implemented in the thyristor's silicon structure rendering any external electronics unnecessary.

6.24

multimode star coupler

passive optical device which splits a number of incoming optical signals to a larger number of outgoing optical signals

Note 1 to entry: In some valve designs it is used to distribute the trigger impulses received by a few fibre optics from the valve base electronics (VBE) to the number of thyristors in a valve section.

6.25

valve cooling circuit

arrangement of tubes for transporting the heat transfer agent from ground potential into the valve arrangement, distributing it to the valve components, and transporting it back

6.26

valve cooling system Teh STANDARD PREVIEW

all equipment needed for removing heat from the valves and rejecting it to the environment, including the valve cooling circuit plus circulating pumps or fans, de-ionisation and filtering equipment, heat exchangers, interconnecting pipework and control system at ground potential

IEC 60700-2:2016

6.27 https://standards.iteh.ai/catalog/standards/sist/dc269acf-5038-437e-a734-

grading electrodes 722f1599ba5b/iec-60700-2-2016

electrodes of non corrosive metal inserted into the cooling circuit at appropriate locations and connected to appropriate electrical potentials to control leakage current flow through the cooling medium in order to avoid partial discharge due to potential mismatch

6.28

thyristor module

part of a valve comprising a mechanical assembly of thyristors with their immediate auxiliaries but without valve reactors

Note 1 to entry: Thyristor modules may be elements of a valve and/or be interchangeable for maintenance purposes.

6.29

valve module

part of a valve comprising a mechanical assembly of thyristors with their immediate auxiliaries and valve reactor(s)

Note 1 to entry: Valve module may be interchangeable for maintenance purpose.

6.30

reactor module

mechanical assembly of one or more valve reactors used in some valve designs

Note 1 to entry: Reactor modules may be elements in the construction of a valve.

[SOURCE: IEC 60633:2015, 6.7, modified – The definition has been rephrased.]

6.31

valve support

part of the valve which mechanically supports and electrically insulates from earth the active part of the valve

6.32

valve structure

structural components of a valve, required in order to physically support the valve modules

6.33

valve tier

one physical layer of a single or a multiple valve unit comprising one or more valve module(s)

6.34

corona shield

conductive surface on the external profile of a single or a multiple valve unit for the purpose of minimising the surface electrical field strength and preventing corona

7 Thyristor valve performance

7.1

valve blocking

operation preventing further firing of a valve

iTeh STANDARD PREVIEW

[SOURCE: IEC 60633:2015, 7.17, modified – The adjective "controllable" has been deleted.]

7.2

valve deblocking

IEC 60700-2:2016

operation permittinguficingaofaalvalvei/catalog/standards/sist/dc269acf-5038-437e-a734-

722f1599ba5b/iec-60700-2-2016

[SOURCE: IEC 60633:2015, 7.18, modified – The adverb "further" and the adjective "controllable" have been deleted.]

7.3 on-state conducting state condition of a valve when the valve exhibits a low resistance

SEE: Figure 4

[SOURCE: IEC 60633:2015, 7.9]

7.4

off-state non-conducting state condition of a valve when all thyristors are turned off

7.5

forward blocking state

non-conducting state of a valve when forward voltage is applied between its main terminals

[SOURCE: IEC 60633:2015, 7.11.1, modified – The adjective "controllable" has been deleted.]

7.6

reverse blocking state

non-conducting state of a valve when reverse voltage is applied between its main terminals

[SOURCE: IEC 60633:2015, 7.11.2]

7.7

firing failure

failure to achieve firing of a valve during the entire forward voltage interval

[SOURCE: IEC 60633:2015, 7.30]

7.8

commutation failure

failure to commutate the forward current from the conducting converter arm to the succeeding converter arm

- 12 -

[SOURCE: IEC 60633:2015, 7.31]

7.9 false firing misfiring firing of a valve at an unintended instant

Thyristor valve voltages, currents and other parameters 8

8.1

valve forward voltage Teh STANDARD PREVIEW

voltage applied between the anode and cathode terminals of a valve or an arm when the anode is positive with respect to the cathode US.ILCII.2

SEE: Figure 4

IEC 60700-2:2016

https://standards.iteh.ai/catalog/standards/sist/dc269acf-5038-437e-a734-

[SOURCE: IEC 60633:2015, 7.7, modified a The noun-valve" has been added to the term.]

8.2

valve forward current

current which flows through a valve in the forward direction

[SOURCE: IEC 60633:2015, 7.5, modified – The noun "valve" has been added to the term.]

8.3

valve reverse voltage

voltage applied between the anode and cathode terminals of a valve or an arm when the anode is negative with respect to the cathode

SEE: Figure 4

[SOURCE: IEC 60633:2015, 7.8, modified – The noun "valve" has been added to the term.]

8.4

valve reverse current

current which flows through a valve in the reverse direction

[SOURCE: IEC 60633:2015, 7.6, modified – The noun "valve" has been added to the term.]

8.5 valve on-state conducting state state of a thyristor valve when all thyristors are turned-on

8.6

valve on-state voltage

voltage drop

forward voltage which, during the on-state, appears across the valve terminals

8.7

valve off-state voltage

forward voltage which, during the non-conducting state, appears across the valve terminals

- 13 -

8.8

valve on-state current

current which flows through a valve during the on-state

8.9

valve conduction interval

part of a cycle during which a valve is in the conducting state

SEE: Figure 4

[SOURCE: IEC 60633:2015, 7.25]

8.10

valve blocking interval

part of a cycle during which a valve is in the non-conducting state

SEE: Figure 4

(standards.iteh.ai)

[SOURCE: IEC 60633:2015, 7.26, modified – The noun "valve" has been added to the term, and the second preferred term "idle interval" (has been deleted.]

https://standards.iteh.ai/catalog/standards/sist/dc269acf-5038-437e-a734-

722f1599ba5b/iec-60700-2-2016

valve forward blocking interval

part of the blocking interval during which a controllable valve is in the forward blocking state

SEE: Figure 4

[SOURCE: IEC 60633:2015, 7.27, modified – The noun "valve" has been added to the term.]

8.12

8.11

valve reverse blocking interval

part of the blocking interval during which a valve is in the reverse blocking state

SEE: Figure 4

[SOURCE: IEC 60633:2015, 7.28, modified – The noun "valve" has been added to the term.]

8.13

valve hold-off interval

time from the instant when the forward current of a controllable valve has decreased to zero to the instant when the same valve is subjected to forward voltage

SEE: Figure 3

[SOURCE: IEC 60633:2015, 7.24, modified – The noun "valve" has been added to the term, and the note to entry has been deleted.]