

TECHNICAL SPECIFICATION

SPECIFICATION TECHNIQUE

**Fuel cell technologies –
Part 7-2: Test methods – Single cell and stack performance tests for solid oxide
fuel cells (SOFC)**

**Technologies des piles à combustible –
Partie 7-2: Méthodes d'essai – Essais de performance de cellule élémentaire et
de pile pour les piles à combustible à oxyde solide (SOFC)**



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2014 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 14 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

Plus de 55 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

TECHNICAL SPECIFICATION

SPECIFICATION TECHNIQUE

**Fuel cell technologies –
Part 7-2: Test methods – Single cell and stack performance tests for solid oxide
fuel cells (SOFC)**

**Technologies des piles à combustible –
Partie 7-2: Méthodes d'essai – Essais de performance de cellule élémentaire et
de pile pour les piles à combustible à oxyde solide (SOFC)**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX



ICS 27.070

ISBN 978-2-8322-1539-5

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

| | |
|--|----|
| FOREWORD..... | 5 |
| INTRODUCTION..... | 7 |
| 1 Scope..... | 8 |
| 2 Normative references | 8 |
| 3 Terms, definitions and symbols..... | 9 |
| 3.1 Terms and definitions..... | 9 |
| 3.2 Symbols..... | 11 |
| 4 General safety conditions | 12 |
| 5 Cell/stack assembly unit | 12 |
| 6 Testing system | 13 |
| 6.1 Subsystems in testing system | 13 |
| 6.1.1 General | 13 |
| 6.1.2 Anode gas control subsystem | 13 |
| 6.1.3 Cathode gas control subsystem | 13 |
| 6.1.4 Cell/stack assembly unit temperature control subsystem | 13 |
| 6.1.5 Output power control subsystem | 14 |
| 6.1.6 Measurement and data acquisition subsystem | 14 |
| 6.1.7 Safety subsystem | 14 |
| 6.1.8 Mechanical load control subsystem..... | 14 |
| 6.1.9 Gas pressure control subsystem for anode and cathode | 14 |
| 6.1.10 Test system control subsystem..... | 14 |
| 6.2 Maximum variation in control items of testing system | 14 |
| 7 Instruments and measurement methods | 15 |
| 7.1 General..... | 15 |
| 7.2 Instrument uncertainty | 15 |
| 7.3 Anode gas | 15 |
| 7.3.1 Anode gas flow rate..... | 15 |
| 7.3.2 Anode gas composition..... | 16 |
| 7.3.3 Anode gas temperature | 16 |
| 7.3.4 Anode gas pressure..... | 17 |
| 7.3.5 Anode exhaust gas flow rate..... | 17 |
| 7.3.6 Anode exhaust gas component..... | 17 |
| 7.3.7 Anode exhaust gas temperature | 17 |
| 7.3.8 Anode exhaust gas pressure..... | 17 |
| 7.4 Cathode gas | 18 |
| 7.4.1 Cathode gas flow rate..... | 18 |
| 7.4.2 Cathode gas component..... | 18 |
| 7.4.3 Cathode gas temperature | 18 |
| 7.4.4 Cathode gas pressure..... | 18 |
| 7.4.5 Cathode exhaust gas flow rate..... | 18 |
| 7.4.6 Cathode exhaust gas component..... | 19 |
| 7.4.7 Cathode exhaust gas temperature | 19 |
| 7.4.8 Cathode exhaust gas pressure | 19 |
| 7.5 Output voltage | 19 |
| 7.6 Output current..... | 19 |

| | | |
|--------|--|----|
| 7.7 | Cell/stack assembly unit temperature | 19 |
| 7.8 | Mechanical load | 19 |
| 7.9 | Total impedance | 20 |
| 7.10 | Ambient condition | 20 |
| 8 | Test preparation | 20 |
| 8.1 | General..... | 20 |
| 8.2 | Standard test condition and test range | 20 |
| 8.3 | Components and impurities of anode gas and cathode gas | 21 |
| 8.4 | Basis of the test procedure | 21 |
| 8.5 | Confirmation of aging condition for unit..... | 21 |
| 8.6 | Confirmation of criteria of stable state..... | 21 |
| 8.7 | Data acquisition method..... | 21 |
| 9 | Test procedure | 21 |
| 9.1 | Set-up..... | 21 |
| 9.2 | Initial conditioning..... | 22 |
| 9.3 | Shut-down | 22 |
| 10 | Performance test | 22 |
| 10.1 | Rated power test..... | 22 |
| 10.1.1 | Objective | 22 |
| 10.1.2 | Test method | 22 |
| 10.1.3 | Presentation of results..... | 22 |
| 10.2 | Current-voltage characteristics test..... | 23 |
| 10.2.1 | Objective | 23 |
| 10.2.2 | Test method | 23 |
| 10.2.3 | Presentation of results..... | 23 |
| 10.3 | Effective fuel utilization dependency test | 24 |
| 10.3.1 | Objective | 24 |
| 10.3.2 | Test method | 24 |
| 10.3.3 | Presentation of results..... | 24 |
| 10.4 | Long term durability test | 25 |
| 10.4.1 | Objective | 25 |
| 10.4.2 | Test method | 25 |
| 10.4.3 | Presentation of results..... | 26 |
| 10.5 | Thermal cycling durability test..... | 26 |
| 10.5.1 | Objective | 26 |
| 10.5.2 | Test method | 26 |
| 10.5.3 | Presentation of results..... | 27 |
| 10.6 | Internal reforming performance test | 27 |
| 10.6.1 | Objective | 27 |
| 10.6.2 | Test method | 27 |
| 10.6.3 | Presentation of results..... | 27 |
| 10.7 | Resistance components identification test..... | 27 |
| 10.7.1 | Objective | 27 |
| 10.7.2 | Test method | 28 |
| 10.7.3 | Presentation of results..... | 28 |
| 11 | Test report..... | 29 |
| 11.1 | General..... | 29 |
| 11.2 | Report items | 29 |

| | | |
|-----------------------|--|----|
| 11.3 | Test unit data description | 30 |
| 11.4 | Test condition description | 30 |
| 11.5 | Test data description | 30 |
| 11.6 | Uncertainty evaluation | 30 |
| Annex A (informative) | Example of cell assembly unit | 31 |
| Annex B (informative) | Calculation of effective fuel utilization | 32 |
| B.1 | Calculation method | 32 |
| B.2 | Calculation examples | 33 |
| B.2.1 | Calculation from anode gas composition and flow-rate..... | 33 |
| B.2.2 | Calculation from supplied H ₂ and H ₂ O flow rate | 33 |
| Annex C (informative) | Calculation of effective oxygen utilization | 34 |
| C.1 | Calculation method | 34 |
| C.2 | Calculation example..... | 34 |
| Annex D (informative) | Maximum width of the voltage hysteresis in <i>I-V</i> characteristic test | 36 |
| Annex E (informative) | Current-voltage characteristic test under constant effective fuel utilization | 37 |
| Annex F (informative) | Test report (template)..... | 38 |
| F.1 | General information | 38 |
| F.2 | Test unit data description | 38 |
| F.3 | Test condition | 39 |
| F.4 | Rated power test..... | 39 |
| F.5 | Current-voltage characteristics test..... | 39 |
| F.6 | Effective fuel utilization dependency test | 40 |
| F.7 | Long-term durability test | 41 |
| F.8 | Thermal cycling durability test..... | 42 |
| F.9 | Internal reforming performance test..... | 42 |
| F.10 | Resistance components identification test..... | 43 |
| Annex G (informative) | Method for finding instrument uncertainty..... | 44 |
| Bibliography | | 45 |
| Figure 1 | – Testing system..... | 13 |
| Figure 2 | – Typical diagram of complex impedance plot for SOFC..... | 29 |
| Figure A.1 | – Example of cell assembly unit..... | 31 |
| Figure D.1 | – Voltage hysteresis at a given sweep rate in <i>I-V</i> characteristic test | 36 |
| Figure E.1 | – Example of the record in current-voltage characteristic test under constant effective fuel utilization | 37 |
| Table 1 | – Symbols | 11 |
| Table B.1 | – n_j for representative fuels | 33 |
| Table B.2 | – Anode gas composition, flow rate of each fuel component f_j , and $n_j f_j$ | 33 |
| Table C.1 | – Cathode gas composition, f_{O_2} , and I_{theory} | 35 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FUEL CELL TECHNOLOGIES –**Part 7-2: Test methods –
Single cell and stack performance tests for solid oxide fuel cells (SOFC)**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC TS 62282-7-2, which is a technical specification, has been prepared by IEC technical committee 105: Fuel cell technologies.

The text of this technical specification is based on the following documents:

| | |
|---------------|------------------|
| Enquiry draft | Report on voting |
| 105/443/DTS | 105/498/RVC |

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 62282 series, under the general title: *Fuel cell technologies*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- transformed into an International standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTech Standards
(<https://standards.iteh.ai>)
Document Preview

IEC TS 62282-7-2:2014

<https://standards.iteh.ai/catalog/standards/iec/91c1-a470-42b0-b1d7-09892135e8a9/iec-ts-62282-7-2-2014>

WITHDRAWN

INTRODUCTION

This technical specification describes test methods for a single cell and stack (denoted as "cell/stack" hereafter) that is to be employed in power generation systems using solid oxide fuel cells (SOFCs).

SOFCs have a broad range of geometry and size. As such, in general, peripherals like current collectors and gas manifolds are unique to each cell or stack and are often incorporated into a cell or stack to form one integrated unit. In addition, they tend to have a significant effect on the power generation characteristics of the cell or stack. This technical specification therefore introduces as its subject "cell/stack assembly units," which are defined as those units containing not only a cell or stack but also peripherals.

Withhold

iTech Standards
(<https://standards.iteh.ai>)
Document Preview

IEC TS 62282-7-2:2014
<https://standards.iteh.ai/catalog/standards/iec/91c1-a470-42b0-b1d7-09892135e8a9/iec-ts-62282-7-2-2014>

FUEL CELL TECHNOLOGIES –

Part 7-2: Test methods – Single cell and stack performance tests for solid oxide fuel cells (SOFC)

1 Scope

This part of IEC 62282, which is a technical specification, provides for SOFC cell/stack assembly units, testing systems, instruments and measuring methods, and test methods to test the performance of SOFC cells and stacks.

This technical specification is not applicable to small button cells that are designed for SOFC material testing and provide no practical means of fuel utilization measurement.

This technical specification is to be used for data exchanges in commercial transactions between cell/stack manufacturers and system developers or for acquiring data on a cell or stack in order to estimate the performance of a system based on it. Users of this technical specification may selectively execute test items suitable for their purposes from those described in this technical specification.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60584-1, *Thermocouples – Part 1: EMF specifications and tolerances*

IEC 60584-2, *Thermocouples – Part 2: Tolerances*

IEC 60584-3, *Thermocouples – Part 3: Extension and compensating cables – Tolerances and identification system*

IEC 61515, *Mineral insulated thermocouple cables and thermocouples*

IEC TS 62282-1:2013, *Fuel cell technologies – Part 1: Terminology*

ISO 4260, *Petroleum products and hydrocarbons – Determination of sulfur content – Wickbold combustion method*

ISO 5168, *Measurement of fluid flow – Procedures for the evaluation of uncertainties*

ISO 6141, *Gas analysis – Requirements for certificates for calibration gases and gas mixtures*

ISO 6142, *Gas analysis – Preparation of calibration gas mixtures – Gravimetric method*

ISO 6143, *Gas analysis – Comparison methods for determining and checking the composition of calibration gas mixtures*

ISO 6145-7, *Gas analysis – Preparation of calibration gas mixtures using dynamic volumetric methods – Part 7: Thermal mass-flow controllers*

ISO 6974 (all parts), *Natural gas – Determination of composition with defined uncertainty by gas chromatography*

ISO 7066-2, *Assessment of uncertainty in the calibration and use of flow measurement devices – Part 2: Non-linear calibration relationships*

ISO 8573-1, *Compressed air – Part 1: Contaminants and purity classes*

ISO 8756, *Air quality – Handling of temperature, pressure and humidity data*

ISO 12185, *Crude petroleum and petroleum products – Determination of density – Oscillating U-tube method*

3 Terms, definitions and symbols

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC TS 62282-1, as well as the following terms and definitions, apply.

3.1.1

cell/stack assembly unit

unit including a single cell or stack, as well as gas supply parts, current collector parts, and any other peripherals as required for power generation tests

3.1.2

active electrode area

geometric electrode area upon which an electrochemical reaction occurs

Note 1 to entry: Usually this is the smaller of the anode and cathode areas.

3.1.3

current density

current divided by active electrode area

3.1.4

average cell voltage

cell/stack assembly unit voltage divided by the number of the cells in a series connection in the unit

3.1.5

normal temperature and pressure

NTP

0 °C and 101,325 kPa, respectively

3.1.6

anode gas

gas which is supplied to the inlet of the anode of a single cell/stack assembly unit

Note 1 to entry: Such a gas belongs to one of the following categories:

- pure hydrogen or mixture which contains hydrogen as a principal component with water vapour or nitrogen;
- reformed gas of raw fuel of SOFC such as methane or kerosene premixed with water vapour or air as oxidant;
- simulated gas of reformat which contains hydrogen, water vapour, carbon monoxide, carbon dioxide, methane, nitrogen, etc, as main components;
- methane, alcohols and other raw fuels directly supplied in pure form or mixed with water vapour and/or air.

3.1.7**cathode gas**

gas which is supplied to the inlet of the cathode of a single cell/stack assembly unit

Note 1 to entry: Oxygen and nitrogen are its main components.

3.1.8**current collector**

conductive material in a fuel cell that collects electrons from the anode side or conducts electrons to the cathode side

3.1.9**stable state**

condition of a cell/stack assembly unit at which the unit is stable enough for any controlling parameter and the output voltage or output current of the unit to remain within its tolerance range of variation

3.1.10**theoretical current**

current when the supplied anode gas or cathode gas is completely consumed in electrochemical reactions divided by the number of cells in a series connection

3.1.11**effective fuel utilization**

ratio of actual output current of the cell/stack assembly unit to the theoretical current

Note 1 to entry: Causes for less-than-optimal currents include losses due to electronic conduction within the cell/stack assembly, gas leaks and anode gas pass-through.

Note 2 to entry: Calculation method of effective fuel utilization is given in Annex B.

3.1.12**effective oxygen utilization**

ratio of actual output current of the cell/stack assembly unit to the theoretical current

Note 1 to entry: Calculation method of effective oxygen utilization is given in Annex C.

3.1.13**maximum effective fuel utilization**

highest effective fuel utilization that the unit can operate at, without causing unacceptable degradation

Note 1 to entry: The acceptable degradation rate is usually obtained from the developer.

3.1.14**minimum cell/stack assembly unit voltage**

lowest cell/stack assembly unit voltage specified by the manufacturer

3.1.15**open circuit voltage**

OCV

voltage across the terminals of a fuel cell with cathode and anode gases present and in the absence of external current flow

Note 1 to entry: Also known as no-load voltage.

3.1.16**power density**

ratio of the power to the active electrode area of a cell/stack assembly unit

Note 1 to entry: Power density is calculated from the voltage multiplied by the current density ($P_d = V \times J$, where J is current density).

3.1.17

total impedance

frequency-dependent losses due to ohmic, activation, diffusion, and concentration effects

3.1.18

total resistance

real part of low-frequency limit of total impedance which is the same as the slope of tangent to I - V curve

3.1.19

stoichiometric ratio

ratio between the number of moles of reactant gas flowing per unit time to that needed by the electrochemical reaction

Note 1 to entry: The terms, “stoichiometric ratio” and “reactant gas utilization,” are related. The reciprocal of the fraction of the gas utilized is the stoichiometric ratio.

3.2 Symbols

Table 1 shows the symbols and units that are used in this technical specification.

Table 1 – Symbols

| Symbol | Definition | Unit |
|-----------|---|-------------------|
| a | Error limit specified from specification of instrument | ** |
| f_a | Flow rate of anode gas | l/min (NTP) |
| f_c | Flow rate of cathode gas | l/min (NTP) |
| f_j | Flow rate of fuel component j in anode gas | l/min (NTP) |
| I | Current | A |
| J | Current density | A/cm ² |
| n | Number of transferred electrons | |
| N | Number of cells in a series connection | |
| p_a | Absolute pressure of anode gas | kPa |
| p_c | Absolute pressure of cathode gas | kPa |
| P | Output power | W |
| P_d | Output power density | W/cm ² |
| t | Time | s, min, h |
| T_{op} | Cell/stack assembly unit operating temperature | °C |
| u_l | Combined standard uncertainty for instruments | ** |
| $u_{l,i}$ | Standard uncertainty for instrument i | ** |
| U_f | Effective fuel utilization | % |
| U_{O_2} | Effective oxygen utilization | % |
| U_l | Extended instrument uncertainty | ** |
| V | Voltage | V |
| x_i | Normalized mole fraction of component i | mol % |
| x_i^* | Non-normalized mole fraction of component i | mol % |
| ζ_j | Hydrocarbon conversion rate for hydrocarbon component j | % |

** Denotes where the unit varies depending on the specification.

4 General safety conditions

An operating fuel cell uses oxidizing and combustible gases. Typically, these gases are stored in high-pressure containers. The fuel cell itself may be operated at pressures greater than atmospheric pressure. Those who carry out cell/stack assembly unit testing shall be trained and experienced in the operation of test systems and specifically in safety procedures involving electrical equipment and reactive, compressed gases.

The test personnel are responsible for obtaining and following all applicable safety codes and generally accepted engineering practices related to their test system, facility, fuels (with particular attention to compressed gases), and exhaust products.

Materials which are compatible with the use and storage of the reactant gases shall be used during testing. Local safety codes and standards for working with hydrogen, hydrocarbons and carbon monoxide should be followed.

In summary, safely operating a test station requires appropriate technical training and experience as well as safety facilities and equipment, all of which are outside the scope of this technical specification.

5 Cell/stack assembly unit

A cell/stack assembly unit includes a cell or stack, gas supply, current leads, and such other peripherals as required for power generation tests. It shall be provided with single or multiple measuring points for temperature and voltage, and one set of current lead points, all to be specified by the manufacturer.

As shown in Annex A, the boundary of a cell/stack assembly unit goes through the anode gas supply port, cathode gas supply port, temperature measuring point, current lead points, voltage measuring points and mechanical load application points.

Some cell/stack assembly units may have no exhaust port for the anode gas or cathode gas because of the configuration of the cells. In such cases, the gas flow field pattern and its material shall be determined by the method recommended by the manufacturer. The load application method shall be also based on the recommendation of the manufacturer. The maximum operating temperature from the manufacturer shall not be exceeded.

If the components of a cell/stack assembly unit other than a cell/stack are not specified by the manufacturer, the following shall be described in the test report, as a minimum:

- a) materials and geometry of the peripheral components to be used for testing;
- b) flow patterns and directions of anode and cathode gases;
- c) locations of temperature measurement, mechanical load application, voltage measurement and current leads;
- d) magnitude of the mechanical load;
- e) configuration of assembly unit and its assembling method.