AMERICAN SOCIETY FOR TESTING AND MATERIALS 100 Barr Harbor Dr., West Conshohocken, PA 19428 Reprinted from the Annual Book of ASTM Standards. Copyright ASTM

# Standard Specification for Type 58 Borosilicate Sealing Glass<sup>1</sup>

This standard is issued under the fixed designation F 105; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon  $(\epsilon)$  indicates an editorial change since the last revision or reapproval.

€<sup>1</sup> Note—Editorial changes were made throughout in November 1995.

## 1. Scope

1.1 This specification covers Type 58 borosilicate sealing glass for use in electronic applications.

Note 1—This specification is primarily intended to consider glass as most generally used, that is, glass in its transparent form as normally encountered in fabricating electronic devices. X1.3 refers to a sealing alloy that is compatible with this glass. Type 58 glass in other forms such as powdered, crushed, sintered, fibrous, etc., are excluded. The requirements of this specification, as applied to these forms, must be established in the raw glass prior to its conversion.

#### 2. Referenced Documents

- 2.1 ASTM Standards:
- C 336 Test Method for Annealing Point and Strain Point of Glass by Fiber Elongation<sup>2</sup>
- C 338 Test Method for Softening Point of Glass<sup>2</sup>
- C 598 Test Method for Annealing Point and Strain Point of Glass by Beam Bending<sup>2</sup>
- D 150 Test Methods for ac Loss Characteristics and Permittivity (Dielectric Constant) of Solid Electrical Insulating Materials<sup>3</sup>
- D 257 Test Methods for dc Resistance or Conductance of Insulating Materials<sup>3</sup> (hadron standards) sist/76612
- E 29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specification<sup>4</sup>
- E 228 Test Method for Linear Thermal Expansion of Solid Materials With a Vitreous Silica Dilatometer<sup>4</sup>
- F 14 Practice for Making and Testing Reference Glass-Metal Bead-Seal<sup>2</sup>
- F 15 Specification for Iron-Nickel-Cobalt Sealing Alloy<sup>5</sup>
- F 140 Practice for Making Reference Glass-Metal Butt Seals and Testing for Expansion Characteristics by Polarimetric Methods<sup>2</sup>
- F 144 Practice for Making Reference Glass-Metal Sandwich Seal and Testing for Expansion Characteristics by

# Polarimetric Methods<sup>2</sup>

### 3. Ordering Information

- 3.1 Orders for material under this specification shall include the following information:
  - 3.1.1 Form,
  - 3.1.2 Type of glass,
  - 3.1.3 Dimensions,
  - 3.1.4 Marking and packaging, and
  - 3.1.5 Certification (if required).

# 4. Chemical Composition

4.1 The typical chemical composition of this glass is as follows (Note 2):

	Weight %
Major Constituents:	
Silica (SiO <sub>2</sub> )	65.0
Alumina (Al <sub>2</sub> O <sub>3</sub> )	7.5
Boron oxide (B <sub>2</sub> O <sub>3</sub> )	18.0
Soda (Na <sub>2</sub> O)	2.0
Potash (K <sub>2</sub> O)	3.0
Barium oxide (BaO)	3.0
Minor Constituents:	
Lithium oxide (Li <sub>2</sub> O)	0.6
Fluorine (F) Dda 1-D84DZe(	0.6, max -1105-721995e1
Reducible oxides (Note 3)	0.05, max

Note 2—Major constituents may be adjusted to give the desired electrical and physical properties to the glass. However, no change shall be made that alters any of these properties without due notification of, and approval by, the user.

Note 3—Total of arsenic trioxide ( $As_2O_3$ ), antimony trioxide ( $Sb_2O_3$ ), and lead oxide (PbO).

# 5. Physical Requirements

5.1 The material shall conform to the physical properties prescribed in Table 1. For electrical properties see Table 2, and its Footnote A.

#### 6. Finish and Workmanship

6.1 The glass shall have a finish that ensures smooth, even surfaces and freedom from cracks, checks, bubbles, and other flaws of a character detrimental to the strength or life of the component or device for which its use is intended.

#### 7. Test Methods

7.1 Softening Point—Test Method C 338.

<sup>&</sup>lt;sup>1</sup> This specification is under the jurisdiction of ASTM Committee C-14 on Glass and Glass Products and is the direct responsibility of Subcommittee C14.04 on Physical and Mechanical Properties.

Current edition approved Nov. 10, 1995. Published January 1996. Originally published as F 105 – 68 T. Last previous edition F 105 – 72 (1991).

<sup>&</sup>lt;sup>2</sup> Annual Book of ASTM Standards, Vol 15.02.

<sup>&</sup>lt;sup>3</sup> Annual Book of ASTM Standards, Vol 10.01.

<sup>&</sup>lt;sup>4</sup> Annual Book of ASTM Standards, Vol 14.02.

<sup>&</sup>lt;sup>5</sup> Annual Book of ASTM Standards, Vol 10.04.