ISO/IEC 14776-261

Edition 1.0 2012-11

INTERNATIONAL STANDARD

colour inside

Information technology – Small Computer System Interface (SCSI) – Part 261: SAS protocol layer (SPL)

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 14776-261:2012
https://standards.iteh.ai/catalog/standards/sist/346b8f2f-8a24-4c9b-a3a5-5b442c6c43a1/iso-iec-14776-261-2012



ISO/IEC 14776-261:2012(E)

THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2012 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.
If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Useful links:

IEC publications search - www.iec.ch/searchpub

The advanced search enables you to find IEC publications by a variety of criteria (reference number, text, technical committee,...).
It also gives information on projects, replaced and withdrawn publications.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary (IEV) on-line.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available on-line and also once a month by email.

Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 14776-261:2012
https://standards.iteh.ai/catalog/standards/sist/346b8f2f-8a24-4c9b-a3a5-5b442c6c43a1/iso-iec-14776-261-2012

ISO/IEC 14776-261

Edition 1.0 2012-11

INTERNATIONAL STANDARD

colour inside

Information technology – Small Computer System Interface (SCSI) – Part 261: SAS protocol layer (SPL)

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 14776-261:2012
https://standards.iteh.ai/catalog/standards/sist/346b8f2f-8a24-4c9b-a3a5-5b442c6c43a1/iso-iec-14776-261-2012

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE XC

ICS 35.200

ISBN 978-2-83220-483-2

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD ... 18
INTRODUCTION ... 20
General ... 20
SCSI standards family ... 21
1 Scope ... 23
2 Normative references ... 23
3 Terms, definitions, symbols, abbreviations, keywords, and conventions ... 25
3.1 Terms and definitions ... 25
3.2 Symbols and abbreviations ... 46
3.3 Keywords ... 48
3.4 Editorial conventions ... 49
3.5 Class diagram and object diagram conventions ... 51
3.6 State machine conventions ... 55
3.6.1 State machine conventions overview ... 55
3.6.2 Transitions ... 56
3.6.3 Messages, requests, indications, confirmations, responses, and event notifications ... 57
3.6.4 State machine counters, timers, and variables ... 57
3.6.5 State machine arguments ... 57
3.7 Bit and byte ordering ... 58
3.8 Notation for procedures and functions ... 58
4 General ... 60
4.1 Architecture ... 60
4.1.1 Architecture overview ... 60
4.1.2 Physical links and phys ... 61
4.1.3 Logical links ... 66
4.1.4 Ports (narrow ports and wide ports) ... 66
4.1.5 Application clients and device servers ... 69
4.1.6 SAS devices ... 70
4.1.7 Expander devices ... 71
4.1.8 Service delivery subsystem ... 72
4.1.9 Domains ... 73
4.1.10 Expander device topologies ... 75
4.1.11 Pathways ... 77
4.1.12 Connections ... 77
4.1.13 Broadcasts ... 79
4.2 Names and identifiers ... 81
4.2.1 Names and identifiers overview ... 81
4.2.2 NAA IEEE Registered format identifier ... 82
4.2.3 NAA Locally Assigned format identifier ... 83
4.2.4 SAS address ... 84
4.2.5 Hashed SAS addresses ... 84
4.2.6 Device names and expander device SAS addresses ... 84
4.2.7 Device name for SATA devices with world wide names ... 85
4.2.8 Port names ... 85
4.2.9 Port identifiers and SAS port SAS addresses ... 85
4.2.10 Phy identifiers ... 86
4.3 State machines ... 87
4.3.1 State machine overview ... 87
4.3.2 Transmit data path ... 88
4.3.3 Receive data path ... 93

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 14776-261:2012
https://standards.iteh.ai/catalog/standards/sist/346b8f2f-8a24-4c9b-a3a5-5b442c6c43a1/iso-iec-14776-261-2012

4.3.4 State machines and SAS Device, SAS Port, and SAS Phy classes 96
4.4 Resets 98
4.4.1 Reset overview 98
4.4.2 Hard reset 100
4.5 I_T nexus loss 100
4.6 Expander device model 101
4.6.1 Expander device model overview 101
4.6.2 Expander ports 102
4.6.3 Expander connection manager (ECM) 103
4.6.4 Expander connection router (ECR) 103
4.6.5 Broadcast propagation processor (BPP) 104
4.6.6 Expander device interfaces 104
4.6.7 Expander device routing 111
4.6.8 Expander device reduced functionality 115
4.6.9 Broadcast (Expander) handling 116
4.7 Discover process 116
4.7.1 Discover process overview 116
4.7.2 Starting the discover process (Broadcast (Change) handling) 116
4.7.3 Discover process traversal 116
4.7.4 Discover process in a self-configuring expander device 118
4.7.5 Enabling multiplexing 119
4.8 Configuration subprocess 120
4.8.1 Configuration subprocess overview 120
4.8.2 Allowed expander device topologies 120
4.8.3 Externally configurable expander device route table optimization 121
4.8.4 Externally configurable expander device expander route index order 122
4.9 Zoning 128
4.9.1 Zoning overview 128
4.9.2 Zoning expander device requirements 132
4.9.3 Zoning operation 134
4.9.4 Zone phy information and link reset sequences 140
4.9.5 Broadcast processing in a zoning expander device with zoning enabled 142
4.9.6 Zone configuration 143
4.10 Phy power conditions 146
4.10.1 Low phy power conditions 146
4.10.2 SATA phy power conditions 148
4.11 SAS device and expander device power conditions 148
4.12 Phy test functions 149
4.12.1 Phy test functions overview 149
4.12.2 Transmit pattern phy test function 149
4.13 Phy events 150
5 Phy layer 155
5.1 Phy layer overview 155
5.2 8b10b coding 155
5.2.1 8b10b coding overview 155
5.2.2 8b10b coding notation conventions 155
5.3 Character encoding and decoding 156
5.3.1 Introduction 156
5.3.2 Bit transmission order 156
5.3.3 Character transmission order 156
5.3.4 Frame transmission order 156
5.3.5 Running disparity (RD) 157
5.3.6 Data characters 157

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 14776-261:2012
https://standards.iteh.ai/catalog/standards/sist/346b8f2f-8a24-4c9b-a3a5-5b442c6c43a1/iso-iec-14776-261-2012

5.3.7 Control characters 163
5.3.8 Encoding characters in the transmitter 164
5.3.9 Decoding characters in the receiver 164
5.4 Dwords, primitives, data dwords, and invalid dwords 164
5.5 Bit order 165
5.6 Out of band (OOB) signals 166
5.6.1 OOB signals overview 166
5.6.2 SP Transmission of OOB signals 166
5.6.3 Receiver detection of OOB signals 167
5.6.4 SATA port selection signal 169
5.6.5 Phy power conditions 170
5.7 Phy reset sequences 170
5.7.1 Phy reset sequences overview 170
5.7.2 SATA phy reset sequence 171
5.7.3 SAS to SATA phy reset sequence 172
5.7.4 SAS to SAS phy reset sequence 174
5.7.5 Phy reset sequence after devices are attached 196
5.8 Phy power condition sequences 197
5.8.1 Transitioning from the active phy power condition to a low phy power condition 197
5.8.2 Transitioning from a low phy power condition to the active phy power condition 197
5.8.3 Events during low phy power condition 198
5.9 SP (phy layer) state machine 200
5.9.1 SP state machine overview 200
5.9.2 SP transmitter and receiver 202
5.9.3 OOB sequence states 204
5.9.4 SAS speed negotiation states 209
5.9.5 SAS phy power conditions states 219
5.9.6 SATA host emulation states 222
5.9.7 SATA port selector state SP25:SATA_PortSel 227
5.9.8 SATA spinup hold state SP26:SATA_SpinupHold 228
5.10 SP_DWS (phy layer dword synchronization) state machine 228
5.10.1 SP_DWS state machine overview 228
5.10.2 SP_DWS receiver 230
5.10.3 SP_DWS0:AcquireSync state 231
5.10.4 SP_DWS1:Valid1 state 231
5.10.5 SP_DWS2:Valid2 state 232
5.10.6 SP_DWS3:SyncAcquired state 232
5.10.7 SP_DWS4:Lost1 state 232
5.10.8 SP_DWS5:Lost1Recovered state 233
5.10.9 SP_DWS6:Lost2 state 233
5.10.10 SP_DWS7:Lost2Recovered state 234
5.10.11 SP_DWS8:Lost3 state 234
5.10.12 SP_DWS9:Lost3Recovered state 234
5.11 Multiplexing 235
5.12 Spinup 236
6 Link layer 237
6.1 Link layer overview 237
6.2 Primitives 237
6.2.1 Primitives overview 237
6.2.2 Primitive summary 238
6.2.3 Primitive encodings 243
6.2.4 Primitive sequences 248
6.2.5 Deletable primitives 252
6.2.6 Primitives not specific to type of connections 256

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 14776-261:2012
https://standards.iteh.ai/catalog/standards/sist/346b8f2f-8a24-4c9b-a3a5-55e6e6e6e6e6/iso-iec-14776-261-2012

6.2.7 Primitives used only inside SSP and SMP connections 262
6.2.8 Primitives used only inside STP connections and on SATA physical links 263
6.3 Physical link rate tolerance management 264
6.3.1 Physical link rate tolerance management overview 264
6.3.2 Phys originating dwords 266
6.3.3 Expander phys forwarding dwords 266
6.4 Idle physical links 267
6.5 CRC 267
6.5.1 CRC overview 267
6.5.2 CRC generation 269
6.5.3 CRC checking 271
6.6 Scrambling 272
6.7 Bit order of CRC and scrambler 274
6.8 Address frames 277
6.8.1 Address frames overview 277
6.8.2 IDENTIFY address frame 279
6.8.3 OPEN address frame 282
6.9 Link reset sequence 285
6.9.1 Link reset sequence overview 285
6.9.2 Expander device handling of link reset sequences 288
6.10 SL_IR (link layer identification and hard reset) state machines 288
6.10.1 SL_IR state machines overview 288
6.10.2 SL_IR transmitter and receiver 290
6.10.3 SL_IR_TIR (transmit IDENTIFY or HARD_RESET) state machine 290
6.10.4 SL_IR_RIF (receive IDENTIFY address frame) state machine 292
6.10.5 SL_IR_IRC (identification and hard reset control) state machine 293
6.11 Entering a low phy power condition 294
6.12 SAS domain changes (Broadcast (Change) usage) 295
6.13 Connections 296
6.13.1 Connections overview 296
6.13.2 Opening a connection 296
6.13.3 Arbitration fairness 298
6.13.4 Arbitration inside an expander device 300
6.13.5 BREAK handling 304
6.13.6 Aborting a connection request 305
6.13.7 Closing a connection 307
6.13.8 Breaking a connection 308
6.14 Rate matching 309
6.15 SL (link layer for SAS logical phys) state machines 312
6.15.1 SL state machines overview 312
6.15.2 SL transmitter and receiver 315
6.15.3 SL_RA (receive OPEN address frame) state machine 317
6.15.4 SL_CC (connection control) state machine 317
6.16 XL (link layer for expander logical phys) state machine 330
6.16.1 XL state machine overview 330
6.16.2 XL transmitter and receiver 335
6.16.3 XL0:Idle state 336
6.16.4 XL1:Request_Path state 338
6.16.5 XL2:Request_Open state 340
6.16.6 XL3:Open_Confirm_Wait state 340
6.16.7 XL4:Open_Reject state 342
6.16.8 XL5:Forward_Open state 342
6.16.9 XL6:Open_Response_Wait state 343
6.16.10 XL7:Connected state 344

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 14776-261:2012
https://standards.iteh.ai/catalog/standards/sist/346b8d1f-8a24-4c9b-a3a5-5b442c6c43a1/iso-iec-14776-261-2012

6.16.11 XL8:Close_Wait state 345
6.16.12 XL9:Break state 346
6.16.13 XL10:Break_Wait state 347
6.16.14 XL11:PS_Request state 347
6.16.15 XL12:PS_Quiet state 348
6.17 SSP link layer 349
6.17.1 Opening an SSP connection 349
6.17.2 Full duplex 349
6.17.3 SSP frame transmission and reception 350
6.17.4 SSP flow control 350
6.17.5 Interlocked frames 351
6.17.6 Breaking an SSP connection 353
6.17.7 Closing an SSP connection 353
6.17.8 SSP (link layer for SSP phys) state machines 354
6.18 STP link layer 365
6.18.1 STP frame transmission and reception 365
6.18.2 STP flow control 366
6.18.3 Continued primitive sequence 370
6.18.4 Affiliations 371
6.18.5 Opening an STP connection 373
6.18.6 Closing an STP connection 375
6.18.7 STP connection management examples 376
6.18.8 STP (link layer for STP phys) state machines 379
6.18.9 SMP target port support 379
6.19 SMP link layer 379
6.19.1 SMP frame transmission and reception 379
6.19.2 SMP flow control 379
6.19.3 Opening an SMP connection 379
6.19.4 Closing an SMP connection 380
6.19.5 SMP (link layer for SMP phys) state machines 380
7 Port layer 385
7.1 Port layer overview 385
7.2 PL (port layer) state machines 385
7.2.1 PL state machines overview 385
7.2.2 PL_OC (port layer overall control) state machine 387
7.2.3 PL_PM (port layer phy manager) state machine 398
8 Transport layer 409
8.1 Transport layer overview 409
8.2 SSP transport layer 410
8.2.1 SSP frame format 410
8.2.2 Information units 414
8.2.3 Sequences of SSP frames 424
8.2.4 SSP transport layer handling of link layer errors 427
8.2.5 SSP transport layer error handling summary 432
8.2.6 ST (transport layer for SSP ports) state machines 434
8.3 STP transport layer 470
8.3.1 Initial FIS 470
8.3.2 BIST Activate FIS 470
8.3.3 TT (transport layer for STP ports) state machines 470
8.4 SMP transport layer 471
8.4.1 SMP transport layer overview 471
8.4.2 SMP_REQUEST frame 472
8.4.3 SMP_RESPONSE frame 472
8.4.4 Sequence of SMP frames 473

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 14776-261:2012
https://standards.iteh.ai/catalog/standards/sist/346b8f2f-8a24-4c9b-a3a5-5b442c6c43a1/iso-iec-14776-261-2012

8.4.5 MT (transport layer for SMP ports) state machines 473
9 Application layer 478
9.1 Application layer overview 478
9.2 SCSI application layer 478
9.2.1 SCSI transport protocol services 478
9.2.2 Application client error handling 490
9.2.3 Device server error handling 491
9.2.4 Task router and task manager error handling 492
9.2.5 SCSI transport protocol event notifications 492
9.2.6 SCSI commands 492
9.2.7 SCSI mode parameters 493
9.2.8 SCSI log parameters 504
9.2.9 SCSI diagnostic parameters 507
9.2.10 SCSI power conditions 514
9.2.11 SCSI vital product data (VPD) 523
9.3 ATA application layer 526
9.4 Management application layer 526
9.4.1 READY LED signal behavior 526
9.4.2 Management protocol services 527
9.4.3 SMP functions 528

Annex A (normative) Jitter tolerance patterns 641

Annex B (informative) SAS to SAS phy reset sequence examples 649

Annex C (informative) CRC 654

Annex D (informative) SAS address hashing 658

Annex E (informative) Scrambling 665

Annex F (informative) ATA architectural notes 669

Annex G (informative) Minimum deletable primitive insertion rate summary 672

Annex H (informative) Zone permission configuration descriptor examples 673

Annex I (informative) SAS addressing 676

Annex J (informative) Expander device handling of connections 677

Annex K (informative) Primitive encoding 698

Bibliography 701

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 14776-261:2012
https://standards.iteh.ai/catalog/standards/sist/346b8f2f-8a24-4c9b-a3a5-5b442c6c43a1/iso-iec-14776-261-2012

Figure 1 — Organization of this standard 20
Figure 2 — SCSI document relationships 21
Figure 3 — ATA document relationships 21
Figure 4 — Classes in class diagrams 51
Figure 5 — Association relationships in class diagrams 52
Figure 6 — Aggregation relationships in class diagrams 53
Figure 7 — Generalization relationships in class diagrams 54
Figure 8 — Dependency relationships in class diagrams 54
Figure 9 — Objects in object diagrams 55
Figure 10 — State machine conventions 56
Figure 11 — SAS Domain class diagram 61
Figure 12 — Phy class diagram 63
Figure 13 — SAS phy object diagram 64
Figure 14 — Expander phy object diagram 65
Figure 15 — Ports (narrow ports and wide ports) 67
Figure 16 — Port class diagram 68
Figure 17 — Port object diagram 69
Figure 18 — SAS devices 71
Figure 19 — Expander device 72
Figure 20 — Domains 73
Figure 21 — SAS domain bridging to ATA domains 73
Figure 22 — SAS domains bridging to ATA domains with SATA port selectors 74
Figure 23 — Devices spanning SAS domains 75
Figure 24 — Single expander device topology example 75
Figure 25 — Multiple expander device topologies 76
Figure 26 — Potential pathways 77
Figure 27 — Multiple connections on wide ports 79
Figure 28 — State machines for SAS devices 87
Figure 29 — State machines for expander devices 88
Figure 30 — Transmit data path in a SAS phy 89
Figure 31 — SSP link, port, SSP transport, and SCSI application layer state machines 90
Figure 32 — SMP link, port, SMP transport, and management application layer state machines 91
Figure 33 — STP link, port, STP transport, and ATA application layer state machines 92
Figure 34 — Transmit data path and state machines in an expander phy 93
Figure 35 — Receive data path in a SAS phy 94
Figure 36 — Receive data path in an expander phy 95
Figure 37 — State machines and SAS Device classes 96
Figure 38 — State machines and Expander Device classes 97
Figure 39 — Reset terminology 99
Figure 40 — Expander device model 102
Figure 41 — Expander device interfaces 105
Figure 42 — Expander device interface detail 106
Figure 43 — Phy-based expander route table 114
Figure 44 — Expander-based expander route table 115
Figure 45 — Level-order traversal example 117
Figure 46 — Examples of invalid topologies 121
Figure 47 — Externally configurable expander device and table-to-table attachment 124
Figure 48 — Expander route index levels example 125
Figure 49 — Expander route index order example 127
Figure 50 — Zoning example 129
Figure 51 — One ZPSDS example 129
Figure 52 — Zone manager location examples 130
Figure 53 — Three ZPSDSes example 131
Figure 54 — Extending a ZPSDS example 133
Figure 55 — Overtaking a ZPSDS example 134
Figure 56 — Zoning expander route table 139
Figure 57 — SAS bit transmission logic 165
Figure 58 — SAS bit reception logic 166

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 14776-261:2012
https://standards.iteh.ai/catalog/standards/sist/346b8f2f-8a24-4c9b-a3a5-5b442c6c43a1/iso-iec-14776-261-2012

Figure 59 — OOB signal transmission 167
Figure 60 — OOB signal detection 169
Figure 61 — SATA OOB sequence 171
Figure 62 — SATA speed negotiation sequence 172
Figure 63 — SAS to SATA OOB sequence 173
Figure 64 — SAS to SAS OOB sequence 175
Figure 65 — SNW-1, SNW-2, and Final-SNW 178
Figure 66 — SNW-3 180
Figure 67 — Train-SNW 185
Figure 68 — SAS speed negotiation sequence SNW flowchart 187
Figure 69 — SAS speed negotiation sequence (both phys SNW-1 through SNW-3) 189
Figure 70 — SAS speed negotiation sequence (phy A: SNW-1 through SNW-3, phy B: SNW-2 only) 190
Figure 71 — SAS speed negotiation sequence (phy A: SNW-3 only, phy B: SNW-1 only) 191
Figure 72 — SAS speed negotiation sequence - phy reset problem in Final-SNW 192
Figure 73 — SAS speed negotiation sequence - phy reset problem in SNW-3 193
Figure 74 — SAS speed negotiation sequence - phy reset problem in Train-SNW 194
Figure 75 — SAS speed negotiation sequence - multiple Train-SNWs 195
Figure 76 — Hot-plug and the phy reset sequence 197
Figure 77 — Transition to active phy power condition 198
Figure 78 — Hot plug and low phy power condition 199
Figure 79 — SP (phy layer) state machine - OOB sequence states 204
Figure 80 — SP (phy layer) state machine - SAS speed negotiation states 210
Figure 81 — SP (phy layer) state machine - SAS speed negotiation states for SNW-3 and Train-SNW 211
Figure 82 — SP (phy layer) state machine - SAS phy power condition states 220
Figure 83 — SP (phy layer) state machine - SATA host emulation states 223
Figure 84 — SP (phy layer) state machine – SATA port selector state 227
Figure 85 — SP (phy layer) state machine - SATA spinup hold state 228
Figure 86 — SP_DWS (phy layer dword synchronization) state machine 230
Figure 87 — Multiplexing disabled 235
Figure 88 — Multiplexing enabled 235
Figure 89 — Transmitting a repeated primitive sequence 249
Figure 90 — Receiving a repeated primitive sequence 249
Figure 91 — Extended primitive sequences 250
Figure 92 — Triple primitive sequences 251
Figure 93 — Redundant primitive sequences 252
Figure 94 — Elasticity buffer 265
Figure 95 — Address frame, SSP frame, and SMP frame CRC bit ordering 270
Figure 96 — STP frame CRC bit ordering 271
Figure 97 — Transmit path bit ordering 274
Figure 98 — Receive path bit ordering 275
Figure 99 — STP transmit path bit ordering 276
Figure 100 — STP receive path bit ordering 277
Figure 101 — Address frame transmission 277
Figure 102 — Identification sequence 286
Figure 103 — Hard reset sequence 287
Figure 104 — SL_IR (link layer identification and hard reset) state machines 289
Figure 105 — Transitioning from the active phy power condition to a low phy power condition 294
Figure 106 — Example simultaneous connection recommendations for wide ports 297
Figure 107 — Aborting a connection request with a BREAK primitive sequence 306
Figure 108 — Connection request timeout example 307
Figure 109 — Closing a connection example 308
Figure 110 — Rate matching example 311
Figure 111 — SL (link layer for SAS logical phys) state machines (part 1) 313
Figure 112 — SL (link layer for SAS logical phys) state machines (part 2) 314
Figure 113 — SL (link layer for SAS logical phys) state machines (part 3) 315
Figure 114 — XL (link layer for expander logical phys) state machine (part 1) 332
Figure 115 — XL (link layer for expander logical phys) state machine (part 2) 333
Figure 116 — XL (link layer for expander logical phys) state machine (part 3) 334

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 14776-261:2012
https://standards.iteh.ai/catalog/standards/sist/346b8f2f-8a24-4c9b-a3a5-5b442c6c43a1/iso-iec-14776-261-2012

Figure 117 — SSP frame transmission 350
Figure 118 — Interlocked frames 352
Figure 119 — Non-interlocked frames with the same initiator port transfer tags 352
Figure 120 — Non-interlocked frames with different initiator port transfer tags 353
Figure 121 — Closing an SSP connection example 354
Figure 122 — SSP (link layer for SSP phys) state machines (part 1 - frame transmission) 356
Figure 123 — SSP (link layer for SSP phys) state machines (part 2 - frame reception) 357
Figure 124 — STP frame transmission 365
Figure 125 — STP flow control 369
Figure 126 — Transmitting a continued primitive sequence 371
Figure 127 — Receiving a continued primitive sequence 371
Figure 128 — Example simultaneous connection recommendations for an expander device 375
Figure 129 — STP initiator port opening an STP connection 377
Figure 130 — STP target port opening an STP connection 378
Figure 131 — SMP frame transmission 379
Figure 132 — SMP_IP (link layer for SMP initiator phys) state machine 381
Figure 133 — SMP_TP (link layer for SMP target phys) state machine 383
Figure 134 — Port layer examples 386
Figure 135 — PL_OC (port layer overall control) state machine 389
Figure 136 — PL_PM (port layer phy manager) state machine (part 1) 400
Figure 137 — PL_PM (port layer phy manager) state machine (part 2) 401
Figure 138 — Task management function sequence of SSP frames 424
Figure 139 — Non-data command sequence of SSP frames 425
Figure 140 — Write command sequence of SSP frames 425
Figure 141 — Read command sequence of SSP frames 426
Figure 142 — Bidirectional command sequence of SSP frames 427
Figure 143 — ST_I (transport layer for SSP initiator ports) state machines 436
Figure 144 — ST_T (transport layer for SSP target ports) state machines 452
Figure 145 — Sequence of SMP frames 473
Figure 146 — MT_IP (transport layer for SMP initiator ports) state machine 474
Figure 147 — MT_TP (transport layer for SMP target ports) state machine 476
Figure 148 — SA_PC (SCSI application layer power condition) state machine for SAS 516
Figure A.1 — CJTPAT pre-scrambling 642
Figure B.1 — SAS speed negotiation sequence (phy A:SNW-1 only, phy B:SNW-1 only) 649
Figure B.2 — SAS speed negotiation sequence (phy A:SNW-1, SNW-2, phy B:SNW-1, SNW-2) 650
Figure B.3 — SAS speed negotiation sequence (phy A:SNW-1, SNW-2, SNW-3, phy B:SNW-1, SNW-2) 651
Figure B.4 — SAS speed negotiation sequence (phy A:SNW-2, SNW-3, phy B:SNW-1, SNW-2) 652
Figure B.5 — SAS speed negotiation sequence (phy A:SNW-1 only, phy B:SNW-2 only) 653
Figure C.1 — CRC generator example 654
Figure C.2 — CRC checker example 654
Figure D.1 — BCH(69, 39, 9) code generator 659
Figure E.1 — Scrambler 665
Figure J.1 — Example topology 677
Figure J.2 — Connection request - OPEN_ACCEPT 679
Figure J.3 — Connection request - OPEN_REJECT by end device 680
Figure J.4 — Connection request - OPEN_REJECT by expander device 681
Figure J.5 — Connection request - arbitration lost 682
Figure J.6 — Connection request - backoff and retry 683
Figure J.7 — Connection request - backoff and reverse path 684
Figure J.8 — Connection close - single step 685
Figure J.9 — Connection close - simultaneous 686
Figure J.10 — BREAK handling during path arbitration when the BREAK_REPLY method is disabled 687
Figure J.11 — BREAK handling during a connection when the BREAK_REPLY method is disabled 688
Figure J.12 — BREAK handling during path arbitration when the BREAK_REPLY method is enabled 689
Figure J.13 — BREAK handling during a connection when the BREAK_REPLY method is enabled 690
Figure J.14 — STP connection - originated by STP initiator port 691
Figure J.15 — STP connection - originated by STP target port in an STP/SATA bridge 692
Figure J.16 — STP connection close - originated by STP initiator port 693

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 14776-261:2012
https://standards.iteh.ai/catalog/standards/sist/346b8f2f-8a24-4c9b-a3a5-5b442c6c43a1/iso-iec-14776-261-2012

Figure J.17 — STP connection close - originated by STP target port in an STP/SATA bridge 694
Figure J.18 — XL1:Request_Path to XL5:Forward_Open transition 695
Figure J.19 — Partial pathway recovery 696

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 14776-261:2012
https://standards.iteh.ai/catalog/standards/sist/346b8f2f-8a24-4c9b-a3a5-5b442c6c43a1/iso-iec-14776-261-2012

Table 1 — Standards bodies 23
Table 2 — Numbering conventions 50
Table 3 — Multiplicity notation in class diagrams 52
Table 4 — Data dword containing a value 58
Table 5 — Data dword containing four one-byte fields 58
Table 6 — Logical links 66
Table 7 — Broadcast types 80
Table 8 — Names and identifiers 82
Table 9 — SAM-5 attribute mapping 82
Table 10 — NAA IEEE Registered format 82
Table 11 — NAA Locally Assigned format 83
Table 12 — Hashed SAS address code parameters 84
Table 13 — Device name created from the IDENTIFY (PACKET) DEVICE world wide name 85
Table 14 — Expander logical phy to ECM requests 107
Table 15 — Expander logical phy to ECM responses 107
Table 16 — ECM to expander logical phy confirmations 108
Table 17 — Expander logical phy to ECR to expander logical phy requests and indications 109
Table 18 — Expander logical phy to ECR to expander logical phy responses and confirmations 109
Table 19 — Expander logical phy to BPP requests 110
Table 20 — BPP to expander logical phy indications 111
Table 21 — Routing attributes and routing methods 112
Table 22 — Expander route table types 113
Table 23 — Expander route table levels for externally configurable expander device R phy A 125
Table 24 — Expander route table levels for externally configurable expander device N 126
Table 25 — Expander route entries for externally configurable expander device E0 phy 1 127
Table 26 — Expander route entries for externally configurable expander device F phy 0 128
Table 27 — Zone manager password 132
Table 28 — Zone phy information 134
Table 29 — Zone phy information usage 135
Table 30 — Zone groups 137
Table 31 — Zone permission table 138
Table 32 — Zone permission table granting minimal permissions 138
Table 33 — Source zone group determination 140
Table 34 — Destination zone group determination 140
Table 35 — Zone phy information fields after a link reset sequence 141
Table 36 — Conditions that cause the ZONE GROUP field to be reset if the ZONE GROUP PERSISTENT bit is set to zero 142
Table 37 — PHY EVENT SOURCE field 151
Table 38 — Bit designations 155
Table 39 — Conversion from byte notation to character name example 156
Table 40 — Data characters 158
Table 41 — Control characters 163
Table 42 — Control character usage 163
Table 43 — Delayed code violation example 164
Table 44 — Phy reset sequence timing specifications 171
Table 45 — SATA speed negotiation sequence timing specifications 172
Table 46 — SAS speed negotiation sequence timing specifications 177
Table 47 — SNW rates used in SNW-1, SNW-2, and Final-SNW 179
Table 48 — SNW-3 phy capabilities bit 180
Table 49 — SNW-3 phy capabilities 181
Table 50 — Requested logical link rate 182
Table 51 — Multiplexing negotiation 182
Table 52 — Supported settings bit priorities 183
Table 53 — Example SNW-3 phy capabilities values 184
Table 54 — Training patterns 185
Table 55 — SP state machine timers 202
Table 56 — Messages to SP transmitter and SP receiver at start of RCDT 212
Table 57 — SP_DWS state machine timers 229

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 14776-261:2012
https://standards.iteh.ai/catalog/standards/sist/346b8f2f-8a24-4c9b-a3a5-5b442c6c43a1/iso-iec-14776-261-2012

Table 58 — Primitive format 237
Table 59 — Deletable primitives 238
Table 60 — Primitives not specific to type of connection 239
Table 61 — Primitives used inside SSP and SMP connections 241
Table 62 — Primitives used inside STP connections and on SATA physical links 242
Table 63 — Primitive encoding for deletable primitives 243
Table 64 — Primitive encoding for primitives not specific to type of connection 244
Table 65 — Primitive encoding for primitives used only inside SSP and SMP connections 246
Table 66 — Primitive encoding for primitives used only inside STP connections and only on SATA physical links 247
Table 67 — Primitive sequences 248
Table 68 — ALIGN primitives 253
Table 69 — MUX primitives 254
Table 70 — NOTIFY primitives 254
Table 71 — AIP primitives 256
Table 72 — BROADCAST primitives 257
Table 73 — CLOSE primitives 258
Table 74 — Abandon-class OPEN_REJECT primitives 259
Table 75 — Retry-class OPEN_REJECT primitives 260
Table 76 — PS_REQ primitives 261
Table 77 — DONE primitives 262
Table 78 — NAK primitives 263
Table 79 — RRDY primitives 263
Table 80 — Physical link rate tolerance management deletable primitive insertion requirement 266
Table 81 — CRC notation and definitions 268
Table 82 — Scrambling for different data dword types 272
Table 83 — Address frame format 278
Table 84 — ADDRESS FRAME TYPE field 278
Table 85 — IDENTIFY address frame format 279
Table 86 — DEVICE TYPE field 280
Table 87 — REASON field 280
Table 88 — OPEN address frame format 282
Table 89 — PROTOCOL field 283
Table 90 — FEATURES field 283
Table 91 — CONNECTION RATE field 283
Table 92 — ARBITRATION WAIT TIME field 285
Table 93 — SL_IR_IRC state machine timers 288
Table 94 — PS_ACK pattern 295
Table 95 — Connection Results of a connection request 298
Table 96 — Arbitration priority for OPEN address frames passing on a logical link 299
Table 97 — Arbitration priority for a Request Path request in the ECM 302
Table 98 — Pathway recovery priority 304
Table 99 — Results of aborting a connection request 305
Table 100 — Results of closing a connection 307
Table 101 — Results of breaking a connection 309
Table 102 — Rate matching deletable primitive insertion requirements 310
Table 103 — SL_CC state machine timers 319
Table 104 — SL_CC state machine variables 319
Table 105 — OPEN_REJECT Received message to Open Failed confirmation mapping 322
Table 106 — XL state machine timers 331
Table 107 — XL state machine variable 331
Table 108 — SSP frame interlock requirements 351
Table 109 — SSP state machines timers 355
Table 110 — STP link layer differences from SATA link layer during an STP connection 366
Table 111 — Affiliation policies 372
Table 112 — Affiliation context relative identifier example 373
Table 113 — PL_OC state machine timers 388
Table 114 — Confirmations from Unable To Connect messages 395

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 14776-261:2012
https://standards.iteh.ai/catalog/standards/sist/346b8f2f-8a24-4c9b-a3a5-5b442c6c43a1/iso-iec-14776-261-2012