



Edition 2.1 2011-04

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



Hand-held motor-operated electric tools - Safety EVIEW Part 2-13: Particular requirements for chain saws (Standards.iten.ai)

Outils électroportatifs à moteur – Sécurité – Partie 2-13: Règles particulières pour les scies à chaîne<sub>4787-a137-</sub>

679d04a844ee/iec-60745-2-13-2006amd1-2009-csv





#### THIS PUBLICATION IS COPYRIGHT PROTECTED

#### Copyright © 2011 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur. Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Email: inmail@iec.ch Web: www.iec.ch

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Catalogue of IEC publications: www.ieo.ch/searchpub ARD PREVIEW

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

IEC Just Published: www.iec.ch/online news/justpub
Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.
IEC 60745-2-13:2006+AMD1:2009 CSV

Electropedia: www.electropedia:provds.iteh.ai/catalog/standards/sist/0a29415a-d49a-4787-af37-

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

Customer Service Centre: <u>www.iec.ch/webstore/custserv</u>

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: <u>csc@iec.ch</u> Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00

#### A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

#### A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue des publications de la CEI: <u>www.iec.ch/searchpub/cur\_fut-f.htm</u>

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

Just Published CEI: <u>www.iec.ch/online\_news/justpub</u>

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

Electropedia: <u>www.electropedia.org</u>

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

Service Clients: <u>www.iec.ch/webstore/custserv/custserv\_entry-f.htm</u>

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: <u>csc@iec.ch</u> Tél.: +41 22 919 02 11

Fax: +41 22 919 03 00





Edition 2.1 2011-04

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



Hand-held motor-operated electric tools. Safety EVIEW Part 2-13: Particular requirements for chain saws

Outils électroportatifs à moteur, <u>Sécurité</u> <u>MD1 2009 CSV</u> Partie 2-13: Règles/particulières pour les scies à chaîne 787-af37-679d04a844ee/jec-60745-2-13-2006amd1-2009-csv

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 25.140.20; 65.060.80

ISBN 978-2-88912-419-0

### CONTENTS

FOREWORD			
1	Scope	7	
2	Normative references	7	
3	Terms and definitions	8	
4	General requirements	9	
5	General conditions for the tests	9	
6	Void	9	
7	Classification	9	
8	Marking and instructions	. 10	
9	Protection against access to live parts	.12	
10	Starting	. 12	
11	Input and current	. 12	
12	Heating	. 13	
13	Leakage current	. 13	
14	Moisture resistance	. 13	
15	Electric strength	. 13	
16	Overload protection of transformers and associated circuits	.13	
17	Endurance (standards.iteh.ai)	. 13	
18	Abnormal operation	. 13	
19	Mechanical hazards/standards.itch.ai/catalog/standards/sist/0a29415a-d49a-4787-af37	.13	
20	Mechanical strength679d04a844ee/iec-60745-2-13-2006amd1-2009-csv		
21	Construction	. 17	
22	Internal wiring	. 19	
23	Components	. 19	
24	Supply connection and external flexible cords	.19	
25	Terminals for external conductors	.19	
26	Provision for earthing	.19	
27	Screws and connections	.19	
28	Creepage distances, clearances and distances through insulation	.19	
29	Resistance to heat, fire and tracking	.19	
30	Resistance to rusting	.19	
31	Radiation, toxicity and similar hazards	.19	
Annexes			
Annex K (normative) Battery tools and battery packs			
Annex L (normative) Battery tools and battery packs provided with mains connection or non-isolated sources			
Annex AA (normative) Symbols for safety recommendations and warnings			
Annex BB (informative) Instructions concerning the proper techniques for basic felling, limbing, and cross-cutting			

60745-2-13 © IEC:2006+A1:2009 - 3 -

Bibliography
--------------

Figure 101 – Chain saw nomenclature	20
Figure 102 – Cutting length	21
Figure 103 – Holding the chain saw	21
Figure 104 – Minimum rear hand guard dimensions	22
Figure 105 – Straight test probe	22
Figure 106 – Chain brake test	23
Figure 107 – Static test for release force	24
Figure 108 – Bar tip guard	24
Figure 109 – Handle gripping area	25
Figure 110 – Impact text fixture for handle insulation	25
Figure BB.101 – Description of felling: escape routes	31
Figure BB.102 – Description of felling: undercutting	31
Figure BB.103 – Tree limbing	
Figure BB.104 – Log supported along the entire length	
Figure BB.105 – Log supported one end	
Figure BB.106 – Log supported both ends	
Figure BB.107 – Bucking a log. (standards.iteh.ai)	
(Stanuarus.iten.al)	

IEC 60745-2-13:2006+AMD1:2009 CSV https://standards.iteh.ai/catalog/standards/sist/0a29415a-d49a-4787-af37-679d04a844ee/iec-60745-2-13-2006amd1-2009-csv

#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

#### HAND-HELD MOTOR-OPERATED ELECTRIC TOOLS – SAFETY–

#### Part 2-13: Particular requirements for chain saws

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in the international and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of IEC 60745-2-13 consists of the second edition (2006) [documents 61F/625/FDIS and 61F/637/RVD] and its amendment 1 (2009) [documents 116/17/FDIS and 116/18/RVD]. It bears the edition number 2.1.

The technical content is therefore identical to the base edition and its amendment and has been prepared for user convenience. A vertical line in the margin shows where the base publication has been modified by amendment 1. Additions and deletions are displayed in red, with deletions being struck through.

International Standard IEC 60745-2-13 has been prepared by subcommittee 61F: Safety of hand-held motor-operated electric tools, of IEC technical committee 61: Safety of household and similar electrical appliances.

The amendment modifies the present part 2-13 to ensure its conformity with the fourth edition (2006) of IEC 60745-1, Hand-held motor-operated electric tools – Safety – Part 1: General requirements

This edition constitutes a technical revision. Main changes include Clause 8: Markings and instructions, introducing detailed safety warnings; Clause 19: Mechanical hazards, with requirements for handles, hand guards, guarding of moving parts, chain catcher, spiked bumper, chain brake, computed kickback angle, guide bar cover, saw chain tension, oiler, balance and run down time; Clause 20: Mechanical strength, with requirements for handles and hand guards; Clause 21: Construction, with requirements for the insulation of knobs and handles.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This part 2 is to be used in conjunction with the latest edition of IEC 60745-1, Hand-held motor-operated electric tools – Safety – Part 1: General requirements, and its amendments. It was established on the basis of the fourth edition (2006) of that standard.

NOTE 1 When "Part 1" is mentioned in this standard, it refers to IEC 60745-1.

This part 2 supplements or modifies the corresponding clauses of IEC 60745-1, so as to convert that publication into the IEC standard; Safety requirements for chain saws.

When a particular subclause of Part 1 is not mentioned in this part 2, that subclause applies as far as is reasonable. When this standard states addition "Symodification" or "replacement", the relevant text in Part/11 is to be adapted accordingly 229415a-d49a-4787-at37-679d04a844ec/iec-60745-2-13-2006and1-2009-csv

NOTE 2 The following numbering system is used:

- subclauses, items, tables and figures that are numbered starting from 101 are additional to those in Part 1;
- additional annexes are lettered AA, BB, etc.

NOTE 3 In this standard, the following print types are used:

- requirements: in roman type;
- test specifications: in italic type;
- notes: in smaller roman type.

IEC 60745 consists of the following parts, under the general title *Hand-held motor-operated electric tools* – *Safety:* 

- Part 1: General requirements
- Part 2-1: Particular requirements for drills and impact drills
- Part 2-2: Particular requirements for screwdrivers and impact wrenches
- Part 2-3: Particular requirements for grinders, polishers and disk-type sanders
- Part 2-4: Particular requirements for sanders and polishers other than disk type
- Part 2-5: Particular requirements for circular saws
- Part 2-6: Particular requirements for hammers
- Part 2-7: Particular requirements for spray guns for non-flammable liquids
- Part 2-8: Particular requirements for shears and nibblers
- Part 2-9: Particular requirements for tappers
- Part 2-11: Particular requirements for reciprocating saws (jig and sabre saws)
- Part 2-12: Particular requirements for concrete vibrators

- Part 2-13: Particular requirements for chain saws
- Part 2-14: Particular requirements for planers
- Part 2-15: Particular requirements for hedge trimmers
- Part 2-16: Particular requirements for tackers
- Part 2-17: Particular requirements for routers and trimmers
- Part 2-18: Particular requirements for strapping tools
- Part 2-19: Particular requirements for jointers
- Part 2-20: Particular requirements for band saws
- Part 2-21: Particular requirements for drain cleaners

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- 6 -

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

## iTeh STANDARD PREVIEW

IMPORTANT – The "colour inside" logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print(this/publication using a colour printer. https://standards.iteh.ai/catalog/standards/sist/0a29415a-d49a-4787-af37-

679d04a844ee/iec-60745-2-13-2006amd1-2009-csv

#### HAND-HELD MOTOR-OPERATED ELECTRIC TOOLS – SAFETY

#### Part 2-13: Particular requirements for chain saws

#### 1 Scope

This clause of Part 1 is applicable, except as follows:

#### Addition:

This standard applies to chain saws for cutting wood and designed for use by one person. This standard does not cover chain saws designed for use in conjunction with a guide-plate and riving knife or in any other way such as with a support or as a stationary or transportable machine.

This standard does not apply to chain saws for tree service as defined in ISO 11681-2, pole cutters and pruners.

### 2 Normative references STANDARD PREVIEW

This clause of Part 1 is applicable texcept as follows: eh.ai)

Addition:

IEC 60745-2-13:2006+AMD1:2009 CSV https://standards.iteh.ai/catalog/standards/sist/0a29415a-d49a-4787-af37-

ISO 3864-3<sup>1</sup>), Graphical symbols<sup>844</sup> Safety colours and safety signs – Part 3: Design criteria for graphical symbols used in safety signs

ISO 6533:2001, Forestry machinery – Portable chain-saw front hand-guard – Dimensions and clearances

ISO 6534:1992, Portable chain-saws – Hand-guards – Mechanical strength

ISO 7914:2002, Forestry machinery – Portable chain-saws – Minimum handle clearance and sizes

ISO 7915:1991, Forestry machinery – Portable chain-saws – Determination of handle strength

ISO 8334:1985, Forestry machinery – Portable chain-saws – Determination of balance

ISO 9518:1998, Forestry machinery – Portable chain-saws – Kickback test

ISO 10726:1992, Portable chain-saws – Chain catcher – Dimensions and mechanical strength

ISO 11681-2:1998, Machinery for forestry – Portable chain-saws – Safety requirements and testing – Part 2: Chain-saws for tree service

<sup>1)</sup> ISO 3864-3 is currently at the DIS stage.

#### 3 Terms and definitions

This clause of Part 1 is applicable, except as follows:

#### 3.101

#### chain saw

tool designed to cut wood with a saw chain and consisting of an integrated unit of handles, motor and cutting attachment, designed to be supported with two hands (see Figure 101)

- 8 -

#### 3.102

#### chain brake

device for stopping or locking the saw chain activated manually or non-manually when kickback occurs

#### 3.103

#### bar tip guard

shield that prevents contact with the saw chain at the tip of the guide bar, for reducing the incidence of kickbacks

#### 3.104

chain brake lever

device, usually the front hand guard, used to activate the chain brake

### iTeh STANDARD PREVIEW

#### 3.105 chain catcher

chain catcher device for restraining the saw chain if it breaks or degrooves (see Figure 101)

#### 3.106

IEC 60745-2-13:2006+AMD1:2009 CSV

https://standards.iteh.ai/catalog/standards/sist/0a29415a-d49a-4787-af37drive sprocket chain drive wheel with teeth<sup>79d04a844ee/iec-60745-2-13-2006amd1-2009-csv</sup>

#### 3.107

#### front handle

support handle located at or towards the front of the motor housing (see Figure 101)

#### 3.108

#### front hand quard

guard between the front handle and the saw chain for protecting the hand from injuries if the hand slips off the handle (see Figure 101)

#### 3.109

#### guide bar

part that supports and guides the saw chain (see Figure 101)

#### 3.110

#### kickback

rapid upward and/or backward motion of the chain saw which can occur when the moving saw chain near the tip of the guide bar contacts an object such as a log or branch

#### 3.111

#### rear hand quard

extension on the lower part of the rear handle for protecting the hand from the saw chain if it breaks or degrooves (see Figure 101)

#### 3.112

#### rear handle

support handle located on the housing or towards the rear of the motor housing (see Figure 101)

#### 3.113

#### saw chain

chain, serving as a cutting tool, consisting of drive links, cutters and side links, held together by rivets (see Figure 101)

#### 3.114

#### spiked bumper

device, fitted in front of the guide bar mounting point, acting as a pivot when in contact with a tree or log (see Figure 101 and Figure 102)

#### 3.115

#### cutting length

distance from the root of the spiked bumper, along the guide bar axis to the outside edge of the cutting link, or on the inside part of the bar tip guard with the chain tension adjuster set at mid- position (see Figure 102)

#### 3.116

#### run down time

elapsed time from the release of the mains switch until the saw chain stops

### 4 General requirements (standards.iteh.ai)

This clause of Part 1 is applicable.60745-2-13:2006+AMD1:2009 CSV

https://standards.iteh.ai/catalog/standards/sist/0a29415a-d49a-4787-af37-

679d04a844ee/iec-60745-2-13-2006amd1-2009-csv

#### 5 General conditions for the tests

This clause of Part 1 is applicable, except as follows:

#### **5.2** Addition:

For the tests of 19.113 one additional sample may be provided.

#### **5.14** Addition:

For tests carried out at normal load, the saw chain and the guide bar may be removed and the drive sprocket of the chain saw loaded by means of a brake.

#### 6 Void

#### 7 Classification

This clause of Part 1 is applicable.

#### 8 Marking and instructions

This clause of Part 1 is applicable, except as follows:

#### 8.1 Addition:

Chain saws shall be marked with the following:

- maximum length of the guide bar in mm;

- identification of the direction of rotation of the saw chain by a legible and durable mark.

In addition, chain saws shall be marked with safety recommendations and warnings of the following substance which shall be written in one of the official languages of the country in which the tool is to be sold.

- 10 -

-"Wear eye protection" or the sign M004 of ISO 7010<sup>2</sup>).

-"Wear ear protection" or the sign M003 of ISO 7010<sup>3)</sup>.

For chain saws with a degree of protection of less than IPX4:

- "Do not expose to rain" or the symbol specified in Annex AA.

For mains supplied tools:

- "Remove plug from the mains immediately if the cable is damaged or cut" or the symbol specified in Annex Weh STANDARD PREVIEW

If other symbols are used they shall be in accordance with ISO 3864-3.

- maximum length of the guide bar in mm;
- identification of the direction of rotation of the saw chain by a legible and durable mark.

In addition, chain saws shall be written in one of the official languages of the country in which the tool is to be sold:

- "Wear eye protection" or the sign M004 of ISO 7010 or the sign specified in Annex AA;
- "Wear ear protection" or the sign M003 of ISO 7010 or the sign specified in Annex AA.

A combination of symbols, such as eye, ear and head protection, is allowed.

For chain saws with a degree of protection of less than IPX4:

- "Do not expose to rain" or the symbol specified in Annex AA.

For mains supplied tools:

- "Remove plug from the mains immediately if the cable is damaged or cut" or the symbol specified in Annex AA.

If other symbols are used, they shall be in accordance with ISO 3864-3.

<sup>&</sup>lt;sup>2)</sup> The future safety sign M004 is currently at the DIS stage as ISO 7010:2003/DAmd6.

<sup>&</sup>lt;sup>3)</sup> The future safety sign M003 is currently at the DIS stage as ISO 7010:2003/DAmd5.

#### 60745-2-13 © IEC:2006+A1:2009 - 11 -

#### **8.12.1.1** *Addition:*

#### Chain saw safety warnings:

- Keep all parts of the body away from the saw chain when the chain saw is operating. Before you start the chain saw, make sure the saw chain is not contacting anything. A moment of inattention while operating chain saws may cause entanglement of your clothing or body with the saw chain.
- Always hold the chain saw with your right hand on the rear handle and your left hand on the front handle. Holding the chain saw with a reversed hand configuration increases the risk of personal injury and should never be done.

NOTE For chain saws designed with the guide bar on the left side, the reference to "right hand" and "left hand" positioning is reversed.

- Hold the power tool by insulated gripping surfaces only, because the saw chain may contact hidden wiring or its own cord. Saw chains contacting a "live" wire may make exposed metal parts of the power tool "live" and could give the operator an electric shock.
- Wear safety glasses and hearing protection. Further protective equipment for head, hands, legs and feet is recommended. Adequate protective clothing will reduce personal injury by flying debris or accidental contact with the saw chain.
- **Do not operate a chain saw in a tree.** Operation of a chain saw while up in a tree may result in personal injury.
- Always keep proper footing and operate the chain saw only when standing on fixed, secure and level surface. Slippery or unstable surfaces such as ladders may cause a loss of balance or control of the chain saw.
- When cutting a limb that is under tension be alert for spring back. When the tension in the wood fibres is released the spring loaded limb may strike the operator and/or throw the chain saw out of control.
- Use extreme caution when cutting brush and saplings. The slender material may catch the saw chain and be whipped toward you or pull you off balance.
- Carry the chain saw by the front handle with the chain saw switched off and away from your body. When transporting or storing the chain saw always fit the guide bar cover. Proper handling of the chain saw will reduce the likelihood of accidental contact with the moving saw chain.
- Follow instructions for lubricating, chain tensioning and changing accessories. Improperly tensioned or lubricated chain may either break or increase the chance for kickback.
- Keep handles dry, clean, and free from oil and grease. Greasy, oily handles are slippery causing loss of control.
- Cut wood only. Do not use chain saw for purposes not intended. For example: do not use chain saw for cutting plastic, masonry or non-wood building materials. Use of the chain saw for operations different than intended could result in a hazardous situation.

#### Causes and operator prevention of kickback:

Kickback may occur when the nose or tip of the guide bar touches an object, or when the wood closes in and pinches the saw chain in the cut.

Tip contact in some cases may cause a sudden reverse reaction, kicking the guide bar up and back towards the operator.

Pinching the saw chain along the top of the guide bar may push the guide bar rapidly back towards the operator.

Either of these reactions may cause you to lose control of the saw which could result in serious personal injury. Do not rely exclusively upon the safety devices built into your saw. As a chain saw user, you should take several steps to keep your cutting jobs free from accident or injury.

Kickback is the result of tool misuse and/or incorrect operating procedures or conditions and can be avoided by taking proper precautions as given below:

• Maintain a firm grip, with thumbs and fingers encircling the chain saw handles, with both hands on the saw and position your body and arm to allow you to resist kickback forces. Kickback forces can be controlled by the operator, if proper precautions are taken. Do not let go of the chain saw.

NOTE A possible illustration for this warning is given in Figure 103.

- **Do not overreach and do not cut above shoulder height.** This helps prevent unintended tip contact and enables better control of the chain saw in unexpected situations.
- Only use replacement bars and chains specified by the manufacturer. Incorrect replacement bars and chains may cause chain breakage and/or kickback.
- Follow the manufacturer's sharpening and maintenance instructions for the saw chain. Decreasing the depth gauge height can lead to increased kickback.
- 8.12.2 a) Addition:
  - 101) Explanation of the safety devices that the chain saw incorporates as part of the original equipment and/or other safety devices that are recommended in the instruction manual
  - 102) Instructions for properly installing and adjusting the guide bar and saw chain
  - 103) An explanation of the safety devices that the chain saw incorporates as part of the original equipment and/or other safety devices that are recommended in the instruction manual (Standards.tten.al)

### 8.12.2 b) Addition: IEC 60745-2-13:2006+AMD1:2009 CSV

https://standards.iteh.ai/catalog/standards/sist/0a29415a-d49a-4787-af37-

- 101) Recommendation/for/the/use of a residual/current/device with a tripping current of 30 mA or less
- 102) Statement to position the cord so that it will not be caught on branches and the like, during cutting
- 103) Recommendation that the first-time user should, as a minimum practice, cutting logs on a saw-horse or cradle
- 104) Instructions to explain the proper techniques for making the basic felling, limbing, and cross-cutting. Examples for the required instructions are given in Annex BB.1 to BB.5
- 105) If a manual oiler control is provided, instructions regarding its use

#### 9 **Protection against access to live parts**

This clause of Part 1 is applicable.

#### 10 Starting

This clause of Part 1 is applicable.

#### 11 Input and current

This clause of Part 1 is applicable.

#### 12 Heating

This clause of Part 1 is applicable, except as follows:

#### **12.4** *Replacement:*

The tool is operated at rated input or rated current for 30 min. The temperature rises are measured at the end of the 30 min.

#### 13 Leakage current

This clause of Part 1 is applicable.

#### **14 Moisture resistance**

This clause of Part 1 is applicable.

#### **15 Electric strength**

This clause of Part 1 is applicable.

# 16 Overload protection of transformers and associated circuits (standards.iteh.ai)

This clause of Part 1 is applicable.

IEC 60745-2-13:2006+AMD1:2009 CSV

**17 Endurance** https://standards.iteh.ai/catalog/standards/sist/0a29415a-d49a-4787-af37-679d04a844ee/iec-60745-2-13-2006amd1-2009-csv

This clause of Part 1 is applicable, except as follows:

#### **17.2** Addition:

The saw chain is removed for the endurance test.

#### **18** Abnormal operation

This clause of Part 1 is applicable.

#### **19 Mechanical hazards**

This clause of Part 1 is applicable, except as follows:

#### **19.1** Addition:

The requirements of this subclause do not apply to those moving parts and guards which are separately covered by 19.102, 19.103 and 19.104.

#### 19.101 Handles

Chain saws shall be fitted with at least two handles to provide safe control. The gripping length of the front handle shall be at least 100 mm.

The handle surfaces shall be so designed and shaped that firm grip may be applied.