

Edition 3.1 2024-05 CONSOLIDATED VERSION

# INTERNATIONAL STANDARD



Power cables with extruded insulation and their accessories for rated voltages from 1 kV ( $U_m = 1,2$  kV) up to 30 kV ( $U_m = 36$  kV) –

Part 2: Cables for rated voltages from 6 kV (U<sub>m</sub> = 7,2 kV) up to 30 kV (U<sub>m</sub> = 36 kV)

# Document Preview

IEC 60502-2:2014

https://standards.iteh.ai/catalog/standards/iec/822b961a-7509-42d8-907a-9fbbb79baad9/iec-60502-2-2014





### THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2024 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

**IEC Secretariat** 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch

www.iec.ch

# About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

### IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

#### IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

#### Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.



Edition 3.1 2024-05 CONSOLIDATED VERSION

# INTERNATIONAL STANDARD



Power cables with extruded insulation and their accessories for rated voltages from 1 kV ( $U_m = 1,2$  kV) up to 30 kV ( $U_m = 36$  kV) –

Part 2: Cables for rated voltages from 6 kV (U<sub>m</sub> = 7,2 kV) up to 30 kV (U<sub>m</sub> = 36 kV)

## Document Preview

IEC 60502-2:2014

https://standards.iteh.ai/catalog/standards/iec/822b961a-7509-42d8-907a-9fbbb79baad9/iec-60502-2-2014

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.060.20 ISBN 978-2-8322-9033-0

Warning! Make sure that you obtained this publication from an authorized distributor.

## CONTENTS

FOI	REWOR	RD		11			
1	Scope			13			
2	Normative references						
3	Terms and definitions						
	3.1	Definition	s of dimensional values (thicknesses, cross-sections, etc.)	15			
	3.2	Definition	s concerning the tests	16			
4	Voltag	e designatio	ns and materials	16			
	4.1	Rated vol	tages	16			
	4.2	Insulating	compounds	17			
	4.3	Sheathing	g compounds	18			
5	Condu	ctors		19			
6	Insulat	tion		19			
	6.1	Material .		19			
	6.2	Insulation	thickness	19			
7	Screer	ning		20			
	7.1	General		20			
	7.2	Conducto	r screen	20			
	7.3	Insulation	screen	20			
8	Assembly of three-core cables, inner coverings and fillers						
	8.1	General	nttns://standards.iteh.ai)	21			
	8.2		erings and fillers				
		8.2.1	Construction	21			
		8.2.2	Material	21			
		8.2.3	Thickness of extruded inner covering	21			
		8.2.4 atalo	Thickness of lapped inner covering	60502 <b>2</b> 1			
	8.3	Cables ha	aving a collective metal layer (see Clause 9)	22			
	8.4		aving a metal layer over each individual core (see Clause 10)				
9	Metal	layers for sir	ngle-core and three-core cables	22			
10	Metal screen						
	10.1	10.1 Construction					
	10.2	Requirem	ents	23			
	10.3	Metal scre	eens not associated with semi-conducting layers	23			
11	Conce	ntric conduc	tor	23			
	11.1	Construct	ion	23			
	11.2	Requirem	ents	23			
	11.3	Application	on	23			
12	Metal	Metal sheath					
	12.1	Lead shea	ath	23			
	12.2	Other me	tal sheaths	23			
13	Metal	armour		24			
	13.1	Types of	metal armour	24			
	13.2	Materials		24			
	13.3	Application	n of armour	24			
		13.3.1	Single-core cables	24			
		13.3.2	Three-core cables	24			

		13.3.3	Separation sheath	24
		13.3.4	Lapped bedding under armour for lead sheathed cables	25
	13.4	Dimensio	ons of the armour wires, <del>and</del> armour tapes and armour strips	25
	13.5	Correlation	on between cable diameters and armour dimensions	25
	13.6	Round or	flat wire armour	26
	13.7	Double ta	ape armour	26
	13.8	Interlock	metal tape armour	27
14	Oversh	eath		27
	14.1	General		27
	14.2			
	14.3	Thicknes	S	28
15	Test co	nditions		28
	15.1	Ambient t	temperature	28
	15.2		cy and waveform of power frequency test voltages	
	15.3	•	n of impulse test voltages	
	15.4		eation of the cable conductor temperature	
16				
10	16.1			
	16.1	_	I resistance of conductors	-
	16.2			
	16.4		scharge testestest	
	10.4	16.4.1	General	
		16.4.1	Test procedure for single-core cables	
		16.4.2	Test procedure for single-core cables  Test procedure for three-core cables	
		16.4.4	Test voltage	
		16.4.5	_	
	16.5		Requirement	
ps:/ <sub>17</sub> a			og/standards/iec/822b961a-7509-42d8-907a-9fbbb79baad9/iec-	
17	•			
	17.1			
	17.2	•	cy of sample tests	
		17.2.1	Conductor examination and check of dimensions	
	47.0	17.2.2	Electrical and physical tests	
	17.3	•	n of tests	
	17.4		or examination	31
	17.5		ment of thickness of insulation and of non-metal sheaths g extruded separation sheaths, but excluding inner extruded	
			s)	31
		17.5.1	General	
		17.5.2	Requirements for the insulation	
		17.5.3	Requirements for the non-metal sheaths	
	17.6		ment of thickness of lead sheath	
	-	17.6.1	General	
		17.6.2	Strip method	
		17.6.3	Ring method	
	17.7		ment of armour wires, <del>-and</del> tapes and armour strips	
		17.7.1	Measurement on wires	
		17.7.2	Measurement on tapes and armour strips	
		17.7.3	Requirements	
			,	

טוע	1.4	UZ	4	$\mathbf{C}$	J V	
	ര	ıΕα	` '	วก	24	ĺ

	17.8	Measurement of external diameter			
	17.9	Voltage test for 4 h			
		17.9.1	Sampling	33	
		17.9.2	Procedure	33	
		17.9.3	Test voltages	33	
		17.9.4	Requirements	34	
	17.10		est for EPR, HEPR and XLPE insulations and elastomeric		
		17.10.1	Procedure		
		17.10.2	Requirements		
4.0	17.11	_	est on interlock armour cable followed by examination		
18	Type te		cal		
	18.1				
	18.2	Cables ha	aving conductor screens and insulation screens		
		18.2.1	General		
		18.2.2	Sequence of tests		
		18.2.3	Special provisions		
		18.2.4	Bending test		
		18.2.5	Partial discharge test	36	
		18.2.6	Tan $\delta$ measurement for cables of rated voltage 6/10 (12) kV		
		400 =	and above		
		18.2.7	Heating cycle test		
		18.2.8	Impulse test followed by a voltage test	37	
		18.2.9	Voltage test for 4 h		
		18.2.10	Resistivity of semi-conducting screens		
	18.3		rated voltage 3,6/6 (7,2) kV having unscreened insulation		
		18.3.1	General		
			Insulation resistance measurement at ambient temperature	38 1502-2	
		18.3.3	Insulation resistance measurement at maximum conductor temperature	30	
		18.3.4	Voltage test for 4 h		
		18.3.5	Impulse test		
19	Tyne te		ectrical		
13	• •				
	19.1 19.2		nent of thickness of insulation		
	19.2				
		19.2.1 19.2.2	Sampling Procedure		
		19.2.2	Requirements		
	19.3		nent of thickness of non-metal sheaths (including extruded	40	
	19.3		n sheaths, but excluding inner coverings)	40	
		19.3.1	Sampling		
		19.3.2	Procedure		
		19.3.3	Requirements		
	19.4		nent of thickness of lead sheath		
		19.4.1	Sampling		
		19.4.2	Procedure		
		19.4.3	Requirements		
	19.5		determining the mechanical properties of insulation before and		
		after agei		40	

•	00002	-2.20	1 T · / \liviD	1.2027	000	
	$\sim 202$	1				

	19.5.1	Sampling	40
	19.5.2	Ageing treatments	41
	19.5.3	Conditioning and mechanical tests	41
	19.5.4	Requirements	41
19.6		determining the mechanical properties of non-metal sheaths	
		d after ageing	
	19.6.1	Sampling	
	19.6.2	Ageing treatments	
	19.6.3	Conditioning and mechanical tests	
	19.6.4	Requirements	
19.7		ageing test on pieces of completed cables	
	19.7.1	General	
	19.7.2	Sampling	
	19.7.3	Ageing treatment	
	19.7.4	Mechanical tests	
	19.7.5	Requirements	
19.8		ass test on PVC sheaths of type ST <sub>2</sub>	
	19.8.1	Procedure	
	19.8.2	Requirements	
19.9		est at high temperature on insulations and non-metal sheaths	
	19.9.1	Procedure	42
	19.9.2	Requirements	42
19.10		VC insulation, and PVC sheaths and halogen free sheaths at ratures	42
	19.10.1	Procedure	42
	19.10.2	Requirements	42
19.11		sistance of PVC insulation and sheaths to cracking (heat shock IEC 60502-2:2014	42
	19.11.11	Procedure / lec/822b961a-7509-42d8-907a-9fbbb79baad9/iec-605	0.42
	19.11.2	Requirements	42
19.12	Ozone res	istance test for EPR and HEPR insulations	43
	19.12.1	Procedure	43
	19.12.2	Requirements	43
19.13		st for EPR, HEPR and XLPE insulations and elastomeric	40
19.14		sion test for elastomeric sheaths	
19.14	19.14.1	Procedure	
	19.14.1	Requirements	
19.15		orption test on insulation	
19.13	19.15.1	Procedure	
	19.15.1	Requirements	
<del>19.16</del>		ead test on single cables	
19.16	•	r fire conditions	
19.10	19.16.1	General	
	19.16.1	Flame spread test for single cables	
	19.16.2	Flame spread test for bunched cables	
	19.16.4	Measurement of smoke density of cables burning under	+4
	13.10.4	defined conditions	44

		19.16.5	Determination of acidity (by pH measurement) and	
			conductivity of gases evolved during combustion of the non-	4.4
		10 10 0	metallic materials in the cable	44
		19.16.6	Fire performance tests on halogen free oversheath material ST <sub>8</sub>	44
		19.16.7	Fire performance tests on halogen free oversheath material	
			ST <sub>12</sub>	45
		19.16.8	Measurement of halogen content of gases evolved during	
			combustion of the non-metallic materials in the cable	
	19.17		nent of carbon black content of black PE oversheaths	45
		19.17.1	Procedure	
		19.17.2	Requirements	
	19.18	Shrinkage	test for XLPE insulation	
		19.18.1	Procedure	46
		19.18.2	Requirements	46
	19.19	Thermal s	tability test for PVC insulation	46
		19.19.1	Procedure	46
		19.19.2	Requirements	46
	19.20	Determina	tion of hardness of HEPR insulation	46
		19.20.1	Procedure	46
		19.20.2	Requirements	46
	19.21	Determina	ition of the elastic modulus of HEPR insulation	46
		19.21.1	Procedure	46
		19.21.2	Requirements	46
	19.22	Shrinkage	test for PE and halogen free oversheaths	46
		19.22.1	Procedure	46
		19.22.2	Requirements	46
	19.23	Strippabili	ty test for insulation screen	47
		19.23.1	General	47_
		19.23.2	Procedure	47
		19.23.3	Requirements	47
	19.24	Water pen	etration test	47
	19.25		tests on halogen free oversheath of type ST <sub>8</sub>	
		19.25.1	General	
		19.25.2	Water absorption test for halogen free oversheath of type ST <sub>8</sub>	48
		19.25.3	Abrasion test on halogen free oversheath of type ST <sub>8</sub>	
	19.26	Bending to	est on interlock armour	
20	Electrica	_	er installation	
	20.1	General		48
	20.2		e test of the oversheath	
	20.2	_	test AC voltage test of the insulation	
Δnn			ctitious calculation method for determination of dimensions of	40
				58
•	A.1	•		
	A.2			
	, <u>.</u>	A.2.1	Conductors	
		A.2.2	Cores	
		A.2.3	Diameter over laid-up cores	
		A.2.4	Inner coverings	
		A.2.5	Concentric conductors and metal screens	
		, \ U	Consolitio conductors and motal solection	00

	A.2.6	Lead sheath	61
	A.2.7	Separation sheath	61
	A.2.8	Lapped bedding	61
	A.2.9	Additional bedding for tape-armoured cables (provided over the inner covering)	62
	A.2.10	Armour	
		Tabulated continuous current ratings for cables having extruded voltage from 3,6/6 kV up to 18/30 kV	
B.1			
B.2	_	nstructions	
B.3		tures	
B.4	•	mal resistivity	
B.5		of installation	
2.0	B.5.1	General	
	B.5.2	Single-core cables in air	
	B.5.3	Single-core cables buried direct	
	B.5.4	Single-core cables in earthenware ducts	
	B.5.5	Three-core cables	
B.6		onding	
B.7		ading	
B.8	Rating fa	actors for grouped circuits	66
B.9	Correction	on factors	66
	rmativa	Rounding of numbers	82
C.1	_	g of numbers for the purpose of the fictitious calculation method	
C.2	-	g of numbers for other purposes	
•	-	Method of measuring resistivity of semi-conducting screens	
•	,	Determination of hardness of HEPR insulations	
	•	<b>e</b> y/standards/iec/822b961a.7509.42d8.907a.9fbbb79baad9/iec.60	
E.2	•	cedure	
	E.2.1	General	
	E.2.2	<u> </u>	
	E.2.3	Surfaces of small radius of curvature	
	E.2.4	Conditioning and test temperature	86
	E.2.5	Number of measurements	
Annex F (no	rmative) V	Nater penetration test	88
F.1	Test piec	e	88
F.2	Test		88
F.3	Requirem	nents	89
Annex G (in	formative)	Determination of the cable conductor temperature	90
G.1	Purpose.		90
G.2	•	on of the temperature of the main test loop	
	G.2.1	General	
	G.2.2	Installation of cable and temperature sensors	
	G.2.3	Calibration method	
G.3		for the test	
3.0	G.3.1	Method 1 – Test using a reference cable	
	G.3.2	Method 2 – Test using conductor temperature calculations	03

Annex H (	normative) Test for water penetration in the conductor	95
H.1	General	95
H.2	Test piece	95
H.3	Test	95
H.4	Requirements	95
	ormative) Methods of determining the weighted value of halogen content of etallic materials in the cable	97
I.1	Calculating the weighted value of the cable when the halogen content of individual materials is tested	97
1.2	Preparation of the test sample for measurement of halogen content on a sample representative of the non-metallic materials in the cable	97
Bibliograp	ny	98
Figure B.1	- Single-core cables in air	64
Figure B.2	- Single-core cables buried direct	65
Figure B.3	- Single-core cables in earthenware ducts	65
Figure B.4	- Three-core cables	66
Figure D.1	Preparation of samples for measurement of resistivity of conductor and screens	
	- Test on surfaces of large radius of curvature	
_	- Test on surfaces of small radius of curvature	
	- Schematic diagram of apparatus for water penetration test	
•	Typical test set-up for the reference loop and the main test loop	
Figure G.2	= Example of an arrangement of the temperature sensors on the conductor rence loop	
	<ul> <li>Schematic diagram of apparatus for water penetration test in the</li> </ul>	
	1EC 60502-2:2014 .iteh.ai/catalog/standards/lec/822b961a-7509-42d8-907a-91bbb79baad9/lec-60	96
Table 1 –	Recommended rated voltages <i>U</i> <sub>0</sub>	17
Table 2 –	Insulating compounds	17
Table 3 –	Maximum conductor temperatures for different types of insulating compound	18
Table 4 –	Maximum conductor temperatures for different types of sheathing compound.	18
Table 5 –	Nominal thickness of PVC/B insulation	19
Table 6 –	Nominal thickness of cross-linked polyethylene (XLPE) insulation	19
	Nominal thickness of ethylene propylene rubber (EPR) and hard ethylene rubber (HEPR) insulation	20
	Thickness of extruded inner covering	
	Nominal diameter of round armour wires	
	Nominal thickness of armour tapes	
	Nominal thickness of armour strips	
	Routine test voltages	
	Number of samples for sample tests	
	Sample test voltages	
	Impulse voltages	
	Electrical type test requirements for insulating compounds	
1 4 5 6 1 9 -	· Libutival typo tost ioquiloilioitis ivi ilisulatilly tullipuullus	+♡
	Non-electrical type tests (see Table 17 to Table 23 and Table 25)	

Table 17 – Test requirements for mechanical characteristics of insulating compounds (before and after ageing)	51
Table 18 – Test requirements for particular characteristics for PVC insulating compound	52
Table 19 – Test requirements for particular characteristics of various crosslinked insulating compounds	53
Table 20 – Test requirements for mechanical characteristics of sheathing compounds (before and after ageing)	54
Table 21 – Test requirements for particular characteristics for PVC sheathing compounds	54
Table 22 – Test requirements for particular characteristics of PE (thermoplastic polyethylene) sheathing compounds	55
Table 23 – Test requirements for particular characteristics of elastomeric sheathing compound	55
Table 25 – Test requirements for particular characteristics of halogen free sheathing compounds	56
Table A.1 – Fictitious diameter of conductor	59
Table A.2 – Increase of diameter for concentric conductors and metal screens	60
Table A.3 – Increase of diameter for additional bedding	62
Table A.4 – Increase of diameter over interlocked armour	62
Table B.1 – Nominal screen cross-sectional areas	63
Table B.2 – Current ratings for single-core cables with XLPE insulation – Rated voltage 3,6/6 kV to 18/30 kV * – Copper conductor	67
Table B.3 – Current ratings for single-core cables with XLPE insulation – Rated voltage 3,6/6 kV to 18/30 kV * – Aluminium conductor	68
Table B.4 – Current ratings for single-core cables with EPR insulation – Rated voltage 3,6/6 kV to 18/30 kV * – Copper conductor	69
Table B.5 – Current ratings for single-core cables with EPR insulation – Rated voltage 3,6/6 kV to 18/30 kV * – Aluminium conductor	02 <u>-2</u> 70
Table B.6 – Current rating for three-core XLPE insulated cables – Rated voltage 3,6/6 kV to 18/30 kV * – Copper conductor, armoured and unarmoured	71
Table B.7 – Current rating for three-core XLPE insulated cables – Rated voltage 3,6/6 kV to 18/30 kV * – Aluminium conductor, armoured and unarmoured	72
Table B.8 – Current rating for three-core EPR insulated cables – Rated voltage 3,6/6 kV to 18/30 kV * – Copper conductor, armoured and unarmoured	73
Table B.9 – Current rating for three-core EPR insulated cables – Rated voltage 3,6/6 kV to 18/30 kV * – Aluminium conductor, armoured and unarmoured	74
Table B.10 – Correction factors for ambient air temperatures other than 30 °C	74
Table B.11 – Correction factors for ambient ground temperatures other than 20 °C	75
Table B.12 – Correction factors for depths of laying other than 0,8 m for direct buried cables	75
Table B.13 – Correction factors for depths of laying other than 0,8 m for cables in ducts	75
Table B.14 – Correction factors for soil thermal resistivities other than 1,5 K⋅m/W for direct buried single-core cables	76
Table B.15 – Correction factors for soil thermal resistivities other than 1,5 K⋅m/W single-core cables in buried ducts	76
Table B.16 – Correction factors for soil thermal resistivities other than 1,5 K·m/W for direct buried three-core cables	77

Table B.17 – Correction factors for soil thermal resistivities other than 1,5 K·m/W for three-core cables in ducts	77
Table B.18 – Correction factors for groups of three-core cables in horizontal formation laid direct in the ground	78
Table B.19 – Correction factors for groups of three-phase circuits of single-core cables laid direct in the ground	78
Table B.20 – Correction factors for groups of three-core cables in single way ducts in horizontal formation	79
Table B.21 – Correction factors for groups of three-phase circuits of single-core cables in single-way ducts	79
Table B.22 – Reduction factors for groups of more than one multi-core cable in air – To be applied to the current-carrying capacity for one multi-core cable in free air	80
Table B.23 – Reduction factors for groups of more than one circuit of single-core cables (Note 2) – To be applied to the current-carrying capacity for one circuit of single-core cables in free air	81

# iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 60502-2:2014

https://standards.iteh.ai/catalog/standards/iec/822b961a-7509-42d8-907a-9fbbb79baad9/iec-60502-2-2014

### INTERNATIONAL ELECTROTECHNICAL COMMISSION

POWER CABLES WITH EXTRUDED INSULATION AND THEIR ACCESSORIES FOR RATED VOLTAGES FROM 1 kV ( $U_{\rm m}$  = 1,2 kV) UP TO 30 kV ( $U_{\rm m}$  = 36 kV) –

Part 2: Cables for rated voltages from 6 kV  $(U_m = 7.2 \text{ kV})$  up to 30 kV  $(U_m = 36 \text{ kV})$ 

#### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 60502-2 edition 3.1 contains the third edition (2014-02) [documents 20/1469A/FDIS and 20/1472/RVD] and its amendment 1 (2024-05) [documents 20/2166/FDIS and 20/2181/RVD].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough

red text. A separate Final version with all changes accepted is available in this publication.

International Standard IEC 60502-2 has been prepared by IEC technical committee 20: Electric cables.

This third edition cancels and replaces the second edition, published in 2005, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) a simplified calculation procedure for the thickness of the lead sheath and the oversheath;
- b) a new subclause for the determination of the cable conductor temperature;
- c) a modified procedure for the routine voltage test;
- d) a new subclause for a routine electrical test on oversheath;
- e) modified requirements for the non-metal sheaths including semi-conductive layer;
- f) modified tolerances for the bending test cylinder;
- g) the inclusion of a 0,1Hz test after installation.

In addition, the modified structure of the IEC 60811 series has been adopted for this third edition.

The following editorial changes have been made within the English version:

- 'metallic' has been replaced by 'metal';
- 'thermosetting' has been replaced by 'crosslinked'.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 60502 series, published under the general title Power cables with extruded insulation and their accessories for rated voltages from 1kV ( $U_{\rm m}$  = 1,2 kV) up to 30 kV ( $U_{\rm m}$  = 36 kV), can be found on the IEC website.

The committee has decided that the contents of this document and its amendment will remain unchanged until the stability date indicated on the IEC website under <a href="webstore.iec.ch">webstore.iec.ch</a> in the data related to the specific document. At this date, the document will be

- reconfirmed,
- · withdrawn, or
- revised.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.