

# INTERNATIONAL STANDARD

# IEC 60245-3

1994

AMENDMENT 1  
1997-06

---

---

Amendment 1

**Rubber insulated cables –  
Rated voltages up to and including 450/750 V –**

**Part 3:  
Heat resistant silicone insulated cables**

(<https://standards.iteh.ai>)  
Document Preview

[IEC 60245-3:1994/AMD1:1997](https://standards.iteh.ai/catalog/standards/iec/cb773b52-1aae-4ddd-8a2f-e7c83f28a73f/iec-60245-3-1994-amd1-1997)

<https://standards.iteh.ai/catalog/standards/iec/cb773b52-1aae-4ddd-8a2f-e7c83f28a73f/iec-60245-3-1994-amd1-1997>

*This **English-language** version is derived from the original **bilingual** publication by leaving out all French-language pages. Missing page numbers correspond to the French-language pages.*

© IEC 1997 Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland  
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: [inmail@iec.ch](mailto:inmail@iec.ch) Web: [www.iec.ch](http://www.iec.ch)



Commission Electrotechnique Internationale  
International Electrotechnical Commission  
Международная Электротехническая Комиссия

## FOREWORD

This amendment has been prepared by subcommittee 20B: Low-voltage cables, of IEC technical committee 20: Electric cables.

The text of this amendment is based on the following documents:

FDIS	Report on voting
20B/229/FDIS	20B/244/RVD

Full information on the voting for the approval of this amendment can be found in the report on voting indicated in the above table.

Page 11

Table 1 – Dimensions of type 245 IEC 03

Replace the existing table 1 by the following new table 1:

**Table 1 - Dimensions of type 245 IEC 03**

1 Nominal cross-sectional area of conductors mm <sup>2</sup>	2 Thickness of insulation Specified value mm	3 Mean overall diameter		4
		Lower limit mm	Upper limit mm	
0,5	0,6	2,6	3,3	
0,75	0,6	2,8	3,5	
1	0,6	2,9	3,7	
1,5	0,7	3,4	4,2	
2,5	0,8	4,0	5,0	
4	0,8	4,5	5,6	
6	0,8	5,0	6,2	
10	1,0	6,2	7,8	
16	1,0	7,3	9,1	