

# INTERNATIONAL STANDARD

# ISO/IEC 11160-1

First edition  
1996-08-01

---

---

## Information technology — Office equipment — Minimum information to be included in specification sheets —

### Printers —

#### (Part 1:

#### Class 1 and Class 2 printers

ISO/IEC 11160-1:1996

<https://standards.iteh.ai/catalog/standards/sist/ef1f0c0e-3235-4069-8ab2-172280132006>

Technologies de l'information — Équipements de bureau — Information  
minimale devant figurer dans les notices techniques — Imprimantes —

Partie 1: Imprimantes classe 1 et classe 2



Reference number  
ISO/IEC 11160-1:1996(E)

## Contents

1 Scope	1
2 Normative references	1
3 Conformance	1
4 Test and measurement conditions	1
5 Information to be included in the specification sheets	2
Annex A - Classification of printers - Class 1 and Class 2	11
Annex B - Classification of printers - Class 3 and Class 4	13
Annex C - Bibliography	15

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 11160-1:1996](https://standards.iteh.ai/catalog/standards/sist/ef1f0c0e-3235-4069-8ab2-12325e942e5a/iso-iec-11160-1-1996)  
<https://standards.iteh.ai/catalog/standards/sist/ef1f0c0e-3235-4069-8ab2-12325e942e5a/iso-iec-11160-1-1996>

© ISO/IEC 1996

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office \* Case Postale 56 \* CH-1211 Genève 20 \* Switzerland  
Printed in Switzerland

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrical Commission) form the specialised system for worldwide standardisation. National Bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organisation to deal with particular fields of mutual interest. Other international organisations, governmental and non-governmental, in liaison with ISO and IEC, also take part to the work.

In the field of information technology, ISO and IEC have established a joint technical committee ISO/IEC JTC1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75% of the national bodies casting a vote.

International Standard ISO/IEC 11160-1, was prepared by Joint Technical Committee ISO/IEC JTC1, *Information technology*, Subcommittee SC28, *Office equipment*.

ISO/IEC 1160 consists of the following parts, under the general title *Information technology - Office equipment - Minimum information to be included in specification sheets - Printers*:

- *Part 1: Class 1 and Class 2 printers*
- *Part 2: Class 3 and Class 4 printers*

Annex A forms an integral part of this part of ISO/IEC 11160. Annexes B and C are for information only.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO/IEC 11160-1:1996  
<https://standards.iteh.ai/catalog/standards/sist/ef1f0c0e-3235-4069-8ab2-12325e942e5a/iso-iec-11160-1-1996>

## Introduction

Printers of many different types and capacities are now available and their specifications vary so widely that it is difficult for potential users to assess which machine might best meet their requirements.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 11160-1:1996](https://standards.iteh.ai/catalog/standards/sist/ef1f0c0e-3235-4069-8ab2-12325e942e5a/iso-iec-11160-1-1996)

<https://standards.iteh.ai/catalog/standards/sist/ef1f0c0e-3235-4069-8ab2-12325e942e5a/iso-iec-11160-1-1996>

**Information technology - Office equipment - Minimum information to be included in specification sheets - Printers -****Part 1: Class 1 and Class 2 printers****1 Scope**

This part of ISO/IEC 11160 specifies the minimum information that is to be included in the specification sheets of printers so that users may compare the characteristics of different machines and select a printer which meets their requirements.

It applies to printers that could be operated in an office environment. Printers requiring specially equipped rooms or specially instructed operators are not within the scope of this part of ISO/IEC 11160.

ISO/IEC 11160 will cover different classes of printers. This part covers Class 1 and Class 2 printers, as defined in annex A.

**2 Normative references**

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO/IEC 11160. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO/IEC 11160 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 216:1975 <sup>1)</sup> ,	<i>Writing paper and certain classes of printed matter - Trimmed sizes - A and B series.</i>
ISO 269:1985,	<i>Correspondence envelopes - Designation and sizes.</i>
ISO 7779:1988 <sup>1)</sup> ,	<i>Acoustics - Measurement of airborne noise emitted by computer and business equipment.</i>
ISO 9295:1988,	<i>Acoustics - Measurement of high-frequency noise emitted by computer and business equipment.</i>
ISO 9296:1988,	<i>Acoustics - Declared noise emission values of computer and business equipment.</i>
ISO/IEC 10561:1991 <sup>1)</sup> ,	<i>Information technology - Printing devices - Method for measuring printer throughput.</i>
IEC 950:1991,	<i>Safety of information technology equipment, including electrical business equipment.</i>

**3 Conformance**

In order to comply with this part of ISO/IEC 11160, specification sheets shall contain, in the order shown, all items listed in clause 5 which are relevant to the machine being described.

**4 Test and measurement conditions**

Unless otherwise specified, all tests and measurements shall be conducted at the following conditions:

- Temperature: 18 °C to 25 °C
- Relative humidity: 30 % to 70 %
- Line voltage: rated input voltage
- Line frequency: rated frequency
- Paper size: A4
- Paper weight: 60 g/m<sup>2</sup> to 90 g/m<sup>2</sup>
- Paper transport direction: standard direction

<sup>1)</sup> Currently under revision

– Test pattern: as specified

Instead of A4 paper size, the size most commonly used in the country may be used, both for the test page and the copies. This shall be indicated in the specification sheet.

When weight of paper (g/m<sup>2</sup>) is given, it is assumed that the paper has been conditioned in the standard atmosphere defined in ISO 3066 (temperature 20 °C ± 2 °C; relative humidity 60 % to 70 %).

## 5 Information to be included in the specification sheets

Table 1 defines, for each parameter, the number and name of the parameter and a short description of the entry. These constitute the information to be included in the specification sheet.

The heading of the specification sheet shall indicate that it has been prepared in accordance with this part of ISO/IEC 11160. The numbers and headings of table 1 shall be used. Parameters which are not applicable may be ignored; the number of the other parameters shall remain unchanged.

The "Remarks and examples" column is provided to help prepare the information sheet, and is not intended to appear in the specification sheet. It is intended to be informative. Test methods to be applied, when not defined in other International Standards, are defined in this column.

Whenever a capacity is given in sheets, the reference paper weight shall be specified.

**Table 1 - Information to be included**

Parameter	Description of the entry	Remarks and examples
<b>1 General data</b>		
<b>1.1 Printer class</b>	Class 1 or Class 2 printer.	See annex A for description of classes.
<b>1.2 Machine name, model and/or model number</b>	Product name, model number.	
<b>1.3 Type</b>		State if the machine is desk-top, portable or floor-standing.
<b>1.4 Printing method</b>	The printing process used.	Non-impact: ink-jet, thermal transfer. Impact: daisy wheel, dot matrix.
<b>1.5 Dot density</b>	Horizontal and vertical dots per 25,4 mm. The design capability of the machine to place the dots.	Note that the theoretical writing resolution and the actual printing resolution may be different. If the dot positioning capability is adjustable, indicate the minimum and maximum capabilities.
<b>1.6 Colour printing</b>		
<b>1.6.1 Monochrome</b>	Specify which colour.	

Table 1 (cont'd)

Parameter	Description of the entry	Remarks and examples
<b>1.6.2 Multi-colour</b>	Available/not available.	Also known as functional colour, spot colour, highlight or accent colour. State the number of discrete colours that can be printed by colorants residing in the machine.
<b>1.6.3 Full colour</b>	Available/not available.	The full colour is often described as YELLOW, MAGENTA, CYAN or YELLOW, MAGENTA, CYAN, BLACK. State if the machine can print full colour, continuous tone, half-tone or both. Applicable to class 2 printers only
<b>1.6.4 Colour transparencies</b>	Available/not available.	Indicate if the colour can be projected.
<b>2 Performance data</b>		
<b>2.1 Printer throughput</b>	Monochrome pages per hour (PPH) according to ISO 10561, colour pages per hour.	Specify if monochrome, colour or both rates are listed.
<b>2.2 Recommended monthly print volume</b>	Manufacturers recommended range of use: number of pages per month.	For the determination of this parameter, the month is considered consisting of 20 days of 8 hours each.
<b>3 Control</b>		
<b>3.1 Interface for hardware connection</b>	State the hardware connector used.	Centronics, RS232, others.
<b>3.2 Interface for connection control</b>	Identify communication protocols.	XON/XOFF.
<b>3.3 Interface for printer control</b>	Identify printer control languages, including version.	ISO 10180, ISO 6429, ISO 646.

Table 1 (cont'd)

Parameter	Description of the entry	Remarks and examples
<b>3.3 Memory</b>		
<b>3.3.1 Input buffer</b>	Size in kilobytes.	
<b>3.3.2 Font memory</b>	Size in kilobytes.	Optional memory that can be added to support additional fonts or font processing.
<b>4 Printing features</b>		
<b>4.1 Printing margins</b>	In millimetres, from the top, bottom, left and right edges of the paper.	Area in which printing is not possible. (This area is given on the condition that the print paper is fed through its ideal position). If the printing margins vary with paper sizes, this situation should be described.
<b>4.2 Printed image orientation</b>	Portrait and/or landscape.	The capability of the printer to print in portrait and landscape orientation without changing the paper feed direction.
<b>5 Fonts and character sets</b>	Specify external cartridges or downloadable fonts applicable to this class of printers.	The capabilities of the basic machine and the capabilities that can be added by additional print elements (external cartridges, external print elements, downloaded fonts) shall be clearly identified.
<b>5.1 Basic capability</b>	List character sets and fonts supplied with the printer in basic configuration.	Indicate types of fonts (Times, Helvetica, OCR-A (ISO 1073-1), OCR-B (ISO 1073-2), others); supported orientation of fonts (portrait, landscape); support for bit-mapped and scaleable fonts per ISO 9541.



Table 1 (cont'd)

Parameter	Description of the entry	Remarks and examples
<b>5.2 Optional capability</b>	List optional character sets and fonts available from suppliers.	Indicate additional types of fonts (Times, Helvetica, OCR-A (ISO 1073-1), OCR-B (ISO 1073-2), others); supported orientation of fonts (portrait, landscape); support for bit-mapped and scaleable fonts per ISO 9541. Obtained via external cartridges, downloaded fonts, etc.
<b>5.3 Coded character set</b>	List the number of the International Standard or the registration number.	ISO 6937, ISO 10646, ISO 8859 1-10, ISO/IEC 10367.
<b>5.4 Character set</b>	List character sets or glyph collections available.	ISO 10036.
<b>5.5 Rendition appearance</b>	Indicate which	Normal, italic, bold, bold italic.
<b>5.6 Inter-character spacing</b>	Indicate character spacing method and maximum and minimum spacing.	Fixed pitch (10 characters per 25,4 mm), proportional spacing.
<b>5.7 Inter-line spacing</b>	Indicate line spacing method and maximum and minimum spacing.	Fixed spacing (6,8 lines per 25,4 mm), proportional spacing.
<b>6 Output material</b>		
<b>6.1 Paper type</b>		Plain, coated, thermal paper. The manufacturer shall specify for which characteristics of the paper, other than normal paper, normal warranted performance can be assured.
<b>6.2 Special material</b>		The manufacturer shall specify the printing materials that can be processed, possibly with degraded performances, e.g. Transparent sheets, labels, envelopes and recycled paper.

Table 1 (cont'd)

Parameter	Description of the entry	Remarks and examples
<b>6.3 Multi-part forms</b>	Available/not available.	1 + $n$ . Indicate the maximum number of copies ( $n$ ) and carbons (if applicable). Also indicate the maximum weight of all parts ( $1+n$ ). Indicate if the print head force is adjustable.
<b>6.4 Paper size</b>	State the minimum and maximum width and the minimum and maximum length of the paper. This indication can be given either in millimetres or by quoting standard paper sizes.	
<b>6.4.1 Paper in sheets</b>	Available/not available. Standard name and/or sizes of paper in millimetres.	A sizes (ISO 216), B sizes (ISO 216), North American sizes.
<b>6.4.2 Paper in continuous forms (roll or fanfold)</b>	Available/not available. Width, maximum and minimum in millimetres; length in meters; diameter of the roll, in millimetres.	Indicate if length is manually pre-selectable (maximum and minimum); and if the paper is cut automatically.
<b>6.4.3 Envelopes</b>	State minimum and maximum sizes of envelopes that can be printed.	Sizes according to ISO 269.
<b>6.5 Paper weight</b>	Minimum and maximum in $\text{g/m}^2$ .	Specify if for sheet or roll.
<b>7 Paper handling</b>		
<b>7.1 Paper supply device</b>	Manual, cassette, tray.	Indicate which are standard and which are optional.
<b>7.2 Paper supply capacity</b>	For roll paper supply: diameter of the roll. For cut sheets paper supply: number of sheets for each paper supply device.	

Table 1 (cont'd)

Parameter	Description of the entry	Remarks and examples
<b>7.3 Paper feed orientation</b>	Long edge feed or short edge feed.	Indicate the paper size.
<b>8 Output handling</b>		Indicate any special function.
<b>9 Physical characteristics</b>		
<b>9.1 Dimensions</b>	Width x depth x height (all expressed in centimetres or millimetres).	Indicate if it is the envelope around or if trays, knobs or other are not included.
<b>9.2 Space required - operation</b>	Width x depth (both expressed in centimetres or millimetres).	Varies with options. This parameter includes space for operator functions such as paper handling and jam removal. Indicate if it is with or without accessories.
<b>9.3 Space required - maintenance</b>	Width x depth (both expressed in centimetres or millimetres).	Varies with options. This parameter includes space for access to all service areas and the use of required tools. Indicate if it is with or without accessories.
<b>9.4 Weight</b>	Installed weight in kilograms.	Indicate if it is with or without accessories.
<b>10 Operating environment</b>	Minimum and maximum ambient temperature, and range of relative humidity.	This indication is intended to give the user a guide to the expected machine operating environment.
<b>11 Power source</b>	Power rating plate in accordance with IEC 950.	
<b>11.1 Rated voltage or voltage range</b>	Expressed in volts.	Indicate if AC or DC. For AC power: indicate the number of phases. For DC power: indicate if built-in battery. Indicate tolerances.
<b>11.2 Rated frequency or frequency range</b>	Expressed in hertz.	For AC power only. Indicate tolerance.