

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Fixed capacitors for use in electronic equipment –
Part 23: Sectional specification – Fixed metallized polyethylene naphthalate film
dielectric surface mount d.c. capacitors**

**Condensateurs fixes utilisés dans les équipements électroniques –
Partie 23: Spécification intermédiaire – Condensateurs fixes pour montage en
surface pour courant continu à diélectrique en film de polynaphtalate d'éthylène
métallisé**



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2015 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 15 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

Plus de 60 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Fixed capacitors for use in electronic equipment –
Part 23: Sectional specification – Fixed metallized polyethylene naphthalate film
dielectric surface mount d.c. capacitors**

**Condensateurs fixes utilisés dans les équipements électroniques –
Partie 23: Spécification intermédiaire – Condensateurs fixes pour montage en
surface pour courant continu à diélectrique en film de polynaphtalate d'éthylène
métallisé**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 31.060.10

ISBN 978-2-8322-2647-6

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD	5
1 General	7
1.1 Scope	7
1.2 Object	7
1.3 Normative references	7
1.4 Information to be given in a detail specification	7
1.4.1 General	7
1.4.2 Outline drawing and dimensions	8
1.4.3 Mounting	8
1.4.4 Ratings and characteristics	8
1.4.5 Marking	9
1.5 Terms and definitions	9
1.6 Marking	9
1.6.1 General	9
1.6.2 Information for marking	9
1.6.3 Marking of capacitors	9
1.6.4 Marking on packaging	10
2 Preferred ratings and characteristics	10
2.1 Preferred characteristics	10
2.1.1 Preferred climatic categories	10
2.2 Preferred values of ratings	10
2.2.1 Nominal capacitance (C_N)	10
2.2.2 Tolerance on nominal capacitance	10
2.2.3 Rated voltage (U_R)	10
2.2.4 Category voltage (U_C)	11
2.2.5 Rated temperature	11
3 Quality assessment procedures	11
3.1 Primary stage of manufacture	11
3.2 Structurally similar components	11
3.3 Certified test records of released lots	11
3.4 Qualification approval procedures	11
3.4.1 General	11
3.4.2 Qualification approval on the basis of the fixed sample size procedure	12
3.5 Quality conformance inspection	19
3.5.1 Formation of inspection lots	19
3.5.2 Test schedule	20
3.5.3 Delayed delivery	20
3.5.4 Assessment levels	20
4 Test and measurement procedures	21
4.1 Mounting	21
4.2 Visual examination and check of dimensions	21
4.2.1 General	21
4.2.2 Visual examination and check of dimensions	21
4.2.3 Requirements	21
4.3 Electrical tests	21
4.3.1 Voltage proof	21

4.3.2	Capacitance	22
4.3.3	Tangent of loss angle ($\tan \delta$)	22
4.3.4	Insulation resistance	23
4.4	Shear test	24
4.5	Substrate bending test	24
4.5.1	General	24
4.5.2	Initial measurement	24
4.5.3	Final inspections and requirements	24
4.6	Resistance to soldering heat	25
4.6.1	General	25
4.6.2	Initial inspections	25
4.6.3	Test conditions	25
4.6.4	Recovery	25
4.6.5	Final inspections and requirements	25
4.7	Solderability	25
4.7.1	General	25
4.7.2	Test conditions	25
4.7.3	Final inspections and requirements	25
4.8	Rapid change of temperature	25
4.8.1	General	25
4.8.2	Initial inspections	26
4.8.3	Test conditions	26
4.8.4	Final inspections and requirements	26
4.9	Climatic sequence	26
4.9.1	General	26
4.9.2	Initial measurements	26
4.9.3	Dry heat	26
4.9.4	Damp heat, cyclic, Test Db, first cycle	26
4.9.5	Cold	26
4.9.6	Damp heat, cyclic, Test Db, remaining cycles	26
4.9.7	Recovery	26
4.9.8	Final inspections and requirements	27
4.10	Damp heat, steady state	27
4.10.1	General	27
4.10.2	Initial inspections	27
4.10.3	Test conditions	27
4.10.4	Recovery	27
4.10.5	Final inspections and requirements	27
4.11	Endurance	27
4.11.1	General	27
4.11.2	Initial inspections	27
4.11.3	Test conditions	27
4.11.4	Final inspections and requirements	28
4.12	Charge and discharge	28
4.12.1	General	28
4.12.2	Initial inspections	28
4.12.3	Test conditions	28
4.12.4	Recovery	29
4.12.5	Final inspections and requirements	29

iTech STANDARD PREVIEW
(standards.iteh.ai)

[IEC 60384-23:2015](https://standards.iteh.ai/catalog/standards/sist/2007b18f-dbcf-412a-892f-19936ebde54/iec-60384-23-2015)

<https://standards.iteh.ai/catalog/standards/sist/2007b18f-dbcf-412a-892f-19936ebde54/iec-60384-23-2015>

4.13	Component solvent resistance (if required)	29
4.14	Solvent resistance of marking (if required)	29
	Bibliography	30
Table 1	– Percentage limit of the rated voltage at a.c. voltage frequency	11
Table 2	– Test and sampling plan for qualification approval Assessment level EZ	13
Table 3	– Test schedule for qualification approval	14
Table 4	– Lot-by-lot inspection	20
Table 5	– Periodic tests	21
Table 6	– Test voltages	22
Table 7	– Tangent of loss angle limits	23
Table 8	– Requirements regarding insulation resistance	24
Table 9	– Correction factor dependent on test temperature	24
Table 10	– Endurance test Grade 1 and Grade 2 capacitors	28
Table 11	– Endurance test Grade 3 capacitors	28

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[IEC 60384-23:2015](#)

<https://standards.iteh.ai/catalog/standards/sist/2007bf8f-dbcf-412a-892f-f19936cbde54/iec-60384-23-2015>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT –**Part 23: Sectional specification – Fixed metallized polyethylene naphthalate film dielectric surface mount d.c. capacitors**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60384-23 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment.

This second edition cancels and replaces the first edition published in 2005 and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Revised all parts of the document based on the ISO/IEC Directives, Part 2:2011 (sixth edition) and harmonization between other similar kinds of documents.
- b) Revised tables and Clause 4 so as to prevent duplications and contradictions.

The text of this standard is based on the following documents:

FDIS	Report on voting
40/2349/FDIS	40/2376/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The list of all parts of the IEC 60384 series, under the (new) general title *Fixed capacitors for use in electronic equipment*, can be found on the IEC web site.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[IEC 60384-23:2015](#)

<https://standards.iteh.ai/catalog/standards/sist/2007bf8f-dbcf-412a-892f-f19936cbde54/iec-60384-23-2015>

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT –

Part 23: Sectional specification – Fixed metallized polyethylene naphthalate film dielectric surface mount d.c. capacitors

1 General

1.1 Scope

This part of IEC 60384 is applicable to fixed surface mount capacitors for direct current, with metallized electrodes and polyethylene naphthalate dielectric for use in electronic equipment. These capacitors have metallized connecting pads or soldering strips and are intended to be mounted directly onto substrates for hybrid circuits or onto printed boards. These capacitors may have "self-healing properties" depending on conditions of use. They are primarily intended for applications where the a.c. component is small with respect to the rated voltage.

Capacitors for radio interference suppression are not included, they are covered by IEC 60384-14.

1.2 Object

The object of this standard is to prescribe preferred ratings and characteristics and to select from IEC 60384-1, the appropriate quality assessment procedures, tests and measuring methods and to give general performance requirements for this type of capacitor. Test severities and requirements prescribed in detail specifications referring to this sectional specification shall be of equal or higher performance level, lower performance levels are not permitted.

1.3 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60062, *Marking codes for resistors and capacitors*

IEC 60063, *Preferred number series for resistors and capacitors*

IEC 60068-1:2013, *Environmental testing – Part 1: General and guidance*

IEC 60384-1:2008, *Fixed capacitors for use in electronic equipment – Part 1: Generic specification*

IEC 61193-2:2007, *Quality assessment systems – Part 2: Selection and use of sampling plans for inspection of electronic components and packages*

ISO 3, *Preferred numbers – Series of preferred numbers*

1.4 Information to be given in a detail specification

1.4.1 General

Detail specifications shall be derived from the relevant blank detail specification.

Detail specifications shall not specify requirements inferior to those of the generic, sectional or blank detail specification. When more severe requirements are included, they shall be listed in 1.9 of the detail specification and indicated in the test schedules, for example by an asterisk.

The information given in 1.4.2 may, for convenience, be presented in tabular form.

The following information shall be given in each detail specification and the values quoted shall preferably be selected from those given in the appropriate clause of this sectional specification.

1.4.2 Outline drawing and dimensions

There shall be an illustration of the capacitor as an aid to easy recognition and for comparison of the capacitor with others. Dimensions and their associated tolerances, which affect interchangeability and mounting, shall be given in the detail specification. All dimensions shall preferably be stated in millimetres, however, when the original dimensions are given in inches, the converted metric dimensions in millimetres shall be added.

The numerical values of the body shall be given as follows:

- width, length and height.

The numerical values of the terminals shall be given as follows:

- width, length and spacing.

When necessary, for example when a number of items (sizes and capacitance/voltage ranges) is covered by a detail specification, the dimensions and their associated tolerances shall be placed in a table below the drawing.

IEC 60384-23:2015

<https://standards.iteh.ai/catalog/standards/sist/2007bf8f-dbcf-412a-892f-1b93060dc34/iec-60384-23-2015>

When the configuration is other than described above, the detail specification shall state such dimensional information as will adequately describe the capacitor.

1.4.3 Mounting

The detail specification shall give guidance on methods of mounting for normal use. Mounting for test and measurement purposes (when required) shall be in accordance with 4.1.

1.4.4 Ratings and characteristics

1.4.4.1 General

The ratings and characteristics shall be in accordance with the relevant clauses of this specification, together with the following.

1.4.4.2 Nominal capacitance range

See 2.2.1.

When products approved to the detail specification have different nominal capacitance ranges, the following statement should be added: "The nominal capacitance range available in each voltage range is given on the IEC online service, www.iecq.org/certificates."

1.4.4.3 Particular characteristics

Additional characteristics may be listed, when they are considered necessary to specify adequately the component for design and application purposes.

1.4.4.4 Soldering

The detail specification shall prescribe the test methods, severities and requirements applicable for the solderability and the resistance to soldering heat tests.

1.4.5 Marking

The detail specification shall specify the content of the marking on the capacitor and on the packaging. Deviations from 1.6 shall be specifically stated.

1.5 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60384-1:2008, as well as the following apply.

1.5.1

performance grade 1 capacitors

<long-life> capacitors for long-life applications with stringent requirements for the electrical parameters

1.5.2

performance grade 2 capacitors

<general purpose> capacitors for general application where the stringent requirements for grade 1 capacitors are not necessary

1.5.3

performance grade 3 capacitors

<low temperature, miniature type> miniature type capacitors having a rated temperature of 85 °C and for which less stringent requirements than for grade 2 capacitors are acceptable

1.6 Marking

1.6.1 General

See IEC 60384-1:2008, 2.4, with the following details.

1.6.2 Information for marking

The information given in the marking is normally selected from the following list. The relative importance of each item is indicated by its position in the list:

- a) nominal capacitance (in clear or code according to IEC 60062);
- b) rated voltage (d.c. voltage may be indicated by the symbol \equiv or —);
- c) tolerance on nominal capacitance;
- d) category voltage;
- e) year and month (or week) of manufacture;
- f) manufacturer's name or trade mark;
- g) climatic category;
- h) manufacturer's type designation;
- i) reference to the detail specification.

NOTE In item b) the first symbol has been taken from IEC 60417-5031:2002-10, symbol for "Direct current".

1.6.3 Marking on capacitors

Marking on capacitors is made when necessary.

Any marking shall be legible and not easily smeared or removed by rubbing with a finger.

1.6.4 Marking on packaging

The packaging containing capacitors should be clearly marked with all the information listed in 1.6.2 as necessary.

2 Preferred ratings and characteristics

2.1 Preferred characteristics

The values given in detail specifications shall preferably be selected from the following.

2.1.1 Preferred climatic categories

The surface mount capacitors covered by this specification are classified into climatic categories according to the general rules given in IEC 60068-1:2013, Annex A.

The lower and upper category temperatures and the duration of the damp heat, steady state test shall be chosen from the following:

Lower category temperature: $-55\text{ }^{\circ}\text{C}$, $-40\text{ }^{\circ}\text{C}$ and $-25\text{ }^{\circ}\text{C}$.

Upper category temperature: $+85\text{ }^{\circ}\text{C}$ (only grade 3); $+100\text{ }^{\circ}\text{C}$, $+125\text{ }^{\circ}\text{C}$ and $+155\text{ }^{\circ}\text{C}$.

Duration of the damp heat, steady state test: 4, 10, 21 and 56 days.

With continuous operation at $125\text{ }^{\circ}\text{C}$ in excess of the endurance test time, accelerated ageing has to be considered (see detail specification).

The severities for the cold and dry heat tests are the lower and upper category temperatures respectively.

2.2 Preferred values of ratings

2.2.1 Nominal capacitance (C_N)

Preferred values of nominal capacitance shall be taken from the E6 series of IEC 60063:

1,0 – 1,5 – 2,2 – 3,3 –, 4,7 and 6,8 and their decimal multiples ($\times 10^n$, n : integer).

If other values are required they shall preferably be chosen from the E12 series.

2.2.2 Tolerance on nominal capacitance

The preferred tolerances on the nominal capacitance are $\pm 5\%$, $\pm 10\%$ and $\pm 20\%$.

2.2.3 Rated voltage (U_R)

The preferred values of rated voltage taken from R 10 series of ISO 3 are:

1,0 – 1,6 – 2,5 – 4,0 – 5,0 – 6,3 and their decimal multiples ($\times 10^n$, n : integer).

The sum of the d.c. voltage and the peak a.c. voltage applied to the capacitor should not exceed the rated voltage.

The value of the peak a.c. voltage should not exceed the percentages of the rated voltage at the frequencies stated in Table 1, unless otherwise specified in the detail specification.

Table 1 – Percentage limit of the rated voltage at a.c. voltage frequency

AC voltage frequency Hz	Percentage limit of the rated voltage %
50	20
100	15
1 000	3
10 000	1

2.2.4 Category voltage (U_C)

The category voltage for Grade 1 and Grade 2 capacitors is:

- for upper category temperature 125 °C: $0,8 U_R$;
- for upper category temperature 155 °C: $0,5 U_R$;

and for Grade 3 capacitors is:

- for upper category temperature 100 °C: $0,8 U_R$;
- for upper category temperature 125 °C: $0,5 U_R$.

2.2.5 Rated temperature

Grade 1 and Grade 2 capacitors:

the standard value of rated temperature is 100 °C.

Grade 3 capacitors:

the standard value of rated temperature is 85 °C.

3 Quality assessment procedures

3.1 Primary stage of manufacture

The primary stage of manufacture is the winding of the capacitor element or the equivalent operation.

3.2 Structurally similar components

Capacitors considered as being structurally similar are capacitors produced with similar processes and materials, though they may be of different case sizes and capacitance and voltage values.

3.3 Certified test records of released lots

The information required in IEC 60384-1:2008, Q.9 shall be made available when prescribed in the detail specification and when requested by a purchaser. After the endurance test the required parameters are the capacitance, $\tan \delta$ and the insulation resistance.

3.4 Qualification approval procedures

3.4.1 General

The procedures for qualification approval testing are given in IEC 60384-1:2008, Q.5.

The schedule to be used for qualification approval testing on the basis of lot-by-lot and periodic tests is given in 3.5. The procedure using a fixed sample size schedule is given in 3.4.2 below.

3.4.2 Qualification approval on the basis of the fixed sample size procedure

3.4.2.1 Sampling

The fixed sample size procedure is described in IEC 60384-1:2008, Q.5.3, list item b). The sample shall be representative of the range of capacitors for which approval is sought. The sample may be the whole or part of the range given in the detail specification.

The sample shall consist of four specimens having the maximum and minimum rated voltages, and, for these voltages, the maximum and minimum capacitances. When there are more than four rated voltages an intermediate voltage shall also be tested. Thus, for the approval of a range, testing is required of either four or six values (capacitance/voltage combinations). When the range consists of less than four values, the number of specimens to be tested shall be that required for four values.

Spare specimens are permitted as follows:

Two (for six values) or three (for four values) per value which may be used as replacements for specimens which are non-conforming because of incidents not attributable to the manufacturer.

The numbers given in Group 0 assume that all groups are applicable. If this is not so the numbers may be reduced accordingly.

When additional groups are introduced into the qualification approval test schedule, the number of specimens required for Group 0 shall be increased by the same number as that required for the additional groups.

Table 2 gives the number of samples to be tested for each group with the permissible number of non-conforming items for qualification approval tests.

3.4.2.2 Tests

The complete series of tests specified in Table 2 and Table 3 are required for the approval of capacitors covered by one detail specification. The tests of each group shall be carried out in the order given.

The whole sample shall be subjected to the tests of Group 0 and then divided for the other groups.

Non-conforming specimens found during the tests of Group 0 shall not be used for the other groups.

Approval is granted when the number of non-conforming items is zero.

Table 2 and Table 3 together form the fixed sample size test schedule for the qualification approval on the basis of the fixed sample size procedure.

Table 2 gives the number of the samples and permissible non-conforming items for each test and test group.

Table 3 gives a summary of the test conditions and performance requirements, and choices of the test conditions and performance requirements in the detail specification.

The test conditions and performance requirements for the qualification approval on the basis of the fixed sample size procedure should be identical to those for quality conformance inspections given in the detail specification.

**Table 2 – Test and sampling plan for qualification approval
Assessment level EZ**

Group No.	Test	Subclause of this publication	Number of specimens <i>n</i> ^a	Permissible number of non-conforming items <i>c</i>
0	Visual examination	4.2	144	0
	Dimensions	4.2		
	Capacitance	4.3.2		
	Tangent of loss angle	4.3.3		
	Voltage proof	4.3.1		
	Insulation resistance	4.3.4		
	Spare specimens		12	
1A	Resistance to soldering heat	4.6	12	0
	Component solvent resistance ^b	4.13		
1B	Solderability	4.7	12	0
	Solvent resistance of the marking ^b	4.14		
2	Substrate bending test	4.5	12	0
3	Mounting	4.1	108	^c
	Visual examination	4.2.1		
	Capacitance	4.3.2		
	Tangent of loss angle	4.3.3		
	Insulation resistance	4.3.4		
	3.1	Shear test	4.4	24
3.1	Rapid change of temperature	4.8		
	Climatic sequence	4.9		
3.2	Damp heat, steady state	4.10	24	0
3.3	Endurance	4.11	36	0
3.4	Charge and discharge	4.12	24	0

^a Capacitance/voltage combinations, see 3.4.2.

^b If required by the detail specification.

^c Specimens found defective after mounting shall not be taken into account when calculating the permissible non-conforming items for the following tests. They shall be replaced by spare parts.