
**Information technology — 8 mm wide
magnetic tape cartridge for information
interchange — Helical scan recording**

iTeh STANDARD PREVIEW

*(Technologies de l'information) — Cartouche pour bande magnétique de
8 mm de large pour l'échange d'information — Enregistrement par
balayage hélicoïdal*

[ISO/IEC 11319:1993](https://standards.iso.org/iso/iec/11319:1993)

<https://standards.iteh.ai/catalog/standards/sist/725d86fb-9aec-432d-8f14-8acde4c89c7b/iso-iec-11319-1993>



Contents

	Page
Section 1 : General	1
1 Scope	1
2 Conformance	1
3 Normative references	1
4 Definitions	1
4.1 AC erase	1
4.2 Average Signal Amplitude	1
4.3 azimuth	1
4.4 back surface	1
4.5 bit cell	1
4.6 byte	1
4.7 cartridge	1
4.8 Cyclic Redundancy Check (CRC) Character	1
4.9 Error Correcting Code (ECC)	2
4.10 flux transition position	2
4.11 flux transition spacing	2
4.12 magnetic tape	2
4.13 Master Standard Reference Tape	2
4.14 Physical Beginning of Tape (PBOT)	2
4.15 Physical End of Tape (PEOT)	2
4.16 physical recording density	2
4.17 Secondary Reference Amplitude	2
4.18 Secondary Reference Field	2
4.19 Secondary Standard Reference Tape	2
4.20 Standard Reference Current (I _r)	2
4.21 Tape Reference Edge	2
4.22 Test Recording Current	2
4.23 tone	2
4.24 track	2
4.25 Typical Field	2

iTech STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 11319:1993](https://standards.iteh.ai/catalog/standards/sist/725d86fb-9aec-432d-8f14-8acde4c89c7b/iso-iec-11319-1993)

<https://standards.iteh.ai/catalog/standards/sist/725d86fb-9aec-432d-8f14-8acde4c89c7b/iso-iec-11319-1993>

5	Environment and safety	2
5.1	Testing environment	3
5.2	Operating environment	3
5.3	Storage environment	3
5.4	Transportation	3
5.5	Safety	3
5.6	Flammability	3
Section 2 : Requirements for the case		3
6	Dimensional and mechanical characteristics of the case	3
6.1	General	3
6.2	Overall dimension (figure 3)	4
6.3	Holding areas	4
6.4	Cartridge insertion	5
6.5	Window (figure 1)	5
6.6	Loading grips (figure 3)	6
6.7	Label areas (figure 3)	6
6.8	Datum areas and datum holes (figures 4, 5 and 6)	6
6.9	Support areas	7
6.10	Recognition holes (figures 5, 6 and 7)	7
6.11	Write-inhibit Hole (figures 6 and 7)	8
6.12	Pre-positioning surfaces (figures 3 and 5)	8
6.13	Cartridge lid (figures 3 and 8)	9
6.14	Cartridge reel lock (figure 11)	10
6.15	Reel access holes (figure 5)	11
6.16	Interface between the reels and the drive spindles (figures 17 and 18)	11
6.17	Light path (figures 5, 7, 15 and 16)	12
6.18	Position of the tape in the case (figure 16)	12
6.19	Tape path zone (figures 16 and 17)	13
6.20	Tape access cavity (figure 5)	13
6.21	Tape access cavity clearance requirements (figure 19)	13
Section 3 : Requirements for the unrecorded tape		31
7	Mechanical, physical and dimensional characteristics of the tape	31
7.1	Materials	31
7.2	Tape length	31
7.2.1	Length of magnetic tape	31
7.2.2	Length of leader and trailer tapes	31
7.2.3	Splicing tape	31
7.3	Width	31
7.4	Discontinuities	31
7.5	Thickness	31
7.5.1	Thickness of magnetic tape	31
7.5.2	Thickness of leader and trailer tape	31

7.6	Longitudinal curvature	31
7.7	Cupping	32
7.8	Coating adhesion (figure 20)	32
7.9	Layer-to-layer adhesion	32
7.10	Tensile strength	33
7.10.1	Breaking strength	33
7.10.2	Yield strength	33
7.11	Residual elongation	33
7.12	Electrical resistance of the surface	33
7.13	Tape winding	34
7.14	Light transmittance of tape	34
8	Magnetic recording performance	34
8.1	Test conditions	34
8.2	Typical Field	35
8.3	Signal Amplitude	35
8.4	Resolution	35
8.5	Narrow-band signal-to-noise ratio	35
8.5.1	Requirement	35
8.5.2	Procedure	35
8.6	Ease of erasure	35
8.7	Tape quality	35
8.7.1	Missing pulses	35
8.7.2	Missing pulse zone	35
8.8	Inhibitor tape	36
Section 4 : Requirements for an interchanged tape		36
9	Format	36
9.1	General	36
9.2	Information matrix	36
9.2.1	Loading of the information matrix	37
10	Method of recording	40
10.1	Physical recording density	40
10.1.1	Long-term average bit cell length	40
10.1.2	Short-term average bit cell length	41
10.1.3	Rate of change	41
10.2	Bit shift	41
10.3	Read signal amplitudes	41

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 11319:1993](https://standards.iteh.ai/catalog/standards/sist/725d86fb-9aec-432d-8f14-8acde4c89c7b/iso-iec-11319-1993)

<https://standards.iteh.ai/catalog/standards/sist/725d86fb-9aec-432d-8f14-8acde4c89c7b/iso-iec-11319-1993>

10.3.1	Amplitude of data signals	41
10.3.2	Amplitude of servo signals	41
10.3.3	Signal amplitude on an analogue tape mark track	41
10.4	Erasure	41
11	Track geometry	42
11.1	Track positions	42
11.2.1	Average track pitch	43
11.2.2	Adjacent track pitch	43
11.3	Track width	43
11.4	Track angle	43
11.5	Linearity of track edges	43
11.6	Azimuth	43
12	Format of an information track	43
12.1	Channel bit	43
12.2	Information Segment	43
12.2.1	Bit Synchronization field	44
12.2.2	Information Segment Number	44
12.2.3	Information Segment field	44
12.3	Information Block	45
12.4	Information Zone	46
12.5	Servo Zone	46
12.6	Information Tracks	46
12.6.1	Format ID Track	47
12.6.2	Data Track	47
12.6.3	Tape Mark Track	47
12.6.4	Splice Track	47
13	Tape Mark	48
13.1	Description	48
13.2	Long Tape Mark	48
13.3	Short Tape Mark	48
13.3.1	Normal Short Tape Mark	48
13.3.2	Alternative Short Tape Mark	48
14	ID Information	49
14.1	Column 00, Row 00	49
14.1.1	Block Type - Data Block	49
14.1.2	Block Type - Data Block	49
14.1.3	Block type - Format ID	49

14.1.4	Block type - Pad Block	49
14.2	Column 00, Row 01	49
14.3	Column 00, Row 02	49
14.4	Column 00, Row 03	49
14.5	Column 00, Row 04	50
14.6	Column 00, Rows 05, 06	50
14.6.1	Row 05	50
14.6.2	Row 06	50
14.7	Column 00, Row 07	50
14.8	Column 00, Rows 08, 09, 10	50
14.8.1	Block type - Data Block	50
14.8.2	Block type - non-Data Block	50
14.9	Column 00, Rows 11, 12, 13	50
15	Rewritten Information Blocks	51
16	Physical tape format	51
16.1	Initial Erased Area	51
16.2	Logical Beginning of Tape Area (LBOT Area)	52
16.3	Usable area of the tape	52
16.4	Post Data erased area	52
<p>ISO/IEC 11319:1993 https://standards.iteh.ai/catalog/standards/sist/725d86fb-9aec-432d-8f14-8acde4c89c7b/iso-iec-11319-1993</p>		
Annexes		
A	Measurement of light transmittance of tape and leaders	53
B	Measurement of bit shift	56
C	Representation of 8-bit bytes by 10-bit patterns	59
D	Recommendations for transportation	62
E	Inhibitor tape	63

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 11319 was prepared by the European Computer Manufacturers Association (as Standard ECMA-145) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Sub-Committee 11, *Flexible magnetic media for digital data interchange*, in parallel with its approval by national bodies of ISO and IEC.

Annexes A, B and C form an integral part of this International Standard. Annexes D and E are for information only.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

This page intentionally left blank

[ISO/IEC 11319:1993](#)

<https://standards.iteh.ai/catalog/standards/sist/725d86fb-9aec-432d-8f14-8acde4c89c7b/iso-iec-11319-1993>

Information technology - 8 mm wide magnetic tape cartridge for information interchange - Helical scan recording

Section 1 : General

1 Scope

This International Standard specifies the physical and magnetic characteristics of an 8 mm wide magnetic tape cartridge to enable interchangeability of such cartridges. It also provides a format and recording method, thus allowing, together with ISO 1001 for Magnetic Tape Labelling, full data interchange by means of such magnetic tape cartridges.

2 Conformance

A magnetic tape cartridge shall be in conformance with this International Standard if it satisfies all mandatory requirements specified herein. The tape requirements shall be satisfied throughout the extent of the tape.

3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO/R 527:1966, *Plastics - Determination of tensile properties.*

ISO 1001:1986, *Information processing - File structure and labelling of magnetic tapes for information interchange.*

ISO 1302:1978, *Technical drawings - Method of indicating surface texture on drawings.*

IEC 950:1990, *Safety of Information Technology Equipment, including Electrical Business Equipment.*

4 Definitions

For the purpose of this International Standard, the following definitions apply.

- 4.1 **AC erase:** A process of erasure utilizing alternating fields of decaying level.
- 4.2 **Average Signal Amplitude:** The average peak-to-peak value of the signal output of the read head measured over a minimum of 1,40 mm, exclusive of missing pulses.
- 4.3 **azimuth:** The angular deviation, in degrees of arc, of the recorded flux transitions on a track from the line normal to the track centreline.
- 4.4 **back surface:** The surface of the tape opposite to the magnetic coating used to record data.
- 4.5 **bit cell:** A distance along the track allocated for the recording of a Channel bit.
- 4.6 **byte:** An ordered set of bits acted upon as a unit.
- 4.7 **cartridge:** A case containing magnetic tape stored on twin reels.
- 4.8 **Cyclic Redundancy Check (CRC) Character:** A character used for error detection.

4.9 Error Correcting Code (ECC): A mathematical procedure yielding bytes used for the detection and correction of errors.

4.10 flux transition position: That point which exhibits the maximum free-space flux density normal to the tape surface.

4.11 flux transition spacing: The distance along a track between successive flux transitions.

4.12 magnetic tape: A tape that accepts and retains magnetic signals intended for input, output, and storage of data for information processing.

4.13 Master Standard Reference Tape: A tape selected as the standard for amplitude, Typical Field and Resolution.

NOTE 1 The Master Standard Reference Tape has been established by the SONY Corporation.

4.14 Physical Beginning of Tape (PBOT): The transition from the tape leader to the opaque area of the splice by which the translucent leader tape is joined to the magnetic tape.

4.15 Physical End of Tape (PEOT): The transition from the opaque area of the splice to the translucent trailer tape.

4.16 physical recording density: The number of recorded flux transitions per unit length of track, expressed in flux transitions per millimetre (ftpmm).

4.17 Secondary Reference Amplitude: The Average Signal Amplitude from the Secondary Standard Reference Tape when it is recorded with the Test Recording Current at 2126 ftpmm.

4.18 Secondary Reference Field: The Typical Field of the Secondary Standard Reference Tape.

4.19 Secondary Standard Reference Tape: A tape the performance of which is known and stated in relation to that of the Master Standard Reference Tape.

ISO/IEC 11319:1993

NOTE 2 Secondary Standard Reference Tapes can be ordered under the Part Number RSE-5001, until the year 2001, from the Sony Corporation, Magnetic Product Group, Data Media Sales Division, 6-7-35 Kitashinagawa, Shinagawa-ku, TOKYO 141, Japan.

It is intended that these be used for calibrating tertiary reference tapes for use in routine calibration.

4.20 Standard Reference Current (I_r): The current that produces the Secondary Reference Field.

4.21 Tape Reference Edge: The lower edge of the tape when the magnetic coating is facing the observer and the supply reel is to the observer's right.

4.22 Test Recording Current: The current that is 1,5 times the Standard Reference Current.

4.23 tone: A signal recorded at 98 ftpmm.

4.24 track: A diagonally positioned area on the tape along which a series of magnetic transitions may be recorded.

4.25 Typical Field: In the plot of the Average Signal Amplitude against the recording field at the physical recording density of 2 126 ftpmm, the minimum field that causes an Average Signal Amplitude equal to 90% of the maximum Average Signal Amplitude.

5 Environment and safety

The conditions specified below refer to ambient conditions immediately surrounding the cartridge. Cartridges exposed to environments outside these limits may still be able to function usefully; however, such exposure may cause permanent damage.

5.1 Testing environment

Unless otherwise specified, tests and measurements made on the cartridge to check the requirements of this International Standard shall be carried out under the following conditions

temperature:	23 °C ± 2 °C
relative Humidity:	40 % to 60 %
conditioning period before testing:	24 h

5.2 Operating environment

Cartridges used for data interchange shall be capable of operating under the following conditions

temperature:	5 °C to 45 °C
relative Humidity:	20 % to 80 %
wet Bulb Temperature:	26 °C max.

There shall be no deposit of moisture on or in the cartridge.

Conditioning before operating:

If a cartridge has been exposed during storage and/or transportation to a condition outside the above values, before use the cartridge shall be conditioned in the operating environment for a time at least equal to the period during which it has been out of the operating environment, up to a maximum of 24 h.

NOTE 3 Rapid variations of temperature should be avoided.

5.3 Storage environment

For long-term or archival storage of cartridges the following conditions shall be observed

temperature:	5 °C to 32 °C
relative Humidity:	20 % to 60 %
wet Bulb Temperature:	26 °C max.

The stray magnetic field at any point on the tape shall not exceed 4 000 A/m. There shall be no deposit of moisture on or in the cartridge.

5.4 Transportation

Recommended limits for the environment to which a cartridge may be subjected during transportation, and the precautions to be taken to minimize the possibility of damage, are provided in annex D.

5.5 Safety

The cartridge and its components shall satisfy the requirements of IEC 950.

5.6 Flammability

The cartridge and its components shall be made from materials which, if ignited from a match flame, do not continue to burn in a still carbon dioxide atmosphere.

Section 2 : Requirements for the case

6 Dimensional and mechanical characteristics of the case

6.1 General

The case of the cartridge shall consist of

- an upper half,
- a lower half,
- a lid pivotally mounted on the upper half.

In the drawings, an embodiment of the cartridge is shown as an example.

- Figure 1 is a perspective view of the cartridge seen from the top.
- Figure 2 is a perspective view of the cartridge seen from the bottom.
- Figure 3 shows the top side with the lid closed using third angle projection.
- Figure 4 shows the bottom side, datum and support areas.
- Figure 5 shows the bottom side with the lid removed.
- Figure 6 shows the enlarged view of the datum and recognition holes.
- Figure 7 shows the cross-sections through the light path holes, the recognition holes and the write-inhibit hole.
- Figure 8 shows details of the lid when closed, rotating and open.
- Figure 9 shows the details of the lid release insertion channel.
- Figure 10 shows the lid lock release requirements.
- Figure 11 shows the reel lock release requirements.
- Figure 12 shows the reel unlock force direction.
- Figure 13 shows the lid release force direction.
- Figure 14 shows the lid opening force direction.
- Figure 15 shows the light path and light window.
- Figure 16 shows the internal tape path and light path.
- Figure 17 shows the cartridge reel and a cross-section view of the cartridge reel.
- Figure 18 shows the cross-section view of the cartridge reel interface with the drive spindle.
- Figure 19 shows the tape access cavity clearance requirements.

The dimensions are referred to three orthogonal Reference Planes X, Y and Z.

6.2 Overall dimension (figure 3)

The overall dimensions of the case with the lid in the closed position shall be

$$L_1 = 62,5 \text{ mm} \pm 0,3 \text{ mm}$$

$$L_2 = 95,0 \text{ mm} \pm 0,2 \text{ mm}$$

$$L_3 = 15,0 \text{ mm} \pm 0,2 \text{ mm}$$

The distance from the rear side to plane X shall be

$$L_4 = 47,35 \text{ mm} \pm 0,15 \text{ mm}$$

The distance from the right side to plane Y shall be

$$L_5 = 13,0 \text{ mm} \pm 0,1 \text{ mm}$$

6.3 Holding areas

The holding areas, shown hatched in figure 3, shall be the areas along which the cartridge shall be held down when inserted in the drive. Their position and dimensions shall be

$$L_6 = 12,0 \text{ mm max.}$$

$$L_7 = 3,0 \text{ mm min.}$$

6.4 Cartridge insertion

The cartridge shall have asymmetrical features to prevent insertion in the drive in other than the correct orientation. These consist of a channel, a recess and an incline.

The channel (figures 3 and 9) shall provide for an unobstructed path, when the lid is closed and locked, to unlock the lid. The dimensions shall be

$$L_8 = 79,7 \text{ mm} \pm 0,2 \text{ mm}$$

$$L_9 = 1,0 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{10} = 0,7 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{11} = 1,0 \text{ mm min.}$$

$$L_{12} = 1,2 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{13} = 0,8 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{14} = 1,2 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{15} = 0,5 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{16} = 1,5 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{17} = 1,0 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{18} = 3,8 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{19} = 0,2 \text{ mm} \pm 0,2 \text{ mm}$$

$$L_{20} = 2,3 \text{ mm min.}$$

$$L_{21} = 2,5 \text{ mm} \pm 0,2 \text{ mm}$$

The recess dimensions (figures 3 and 5) shall be

$$L_{22} = 7,5 \text{ mm max.}$$

$$L_{23} = 11,0 \text{ mm} \pm 0,2 \text{ mm}$$

$$L_{24} = 1,5 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{25} = 1,5 \text{ mm} \pm 0,1 \text{ mm}$$

The incline (figure 8) is part of the lid structure and the dimensions shall be

$$L_{26} = 7,7 \text{ mm} \begin{matrix} + 0,0 \\ - 2,5 \end{matrix} \text{ mm}$$

$$L_{27} = 0,55 \text{ mm} \begin{matrix} + 0,05 \\ - 0,10 \end{matrix} \text{ mm}$$

$$A_1 = 17,5^\circ \pm 4,0^\circ$$

6.5 Window (figure 1)

A window may be provided on the top side so that a part of the reel is visible. The window, if provided, shall not extend beyond the height of the cartridge.

6.6 Loading grips (figure 3)

The cartridge shall have loading grips for automatic loading into a drive.

The dimensions and positions of the loading grips shall be

$$L_{28} = 39,35 \text{ mm} \pm 0,20 \text{ mm}$$

$$L_{29} = 1,5 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{30} = 5,0 \text{ mm} \pm 0,3 \text{ mm}$$

$$L_{31} = 2,0 \text{ mm} \pm 0,2 \text{ mm}$$

$$A_2 = 90^\circ \pm 5^\circ$$

6.7 Label areas (figure 3)

A portion of the rear side of the cartridge and a portion of the top side of the cartridge may be used for labels. The rear side area provides for readability of the label when it is stacked or inserted into the drive. The position and the size of the labels shall not interfere with the operation or clearance requirements of the cartridge component parts.

The area used for labels on the top side shall not extend beyond the inner edge of the holding areas defined by L_6 and L_7 .

The position and dimensions of the rear side label area shall be

$$L_{32} = 0,5 \text{ mm min.}$$

$$L_{33} = 1,5 \text{ mm min.}$$

$$L_{34} = 80,0 \text{ mm max.}$$

iTeh STANDARD PREVIEW
(standards.iteh.ai)

The depth of the label depression shall be 0,3 mm max. IEC 11319:1993

6.8 Datum areas and datum holes (figures 4, 5 and 6)

<https://standards.iteh.ai/catalog/standards/sist/725d86fb-9acc-432d-8f14-8acdc4c89c7b/iso-iec-11319-1993>

The annular datum areas A, B and C shall lie in plane Z. They determine the vertical position of the cartridge in the drive. Each shall have a diameter D_1 equal to 6,0 mm \pm 0,1 mm and be concentric with the respective datum hole.

The centres of datum holes A and B lie in plane X.

The centre of the circular datum hole A shall be at the intersection of planes X and Y (see figure 5).

The distance from the centre of datum hole B to plane Y (see figure 4) shall be

$$L_{35} = 68,0 \text{ mm} \pm 0,1 \text{ mm}$$

The distance from the centre of the circular datum hole C to plane Y (see figure 6) shall be

$$L_{36} = 10,20 \text{ mm} \pm 0,05 \text{ mm}$$

The distance from the centre of datum hole D to plane Y (see figure 6) shall be

$$L_{37} = 79,2 \text{ mm} \pm 0,1 \text{ mm}$$

The distance from the centres of datum holes C and D to plane X (see figure 5) shall be

$$L_{38} = 36,35 \text{ mm} \pm 0,08 \text{ mm}$$

The diameter of datum hole A and datum hole C shall be 3,00 mm $\begin{matrix} + 0,05 \\ - 0,00 \end{matrix}$ mm. The dimensions of datum hole A and datum hole C shall be

$$L_{39} = 1,2 \text{ mm} \begin{matrix} + 1,0 \\ - 0,0 \end{matrix} \text{ mm}$$

$$L_{40} = 2,6 \text{ mm min.}$$

$$L_{41} = 1,5 \text{ mm min.}$$

$$L_{42} = 4,0 \text{ mm min.}$$

$$L_{43} = 0,3 \text{ mm max.}$$

$$A_3 = 45^\circ \pm 1^\circ$$

The dimensions of datum hole B and datum hole D shall be

$$L_{39} = 1,2 \text{ mm} \begin{matrix} + 1,0 \\ - 0,0 \end{matrix} \text{ mm}$$

$$L_{40} = 2,6 \text{ mm min.}$$

$$L_{41} = 1,5 \text{ mm min.}$$

$$L_{42} = 4,0 \text{ mm min.}$$

$$L_{43} = 0,3 \text{ mm max.}$$

$$L_{44} = 3,00 \text{ mm} \begin{matrix} + 0,05 \\ - 0,00 \end{matrix} \text{ mm}$$

$$L_{45} = 3,5 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{46} = 3,00 \text{ mm} \pm 0,05 \text{ mm}$$

$$A_3 = 45^\circ \pm 1^\circ$$

$$R_1 = 1,7 \text{ mm min.}$$

STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 11319:1993

<https://standards.iteh.ai/catalog/standards/sist/725d86fb-9acc-432d-8f14-8acde4c89c7b/iso-iec-11319-1993>

6.9 Support areas

The cartridge support areas are shown shaded in figure 4. Support areas A, B and C shall be coplanar with datum areas A, B and C, respectively, within $\pm 0,1$ mm. Support area D shall be coplanar with datum plane Z within $\pm 0,15$ mm.

The areas within L_{49} of the edge of the cartridge shall be recessed from the support areas.

The dimensions and positions of the support areas shall be

$$L_{35} = 68,0 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{47} = 10,0 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{48} = 11,0 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{49} = 0,5 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{50} = 7,0 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{51} = 30,0 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{52} = 5,5 \text{ mm} \pm 0,1 \text{ mm}$$

$$L_{53} = 64,5 \text{ mm} \pm 0,2 \text{ mm}$$

6.10 Recognition holes (figures 5, 6 and 7)

There shall be 5 recognition holes numbered 1 to 5 as shown in figure 6.