



Edition 2.0 2012-07

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Incandescent lamps esafety specifications -PREVIEW Part 3: Tungsten halogen lamps (non-vehicle) (standards.iteh.ai)

Lampes à incandescence – Prescriptions de sécurité – Partie 3: Lampes tungstène-halogène (véhicules exceptés)

0b5677073406/iec-60432-3-2012





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2012 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur. Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

| IEC Central Office | Tel.: +41 22 919 02 11 |
|--------------------|------------------------|
| 3. rue de Varembé | Fax: +41 22 919 03 00 |
| CH-1211 Geneva 20 | info@iec.ch |
| Switzerland | www.iec.ch |

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Useful links:

IEC publications search - www.iec.ch/searchpub

The advanced search enables you to find **IEC publications ICCS**. The world's leading online dictionary of electronic and by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced <u>land₆₀₄₃₂₋₃</u> additional languages. Also known as the International withdrawn publications. https://standards.iteh.ai/catalog/standards/sts/90/EUC9-UE/S-4583-08C4-

IEC Just Published - webstore.iec.ch/justpublished/77073406/icc-60@ustome/Service Centre - webstore.iec.ch/csc

Stay up to date on all new IEC publications. Just Published details all new publications released. Available on-line and also once a month by email.

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Liens utiles:

Recherche de publications CEI - www.iec.ch/searchpub

La recherche avancée vous permet de trouver des publications CEI en utilisant différents critères (numéro de référence, texte, comité d'études,...).

Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

Just Published CEI - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications de la CEI. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (VEI) en ligne.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.





Edition 2.0 2012-07

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Incandescent lamps e Safety specifications - PREVIEW Part 3: Tungsten halogen lamps (non-vehicle) h.ai)

Lampes à incandescence – Prescriptions, de sécurité – Partie 3: Lampes tungstène halogène (véhicules exceptés) 0b5677073406/iec-60432-3-2012

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

PRICE CODE CODE PRIX



ICS 29.140.20

ISBN 978-2-83220-197-8

Warning! Make sure that you obtained this publication from an authorized distributor. Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

 Registered trademark of the International Electrotechnical Commission Marque déposée de la Commission Electrotechnique Internationale

CONTENTS

| FO | REWC | ORD | 4 | | | |
|--|--|--|--------|--|--|--|
| 1 | Gene | eral | 6 | | | |
| | 1.1 | Scope | 6 | | | |
| | 1.2 | Normative references | 6 | | | |
| | 1.3 | Terms and definitions | 7 | | | |
| 2 | Requ | uirements | 9 | | | |
| | 2.1 | General | 9 | | | |
| | 2.2 | Marking | 10 | | | |
| | | 2.2.1 Lamp marking | 10 | | | |
| | | 2.2.2 Additional information and marking | | | | |
| | 2.3 | Caps or bases | | | | |
| | | 2.3.1 General | | | | |
| | | 2.3.2 Creepage distances | | | | |
| | | 2.3.3 Dimensions | | | | |
| | 2.4 | Photobiological safety | | | | |
| | 2.5 | Gas pressure of low-pressure self-shielded extra low voltage lamps | 12 | | | |
| | 2.6 | Safety at end of life of self-shielded lamps with rated voltages from range B or | 12 | | | |
| | 2.7 | CiTeh STANDARD PREVIEW | 12 | | | |
| 3 | | ssment (standards.iteh.ai) | 13 | | | |
| Ū | 3.1 | General | | | | |
| | 3.2 | Whole production assessment by means of manufacturer's records | 13 | | | |
| | 0.2 | 3.2.1 Assessment of manufacturer's records for particular tests | | | | |
| | | 3.2.2 Sampling procedures for the whole production testing | | | | |
| | 3.3 | Assessment of batches | | | | |
| | 0.0 | 3.3.1 Sampling for batch testing | | | | |
| | | 3.3.2 Number of lamps in the batch sample | | | | |
| | | 3.3.3 Sequence of the tests | | | | |
| | | 3.3.4 Rejection conditions of batches | | | | |
| Anr | nex A | (normative) Symbols | 19 | | | |
| Anr | nex B | (normative) Method of testing the gas-pressure | 21 | | | |
| | | (informative) Information for luminaire design | | | | |
| | | (normative) Conditions of compliance for design tests | | | | |
| | | | | | | |
| | Annex E (informative) Bulb wall temperature measurement | | | | | |
| | Annex F (normative) Induced failure test | | | | | |
| Bib | liograp | phy | 32 | | | |
| | | | | | | |
| Tab | ole 1 – | - Grouping of test records – Sampling and acceptable quality levels (AQL) | 14 | | | |
| Tab | ole 2 – | - Acceptance numbers AQL = 0,25 % | 15 | | | |
| Tab | Table 3 – Acceptance numbers AQL = 0,65 % | | | | | |
| Tab | Table 4 – Acceptance numbers AQL = 2,5 % | | | | | |
| Table 5 – Batch sample size and rejection number | | | | | | |
| | Table C.1 – Fuse values for general purpose ELV tungsten halogen lamps | | | | | |
| | Table C.2 – Fuse values for photographic lamps | | | | | |
| i al | | | ··· ∠+ | | | |

| Table C.3 – List of maximum bulb temperatures | 24 |
|--|----|
| Table C.4 – Maximum base-pin temperatures | |
| Table C.5 – Maximum contact temperatures | 26 |
| Table C.6 – Maximum reflector-rim temperatures | |

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>IEC 60432-3:2012</u> https://standards.iteh.ai/catalog/standards/sist/89dfe0c9-0e75-4585-b8c4-0b5677073406/iec-60432-3-2012

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INCANDESCENT LAMPS – SAFETY SPECIFICATIONS –

Part 3: Tungsten halogen lamps (non-vehicle)

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national for regional publication shall be clearly indicated in the latter. https://standards.iteh.ai/catalog/standards/sist/89dfe0c9-0e75-4585-b8c4-
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60432-3 has been prepared by subcommittee 34A: Lamps, of IEC technical committee 34: Lamps and related equipment.

This second edition of IEC 60432-3 cancels and replaces the first edition published in 2002, Amendment 1 (2005) and Amendment 2 (2008). The document 34A/1567/FDIS, circulated to the National Committees as Amendment 3, led to the publication of this new edition.

The main changes with respect to the previous edition are as follows:

- adapting the cold fill pressure requirements and tests for self-shielded lamps to the state of the technology,
- introduction of requirements to fully cover photobiological safety according to IEC 62471.

The text of this standard is based on the first edition, its Amendments 1 and 2, and the following documents:

| FDIS | Report on voting |
|---------------|------------------|
| 34A/1567/FDIS | 34A/1585/RVD |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 60432 series, published under the general title *Incandescent lamps* – *Safety specifications* can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended. iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>IEC 60432-3:2012</u> https://standards.iteh.ai/catalog/standards/sist/89dfe0c9-0e75-4585-b8c4-0b5677073406/iec-60432-3-2012

INCANDESCENT LAMPS – SAFETY SPECIFICATIONS –

Part 3: Tungsten halogen lamps (non-vehicle)

1 General

1.1 Scope

This part of IEC 60432 specifies the safety requirements for single-capped and double-capped tungsten halogen lamps, having rated voltages of up to 250 V, used for the following applications:

- projection (including cinematograph and still projection),
- photographic (including studio),
- floodlighting,
- special purpose,
- general purpose,

• stage lighting, iTeh STANDARD PREVIEW

This International Standard does not apply to general purpose single-capped tungsten halogen lamps, covered by IEC 60432-2, that are used as replacement for conventional tungsten filament lamps.

IEC 60432-3:2012

This part of IEC^{160432¹} covers^{ai/cphotobiological/8} safety-⁰ according^{c4} to IEC 62471 and IEC/TR 62471-2. Lamps covered by this part of IEC¹60432 do not reach risk levels that require risk group marking if they are

- a) floodlight lamps,
- b) general purpose capsule lamps, or
- c) general purpose reflector lamps.

1.2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-845, International Electrotechnical Vocabulary – Part 845: Lighting Available from: http://www.electropedia.org/

IEC 60061-1, Lamp caps and holders together with gauges for the control of interchangeability and safety – Part 1: Lamp caps

IEC 60061-3, Lamp caps and holders together with gauges for the control of interchangeability and safety – Part 3: Gauges

IEC 60061-4, Lamp caps and holders together with gauges for the control of interchangeability and safety – Part 4: Guidelines and general information

IEC 60357, Tungsten halogen lamps (non-vehicle) – Performance specifications

IEC 60432-1:1999, Incandescent lamps – Safety specifications – Part 1: Tungsten filament lamps for domestic and similar general lighting purposes

IEC 62471, Photobiological safety of lamps and lamp systems

IEC/TR 62471-2, Photobiological safety of lamps and lamp systems - Part 2: Guidance on manufacturing requirements relating to non-laser optical radiation safety

Terms and definitions 1.3

For the purposes of this document, the terms and definitions given in IEC 60050-845 as well as the following apply.

1.3.1

tungsten halogen lamp

gas-filled lamp containing halogens or halogen compounds, the filament being of tungsten

1.3.2

single-capped tungsten halogen lamp

tungsten halogen lamp having a single cap or base

1.3.3

double-capped tungsten halogen lamp

tungsten halogen lamp having a cap or base on each end of the lamp

1.3.4

1.3.4 (standards.iteh.ai) extra low voltage tungsten halogen lamp

tungsten halogen lamp with a rated voltage lower than 50 V

Note 1 to entry: Abbreviated: ELV tungsten halogen lamp. c-60432-3-2012

1.3.5

extra low voltage low-pressure tungsten halogen lamp

tungsten halogen lamp with a gas pressure below a certain value and a rated voltage less than or equal to 12 V

1.3.6

self-shielded tungsten halogen lamp

tungsten halogen lamp for which the luminaire needs no protective shield

Note 1 to entry: Abbreviated: self-shielded lamp.

Examples of self-shielded tungsten halogen lamps are:

- ELV tungsten halogen lamps with integral outer envelope; •
- ELV low-pressure tungsten halogen lamps;
- mains voltage tungsten halogen lamps which conform to IEC 60432-2;
- mains voltage tungsten halogen lamps which conform to the relevant clauses of this standard.

1.3.7

outer envelope

transparent or translucent enclosure containing a tungsten halogen light source

Note 1 to entry: The enclosure can also consist of a reflector with integral front cover.

1.3.8

rated voltage

voltage or voltage range specified in this standard or assigned by the manufacturer or responsible vendor

Note 1 to entry: If lamps are marked with a voltage range, they are appropriate for use on any supply voltage within that range.

1.3.9

test voltage

rated voltage unless otherwise specified

Note 1 to entry: If lamps are marked with a voltage range, the test voltage is the mean of the voltage range, unless otherwise specified.

1.3.10

rated wattage

wattage specified in this standard or assigned by the manufacturer or responsible vendor

1.3.11

rated current

current specified in this standard or assigned by the manufacturer or responsible vendor

1.3.12

test current

rated current unless otherwise specified DARD PREVIEW

1.3.13

(standards.iteh.ai)

specific effective radiant UV power

effective power of the UV radiation of a lamp related to its luminous flux

https://standards.iteh.ai/catalog/standards/sist/89dfe0c9-0e75-4585-b8c4-

Note 1 to entry: The specific effective radiant UV power is expressed in:² mW/klm.

For a reflector lamp, this is the effective irradiance of the UV radiation related to the illuminance.

Note 2 to entry: The effective irradiance of the UV radiation related to the illuminance is expressed in $mW/(m^2\cdot klx).$

Note 3 to entry: The effective power (or irradiance) of the UV radiation is obtained by weighting the spectral power distribution of the lamp with the action spectrum published by the American Conference of Governmental Industrial Hygienists (ACGIH), which is endorsed by the World Health Organization (WHO) and recommended by the International Radiation Protection Association (IRPA). For references, see Bibliography.

1.3.14

maximum pinch temperature

maximum temperature which the components in the pinch/seal of a lamp are designed to withstand over the expected life of the lamp

1.3.15

maximum lamp cap-contact, base-pin or base-post temperature

maximum temperature of the lamp cap-contact, base-pin or base-post, which should be observed to safeguard electrical contact over the expected life of the lamp

1.3.16

maximum cap temperature

maximum temperature for which the components in the cap area of a lamp are designed to withstand over the expected life of the lamp

1.3.17

maximum reflector-rim temperature

maximum temperature for which the connection between front cover and reflector is designed to withstand over the expected life of the lamp

1.3.18

group

lamps for the same application as defined by the scope of this standard

1.3.19

type

lamps of the same group having the same nominal wattage, bulb shape and cap

1.3.20

family

grouping of lamps characterized by common features such as materials, components and/or method of processing

1.3.21

design test

test made on a sample for the purpose of checking compliance of the design of a family, group or a number of groups with the requirements of the relevant clause

1.3.22 iTeh STANDARD PREVIEW

test, or series of tests, repeated at intervals in order to check that a product does not deviate in certain respects from the given design

1.3.23

IEC 60432-3:2012

running test https://standards.iteh.ai/catalog/standards/sist/89dfe0c9-0e75-4585-b8c4-

test repeated at frequent intervals to provide data for assessment

1.3.24

batch

all lamps in one family and/or group and identified as such and put forward at one time for checking compliance

1.3.25

whole production

production during a period of twelve months of all types of lamps within the scope of this standard and nominated in a list of the manufacturer for inclusion in the certificate

1.3.26

breakdown

plasma discharge between two points inside the bulb of the lamp with maximum difference of electrical potential

Note 1 to entry: For the purposes of this standard, it is assumed that breakdown has occurred if the current exceeds the rated current by a factor of 5 (under consideration).

2 Requirements

2.1 General

Tungsten halogen lamps shall be so designed and constructed that in normal use they present no danger to the user or surroundings.

In general, compliance is checked by carrying out all the relevant tests specified in this standard. For the purposes of this standard, the voltage designations shown in IEC 60357 apply.

2.2 Marking

2.2.1 Lamp marking

The following information shall be legibly and durably marked on the lamps:

- mark of origin (this may take the form of a trademark, the manufacturer's name, the brand name or the name of the responsible vendor);
- rated wattage (marked "W" or "watts");
- rated voltage or rated voltage range (marked "V" or "volts"), or for airfield lamps the rated current (marked "A").

The rated voltage marking for lamps intended for use on United Kingdom supply voltages may be "240 volts" or "240 V".

NOTE The United Kingdom implementation of 230 V (European harmonization process) allows supply voltages to remain at 240 V.

Compliance is checked on unused lamps as follows:

- presence and legibility by visual inspection; durability by applying the following test.

The area of the marking on the lamp shall be rubbed by hand with a smooth cloth, moistened with water, for a period of 15 s.

IEC 60432-3:2012

After this test, the marking shall still be legible. /iec-60432-3-2012

2.2.2 Additional information and marking

If applicable, the following information shall be given.

a) Lamps shall be supplied with an appropriate cautionary notice indicating the need of a protective shield to be fitted to the luminaire. Alternatively the immediate lamp wrapping or container may be marked with the corresponding symbol as shown in Clause A.1.

NOTE In North America, a suitable cautionary notice is required. Use of the symbol is optional.

b) For self-shielded lamps (not needing luminaire shielding), the immediate lamp wrapping or container shall be marked with the symbol as shown in Clause A.2.

NOTE 1 This does not apply to lamps covered by IEC 60432-2.

NOTE 2 In North America, a written notice may be used in place of this symbol.

c) For dichroic-coated reflector lamps, the immediate lamp wrapping or container shall be marked with the symbol as shown in Clause A.3.

NOTE This symbol is not required in North America.

d) Double-capped lamps, with rated voltages 50 V - 250 V, shall be supplied with a cautionary notice or symbol as shown in Clause A.4 indicating that the luminaire shall be disconnected from the power supply before insertion or withdrawal of the lamp.

NOTE 1 In the USA, special package marking is required regarding the use of 500 W double-capped halogen lamps in residential indoor luminaires.

NOTE 2 In North America, a suitable cautionary notice is required. Use of the symbol is optional.

e) Projection lamps, photographic lamps, special purpose and stage lighting lamps shall be marked with the following symbol on the packaging or accompanying information.



f) Projection lamps, photographic lamps, special purpose and stage lighting lamps shall be marked with the following symbol on the packaging or accompanying information.



Information shall be given on the manufacturer's homepage, catalogue or similar means of information on how to address IR hazards properly.

IEC 60432-3:2012

Compliance is checked by visual tinspection tandards/sist/89dfe0c9-0e75-4585-b8c4-

0b5677073406/iec-60432-3-2012

2.3 Caps or bases

2.3.1 General

Caps or bases originally developed for single-capped ELV lamps shall not be used for general purpose tungsten halogen lamps with rated voltages higher than 50 V.

NOTE Examples of such ELV fits are: G4, GU4, GY4, GX5.3, GU5.3, G6.35, GY6.35, GU7 and G53.

The GU10 base shall be used for aluminised reflector lamps only. The G9, GU10 or GZ10 base shall be used for self-shielded lamps only.

Compliance is checked by inspection.

2.3.2 Creepage distances

The minimum creepage distance between contacts or between contacts and the metal shell of the cap, if any, shall be in accordance with the recommendations in IEC 60061-4.

Compliance is checked by measurement.

2.3.3 Dimensions

If tungsten halogen lamps use standardized caps/bases they shall be in accordance with the requirements of IEC 60061-1.

Compliance is checked on finished lamps by using the gauges of IEC 60061-3.

Non standardized caps/bases shall be in accordance with the manufacturer's specification.

Compliance is checked by inspection.

2.4 Photobiological safety

The specific effective radiant UV power of self-shielded tungsten halogen lamps shall not exceed:

- 2 mW/klm or,
- for reflector lamps 2 mW/(m²·klx).

Compliance is checked by measurement of the spectral power distribution.

NOTE Blue light and infrared hazards are covered by marking requirements.

2.5 Gas pressure of low-pressure self-shielded extra low voltage lamps

During operation, the gas pressure of single-capped low-pressure self-shielded ELV tungsten halogen lamps shall be limited. This shall be achieved by restricting:

- a) the cold fill pressure to less than 1×10^5 Pa (1 bar) for rated wattages above 50 W and up to 100 W, and
- b) the cold fill pressure to less than 4×10^5 Pa (4 bar) for rated wattages up to 50 W, and
- c) the lamp volume to 1 cm³ maximum DARD PREVIEW

Compliance is checked by inspection and by means of the test specified in Annex B.

2.6 Safety at end of life of self-shielded lamps with rated voltages from range B or C https://standards.iteh.ai/catalog/standards/sist/89dfe0c9-0e75-4585-b8c4-

When tested under the specified conditions champ failure shall not be accompanied by breakage of the bulb nor its ejection from the cap.

For bayonet capped lamps, it is also required that there shall not be an internal short-circuit to the cap shell after the test.

The test conditions are:

- an induced-failure test in accordance with Annex F, or
- an operation-to-failure test.

The operation-to-failure test shall be carried out under the conditions specified for the life test procedure in Annex A of IEC 60357:2002. The test rack circuit characteristics shall be in line with Table E.1 of IEC 60432-1:1999. The test is continued until end of life.

NOTE 1 In the event of dispute the reference test method is the induced failure test.

NOTE 2 Some lamp designs are not suitable for testing with the induced failure test because a breakdown cannot reliably be achieved. Such lamps, provided they are of voltage range B or C, will be submitted to an operation-to-failure test as described above.

2.7 Information for luminaire design

Refer to Annex C.

3 Assessment

3.1 General

This clause specifies the method a manufacturer should use to show that his product conforms to this standard on the basis of whole production assessment, in association with his test records on finished products. This method can also be applied for certification purposes. Subclause 3.2 gives details of assessment by means of the manufacturer's records.

Details of a batch test procedure which can be used to make limited assessment of batches are given in 3.3. Requirements for batch testing are included in order to enable the assessment of batches presumed to contain unsafe lamps. As some safety requirements cannot be checked by batch testing, and as there may be no previous knowledge of the manufacturer's quality, batch testing cannot be used for certification purposes nor in any way for an approval of the batch. Where a batch is found to be acceptable, a testing agency may only conclude that there is no reason to reject the batch on safety grounds.

3.2 Whole production assessment by means of manufacturer's records

The manufacturer shall show evidence that his products comply with the particular requirements of 3.2.1. To this end, the manufacturer shall make available all the results of his product testing pertinent to the requirements of this standard.

The test results may be drawn from working records and, as such, may not be immediately available in collated form.eh STANDARD PREVIEW

The assessment shall be based an general son individual factories, each meeting the acceptance criteria of 3.2.1. However, a number of factories may be grouped together, providing they are under the same quality management. For certification purposes, one certificate may be issued to cover a nominated group of factories, but the certification authority shall have the right to visit each plant to examine the local relevant records and quality control procedures.

For certification purposes, the manufacturer shall declare a list of marks of origin and corresponding lamp families, groups and/or types which are within the scope of this standard and manufactured in a nominated group of factories. The certificate shall be taken to include all lamps so listed made by the manufacturer. Notification of additions or deletions may be made at any time.

In presenting the test results, the manufacturer may combine the results of different lamp families, groups and/or types according to column 4 of Table 1.

The whole production assessment requires that the quality control procedures of a manufacturer shall satisfy recognized quality system requirements for final inspection. Within the framework of a quality assurance system based also on in-process inspection and testing, the manufacturer may show compliance with some of the requirements of this standard by means of in-process inspection instead of finished product testing.

The manufacturer shall provide sufficient test records with respect to each clause and subclause as indicated in column 5 of Table 1.