



Edition 3.2 2019-06 CONSOLIDATED VERSION

INTERNATIONAL STANDARD





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2019 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11

info@iec.ch www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization th<mark>a</mark>t prepares and publishes International Standards for all electrical, electronic and related technologies.

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.


IEC Glossary /std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of EC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.



Edition 3.2 2019-06 CONSOLIDATED VERSION

INTERNATIONAL STANDARD



Global maritime distress and safety system (GMDSS)

Part 4: Inmarsat-C ship earth station and Inmarsat enhanced group call (EGC) equipment – Operational and performance requirements, methods of testing and required test results



https://standards.iteh.ai/ //standards/ec/97b9abea-e678-40a4-b726-050fbe5cbd6b/iec-61097-4-201

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 47.020.70 ISBN 978-2-8322-7116-2

Warning! Make sure that you obtained this publication from an authorized distributor.







Edition 3.2 2019-06 CONSOLIDATED VERSION

REDLINE VERSION



CONTENTS

FC	REW	ORD	4		
IN ⁻	TRODUCTION to Amendment 26				
1	Scope				
2	Norr	native references	7		
3	Performance requirements				
	3.1	3.1 Overview			
	3.2	Non-operational requirements			
		3.2.1 General			
		3.2.3 Power supply changeover			
	3.3	Operational requirements for ship earth stations	<u>, </u>		
		3.3.1 Capabilities	9		
		3.3.2 Ship station identity	10		
		3.3.3 Distress alerting	10		
		3.3.3 Distress alerting	10		
	3.4	Out and the mail and market and and to the EOO market beautiful.	4.		
		3.4.1 Capabilities	11		
		3.4.2 General	1		
		3.4.3 Position and area code updating	1		
		3.4.4 Indication of receipt of priority message	12		
		3.4.5 Indication of tuning and synchronisation	12		
		3.4.6 Printing selection	12		
		3.4.7 Printing device	12		
	3.5 Performance related requirements from IEC 60945				
	3.6	Other requirements			
	3.7	Long-range identification and tracking			
		3.7.1 General			
		3.7.2 Capabilities	14		
		3.7.3 Functionality			
	3.7.4 Communication system				
4	Technical characteristics				
	4.1	Overview	16		
	4.2	Environmental and electromagnetic compatibility requirement	16		
	4.3	Radiated spurious emissions	17		
	4.4	Interfaces	17		
5	Meth	nods of testing and required test results	17		
	5.1	Overview	17		
		5.1.1 General	17		
		5.1.2 Performance requirements	18		
		5.1.3 Technical characteristics	18		
	5.2	Tests of non-operational requirements	18		
	5.3	Tests of operational requirements for ship earth stations	18		
		5.3.1 Capabilities	18		
		5.3.2 Ship station identity	18		
		5.3.3 Distress alerting	18		
		5.3.4 Position updating	19		

5.4	Tests	of operational requirements for EGC receivers	19			
	5.4.1	Capabilities	19			
	5.4.2	General	19			
	5.4.3	Position and area code updating	19			
	5.4.4	Indication of receipt of priority message	20			
	5.4.5	Indication of tuning and synchronisation				
	5.4.6	Printing selection	20			
	5.4.7	Printing device	20			
5.5	Tests	of performance related requirements from IEC 60945	20			
5.6		of other requirements				
5.7		ange identification and tracking	20			
	5.7.1		20			
	5.7.2	Capabilities	21			
	5.7.3	Capabilities Functionality Communication system	21			
	5.7.4	Communication system	21			
5.8		or technical characteristics				
	5.8.1	Inmarsat tests				
	5.8.2	Tests for environmental and electromagnetic compatibility				
	5.8.3	Interfaces				
Annex A (normative) Requirements relating to installation						
Annex B	(normat	ive) Radiated unwanted emissions	25			
Annex C (informative) Inmarsat RTP schedule of tests.						
Bibliography						
		Cincle Peview				
Table 1 -	- Data to	be transmitted from the shipborne equipment	15			
Table 2 – Environmental conditions						
Table B.	l – Limi	s of unwanted emissions up to 1 000 MHz				
Table B.2 – Limits of unwanted emissions above 1 000 MHz						
Table B.3 – Limits of unwanted emission within the operating band with carrier-on						
Table C.1 – Phase Inmarsat-C schedule of tests						
Table C.2 - Phase I EGC receiver schedule of tests						
	//	se N schedule of tests	0.4			

INTERNATIONAL ELECTROTECHNICAL COMMISSION

GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) -

Part 4: Inmarsat-C ship earth station and Inmarsat enhanced group call (EGC) equipment – Operational and performance requirements, methods of testing and required test results

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC ontechnical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its echnical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendments has been prepared for user convenience.

IEC 61097-4 edition 3.2 contains the third edition (2012-05) [documents 80/659/FDIS and 80/666/RVD], its amendment 1 (2016-08) [documents 80/789/CDV and 80/808/RVC] and its amendment 2 (2019-06) [documents 80/926/FDIS and 80/929/RVD].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendments 1 and 2. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

International Standard IEC 61097-4 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

This edition constitutes a technical revision. The main changes with respect to the previous edition are:

- the IMO references and requirements have been updated to the new performance standards for enhanced group call equipment adopted in 2010 as resolution MSC.306(87). The new performance standards incorporate new requirements for an indication of ship's position which has not been updated (3.4.3) and an alarm for paper low condition (3.4.7). These two requirements are, however, derived from Inmarsat documentation so there is no technical change to equipment;
- a new subclause has been added (3.7) concerning long-range identification and tracking (LRIT) to support IMO performance standards given in resolution MSC.263(84) adopted in 2008;
- references to Inmarsat documentation have been simplified by moving the content of Tables 1, 2, 4 and 5 into a new Annex C;
- the text has been editorially updated to conform to the ISQ/IEQ Directives.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 61097 series, published under the general title Global maritime distress and safety system (CMDSS), can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.ec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION to Amendment 2

NOTE This amendment adds a requirement for an interface for alert management and removes the requirement to produce a printed copy of received safety information providing there is an interface to other navigation display equipment. This results from amendments to the performance standards for enhanced group call equipment agreed by the International Maritime Organization in resolution MSC.431(98) in 2017. It can be noted that the technical provisions for the interface for the transfer of received data to other navigation display equipment were included in IEC 61097-4:2012/AMD1:2016.



GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) -

Part 4: Inmarsat-C ship earth station and Inmarsat enhanced group call (EGC) equipment – Operational and performance requirements, methods of testing and required test results

1 Scope

This part of IEC 61097 specifies the performance requirements and methods of testing for Inmarsat-C ship earth stations (SES) capable of transmitting and receiving direct printing communications, and for enhanced group call (EGC) receivers for use in the GMDSS and for use for long-range identification and tracking (LRIT). The available variants are:

Class 0: An EGC receiver, either stand-alone or an element of a CMDSS installation in

accordance with the Inmarsat design and installation guidelines (DIGs) for

GMDSS installations.

Class 1: A basic SES providing shore-to-ship and ship-to-shore message transfer only.

Class 2: As class 1 but with EGC as an alternative to shore-to-ship transfer using a

shared receiver.

Class 3: As class 1 but with EGC using an independent receiver.

NOTE 1 The 34th session of the IMO Sub-Committee on Radiocommunications decided that class 2 equipment would be adequate to provide sufficient availability for the reception of maritime safety information for the GMDSS.

The standard complies with IMO performance requirements stated in the normative references, Inmarsat technical characteristics and test procedures, and IEC 60945 general requirements except where modifications are explicitly stated in this standard. Technical characteristics essential to GMDSS and LRIT operation as defined by the IMO are identified.

All text of this standard, whose wording is identical to that in IMO SOLAS Convention 1974 as amended in 1988 and Resolutions A.807(19), MSC.263(84) and MSC.306(87) is printed in *italics* and reference made to the Resolution/Recommendation and subclause number.

This standard covers equipment construction and testing. Matters relating to installation may also be found in the immarsat Maritime design and installation guidelines (see Bibliography). Those to be found in IMO Resolutions A.807(19), MSC.263(84) and MSC.306(87) are reproduced in Annex A.

Responsibility for type approval of Inmarsat-C and Inmarsat-EGC is vested in Inmarsat by IMO Resolutions A.807(19) and MSC.306(87) (see 3.2.1). Therefore, this standard does not reproduce Inmarsat test procedures in full, but refers to where they are given in Inmarsat documentation cited in the normative references to this standard (Annex C).

NOTE 2 For the purposes of this standard the terms Inmarsat-C, Inmarsat Standard-C, Standard-C refer to the same equipment.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945:2002, Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results

IEC 61108 (all parts), Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS)

IEC 61162-1, Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners

IEC 62923-1, Maritime navigation and radiocommunication equipment and systems – Bridge alert management – Part 1: Operational and performance requirements, methods of testing and required test results

IEC 62923-2, Maritime navigation and radiocommunication equipment and systems – Bridge alert management – Part 2: Alert and cluster identifiers and other additional realizes

IMO, International Convention for the safety of life at sea (SOLAS), 1974 as amended

IMO Resolution A.694(17):1991, General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids

IMO Resolution A.807(19):1995, Performance Standards for INMARSAT-C ship earth stations capable of transmitting and receiving direct-printing communications as amended by Resolution MSC.68(68) Annex 4

IMO Resolution MSC.263(84):2008, Revised performance standards and functional requirements for the long-range identification and tracking of ships.

IMO Resolution MSC.302(87) (2010), Rerformance standards for bridge alert management

IMO Resolution MSC.306(87):2010, Revised performance standards for enhanced group call (EGC) equipment

Inmarsat, Inmarsat-C System definition manual (SDM) Volume 2 – Part 2, Application Note 2, Position reporting service

Inmarsat, Inmarsat-C System definition manual (SDM) Volume 2 – Part 2, Application Note 3, Application developers guide to data reporting and polling

Inmarsat, Inmarsat-C System definition manual (SDM) Volume 3 – Part 2, Chapter 2, Mobile earth station technical requirements

Inmarsat, Inmarsat-C System definition manual (SDM) Volume 3 – Part 2, Chapter 5, Ship earth station technical requirements

Inmarsat, Inmarsat-C System definition manual (SDM) Volume 3 – Part 2, Chapter 8, Technical requirements for an EGC receiver

Inmarsat, Recommended test procedures (RTP) for the type approval of Inmarsat-C mobile earth stations

3 Performance requirements

3.1 Overview

Subclauses 3.2 through 3.4 of this standard describe performance requirements directly attributable to IMO Resolutions A.807(19) and MSC.306(87) as listed in the normative references. Subclause 3.5 is provided to highlight those requirements of IMO Resolution A.694(17) which are not included in the normal Inmarsat requirements for Inmarsat-C SES type approval. Subclause 3.6 describes other requirements which are required to make the equipment suitable for GMDSS applications. Subclause 3.7 describes performance requirements attributable to IMO Resolution MSC.263(84) for long-range identification and tracking.

3.2 Non-operational requirements

3.2.1 General

(A.807(19) A1.1/MSC.306(87) A1.1) The Inmarsat Standard-C ship earth station installation capable of transmitting and receiving direct-printing communications, and the enhanced group call equipment to be used in the GMDSS shall comply with the general requirements set out in Assembly resolution A.694(17) as detailed in IEC 60945 and this IEC standard.

(A.807(19) A2/MSC.306(87) 2) The ship earth station and the EGC equipment shall be type-approved by Inmarsat and shall comply with the environmental conditions and electromagnetic compatibility requirements specified in IEC 60945.

3.2.2 Warning of radiation hazard

(A.807(19) A4) In order to permit a warning of potential radiation hazards to be displayed in appropriate locations, a label shall be attached to the radome indicating the distances external to the radome at which radiation levels of 100 W/m², 25 W/m² and 10 W/m² exist. However, the distances which are within the radome need not be indicated.

NOTE Due to the low transmitted power of Inmarsat-C transmitters (less than 16 dBW) and the omnidirectional antenna used, this label is not normally required.

3.2.3 Power supply changeover

(See 5.2)

(A.807(19) A5.2/MSC.306(87) A4.2) Changing from one source of supply to another or any interruption of up to 60 s duration of the supply of electrical energy shall not require the equipment to be manually re-initialized and shall not result in loss of received messages stored in the memory.

3.3 Operational requirements for ship earth stations

3.3.1 Capabilities

(See 5.3.1)

The equipment shall comply with regulations IV/8 through IV/10 of SOLAS 1974, as amended, which prescribe the capabilities of Inmarsat ship earth stations to meet the GMDSS requirements for ships in the various sea areas. The four capabilities are:

- (SOLAS IV/8.1.5.1/IV/9.1.3.3 and IV/10.1.4.3): means of initiating the transmission of shipto-shore distress alerts.
- (SOLAS IV/10.1.1.1): transmitting and receiving distress and safety communications using direct-printing telegraphy.
- (SOLAS IV/10.1.1.2): initiating and receiving distress priority calls.

- (SOLAS IV/9.3.2/IV/10.1.1.4): transmitting and receiving general radiocommunications, using either radiotelephony or direct-printing telegraphy.

NOTE In the case of this equipment only direct-printing telegraphy applies.

3.3.2 Ship station identity

(See 5.3.2)

(A.807(19) A3.1): No control external to the equipment shall be available for alteration of the ship station identity.

3.3.3 Distress alerting

(See 5.3.3)

(A.807(19) A3.2): It shall be possible to initiate and make distress calls from the position from which the ship is normally navigated and from at least one other position designated for distress alerting.

(A.807(19) A3.3): A distress alert shall be activated only by means of a dedicated distress button. This button shall not be any key of an ITU-T digital input panel or an ISO keyboard provided on the equipment.

(A.807(19) A3.4): The dedicated distress button shall:

- 1) be clearly identified; and
- 2) be protected against inadvertent operation.

(A.807(19) A3.5): The distress alert initiation shall require at least two independent actions.

(A.807(19) A3.6): The equipment shall indicate the status of the distress alert transmission.

(A.807(19) A3.7). It shall be possible to interrupt and initiate distress messages at any time.

It shall be possible to select the content of, but not initiate a distress alert using the equipment keyboard or other means, before depressing one of the dedicated buttons to initiate the distress alert. It shall also be possible to activate an undesignated (see Note) distress alert by depressing one of the buttons, at any time.

NOTE Undesignated - unspecified distress alert, i.e. the default setting. All other selectable alerts are "designated".

3.3.4 Position updating

(See 5.3.4)

(A.807(19) A3.8): Facilities shall be provided to automatically update the ship's position and the time at which the position was determined from a suitable electronic position-fixing aid which may be an integral part of the equipment. For equipment which does not have an integral position-fixing aid, such facilities shall include a suitable interface conforming to IEC 61162.

The integral electronic position-fixing aid shall comply with the applicable requirements of the IEC 61108 series.

As a minimum, the interface shall support the sentences GNS, RMC and ZDA described in IEC 61162-1.